

CAQ-specific Configurations

1.1 Overview

1.1.1 Archiving of inspection requirements

1.1.1.1 Data structures

The default archiving of inspection requirements is object-related, i.e. each separate inspection requirement is evaluated in the archiving process. If the conditions specified via configuration parameters are fulfilled, the requirement is archived. In this process, all detailed data included is also archived.

Optionally, you can use the above parameters to delete the data (instead of archiving).

By default, there is a separate configuration for each individual HYDRA-CAQ data type (in-production inspection, goods receipt or goods issue inspection, initial sample inspection, QMS data). You can therefore archive inspection requirements of the goods receipt area in other intervals than data of the production data.

By default, the details saved for inspection requirements are identical for each data type. This may be the following data:

Data	Source table(s)	
Inspection requirements	caq_pruefanf caq_pan_zusatz	
Inspection orders	caq_paukop	
Inspection order configurations Characteristic configurations	caq_paukonf	
Inspection points	caq_numpool caq_ppktm_info	
QMS: Dynamic modification history of inspection points based on characteristics	caq_dyhis_ppktmm	
Characteristics	caq_merkmal caq_merk_zusatz	
Inspection frequencies	caq_prueffreq	
Inspection specifications depending on quantities	caq_mengabh_prf	
Documents	caq_dokus	
Tool assignments	caq_werkzzuord	
Samples Characteristic results	caq_paustich	
Assignment of samples to numbers Assignment of samples to inspection points	caq_paunumm	
Characteristic attributes	caq_paumm_ausp	
Single values	caq_paumwert	
Failure analysis entries	caq_fhlanal	

Data	Source table(s)	
Measures and corresponding parameters	caq_massn caq_mass_param	
Inspection matrix Assignment of characteristics to inspection points	caq_pruefmatrix	

Events and logging entries for inspection requirements are archived separately. The archiving configuration of this data is described in the sections that follow.

Inspection requirements for the PMV data type (calibration/maintenance) are not archived by default.



The archiving configuration defines key fields. The key fields are used to filter the data when the data is reloaded. For example, all inspection requirements of the period x are filtered for article 4711. The key fields are assigned as follows by default.

Key 1: rec_type, e.g. FEP

Key 2: area, e.g. F for production

Key 3: pruefanf_nr (unique inspection requirement number)

Key 4: auftrag_nr (order number of inspection requirement)

Key 5: artikel_nr (article number of inspection requirement)

If you use the database Oracle, all 5 key fields must be filled for the archiving of the inspection requirements. If for example the article number is missing in an inspection requirement, this inspection requirement is not archived. If you want to archive such inspection requirements, the relevant key field must not have a content in the archiving configuration. With the example of the article number, this means that you cannot filter by the article number in a reload.

1.1.1.2 Standard configuration (with license FEP-/WEP-/QMS-ARC)

If one of the licenses FEP-/WEP-/QMS-ARC is available, the inspection requirements of the below mentioned data types are saved by default using the structure mentioned above.

For each of these data types, a separate configuration is provided. You can use the separate configurations to configure separate archiving periods, for example. The data type WAP (goods issue) is assigned to the licenses FEP-*

The standard configuration of the inspection requirements provides a two-step archiving.

In a first step, data is moved to the medium-term data area. Here, data is directly available for evaluations/reports using the medium-term data area. This data cannot be changed.

In a second step, data is moved to the long-term data area. In this case, data is no longer directly available for evaluations/reports. Data needs to be reloaded first to be able to use it for evaluations/reports in HYDRA.

Standard configurations for the first and second archiving level of inspection requirements and the respective intervals are described in the following table.

Product	Object	Description of the action	Default interval
CAQ	FEP	Moving the production inspection requirements from the online data set to the medium-term data set.	1 year
CAQ	A_FEP	Moving the production inspection requirements from the medium-term data set to the long-term data set.	3 years
CAQ	WEP	Moving the inspection requirements of the goods receipt from the online data set to the medium-term data set.	1 year
CAQ	A_WEP	Moving the inspection requirements of the goods receipt from the medium-term data set to the long-term data set.	3 years
CAQ	WAP	Moving the inspection requirements of the goods issue from the online data set to the medium-term data set.	1 year
CAQ	A_WAP	Moving the inspection requirements of the goods issue from the medium-term data set to the long-term data set.	3 years
CAQ	EMU	Moving the inspection requirements of initial samples from the online data set to the medium-term data set.	1 year
CAQ	A_EMU	Moving the inspection requirements of initial samples from the medium-term data set to the long-term data set.	3 years
QMS	QMS	Moving the QMS inspection requirements from the online data set to the medium-term data set.	3 months
QMS	A_QMS	Moving the QMS inspection requirements from the medium-term data set to the long-term data set.	3 years

To identify the intervals, the editing date of the inspection requirement is used as reference. Not all inspection requirements are archived. The respective status specifies whether an inspection requirement is archived or not. By default, only completed and canceled inspection requirements are archived.

QMS collective requirements must be uploaded to the PPS system in order to be archived. Administrative data on archived CAQ inspection requirements is archived for 12 years in the arc_verw_caq table by default.

1.1.1.3 Activities without license FEP-/WEP-/QMS-ARC

If no active license FEP-/WEP-/QMS-ARC is available, this archiving configuration does not affect the inspection requirements.

In contrast to other HYDRA data, inspection requirements are not removed in this case. They permanently remain in the online data area, unless they are included in another archiving configuration. The data type WAP (goods issue) is assigned to the licenses FEP-*.

The inspection requirements of QMS data are an exception. The results of these inspection requirements are normally uploaded to the PPS system. For this reason it is not required to keep this data in HYDRA. The data is removed from the system after expiration of the period of time defined for the product QMS/object QMS in section [1.1.1.2 Standard configuration \(with license FEP-/WEP-/QMS-ARC\)](#), just as it is the case for other HYDRA data areas if the configuration has not been changed.

1.1.2 Archiving of collective requirements

1.1.2.1 Data structures

The default archiving of collective requirements is object-related, i.e. each collective requirement is evaluated in the archiving process. If the conditions specified via configuration parameters are fulfilled, the requirement is archived. In this process, all detailed data included is also archived.

Optionally, you can use the above parameters to delete the data (instead of archiving).

In contrast to the archiving of inspection requirements, the collective requirements are not archived with reference to their data types. Consequently, it is not possible to define parameters for different intervals for the collective requirements of different data types.

The details saved by default for a collective requirement are:

Data	Source table(s)	
Collective requirements	caq_sammelanf	
Inspection frequencies	caq_prueffreq	

Logging entries for collective requirements are archived separately. The archiving configuration of this data is described in the sections that follow.

1.1.2.2 Standard configuration (with license FEP-/WEP-/QMS-ARC)

If one of the licenses FEP-/WEP-/QMS-ARC is available, the collective requirements are saved by default using the structure mentioned above and irrespective of their data type.

The standard configuration of the collective requirements provides a two-step archiving.

In a first step, data is moved to the medium-term data area. Here, data is directly available for evaluations/reports using the medium-term data area. This data cannot be changed.

In a second step, data is moved to the long-term data area. In this case, data is no longer directly available for evaluations/reports. Data needs to be reloaded first to be able to use it for evaluations/reports in HYDRA.

The standard configurations for the first and second archiving level of the collective requirements are described below.

Product	Object	Description of the action	Default interval
CAQ	SAN	Moving collective requirements from the online data set to the medium-term data set.	1 year
CAQ	A_SAN	Moving collective requirements from the medium-term data set to the long-term data set.	3 years

To identify the intervals, the editing date of the collective requirement is used as reference.

By default, only the collective requirements without inspection requirements in the online data area are archived in the medium-term data area. This ensures that a collective requirement is only archived in the medium-term data area, if all included inspection requirements have also been archived.

Archiving to the long-term data area works on the same principle. Only if all inspection requirements included in the collective requirement do no longer exist in the medium-term data set, the collective requirement is transferred to the long-term data set (respecting the interval).

Administrative data on archived CAQ collective requirements is archived for 12 years in the `arc_verw_caq` table by default.

1.1.2.3 Activities without license FEP-/WEP-/QMS-ARC

If no active license FEP-/WEP-/QMS-ARC is available, this archiving configuration does not affect the collective requirements.

In contrast to other HYDRA data, collective requirements are not removed in this case. They permanently remain in the online data area, unless they are included in another archiving configuration.

1.1.3 Archiving of CAQ events

1.1.3.1 Data structures

By default, CAQ events are archived in relation to time. The archiving is always performed and it does not matter if the included CAQ objects (e.g. inspection requirements or their details) have been archived or not.

Optionally, you can use the above parameters to delete the data (instead of archiving).

By default, the events are archived separately, if applicable with the relevant detail data. The following data is archived:

Data	Source table(s)
CAQ events	event_caq
Optional dialog data for events	event_dlg_data

1.1.3.2 Standard configuration (with license FEP-/WEP-/QMS-ARC)

If one of the licenses FEP-/WEP-/QMS-ARC is available, the CAQ events are saved by default using the structure mentioned above and irrespective of their data type.

The standard configuration of the CAQ events provides a two-step archiving.

In a first step, data is moved to the medium-term data area. Here, data is directly available for evaluations/reports using the medium-term data area.

In a second step, data is moved to the long-term data area. In this case, data is no longer directly available for evaluations/reports. Data needs to be reloaded first to be able to use it for evaluations/reports in HYDRA.

The standard configurations for the first and second archiving level of the CAQ events are described below.

Product	Object	Description of the action	Default interval
CAQ	EREIGCAQ	Moving entries of CAQ events from the online data set to the medium-term data set.	35 days
CAQ	A_ EREIGCAQ	Moving entries of CAQ events from the medium-term data set to the long-term data set.	3 years

To identify the intervals, the date of the CAQ event is used as reference.

Administrative data on archived CAQ events is archived for 12 years in the arc_verw_caq table by default.

1.1.3.3 Activities without license FEP-/WEP-/QMS-ARC

If no active license FEP-/WEP-/QMS-ARC is available, this archiving configuration does not affect the CAQ events.

In contrast to other HYDRA data, CAQ events are not removed in this case. They permanently remain in the online data area, unless they are included in another archiving configuration.

1.1.4 Archiving of CAQ logging entries

1.1.4.1 Data structures

By default, CAQ logging entries are archived in relation to time. The archiving is always performed and it does not matter if the included CAQ objects (e.g. inspection requirements or their details) have been archived or not.

Optionally, you can use the above parameters to delete the data (instead of archiving).

By default, the logging entries are archived separately, if applicable with the relevant detail data. The following data is archived:

Data	Source table(s)
Logging entries	hyd_logging
Additional data to logging entries	hyd_logging_data

1.1.4.2 Standard configuration (with license FEP-/WEP-/QMS-ARC)

If one of the licenses FEP-/WEP-/QMS-ARC is available, the CAQ logging entries are saved by default using the structure mentioned above.

The standard configuration of the CAQ logging entries provides a two-step archiving.

In a first step, data is moved to the medium-term data area. Here, data is directly available for evaluations/reports using the medium-term data area.

In a second step, data is moved to the long-term data area. In this case, data is no longer directly available for evaluations/reports. Data needs to be reloaded first to be able to use it for evaluations/reports in HYDRA.

The default configurations for the first and second archiving level of CAQ logging entries are described in the below table.

Product	Object	Description of the action	Default interval
CAQ	LOG	Moving CAQ logging entries from the online data set to the medium-term data set.	35 days
CAQ	A_LOG	Moving the CAQ logging entries from the medium-term data set to the long-term data set.	3 years

To identify the intervals, the date of the logging entry is used as reference.

Administrative data on archived CAQ logging entries is archived for 12 years in the arc_verw_caq table by default.

1.1.4.3 Activities without license FEP-/WEP-/QMS-ARC

If no active license FEP-/WEP-/QMS-ARC is available, this archiving configuration does not affect the CAQ logging entries.

In contrast to other HYDRA data, CAQ logging entries are not removed in this case. They permanently remain in the online data area, unless they are included in another archiving configuration.

1.1.5 Archiving of the document management

The documents of the HYDRA document management are archived when the relevant object is archived. The files themselves remain at their original storage location and are not archived.

As part of the HYDRA document management of the CAQ, you can assign documents to the following objects.

- Inspection points
- Inspection step characteristics/inspection point characteristics
- Measured values/attributive inspection results

To archive the documents, make the following entries in the data management.

Product	Object	Description of the action	Default interval
CAQ	DOCLINK	Moving the document entry from the online data set to the medium-term data set.	0 days

Product	Object	Description of the action	Default interval
CAQ	A_DOCLINK	Moving the document entry from the medium-term data set to the long-term data set.	0 days

Set the interval to "0 days" so that the archiving is directly performed after the archiving of the respective object.