

1 Configurations specific to HLS

Summary

The HYDRA Data Management can be used to configure the retention period for HLS planning data relevant to uploads (plan, remove from the plan, re-plan operations) and individual shift/assignment times.

Configuration

In this case, configuration is performed using the [HYDRA Data Management](#). This program is started from the central archiving script hyarc.scr. This program is planned to be run on a daily basis within the [Scheduler](#) by default.

Those data will be deleted the "retention period" of which (see values in the below table) has been exceeded.

Please note: it is not planned to transfer data to archive tables.

Product	Object	Object designation	Transfer	Default interval
HLS	HLSLOG	HLS planning data relevant to uploads (plan, replan, deallocate operations)	Data is deleted within the online dataset. Data is not transferred to the medium-term dataset.	35 days
HLS	PERS_SHIFT	Individual shift/assignment times for planning	Data is deleted within the online dataset. Data is not transferred to the medium-term dataset.	35 days

Deletion by hy_cron.sql

Subject to the given characteristics, [individual shift/assignment times](#) are still deleted using the script hy_cron.sql or the [HYDRA Data Management](#) is already used for this purpose.

To determine which archiving type is in use, check (you or your system administrator) whether or not the script hy_cron.sql includes the below entry within the HYDRA directory on the HYDRA server:

```
delete from hls_pers_schichtm where bearb_date < today - 35;
```

If this is the case, archiving is still performed by the separate deletion script hy_cron.sql.

If the entry does not exist or is commented out by inputting "#" in front of each line, archiving is performed using the [HYDRA Data Management](#) (see above).