

1 MLE Archiving

Overview

MLE archiving is divided into two essential steps:

- In the first step data is transferred from online tables to archive tables. The affected time range can be configured by a program parameter.
- In the second step data is deleted from archive tables. The affected time range can directly be specified via the application.

Moving data to archive tables

Moving data from online tables to archive tables is controlled via the program parameter of the archiving program `hysaparc.exe/out`. If no parameter is specified as supplied with the standard system, all data will be moved from MLE inbound and outbound transactions to archive tables. But the following must apply:

The editing data is less than or equal to the current date minus the program parameter set for archiving.

Proceed as described below to change the default setting (2 days):

- If Windows is used:
MLE tables are archived by starting the script `hyarc.scr` in the HYDRA directory (`HYDRADIR`). This script controls various archiving processes. By default, the script includes the following entry:

```
hysaparc.exe /TL=TRL_ALL /KEEPDAYS_UNKNOWN=60
```

Add the below-mentioned program parameter including the required value to this entry. Using this example, data is transferred to archive tables after 14 days:

```
hysaparc.exe /TL=TRL_ALL /KEEPDAYS_UNKNOWN=60 /ARC_DAYS=14
```

- If Linux is used:
MLE tables are archived by starting the script `hyarc.scr` in the HYDRA directory (HYDRADIR). This script controls various archiving processes. By default, the script includes the following entry:

```
hysaparc.out /TL=TRL_ALL /KEEPDAYS_UNKNOWN=60
```

Add the below-mentioned program parameter including the required value to this entry. Using this example, data is transferred to archive tables after 14 days:

```
hysaparc.out /TL=TRL_ALL /KEEPDAYS_UNKNOWN=60 /ARC_DAYS=14
```

Deleting data from archive tables

The retention period defined for each message type in the MLE distribution model specifies when archive tables are cleared.

The stated retention period starts with the point in time of editing a transaction.



If the period for moving data from online tables to archive tables is increased to 14 days (see example), the retention period should also be 14 days at least. Otherwise, data will immediately be deleted from archive tables.