

1 Archiving in MPL/TRT

Overview

In the MPL product group, data is usually kept online for 7 days before it is moved to the long-term data area.

You can access data older than 7 days in a variety of MPL evaluations/reports. For this purpose, MPL postings are provided in a special medium-term or archive area. This data is largely accessed automatically if the selection period exceeds the short-term data area. In a few applications, the option to "Consider long-term data" is provided in the selection area and can be used to access this data.

The MPL archiving integrates the following data:

Object	DB table online area	DB table archive area
Batch inventory	los_bestand	a_los_bestand
Batch attributes	los_attribute	a_los_attribute
Batch assignments	los_zuordnung	a_los_zuordnung
Batch events	event_los	a_event_los
Material movements	event_mlb	a_event_mlb
Batch logs	mpl_los_prot	mpl_a_los_prot
Batch relations	mpl_beziehungen	a_mpl_beziehungen
Document management	hyd_document hyd_documenttext	a_hyd_document a_hyd_documenttext
Change history	hyd_logging hyd_logging_data	a_hyd_logging a_hyd_logging_data

Configuration

Using HYDRA Data Management, you can configure how long data is to be kept in the different data areas.

The transfer of data into archive tables includes the data with a "retention period" that has expired (in number of days/months/years; see the values in parentheses in the table below). If MPL/TRT archiving is not licensed, data will be deleted after the configured retention period.

Product	Object	Object name	Action	Default interval
MPL	LOSDELETE	Archiving of all batches with batch status "D" (deleted). Affected table: los_bestand (v);(a)	Deletion	0 day
MPL	MPLBAHNVERT	Archiving of all cutting plans whose order number does no longer exist in the table auftrag_status. Affected table: auftrag_status (v) mpl_bahnverteilung (a) mpl_bahnlayout (a)	Deletion	0 day
MPL	LOSAB	Archiving of all batches with batch status "A" (processed), that are not assigned to the material status "V" (packed) or that are not at all assigned to a material status (material status = empty) and where the interval has been exceeded. Affected table: los_bestand (v);(a)	Archiving of online data --> archive tables	7 days
MPL	LOSPACKED	Archiving of all batches with batch status "A" (processed), that are assigned to the material status "V" (packed), the associated merged batch does no longer exist and exceeding the interval. Affected table: los_bestand (v);(a)	Archiving of online data --> archive tables	7 days
MPL	A_LOSBESTAND	Archiving of all batches exceeding the interval. Affected table: a_los_bestand (v);(a)	Export of archive table → file system	2 years
MPL	LOSEXPIRED	Archiving of all batches with batch status "V" (expired) and exceeding the interval. Affected table: los_bestand (v);(a)	Archiving of online data --> archive tables	7 days

Product	Object	Object name	Action	Default interval
MPL	A_LOSEXPIRED	Archiving of all batches exceeding the interval. Affected table: a_los_bestand (v);(a)	Export of archive table → file system	3 years
MPL	LOSLEER	Archiving of all batches with a status that is not "L" (running), with zero quantity and exceeding the interval. Affected table: los_bestand (v);(a)	Archiving of online data --> archive tables	7 days
MPL	LOSMATPUF	Archiving of all batches with a status that is not "L" (running), that are not assigned to a material buffer or the assigned material buffer does no longer exist and exceeding the interval. Affected table: los_bestand (v);(a)	Archiving of online data --> archive tables	7 days
MPL	LOSWASTEBASKET	Archiving of all batches with a status that is not "L" (running), that are assigned to a material buffer identified as "recycle bin" and exceeding the interval. Affected table: los_bestand (v);(a)	Archiving of online data --> archive tables	1 day
MPL	LOSTRANSPORT	Archiving of all batches with batch status "T" (transport) Affected table: los_bestand (v);(a)	Archiving of online data --> archive tables	0 day
MPL	LOSZUORD	Archiving of all batch assignments if both batches belonging to the assignment do no longer exist in the table los_bestand. Affected table: los_bestand (v) los_zuordnung (a)	Archiving of online data --> archive tables	-
MPL	A_LOSZUORD	Archiving of all batch assignments if both batches belonging to the assignment do no longer exist in the table a_los_bestand. Affected table: a_los_bestand (v) a_los_zuordnung (a)	Export of archive table → file system	See above

Product	Object	Object name	Action	Default interval
MPL	LOSPROTOKOLL	Archiving of all batch logs with batches no longer existing in the table los_bestand. Affected table: los_bestand (v) mpl_los_prot (a)	Archiving of online data --> archive tables	-
MPL	LOSEVENTMLB	Archiving of all batch events "material movement" with batches no longer existing in the table los_bestand. Affected table: los_bestand (v) event_mlb (a)	Archiving of online data --> archive tables	-
MPL	A_LOSEVENTMLB	Archiving of all batch events "material movement" exceeding the interval. Affected table: a_event_mlb (v);(a)	Export of archive table → file system	2 years
MPL	LOSEVENTMLB2	Archiving of all batch events with a batch number of "null", "", or "@" in the table event_mlb and exceeding the interval. Affected table: event_mlb (v);(a)	Archiving of online data --> archive tables	7 day
MPL	LOSATTRIBUTE	Archiving of all batch attributes with batches no longer existing in the table los_bestand. Affected table: los_bestand (v) los_attribute (a)	Archiving of online data --> archive tables	0 day
MPL	A_LOSATATTRIBUTE	Archiving of all batch attributes with batches no longer existing in the table a_los_bestand. Affected table: a_los_bestand (v) a_los_attribute (a)	Export of archive table → file system	See above
MPL	LOSEVENTLOS	Archiving of all batch events batches exceeding the interval. Affected table: event_los (v);(a)	Archiving of online data --> archive tables	35 day

Product	Object	Object name	Action	Default interval
MPL	LOSRELATIONS	Archiving of all relationship data exceeding the interval. Affected table: mpl_beziehung (v);(a)	Archiving of online data --> archive tables	35 day
MPL	A_LOSRELATIONS	Archiving of all relationship data exceeding the interval. Affected table: a_mpl_beziehung (v);(a)	Export of archive table → file system	2 years
MPL	DOCLINK	Archiving of all hyd_documente with batches no longer existing in the table los_bestand. Affected table: los_bestand (v) hyd_document (a) hyd_documenttext (a)	Archiving of online data --> archive tables	0 day
MPL	A_DOCLINK	Archiving of all hyd_documente with batches no longer existing in the table a_los_bestand. Affected table: a_los_bestand (v) a_hyd_document (a) a_hyd_documenttext (a)	Export of archive table → file system	See above
MPL	CHANGELOG	Archiving of all change logs exceeding the interval. Affected table: hyd_logging (v);(a)	Archiving of online data --> archive tables	35 day
MPL	A_CHANGELOG	Archiving of all change logs exceeding the interval. Affected table: a_hyd_logging (v);(a)	Export of archive table → file system	3 years
MPL	DEMAND	Archiving of material-related requirements Affected table: demand_request (v);(a) demand_acknowledge (v);(a)	Archiving of online data --> archive tables	14 day
MPL	A_DEMAND	Archiving of material-related requirements Affected table: a_demand_request (v);(a) a_demand_acknowledge (v);(a)	Export of archive table → file system	2 years

(v) = table used to compare entries.

(a) = table including the entries to be archived.

Configuration of material-related requirements (interface EIS-WMS)

The objects "DEMAND" and "A_DEMAND" are used with the interface EIS-WMS.

Material-related requirements are identified by the value "L" in field LEVEL in the interface.

For information on the interface EIS-WMS, follow the link: [Interface to Warehouse Management Systems](#).

Product	Object	Object name	Action	Default interval
MPL	DEMAND	Archiving of material-related requirements Affected table: demand_request (v);(a) demand_acknowledge (v);(a)	Archiving of online data --> archive tables	14 day
MPL	A_DEMAND	Archiving of material-related requirements Affected table: a_demand_request (v);(a) a_demand_acknowledge (v);(a)	Export of archive table → file system	2 years

(v) = table used to compare entries.

(a) = table including the entries to be archived.