

1 Further MLE Escalations

Event	Description	Identifications	Description	Notes
SAP.INBOUND_NOC ONNECT	No connection to SAP possible (HYDRA inbound)	LOGSYS	Log. System, for which no connection can be established.	This event will be triggered if the RFC server cannot connect to SAP and/or cancels an existing connection.
		ROLE	Active role for the log. system	
		HOST	SAP system (name or IP)	
		GATEWAY	Gateway on the SAP server	
		RFCERRGRP)*1	RFC failure group 1	
		RFCERRKEY)*1	RFC error key	
		RFCERRMSG)*1	RFC error message	
SAP.INBOUND_FILE _MOVE_ERR	Error copying/ moving the files at the file port	MESTYP	Message type	This event will be triggered if it is not possible to write new files in the HYDRA file port inbound processing.
		MESFCT	Message function	
		WORKPATH	Work directory	
		IFPATH	Interface path	
SAP.INBOUND_NO_ DIST_MODEL	No distribution model for a message type at the HYDRA mySAP inbound processing	MESTYP	Message type	This event will be triggered if there is no distribution model for a message type in HYDRA mySAP inbound processing.
		TAID	Transaction number	
		VERWEIS	Reference of the IDoc	
		IDOCNUM	IDoc number of the IDoc	
SAP.INBOUND_DISP _DS_ERROR	Incorrect data record in the HYDRA mySAP inboundprocessing	MESTYP	Message type	This event will be triggered if at least one data record is missing in HYDRA mySAP inbound processing.
		TAID	Transaction number	
		VERWEIS	Reference of the IDoc	
		IDOCNUM	IDoc number of the IDoc	
SAP.INBOUND_DISP _DS_UNKNOWN	Unknown data record in the HYDRA mySAP inbound processing	MESTYP	Message type	This event will be triggered if at least one data record is unknown in HYDRA mySAP inbound processing.
		TAID	Transaction number	
		VERWEIS	Reference of the IDoc	
		IDOCNUM	IDoc number of the IDoc	
SAP.INBOUND_DISP _IDOC_ERROR	Incorrect IDoc in the HYDRA mySAP inbound processing	MESTYP	Message type	This event will be triggered if the complete IDoc could not be processed in HYDRA mySAP inbound processing.
		TAID	Transaction number	
		VERWEIS	Reference of the IDoc	
		IDOCNUM	IDoc number of the IDoc	
SAP.OUTBOUND_L OGON_FAILURE	Logon error in the confirmation of data to SAP	LOGSYS	Logical system	This event will be triggered if it is detected during the confirmation of data to SAP that a confirmation is not possible since the CPIC user is blocked.
		ROLE	Active role of the logical system	
		HOST	SAP destination computer of the confirmation	
		USR	CPIC user for confirmations to SAP	
		RFCERRGRP)*1	RFC failure group 1	
		RFCERRKEY)*1	RFC error key	
		RFCERRMSG)*1	RFC error message	
SAP.OUTBOUND_N OCONNECT	No connection to SAP possible (HYDRA outbound)	LOGSYS	Logical system	This event will be triggered if the RFC client cannot establish a connection to SAP.
		ROLE	Active role of the logical system	
		HOST	SAP destination computer of the confirmation	

Event	Description	Identifications	Description	Notes
		USR	CPIC user for confirmations to SAP	
		RFCERRGRP)*1	RFC failure group 1	
		RFCERRKEY)*1	RFC error key	
		RFCERRMSG)*1	RFC error message	
SAP.HYINFO_EXCEPTION	Exception (error) in the HYINFO function module in SAP	LOCLTID	Transaction number of the connection concerned	This event will be triggered if an exception (error) occurs in the HYINFO function module in SAP that prevents further processing.
		MESTYP	Message type	
		RFCERRGRP)*1	RFC failure group 1	
		RFCERRKEY)*1	RFC error key	
		RFCERRMSG)*1	RFC error message	
SAP.OUTBOUND_FILE_STILL_THERE	Error in copying/moving the files at the file port	MESTYP	Message type	This event will be triggered if no new files can be written in the HYDRA file port outbound processing since already existing files are not called by the partner system.
		MESFCT	Message function	
		WORKPATH	Work directory	
		IFPATH	Interface path	
MLE.INBOUND_BAPI_ERROR				Escalation extended by the complete result string of the BAPI call.

