

1 SAP.OUTBOUND_FM_POST_ERROR

Description

Prerequisites:



hysapupl.exe/out V8.1.1.91

db_sql/dbp_esk_sap_outbound_fm_post_error.hsc

The event SAP.OUTBOUND_FM_POST_ERROR is provided as event if the required conditions are given within the application. The following basic requirements have to be met in order for the event to be provided:

- A synchronous or transactional communication is established with SAP, whereas MES acts as RFC client (i.e. actively starts communication).
- The function module (a normal function module or BAPI) started in this context optionally provides:
 - An error structure of the type BAPI* (i.e. e.g. BAPIRET1, BAPIRET2, BAPIRETURN or others) as export parameter.
 - An error structure of the BAPI* (i.e. e.g. BAPIRET1, BAPIRET1, BAPIRETURN or others) as table parameter.
 - Explicit exceptions.

If these conditions are met, the event will be provided in the following cases:

- If it is a business error

In this case the fields of the BAPI return structures include the error message's user data, provided that the module supports them.

Subject to the module, business errors can also be provided by exceptions. In this case, RFC fields include more detailed information on the error type.

- If it is an RFC communication error

In this case, RFC fields include more detailed information on the error type.

Further details about the exact data and how they are provided can be found in the relevant descriptions about interfaces, as they each start individual modules. Irrespective of the individual characteristics, the event provides the following data:

- TID (Key1)
Unique number generated during communication with the external system.
- SAP.FB - technical name of the function module / BAPI (Key 2)
Provides the name of the SAP function module – it matches exactly the technical name of the module from the Function Builder (SE37) in SAP.
- TYPE - from the RETURN structure of the BAPI (Key 3)
The parameter may have the following values:
'S' for success messages
'E' for errors
'W' for alerts
'I' for information messages
'A' for interruptions
- ID - from the RETURN structure of the function module / BAPI (Key 4)
ID of an SAP message from table T100. This ID summarizes messages pertaining to a specific component.
- NUMBER - from the RETURN structure of the function module / BAPI (Key 5)
Number of an R/3 message from table T100
- MESSAGE= from the RETURN structure of the function module / BAPI
Text of the message
- LOG_NO - from the RETURN structure of the function module / BAPI
Uniquely identifies a protocol/log
- LOG_MSG_NO - from the RETURN structure of the function module / BAPI
The internal, consecutive number of the message within a protocol.
This number does not necessarily represent the chronological order.
- MESSAGE_V1 - from the RETURN structure of the function module / BAPI
One of up to four values that can be used in variables of a T100 message. Variables are replaced in the order in which they appear in the message text.
- MESSAGE_V2 - from the RETURN structure of the function module / BAPI
One of up to four values that can be used in variables of a T100 message. Variables are replaced in the order in which they appear in the message text.

- MESSAGE_V3 - from the RETURN structure of the function module / BAPI
One of up to four values that can be used in variables of a T100 message. Variables are replaced in the order in which they appear in the message text.
- MESSAGE_V4 - from the RETURN structure of the function module / BAPI
One of up to four values that can be used in variables of a T100 message. Variables are replaced in the order in which they appear in the message text.
- RFCERRGRP - from RFC communication
RFC error group
- RFCERRKEY - from RFC communication
RFC error key
- RFCERRMSG - from RFC communication
RFC error message
- RFCEXC= from RFC communication