

1 Data container Z2BAPI000

The base structure Z2BAPI000 is used as basis to transfer data from external systems. Depending on the data type, different posting and IDoc types will be used. The segment structure Z2BAPI000, however, is always the same.



To create the segment name Z2BAPI000 in SAP, it must also be generated in SAP according to the scheme Z1 <Segment name>. Versioning in SAP outbound processing is then used to generate the segment names of the form Z2 <Segment name><Version>.

Example: **Z1BAPI** becomes **Z2BAPI000**

The segment consists of the following 3 fields:

Field	Type	Length	Description
TRANSACTION	CHAR	20	Name of the transaction in HYDRA (Dialog identification in HYDRA)
DESC	CHAR	40	Comment
DATA	CHAR	940	Dialog data string for HYDRA

The TRANSACTION field contains the control command that is also transferred in the DATA field. It has no function here and is only used for information purposes.

The DESC field can be used to transfer a comment text describing the operation.

The DATA field is used to transfer the user data. The transfer is realized in the HYDRA HYBAPI format, i.e. a dialog data string composed of the control command and the user data is transferred. The control command is always transferred with the "DLG=" acronym followed by the command itself. The control command is followed by several data identified by a dialog identification and separated by "|". The dialog string itself must be terminated by a pipe "|".

