

1 Data Collection in HYDRA-BDE

1.1 1.1 Summary

In HYDRA data is generally recorded by collecting and processing dialogs. Processing of a dialog results in events that are the basis for updating (calculation of statuses) and posting (generation of log records).

Core functions of data acquisition are the functions to resolve dialogs into events as well as checking and processing functions that lead to the generation of events within the system.

Dialogs

Dialogs represent the system's interface with the shop floor.

Events are generated by resolving the dialog. Resolving of the dialog into individual events is performed based on dialog data, the processing logic of the dialog (incl. configurations) and the context of the dialog (posting status).

Some of the HYDRA-BDE input dialogs are:

Dialog	Meaning
A_AN	Log operation on
A_P_AN	Log operation and person on (together)
A_TR	Confirm/upload OP partially
A_UN	Interrupt operation
A_AB	Log operation off
P_AN	Log person on
P_AB	Log person off
P_AAB	Log all persons off (1... n P_AB)
SA_AN	Log merged operation on
SA_TR	Partial upload of merged operation
SA_AB SA_ABME	Log merged operation off

Events

Events result from resolving dialogs and are thus the result of data input. Which events get to the system at what times, as a result, represents an important point of controlling the software.

Further, partly optional, data acquisition functions are:

- logging of the dialog and the resulting event,
- provision of the posting result,
- provision of current information in the form of lists (e.g. machine lists, order lists),
- escalations.