

1 Mapping of the SAP-PMCC3 in HYDRA

Summary

In the course of a connection of HYDRA to SAP PM, HYDRA must collect PM-relevant data and transfer them to SAP. The base data here are PM-maintenance and service orders transferred from SAP to HYDRA.

The download trigger for PM-maintenance orders (PP-PDC / CC3) comes from SAP. The data are transferred as IDoc (intermediate document) and maintained in HYDRA.

The upload of the confirmations for PM maintenance orders is controlled via SAP in accordance with the requirements specified by the user.

To realize the communication with the BDE subsystems, SAP provides several IDocs via the PP-PDC interface. The following IDocs are used:

Download of PM maintenance orders (PP-PDC/ CC3):

IDoc type:	OPERA3
Message type:	OPERA3
Message function:	APP/ DEL/ UPD
Segment type:	OPERA3

Download of PM upload requests (PP-PDC/ CC3):

IDoc type:	REQUI3
Message type:	REQUI3
Message function:	REQUI3
Segment type:	REQUI3

Upload of confirmations of maintenance orders (PP-PDC/ CC3):

IDoc type:	CONF32
Message type:	CONF32

Segment type: CONF5

Download of operation data SAP → HYDRA

The operations are transferred in an IDoc of the *OPERA3* type. This may be an initial, delta or deletion download.

The upload request is transferred in an IDoc of the *REQUI3* type. When this is received in HYDRA, confirmations that exist already in HYDRA interface tables will be transferred to SAP.

Upload of confirmations HYDRA → SAP

Confirmations are uploaded either cyclically from HYDRA or from SAP R/3. The interface offers numerous options to this end so that the specific requirements can be mapped.

The transfer of confirmations/uploads to SAP R/3 is either controlled by HYDRA or by SAP R/3 and is made in an IDoc of the *CONF32* type.

