

1 Escalation Management - Summary

Summary

HYDRA Escalation Management provides a framework of functions for forwarding events occurring or entered in HYDRA to individual users or user groups in real time. In this context, Escalation Management actively undertakes notification steps.

After sending a notification, Escalation Management monitors the time it takes the notified person to acknowledge the notification and the time until the escalation is closed. Escalations can be forwarded to other users or user groups during processing.

Implementation Notes

You use the HYDRA escalation management module if you want to be notified actively and in realtime about specific events in the production environment to avoid breakdowns through immediate reaction and to increase efficiency as well as productivity.

You use the HYDRA escalation management module if you want to monitor response times to escalations of certain departments or people.

Integration

HYDRA Escalation Management provides a framework for further HYDRA components to be able to forward and trace back triggered events.

To be able to inform people, the escalation management module refers to the HYDRA user administration (see the SIS-MWV component) as well as to the HR master data defined in HYDRA (see SIS-IPS component).

If the collection and maintenance of labor times (PZE-EPP) component is in use, the escalation management allows for the recipient to be determined subject to the currently recorded attendance time in the company.

Notifications may also be sent by e-mail as the module is integrated with the local mail server.

Functions

The HYDRA Escalation Management provides the following functions:

- Definition of the recipient:
 - Assignment of individual people as recipient of messages

- Summary of several individual people to a function group as recipient of a message
- Notification of the user:
 - Notification of users of MES Operation Cockpit in MOC
 - Notification of recipients by e-mail
- Integration with HR:
 - Check whether recipients are present by comparing the people's attendances and absences recorded using HYDRA-PZE
 - Definition of representatives, provided that the employee to be informed originally is not available (information from above-mentioned comparison)
- Dispatch of messages on the basis of flexible configuration of conditions
- Management of messages:
 - Signing function for messages/forwarded messages to MOC
 - Possibility to forward a message to another user
 - Reports on traceability of escalations and monitoring of response times
- Provision of escalations:
 - Trigger of an escalation, provided that a valid recipient could not be determined
 - Trigger of an escalation for undealt/unprocessed escalations

Structure of components

The Escalation Manager is the heart of Escalation Management. It is a continuously running process (hyeskmgr.out/hyeskmgr.out) which receives events generated by individual applications and checks whether escalations have been configured for these events. If this is the case, the Escalation Manager creates messages for users or user groups according to the configuration and for the communication technologies that are stored.

The individual HYDRA applications generate the events. The reasons for events may be, for example, errors or exceptional situations (e.g. hard disk is full). But events can also be the result of "normal" data collection and processing in HYDRA (e.g. if a new machine status is entered at the terminal).

In these cases, the applications create an event. This event is characterized by a unique designation that applies for the entire system. The applications also transfer data to the Escalation Manager. The event determines the type and scope of the transferred data. In many cases, this data can be used as condition in the configuration, and it may also be integrated in the messages to be sent.

Not all applications can generate a message on their own in all error cases or exceptional situations (e.g. a terminal cannot report that it is currently offline). For this reason, the Escalation Manager provides another component that is called Escalation Agent. The Escalation Agent cyclically checks the current status of values that have been assigned to cyclical monitoring. The Control Agent sends the affected event to the Escalation Manager if violations are detected during monitoring. Once per hour the Escalation Manager updates its internal list of configured events with the cyclical events stored within the database.

Available Escalations

The HYDRA Escalation Management, as it is described in this documentation, is an integral part of the HYDRA MESWeaver. Escalations are triggered by individual applications which are to be assigned to the individual HYDRA modules. Furthermore, available escalations depend on the different release versions. For this reason, please find below a list indicating the available escalations for the corresponding release and module in separate documents.

HYD-ESK Module

Event	Description	ID	Description	Please Note
ESK.NO_PERSON_AVAILABLE	No person available	ESK.ESKID	Event for which no person could be determined	The event is triggered if no active person could be determined within a functional group, when checking attendance times using the console and/or HYDRA-PZE .
		ESK.ESKBEZ	Event description	
		ESK.RCV:FKT	Functional group of recipients	
ESK.UNPROCESSED_ESCALATION	Undealt escalation	ESK.ESKVERWEIS	Event ID Unique event ID displayed in the escalation management module and that consists of the event and the unique reference .	The event is triggered if an escalation that occurred remains undealt.
		ESK.VERWEIS	Reference Unique reference to the event	
		ESK.ESKID	Event	
		ESK.ESKBEZ	Description of the event	
		ESK.MSGSUBJ	Subject of the message	
		ESK.MSGTXT	Text of the message	

Event	Description	ID	Description	Please Note
		ESK.DATB	Triggering date	
		ESK.ZEIB	Triggering time	
		ESK.DAUER	Duration (in seconds)	
		ESK.RCV:ART	Recipient type	
		ESK.RCV:BEARB	The recipient's user name	
		ESK.RCV:PNR	The recipient's personnel number	
		ESK.RCV:FKT	Functional group of recipients (if available)	
		PNR.PVORNAME	The recipient's first name	
		PNR.PNAME	The recipient's last name	
		ESK.RCV:BEZ	Recipient	
HYD.LOCKED_RECORD	Blocked record data	LOCK.APPLICATIO N	The application that is blocked!	The event is triggered if a blocked record blocks processing in the "hyd_lock" table (e.g. if uploads come to a halt)
		LOCK.USR	User who activated the block	
		LOCK.BEARB	Editor who activated the block	
		LOCK.MODUL	HYDRA module which activated the block	
		LOCK.KEY:1 LOCK.KEY:5	Values that are blocked	
		LOCK.DAT	Blocking date	
		LOCK.ZEI	Blocking time	
		LOCK.DURATION	Blocking duration	