

1 MOC Update Package Creator

1.1 Overview

Menu	Extras → Generate update package
Transaction code	
Function authorization	mupc

You can generate update packages with the "MOC Update Package Creator". You can create packages for the MOC client and for the server. You use the Maintenance Manager to install the generated update packages on the server. The MOC updates are distributed via the MOC updater.

You mainly use the MOC Update Package Creator to generate updates for the deployment of applications and services that you have developed using the MES Development Suite. You can also use the generated update packages to distribute the configurations that you have made locally in the MOC.

The MOC Update Package Creator is available in German and English. The MOC Update Package Creator is an independent Windows application. Therefore, the Update Package Creator does not use the language set in the MOC, but the language set in the operating system.

Experienced users can start the MOC Update Package Creator via the Windows command line from the installation directory of the MOC or via a link. Enter the language using command line parameters.



MOCUPC.exe path=<MOC_inst_path> l=<language> s=<scope>

<MOC_inst_path>: path of the MOC installation

<language>: language ("en" or "de")

<scope>: "local" or "custom" (custom only for MPDV or partner)

Example: D:\Moc>MOCUPC.exe path=d:\moc l=en s=local

After start of the MOC Update Package Creator, two tabs are available: One tab for the generation of MOC packages and one for server packages. You must generate separate update packages for MOC and server.

1.2 Generate MOC packages

The screenshot shows the 'MOC Update Package Creator' application window. The 'MOC-Package' tab is selected. The main heading is 'Create MOC update package'. The 'Path-Selection' section has two text boxes: 'Folder, which contains the relevant files for the update:' with the path 'D:\MOC\' and 'Folder that contains the generated update, once it has been created:' with the path 'D:\tmp\MOC-Packages'. The 'Update-Information' section has 'Update filename:' set to 'U_Units', 'Version number' set to '1.0.MOC.10', and 'Brief description of the update:' set to 'Customized App Units'. There are 'Load', 'Save', and 'Delete' buttons. The 'Domain-Information' section has 'Configuration level:' with 'local' selected. A tree view shows the file structure: 'local' (expanded) contains 'conf' (checked), 'resources' (unchecked), and 'Apps' (checked). 'Apps' contains 'TerminalConfiguration' (unchecked), 'Units' (checked), 'MainMenu.config' (unchecked), and 'System.config' (unchecked). A 'Generate update package' button is at the bottom.

For the generation of MOC packages, you must select the files in a tree view that you want to include in the update. You can save the selected files in "update package profiles". Later, you can reload these profiles and generate a new package with the same files.

The packages include a version number. The last created version number is saved in the "update package profile". If you create a new version of the same package, you can easily identify the last version and increase the number by one.

Field description

Folder, which contains the relevant files for the update

This field shows the installation directory of the MOC, which includes the configurations or adjustments. On start of the MOC Update Package Creator, the system populates this field with the correct entry. The folder with the relevant files for the update includes the subfolders with the selected configuration scope ("local" or "custom").

Folder that contains the generated update, once it has been created

The generated updates are stored in this folder. This folder must already exist. It is not created automatically.

Update file name

Name of the update file. The file name of the update is also the name of the update package profile if you save the profile.



The update name must not include blank characters or umlauts.

Brief description of the update

This description is, e.g., displayed in the update overview of the Maintenance Manager.

Version number

MOC packages include version numbers. You can only install packages with the same name in the Maintenance Manager, if they have a higher version number. The version number is automatically populated. The version number that has been created last is entered here. The update overview of the Maintenance Manager also shows the version.

Version numbers should have the following format: "<x>.<y>.<customer abbreviation>.<zzzz>", e.g. "1.1.CUST.17".

Configuration scope

The configuration scope "local" includes the developments of the customer. The configuration scope "custom" is used by MPDV or the MPDV partners.

File selection (tree view)

Select the files in the tree view that you want to include in the update.

Load/Save/Delete Update Package Profile

The system uses the name of the field "Update file name" for the administration of the update package profiles. The saved profiles include the following information:

- Folder that contains the generated update once it has been created
- Update file name
- Short description of the contents

- Last created version number
- Configuration scope
- The files that you have selected in the tree view

If you load an existing profile, you should check in the tree view, if new files have been added since the last time the profile was saved in the directory structure. If required, you must activate the new files and add them to the profile by saving the profile again.

Click the button "Generate update package" to create the update package. The Maintenance Manager can then install the update package in the server.

In the MOC clients, the updates are usually installed with the MOC Updater. You can immediately search for updates, if you select in the menu: Help → Search for updates.

1.3 Generate server packages

The screenshot shows the 'MOC Update Package Creator' application window with the 'Server-Package' tab selected. The window title is 'MOC Update Package Creator'. The main heading is 'Create server update package'. There are three sections: 'Path-Selection', 'Update-Information', and 'Domain-Information'.

Path-Selection

Development directory, which contains the domains for the update:
Path: ...

Folder that contains the generated update, once it has been created:
Path: ...

Update-Information

Package name: Brief description of the update:

Domain-Information

Domain(s) in the development directory: Set standard version:

	Domain	Add	Allocate version (only by adding)
☐	AbsenceReasons	☐	
☐	IncentiveBonuses	☐	
☒	MyTest	☒	1.1.CUST.1

You use "Server packages" to distribute server data of the MPDV repository. You can also use server packages to distribute JAVA artifacts that you have developed yourself using the MES Development Suite (MDS). A list view shows the domains created in the repository.

Activate the domains in the list view that you want to include in the update package. The system assigns version numbers to the domains. With server packages, each domain gets an own version number. The installation in the Maintenance Manager can only be performed, if the domains in the server package have a higher version number than the domain versions that are already installed.

Field descriptions

Development directory, which contains the domains for the update

This field shows the directory where the MPDV Repository Client (MRC) stores the server domains. It is the same path that is entered as "Server source" in the MRC workset.

If you want to use server packages to distribute configuration files and JAVA artifacts that you have developed yourself using the MES Development Suite (MDS), you must store these files and artifacts in the domain directory structure of the MRC.

<Source directory>/

<Domain1>/

Interpreter/

List Interpreter and BAPI interpreter configurations

ReferenceData/

Reference data configurations

ExtSvc/

JAVA Class files of the Simple External Services (including package structure)

ExtSvcMapping/

Mapping configuration files of the SimpleExternalServices

User exit/

JAVA Class files of the User Exits (including package structure)

<Domain2>/

...



Folder that contains the generated update, once it has been created

The generated updates are stored in this folder. This folder must already exist. It is not created automatically.

Package name

Name of the update file. The Update Package Creator automatically adds "-server" to the file name. You can therefore use the same name for the client and the server package.



The update name must not include blank characters or umlauts.

Brief description of the update

This description is, e.g., displayed in the update overview of the Maintenance Manager.

Set standard version,**Complete column "Version" in the domain table**

With the server package, a version is required for each domain. If you enter a version number in the field "Set standard version", this version number is assigned to all domains that are activated in the list. You can also assign individual version numbers for activated domains. If the field "Set standard version" is left empty, you must assign an individual version to each activated domain.

Version numbers should have the following format: "<x>.<y>.<customer abbreviation>.<zzzz>", e.g. "1.1.CUST.17".

Domain selection (list view)

The list shows the domains that are included in the development directory. Activate the domains in the list view that you want to include in the update package. The system assigns version numbers to the domains.

Click the button "Generate update package" to create the update package. The Maintenance Manager can then install the update package in the server.

The system stores the values of the two fields "Development directory, which contains the domains for the update" and "Folder, which contains the relevant files for the update". When the MOC Update Package Creator is started the next time, the application populates these two fields with the values that were last entered in this field.