

1 Order-related KPIs

Purpose

Different order-related key performance indicators (KPI) and information are not calculated online when requesting data but cyclically by a program started by the HYDRA Scheduler. This affects the following KPIs and information:

KPIs relating to operations

- Transition time - operation
- Wait time - operation

KPIs relating to orders

- Last recorded operation: the yield of the order is taken from this operation.
- Current operation
- Remaining run time of the order: Total of remaining run times (remaining run time formula 1) of its operations
- Remaining run time 2 of the order: Total of remaining run times (remaining run time formula 2) of its operations
- Transition time: order
- Wait time: order

The HYDRA Scheduler automatically calculates KPIs via a batch job with the following configurations.

Requirements

Meet the following requirements to show the above-mentioned KPIs and information in the MOC applications:

- Provide the following programs/files on the server:
 - adekeyfigures.exe/out version 8.1.1.2 or higher
 - adekeyfigures.scr
 - db_sql\dbp_adekeyfigures.hsc version 1.80899 or higher
- Run the following database patches:
 - hydscr db_sql\dbp_adekeyfigures.hsc >.\tmp\ dbp_adekeyfigures.log
 - hydscr db_sql\dbp_adekeyfigures_wait_time_between_ops.hsc
>.\tmp\dbp_adekeyfigures_wait_time_between_ops.log



These patches calculate KPIs for all available operations. This process might take a while depending on the data volume.

Check entries in the two log files:

- Enable the entry "Order Keyfigure Calculation" in the HYDRA Scheduler:

Windows command: `sh.exe ./adekeyfigures.scr AUNR=*`

Linux command: `./adekeyfigures.scr AUNR=*`

Procedure

If the HYDRA Scheduler does not include this entry, use a patch to create it:

- Windows: `hydscr db_sql\dbp_adekeyfigures.hsc`
- Linux: `hydscr.out db_sql\dbp_adekeyfigures.hsc`

Then, enable the entry in the HYDRA Scheduler.

As an alternative, you can also enter the settings manually in the HYDRA Scheduler (please leave unmentioned fields empty):

Field	Value
<i>Command tab</i>	
Type	S (Standard)
Category	F (Fixed)
Visible	Visible
Active	☒
HYDRA user	0
Command (Windows)	<code>sh.exe ./adekeyfigures.scr AUNR=*</code>
Command (Linux)	<code>./adekeyfigures.scr AUNR=*</code>
Comment	Order Keyfigure Calculation
<i>Fixed point in time tab</i>	
Hour	0
Minute	30



We recommend running the program only once a day (at night), as it affects the entire online order data. Customers may only disregard this recommendation in individual cases if it is sure that the entire system load will not be affected.

Result

The following applications, among others, show the calculated data:

- [Order overview](#)
- [Order profile](#)
- [Lean Performance Analysis](#)

1.1 Miscellaneous

Integration of archived orders

HYDRA 7 calculated wait times upon data request. The order overview and order profile showed these wait times. The system calculated all requested data, no matter if they were archived. This has changed with HYDRA 8. HYDRA 8 calculates some KPIs, such as the wait time, at cyclic intervals and stores the result with the object. The Scheduler triggers this cyclic job that "only" integrates online data. Therefore, this calculation does not affect archived data.

If you want to calculate the KPIs for archived order data, you can start the KPI program as of version 8.1.1.6 once or multiple times (depending on the parameters). Normally, the Scheduler triggers this KPI program cyclically.

You can run the program using the following parameters or a combination of these parameters:

- /ARCHIV
- /MAXRUNTIME
- /LAST_LOGOFF

ARCHIV parameter

Only edits archived orders.

MAXRUNTIME parameter

Defines a maximum runtime for the program. Specifies the runtime in minutes. The default value is 60 minutes.

LAST_LOGOFF parameter

Only edits orders with at least one operation finished during the defined period (starting today until the specified LAST_LOGOFF date). Specify the date in the following format: MM/DD/YYYY

If after reaching the maximum runtime, the program identifies that the archive still includes orders that have to be calculated, the program records this information in a log file entitled adekeyfigures.pro. You can find this file here: <System>\err\adekeyfigures.pro.

Example:

```
*****
02.02.16 17:49 max. runtime (30 min) reached => program stop
02.02.16 17:49 please restart the program to calculate 134827 remaining orders!
*****
```

Once the program has calculated all archived orders, the output can look as follows:

```
*****
02.02.16 17:51 keyfigure calculation in archive finished!
*****
```

Example with all available parameters:

- Windows: sh.exe ./adekeyfigures.scr /ARCHIV /MAXRUNTIME=60 /LAST_LOGOFF=01/01/2014
- Linux: ./adekeyfigures.scr /ARCHIV /MAXRUNTIME=60 /LAST_LOGOFF=01/01/2014

Wait time between operations

The patch dbp_adekeyfigures_wait_time_between_ops.hsc generates an INI entry including the following data at the end of processing:

Name: ADEKEYFIGURES
 Section: AG
 Key: WAIT_TIME_BETWEEN_OPS
 Value: Y
 Active ☒

This INI entry activates the calculation of wait times between operations. This processing is quite time-consuming. You should disable the processing, if you do not need the KPI "wait time between operations".