

1 Documentation Complaint Management 8d Report

Usage

The report shows header data for the complaints for one of the failures selected for the 8d report as well as details about this failure and the measures taken.

It makes use of the data from the XML files listed under the item data sources.

Requirements

The 8d report is prepared using the complaintdetail_8d_report_de.dotm template and using the macro-library in hydramacrolibrary.dotm.

Procedure

The report is created by going to the application **ComplaintManagementExport** that can be called up by clicking on the **Output form** button in complaint management - while the failures are selected.

Data sources

The XML data sources are structured hierarchically using counters. There is one XML file for each data record of the upper-level XML file with detailed information about this data record.

1. root-<Counter1>_AnalysisAssignedComplaintFailureType.xml

Contains data about the failure.

Counter1 equals the failures selected in MOC.

1.1. root-<Counter1>-<Counter2>_ComplaintList.xml

Contains the header data from the upper-level complaint.

Counter1 equals the failure that the complaint is assigned to.

Counter2 equals the set of complaints. Because the failure was selected in the context of a specific complaint, this is only one set and Counter2 is therefore always 1.

1.2. root-<Counter1>-<Counter2>_ComplaintDetailList.xml

Contains the header data from the upper-level complaint details.

Counter1 equals the failure that the complaint details are assigned to.

Counter2 equals the set of complaints. Because the failure was selected in the context of a specific complaint and its complaint details were selected, this is only one set and Counter2 is therefore always 1.

1.3. root-<Counter1>-<Counter2>_ComplaintDocuments.xml

Contains data belonging to the documents of the upper-level complaints.

Counter1 equals the failure that is assigned to the complaint with its documents.

Counter2 equals the set of documents.

1.4. root-<Counter1>-<Counter2>_FailureCauses.xml

Contains the causes of the selected failures.

Counter1 equals the failure that the failure causes are assigned to.

Counter2 equals the set of causes.

1.5. root-<Counter1>-<Counter2>-<Counter3>_CompanyAddress.xml

Contains the address data from the upper-level complaint.

Counter1 equals the failure that the complaint with the address data is assigned to.

Counter2 is the result of the structure of the data sources and does not have any specific reference.

Counter3 equals the set of address data. Because the failure was selected in the context of a specific complaint and its complaint details were selected, this is only one set and Counter3 is therefore always 1.

1.6. root-<Counter1>-<Counter2>-<Counter3>_ComplaintDetailMeasure.xml

Contains the measures corresponding to the selected failures.

Counter1 equals the failure that the measures are assigned to.

Counter2 is the result of the structure of the data sources and does not have any specific reference.

Counter3 equals the set of measures.

Structure

The report is made up of a header area and a detail area.

Shown in the header are the data belonging to the upper-level complaints including all of the complaint details **root-<Counter1>-<Counter2>_ComplaintList.xml**, **root-<Counter1>-<Counter2>_ComplaintDetailList.xml** und **root-<Counter1>-<Counter2>-<Counter3>_CompanyAddress.xml** . The only function of the table there is for layout purposes.

Shown in the detail area are the data for the failure, the corresponding measures, causes and documents listed in a table. Linked to this table are **root-<Counter1>_AnalysisAssignedComplaintFailureType.xml**, **root-<Counter1>-<Counter2>_FailureCauses.xml**, **root-<Counter1>-<Counter2>-<Counter3>_ComplaintDetailMeasure.xml** and **root-<Counter1>-<Counter2>_ComplaintDocuments.xml** as data sources.

UserExits used (in the Word macro)

Only the UserExit **UeFillRowFromXmlAfter** is used. Several filtering actions are made in it.

- In the **Causes** table, failures are filtered out that are not of the failure cause type.
- Filtered in the **ShortTermMeasures** table are all measures that are of the short-term type.
- Filtered in the **MediumTermMeasures** table are all measures that are of the medium-term type.
- Filtered in the **LongTermMeasures** table are all measures that are of the long-term type.
- Filtered in the **SuccessMonitoring** table are all assignments that are of the success monitoring type.
- Filtered in the **Prediction** table are all assignments that are of the prediction type.