

1 Documentation of Inspection Results Word Reports

Usage

The certificate shows header data of the inspection requirement as well as inspection results of included characteristics. Data of XML files listed in the section dealing with data sources is used.

Requirements

The certificate is created using the inspectionrequirement_certificate_en.dotm template and the macro library hydramacrolibrary.dotm.

Procedure

Reports are created using the InspectionRequirementExport application that is started by the button "output form" of the initial sample application.

Data sources

1. root-<Zähler1>_ReqList.xml

Includes header data of inspection requirements.

Zähler1 corresponds to the inspection requirement selected in MOC.

1.1. root-<Zähler1>-<Zähler2>_CharList_Req.xml

Includes characteristics of the higher-level inspection requirement and characteristic specifications.

Zähler1 corresponds to the higher-level inspection requirement to which characteristics are assigned

Zähler2 corresponds to the set of characteristics. In the inspection requirements area this is only one set and, as a result, Zähler2 is always 1.

1.2. root-<Zähler1>-1-<Zähler2>_Statistics_Req.xml

Includes the statistical values for the corresponding characteristic.

Subject to the structure of XML files, Zähler2 is always 1.

2. InspectionRequirement_Certificate_de.xml

Includes detail data for print control such as the user name by which the report was requested in MOC.

Structure

The certificate is divided into header area and detail area.

The header area only shows data from **root-<Zähler1>_ReqList.xml**.

The table that is stored there only provides layout functions.

The detail area shows characteristics including corresponding specifications in a structured way within a table.

Root-<Zähler1>-<Zähler2>_CharList_Req.xml is linked to this table as data source.

In the columns “result (xquer)”, “minimum” and “maximum” the cells are merged and include a sub-table listing inspection results. **Root-<Zähler1>-1-<Zähler2>_Statistics_Req.xml** is linked as data sources to this table.

Characteristic	Unit	Result (values average)	Minimum	Maximum	Result attributive
#LINK:qmcharacteristic.designation	#LINK: unit.id	#LINK: characteristicsta tics.xq #LINK: characteristicsta tics.xmin #LINK: characteristicsta tics.xmax			#LINK:qm characteri stic.inspe ction_res ult

Subordinate table

The content of **InspectionRequirement_Certificate_en.xml** is used in the footer only. But it is also available beyond the footer to modify the certificate.

UserExits in use

Only the UserExit **UeFillRowFromXmlAfter** is used. In this UserExit entries of the **CharacteristicList** table are removed from the column “attributive result” (fourth column) if the “variable” value is set in the data element node **/qmcharacteristic.inspection_type.designation_short**.