

1 HYDRA configurations relevant to applications

Deactivation of outbound processing (general)

In most instances HYDRA outbound processing consists of two stages:

- Supply of uploads/confirmations from the data model into [MLE outbound transactions](#)

Specialized programs (e.g. myerprck.exe/out) normally provide the data using cyclic jobs. This results in open data segments in MLE outbound transactions.

The corresponding interface descriptions specify the configurations required for carrying out these jobs.

These jobs must still be active even if the database-based interface is in use.

- Export of provided uploads/confirmations (to the file system / SAP)

The export program "hysapupl.exe/out" is mostly used in order to export the provided, open data segments. In the majority of cases the export program is directly started via the [HYDRA Scheduler](#). But sometimes it can also be started differently.

Starting of the export program must be disabled, provided that data is transferred via the database-based interface instead of exporting it to SAP or the file system.

The documentation dealing with the relevant interface describes how the export program is started.

Disable processing for the EIS-ERP interface (Windows)

The export program hysapupl.exe/out for the EIS-ERP interface is not started via the Scheduler but via a script. Proceed as follows if Windows is used as server operating system:

- Copy the supplied script *myerprck.scr* from the HYDRA directory of the HYDRA server to the customer namespace *u_myerprck.scr*.
- Open the script *u_myerprck.scr* and change starting of "hysapupl.exe" as follows:

Previously:

```
# Starting the upload to generate the upload file HY72ADRCK_TIMETICKET.ASV for
standard uploads/confirmations.

if [ `hyliz.exe -r HYD-ESK` -gt 0 ]

then
```

```
hysapupl.exe /UPLSEGNAM=HY72ADRCK_TIMETICKET
```

```
fi
```

Afterwards:

```
## Starting the upload to generate the upload file HY72ADRCK_TIMETICKET.ASV for
standard uploads/confirmations.
```

```
#if [ `hyliz.exe -r HYD-PPS` -gt 0 ]
```

```
#then
```

```
#    hysapupl.exe /UPLSEGNAM=HY72ADRCK_TIMETICKET
```

```
#fi
```

- Use the customized script in order to start the interface in the [HYDRA Scheduler](#). For this purpose, identify the Scheduler entry meeting the following conditions:

Parameter name	Value
Product key	HYD-PPS
License key	HYD-PPS
Command (prior to the modification)	sh.exe ./myerprck.scr /MESTYP=HY72ADRCK_TT
Command (after the modification)	sh.exe ./u myerprck.scr /MESTYP=HY72ADRCK_TT
Comment	Standard ADE confirmations/uploads for PPS (only if HYD-PPS)

Disable processing for the EIS-ERP interface (Linux)

The export program hysapupl.exe/out for the EIS-ERP interface is not started via the Scheduler but via a script. Proceed as follows if Linux is used as server operating system:

- Copy the supplied script *myerprck.scr* from the HYDRA directory of the HYDRA server to the customer namespace *u_myerprck.scr*.
- Open the script *u_myerprck.scr* and change starting of "hysapupl.out" as follows:

Previously:

```
# Starting the upload to generate the upload file HY72ADRCK_TIMETICKET.ASV for
standard uploads/confirmations.
```

```
if [ `hyliz.out -r HYD-PPS` -gt 0 ]
```

then

```
hysapupl.out /UPLSEGNAM=HY72ADRCK_TIMETICKET
```

fi

Afterwards:

```
## Starting the upload to generate the upload file HY72ADRCK_TIMETICKET.ASV for
standard uploads/confirmations.
```

```
#if [ `hyliz.out -r HYD-PPS` -gt 0 ]
```

```
#then
```

```
# hysapupl.out /UPLSEGNAM=HY72ADRCK_TIMETICKET
```

```
#fi
```

- Use the customized script in order to start the interface in the [HYDRA Scheduler](#). For this purpose, identify the Scheduler entry meeting the following conditions:

Parameter name	Value
Product key	HYD-PPS
License key	HYD-PPS
Command (prior to the modification)	./myerprck.scr /MESTYP=HY72ADRCK_TT
Command (after the modification)	./ u myerprck.scr /MESTYP=HY72ADRCK_TT
Comment	Standard ADE confirmations/uploads for PPS (only if HYD-PPS)