

1 HYDRA Settings Relevant to the Application

	→	
--	---	--

Maintenance of the HYDRA distribution model – inbound

Change existing entries or create new entries in the [HYDRA distribution model](#) for HYDRA inbound processing:

Parameter name	Value
Processing the PPCC2RECORDER IDoc of the PP-PDC interface	
Message type	PPCC2RECORDER
Priority	None
Command	hysapinf.scr
Command parameter	/RECTYPE
Description	PP-PDC / HYINFO – request additional data
Log. target system	Created logical system
Retention period	10
Processing the PPCC2RECORDER IDoc and HYINFO additional data	
Message type	PPCC2HYINFOORDER
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANTE=< MLE version to be used >
Description	PP-PDC / HYINFO transfer of additional data
Log. target system	Created logical system
Retention period	10

No deletion of the operation's material, tool, NC program

If HYDRA receives components, tools, or NC programs for the operation, the system enters the first element transferred for the operation in the corresponding fields "material", "tool" or "DNC". The same applies if the tool is assigned by a production variant/version in the Shop Floor Scheduling module.

In both cases it might be necessary to prevent these operation entries from being deleted when the components and PRT lists are deleted routinely while the system transfers the next operation. You can achieve this by setting the relevant entries in the [HYDRA INI configuration](#):

Parameter name	Value
For the material	
INI name	SAP
Section	E2BP_PP_PDC_OPERA2000
Key	PREVENT_ANR_RES_MAT_FROM_DELETION
Value	Y → yes N → no
Active	Yes
Comment	Prevents the first resource of the type "material" (ID "MAT") included in the component list from being deleted when the component list is deleted.
For the tool	
INI name	SAP
Section	E2BP_PP_PDC_OPERA2000
Key	PREVENT_ANR_RES_WNR_FROM_DELETION
Value	Y → yes N → no
Active	Yes

Parameter name	Value
Comment	Prevents the first resource of the type "tool" (ID "FHM"/"PRT") included in the component list from being deleted when the PRT list is deleted.
For the DNC program	
INI name	SAP
Section	E2BP_PP_PDC_OPERA2000
Key	PREVENT_ANR_RES_DNC_FROM_DELETION
Value	Y → yes N → no
Active	Yes
Comment	Prevents the first resource of the type "DNC resource" (ID "DNC") included in the component list from being deleted when the component list is deleted.

Requirements:



.\custom\userexit\mle_convfield_in.hsc:

V8.1.1.64407

MLE version:

HY72_031

Preventing the call for deletion records

Use an [INI entry](#) if you do not want to request additional data for deletion records:

Parameter name	Value
INI name	SAP
Section	REQUEST_DELETED_OP
Key	PPCC2RECORDER for PP-PDC

Parameter name	Value
	OPERA3 for KK3 OPERA4 for KK4
Value	Y → yes N → no
Active	Yes
Comment	No additional data for deletion records



Requirements:

hysapinf.exe/out:

V8.1.1.41

Preventing the transfer of overdelivery/underdelivery details from record type "AV"

Configure the [HYDRA INI configuration](#) to prevent the overdelivery/underdelivery information from the record type "AV" from being transferred:

Parameter name	Value
INI name	SAP
Section	HYINFO_AV
Key	USE_OVER_UNDER_DELIVERY_CHECK
Value	Y → yes (set by default) N → no
Active	Yes
Comment	Transfers overdelivery/underdelivery data from the HYINFO AV segment

If you use the information interface for SAP PP, you cannot use BAPINOUPDATE for the fields of the following record types:



- Order header data (AK)
- User fields for the header/ operation (AU)
- Operation data (AV)
- Additional texts for the operation (AI)
- Component list (AM)
- Production resources and tools (AF)
- Documents (AC)

Activating the transfer of dialog data strings

Use the following program parameter to activate the transfer of dialog data strings via the HYINFO module in the ZPP_HYBAPI structure when calling the executing program in the script hysapinf.scr:

Call prior to the change (example for Windows):

```
$HY_PATH/hysapinf.exe /TL=TRL_ALL $1 $2 $3 $4 $5 $6 $7
```

Call after the change (example for Windows):

```
$HY_PATH/hysapinf.exe /Z2BAPT000=ADD $1 $2 $3 $4 $5 $6 $7
```



Requirements:

hysapinf.exe/out:

V8.1.1.43

Changing the name of the function module Z_PP_HYINFO_GET

If you cannot use the name of the HYINFO function module given by MPDV (e.g. as internal naming conventions prevent it), you can change this name. To do so, use the following program parameter when calling the executing program in the script hysapinf.scr:

Call prior to the change (example for Windows):

```
$HY_PATH/hysapinf.exe /TL=TRL_ALL $1 $2 $3 $4 $5 $6 $7
```

Call after the change (example for Windows):

```
$HY_PATH/hysapinf.exe /HYINFO_GET=<New Name> $1 $2 $3 $4 $5 $6 $7
```

Changing the name of the table ZPP_HYINFO

If you cannot use the name of the ZPP_HYINFO table given by MPDV (e.g. as internal naming conventions prevent it), you can change this name. To do so, use the following program parameter when calling the executing program in the script hysapinf.scr:

Call prior to the change (example for Windows):

```
$HY_PATH/hysapinf.exe /TL=TRL_ALL $1 $2 $3 $4 $5 $6 $7
```

Call after the change (example for Windows):

```
$HY_PATH/hysapinf.exe /HYINFO_ITAB=<New Name> $1 $2 $3 $4 $5 $6 $7
```

Changing the name of the table ZPP_HYBAPI

If you cannot use the name of the ZPP_HYBAPI table given by MPDV (e.g. as internal naming conventions prevent it), you can change this name. To do so, use the following program parameter when calling the executing program in the script hysapinf.scr:

Call prior to the change (example for Windows):

```
$HY_PATH/hysapinf.exe /TL=TRL_ALL $1 $2 $3 $4 $5 $6 $7
```

Call after the change (example for Windows):

```
$HY_PATH/hysapinf.exe /Z2BAPI_ITAB=<New Name> $1 $2 $3 $4 $5 $6 $7
```

Prevent processing of OPs until HYINFO is processed

Add the following entry to the [HYDRA INI configuration](#) if you want to lock operations until the original data and additional data have been imported completely from the HYINFO module ([MBL SAP Implementation HYINFO FB](#)).

Parameter name	Value
INI name	SAP
Section	E2BP_PP_PDC_OPERA2000
Key	SET_OPS_TO_BLOCKED
Value	Y → yes
Active	Yes

Parameter name	Value
Comment	Locks OPs until HYINFO has been processed

Requirements:

This function requires service pack 14 (or higher) or installation of an update package. The update package must include the following software components:



hymw.exe/out:	V8.1.1.646
hyerror.msg/en	V8.1.1.646
lib\b_anr.dll/so	V8.1.1.356
MLE version	HY72_034
MOC Language Resources	1.0.STD.66720