

1 Application-Relevant Settings in HYDRA

Maintenance of the HYDRA distribution model - inbound processing

Use the [HYDRA distribution model](#) to maintain entries for HYDRA inbound processing:

Name of the parameter	Value
To process PM/ CS production orders	
Message type	OPERA3
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANT= <MLE variant to be used>
Description	PM-CC3 – download PM/ CS orders
Log. target system	Created logical system
Storage duration	10
To process the upload request	
Message type	REQUI3
Priority	High
Command	hysapupl.scr
Command parameter	/UPLSEGNAM=E2CONF5
Description	PP-CC3 – Upload request
Log. target system	Created logical system
Storage duration	10

Maintenance of the HYDRA distribution model - outbound processing

Use the [HYDRA distribution model](#) to maintain entries for HYDRA outbound processing:

Name of the parameter	Value
To upload time tickets	
Message type	CONF32
Description	PP-CC3 – Upload time tickets
IDoc-Typ	CONF32
Storage duration	10
Log. target system	Created logical system
Segment name 1	E2CONF5

Activation of initial download

As of program version

.lib\b_anr.dll V8.1.1.326

the initial download has to be enabled explicitly for security reasons.

Create the following entry in [HYDRA INI configuration](#) if you would like to activate the initial download for the system:

Parameter name	Value
INI name	SAP
Section	INITIAL_DOWNLOAD_ACTIVATION
Key	ACTIV_TILL
Value	<date value in the format MM/DD/YYYY>
Active	Yes

Parameter name	Value
Comment	Activation of initial download