

1 Application-Relevant Settings in HYDRA

Maintenance of the HYDRA distribution model - inbound processing

Use the [HYDRA distribution model](#) to maintain entries for HYDRA inbound processing:

Name of the parameter	Value
To process production orders	
Message type	PPCC2RECORDER
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANTE =< MLE variant to be used >
Description	PP-PDC – Download of production orders
Log. Target system	Created logical system
Storage duration	10
To process the upload request	
Message type	PPCC2REQCONF
Priority	High
Command	hysapupl.scr
Command parameter	/UPLSEGNAM=E2BP_PP_TIMETICKET
Description	PP-PDC – Upload request
Log. Target system	Created logical system
Storage duration	10
To process variances	
Message type	DIFFE2
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANTE =< MLE variant to be used >
Description	PP-PDC – Variances
Log. Target system	Created logical system
Storage duration	10

Name of the parameter	Value
To process general quantity units	
Message type	UNIT2
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANTE =< MLE variant to be used >
Description	PP-PDC – Gen. qty. unit
Log. Target system	Created logical system
Storage duration	10
To process material-dependent quantity units	
Message type	UNIMA2
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANTE =< MLE variant to be used >
Description	PP-PDC – Gen. qty. unit
Log. Target system	Created logical system
Storage duration	10

Maintenance of the HYDRA distribution model - outbound processing

Use the [HYDRA distribution model](#) to maintain entries for HYDRA outbound processing:

Name of the parameter	Value
To upload time tickets	
Message type	PPCC2PRETTICKET
Description	PP-PDC – Upload of time tickets
IDoc type	PPCC2PRETTICKET01
Storage duration	10
Log. target system	Created logical system
Segment name 1	E2BP_PP_TIMETICKET

Activation of initial download

Since program version

.lib\b_anr.dll

V8.1.1.326

the initial download function needs to be enabled explicitly for security reasons.

Create the following entry in the [HYDRA INI configuration](#) if you would like to enable the initial download function for the system:

Parameter name	Value
INI name	SAP
Section	INITIAL_DOWNLOAD_ACTIVATION
Key	ACTIV_TILL
Value	<date in the format MM/DD/YYYY>
Active	Yes
Comment	Activation of the initial download

Behavior when deleting interrupted operations

Specific application functions of the production order or its operations result in a deletion download from SAP to HYDRA. This includes, among other things:

- Setting of a deletion flag
- Technical completion in SAP

By default, data of an interrupted operation will be deleted if the deletion download arrives in HYDRA.

However, special customizing settings within [order status assignment](#) can prevent this process. The following configurations have to be set e.g. for the “interrupted” operation status:

Field	Value
Alterable order data	J or M
Action	E or X