

1 Application-relevant settings in HYDRA

Maintenance of the HYDRA distribution model - inbound processing

Use the [HYDRA distribution model](#) to maintain entries for HYDRA inbound processing:

Name of the parameter	Value
To process production orders	
Message type	PP_PI_PCS_HYDRA_INBOUND
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANTE =<MLE variant to use>
Description	PP-PI – Download of process orders
Log. Target system	Created logical system
Storage duration	10

Maintenance of the HYDRA distribution model - outbound processing

Use the [HYDRA distribution model](#) to maintain entries for HYDRA outbound processing:

Name of the parameter	Value
To upload phase confirmations	
Message type	PI_PHCON
Description	PP-PI – Upload of phase confirmations
IDoc-Typ	PI_PHCON
Storage duration	10
Log. Target system	Created logical system

Name of the parameter	Value
Segment name 1	PI_PHCON

Maintenance of the tRFC-Destination

Also for the MLE upload PP-PI-PCS specific settings have to be applied. In the configuration of [MLE Logical System](#) a new entry has to be applied for the program type "RFC-Client". In that entry the RFC destination name that has been created in SAP has to be provided.

Name of the parameter	Value
RFC_DESTINATION_FPR_TRFC	<Name of the RFC-destination created for HYDRA in SAP (SM59)>

Configuration of the confirmation prefix

In order to be able to transfer confirmations from several HYDRA systems back into SAP PP-PI, a unique identifier has to be applied. In case no INI-entry is given or the value is blank, the value "01" will be used.

This prefix can be configured using [HYDRA-INI-Configuration](#):

Parameter name	Value
INI-Name	PP-PI_PCS
Section	PP-PI-PCS_MSID_PREFIX
Key	KEY
Value	<Value to be used as unique identifier>
Active	Yes
Remark	PP-PI-PCS: Confirmation prefix

Maintenance of the HYDRA Scheduler

Use the [HYDRA Scheduler](#) to maintain entries for HYDRA outbound processing:

Parameter name	Value
To transfer confirmations from the application into the MLE outbound transactions	
Product key	SAP-PPPI
License key	SAP-PPPI
Command (Windows):	sh.exe ./myerprck.scr /MESTYP=PI_PHCON /KAT=FA
Command (Unix):	./myerprck.scr /MESTYP=PI_PHCON /KAT=FA
Comment:	SAP-PPPI: Confirmations → MLE outbound transactions
Intervall	5
To transfer confirmations from the MLE outbound transactions to SAP PP-PI	
Product key	SAP-PPPI
License key	SAP-PPPI
Command (Windows):	sh.exe ./hysapupl.scr /UPLSEGNAM=PI_PHCON /SINGLE_IDOC /SUBLEVEL=2 /SUBPROT=ON /PP-PI-PCS
Command (Unix):	./hysapupl.scr /UPLSEGNAM=BFLUSHDATAMTS /SINGLE_IDOC /SUBLEVEL=2 /SUBPROT=ON /PP-PI-PCS
Comment:	SAP-PPPI: Confirmations MLE outbound transactions → SAP
Intervall	5