

1 Application-Relevant Settings in HYDRA

Maintenance of the HYDRA distribution model – inbound processing

Edit entries for HYDRA inbound processing in the [HYDRA distribution model](#):

Parameter name	Value
For processing of network plans	
Message type	OPERA4
Priority	None
Command	mle72imp.scr
Command parameter	/VARIANTE=< MLE variant to be used >
Description	PS-CC4 – Download of network plans
Log. target system	Created logical system
Storage duration	10
For processing of upload request	
Message type	REQUI4
Priority	High
Command	hysapupl.scr
Command parameter	/UPLSEGNAM=E2CONF7
Description	PS-CC4 – Upload request
Log. target system	Created logical system
Storage duration	10

Maintenance of the HYDRA distribution model – outbound processing

Edit entries for the HYDRA outbound processing in the [HYDRA distribution model](#):

Parameter name	Value
For uploading time tickets	
Message type	CONF42
Description	PS-CC4 – Upload of time tickets
IDoc type	CONF42
Storage duration	10
Log. target system	Created logical system
Segment name 1	E2CONF7

Activation of initial download

As of program version

.lib\b_anr.dll V8.1.1.326

the initial download has to be enabled explicitly for security reasons.

Create the following entry in [HYDRA INI configuration](#) if you would like to activate the initial download for the system:

Parameter name	Value
INI name	SAP
Section	INITIAL_DOWNLOAD_ACTIVATION
Key	ACTIV_TILL
Value	<Date value in the format MM/DD/YYYY>
Active	Yes

Parameter name	Value
Comment	Activation of initial download