

Manual

MES Cockpit Services Manufacturing for 5 individual KPIs MC-SMI 3.2

Version 1.2.23049

Last changed on: 01.09.2020

Copyright

©Copyright 2020 All rights reserved.

SAP® and R/3® are registered trademarks of SAP AG.

WINDOWS® is a registered trademark of Microsoft Corporation.

MPDV® and HYDRA® are registered trademarks of MPDV Mikrolab GmbH.

ORACLE® is a registered trademark of ORACLE Corporation, California, USA.

Copying and distribution of this documentation or any part thereof, for any purpose or in any form, is prohibited without prior written permission from MPDV Mikrolab GmbH.

The information contained in this documentation is subject to change without prior notice.

Contents

1	MES-Cockpit Services Manufacturing for 5 individual KPIs.....	4
2	Formula Management	5
3	Basic KPIs	14
3.1	Object "workplaces"	14
3.2	Object "order"	15
3.3	Object "operation"	16

1 MES-Cockpit Services Manufacturing for 5 individual KPIs

Purpose

You can use the function package "MES-Cockpit Services Manufacturing for 5 individual KPIs" of the MES-Cockpit to change existing KPIs or to create new KPIs that are displayed on the MES-Cockpit. You define the KPIs in the formula management of the administration client. You can use any basic KPI that is available (see below).

2 Formula Management

Summary

Menu	System administration --> System administration --> Formula management
Transaction code	foma
Function authorization	mdfoma

The screenshot displays the SAP Formula Management (FOMA) transaction. The interface includes a top toolbar with various icons for data request, printing, editing, and saving. Below the toolbar is a selection area with fields for 'Formula' and 'Type'. The main area is split into two panes. The left pane shows a list of formulas with columns for 'Formula', 'Type', and 'Comment'. The right pane shows the details for the selected formula 'RLFZ', including its type '3', the formula text, a comment, and an 'Editable' checkbox.

Formula	Type	Comment
RLFZ	Determin. of remaining run t...	Remaining time (release upgrade)
RLZ_ZO	Determin. of remaining run t...	Remaining term based on time
RLZBRU	Determin. of remaining run t...	RRT gross (RPA1-11)/yield x (target qu
RLZNET	Determin. of remaining run t...	RRT net: RPA11/yield x (target quant
RLZVGW	Determin. of remaining run t...	RRT due to default value 3[min]
AQUOTE	Formulas for key figures	Scrap rate
AUSBGD	Formulas for key figures	Output rate
BNGRAD	Formulas for key figures	Assignment utilization rate
IZYCLC	Formulas for key figures	Actual cycle
NGRAD	Formulas for key figures	Capacity utilization rate
SSKGUT	Formulas for key figures	Target quantity per shift
ao	Formulas for MOC	Organizational failure rate
at	Formulas for MOC	Technische Ausfallrate
aw	Formulas for MOC	Maintenance-related failure rate
ng	Formulas for MOC	Gesamtnutzungsgrad
rcu	Formulas for MOC	Capacity utilization rate
rcur	Formulas for MOC	Capacity utilization reserve
ta	Formulas for MOC	Ausfallzeit wegen kurzzeitig fehlender A
tb	Formulas for MOC	Occupancy time
tc	Formulas for MOC	Test time
tn	Formulas for MOC	Nutzungszeit
to	Formulas for MOC	Organizational downtime
tr	Formulas for MOC	Setup time

Usage

Formulas are defined for different purposes within the formula management function, e.g. to convert quantities into alternative units or even to determine process times.

To provide for more clarity the context is respectively defined within the formula management function.

Integration

The formula management function is used by different components within the system. These components are, among others:

- HYDRA Shop Floor Scheduling (HLS): to compute the remaining run time
- MES Link & Enabling (MLE): to calculate default values and/or to determine conditions
- Material & Production Logistics (MPL): Conversion of quantities into other quantity units
- Shop Floor Data Collection (BDE): to compute the processing time
- Shop Floor Data Collection (BDE): to convert quantities into other quantity units
- ←**Selection criteria**

The application provides the following selection criteria:

Formula

Formula name

Type

Restricts the formula types

Field descriptions

Formula

Formula key;

Unique/distinct within the context, e.g. 0001

Type

Formula type, to be able to differentiate them logically

- | | |
|-----|---|
| 1 | Quantity conversion |
| 2 | Determination of process time |
| 3 | Determination of remaining run time |
| 7 | Formulas to restrict composition |
| 8 | Formulas for the composition scrap rate |
| 50 | MLE (MES Link&Enabling) conditions |
| 999 | User-defined |
| 60 | Workplace formula (MES-Cockpit) |
| 61 | Order formula (MES-Cockpit) |
| 62 | Operation formula (MES-Cockpit) |

63 General formulas (MES-Cockpit)

The selected type is decisive for the transfer of formulas and KPIs into MES-Cockpit. As formulas are filtered based on the selected type.

Responsibility area

Assignment of a responsibility area

Comment Designation or description of the formula

Editable

This value is set for the formulas delivered by MPDV; formulas that are configured with "editable = N" can neither be changed nor deleted.

Functions, operators and absolute terms to be used in formulas and conditions

The following operators and expressions may be used to formulate conditions:

Functions	
abs(x)	Calculates the absolute value
atan(x)	Calculates the arc tangent
cosh(x)	Calculates the hyperbolic cosine
float(x)	Converts the value into a floating point number
sqrt(x)	Calculates the square root
acos(x)	Calculates the arc cosine
atan2(y,x)	Calculates the arc tangent of y/x
exp(x)	Calculates the exponential value
log(x)	Calculates the logarithm
sin(x)	Calculates the sine
tan(x)	Calculates the tangent
asin(x)	Calculates the arc sine
cos(x)	Calculates the cosine
int(x)	Converts the value into an integer
log10(x)	Calculates the logarithm
round(x)	Rounds to integer value
round(x,y)	Rounds the value x to y decimal places
sinh(x)	Calculates the hyperbolic sine
tanh(x)	Calculates the hyperbolic tangent
trunc(x)	Reduces the value x to an integer value
trunc(x,y)	Reduces the value x to y decimal places
string(x)	Converts the value into a character string

Operators	
x and y	The AND operator "and" delivers the value 1 (true) if both conditions are TRUE. Otherwise, the value 0 (false) is returned.
x or y	The OR operator "or" delivers the value 1 (true) if one of the conditions is TRUE. Otherwise, the value 0 (false) is returned.
x like y	The relational operator "like" delivers the value 1 (true) if the first operand corresponds to the pattern of the second operand. Otherwise, the value 0 (false) is returned. The pattern may include the following placeholders: "*" --> 0 -n any characters "?"--> exactly one (random) character
!x	The logical negation operator "NOT" returns the value 0 (false) if the value is unequal to 0 (true) and the value 1 (true) if the value is 0 (false).
x + y	Addition
x - y	Subtraction
x / y	Division
x * y	Multiplication
x ** y	Calculates x raised to the power of y
x << y x >> y	The bitwise shift operators shift the first operand to the left (<<) or to the right (>>) by the number of positions specified by the second operand.
x < y	Returns 1 (true) if the value x is less than y, otherwise 0 (false)
x <= y	Returns 1 (true) if the value x is less than or equal to y, otherwise 0 (false)
x > y	Returns 1 (true) if the value x is greater than y, otherwise 0 (false)
x >= y	Returns 1 (true) if the value x is greater than or equal to y, otherwise 0 (false)
x == y	Returns 1 (true) if the value x is equal to y, otherwise 0 (false)
x != y	Returns 1 (true) if the value x is unequal to y, otherwise 0 (false)
x & y	The bitwise AND operator compares every bit of the first operand with the corresponding bit of the second operand. If both bits are 1 the bit is set to 1 in the resulting value. Otherwise, the bit is set to 0 in the resulting value.
x ^ y	The bitwise Exclusive-OR operator compares each bit of the first operand with the corresponding bit of the second operand. If one bit is 0 and the other bit is 1 the bit is set to 1 in the resulting value. Otherwise, the bit is set to 0 in the resulting value
x y	The bitwise Inclusive-OR operator compares each bit of the first operand with the corresponding bit of the second operand. If one bit is 1 the bit is set to 1 in the resulting value. Otherwise, the bit is set to 0 in the resulting value.

Absolute term (constant)	
pi	3.141592654
e	2.718281828

Please note for the definition of formulas in MES-Cockpit

Formula definitions used for MES-Cockpit provide the following features:

- Reference to other formulas

By stating @(<formula2>) a calculation can be based on an existing formula

- Definition of conditions

Field contents can be checked by defining conditions. Example: `if(w.cycle.target > 0, w.rpa11, 0)`

→ The duration posted on the resource performance account should only be integrated in the calculation if the target cycle is greater than 0.

Utilization in HYDRA-BDE (Shop Floor Data Collection)

Formulas can be used to calculate the following values (provided that they are not collected explicitly):

- Waiting time
- Setup time
- Processing time
- Inspection time
- Teardown/retooling time
- Target cycle The target cycle has been designed to monitor machines on the basis of cycles within the scope of machine data collection (HYDRA-MDE).
- Remaining run time The remaining run time of an operation is computed on the basis of the formula that is defined for the operation (tab durations > RRT formula).
→→→→→

The corresponding formula fields of the operation refer to the respective formulas defined in the formula management function. In addition to the basic arithmetic operations, it can be referred to the operation fields listed below. These are fields that are defined as target values for the operation and fields that are available as status information (actual values).

Target values at the operation

Target quantity: base quantity unit	ANR.SGR:GUTB
Target quantity: primary quantity unit	ANR.SGR:GUTP / ANR.SGR:GUT
Target quantity: secondary quantity unit	ANR.SGR:GUTS
Target quantity: tertiary quantity unit	ANR.SGR:GUTT
Target scrap: base quantity unit	ANR.SGR:AUSB
Target scrap: primary quantity unit	ANR.SGR:AUSP / ANR.SGR:AUS
Target scrap: secondary quantity unit	ANR.SGR:AUSS
Target scrap: tertiary quantity unit	ANR.SGR:AUST
Unit quantity	ANR.EINHMENGE
Target cycle	ANR.SZY
Partitioning	ANR.TLG
Factor	ANR.IMPFAKT
Waiting time	ANR.WARTZ
Setup time	ANR.RUEZ
Additional setup time (due to setup change)	ANR.RUEZ:ZUSCHL
Processing time	ANR.BEARBZ

Target values at the operation

Inspection time	ANR.PZ
Teardown/retooling time	ANR.ABRZ
Delivery time	ANR.LIEZ
Transport time	ANR.TPZ
Delivery time (external production)	ANR.LIZ
Number of splits	ANR.ANZSPLIT
Default values 1 ... 10	ANR.VGW01 ... ANR.VGW10

Actual values at the operation (OP status)

Resource performance account 1 - SUT	ANR.EGR:BMK01
Resource performance account 2 - DCI	ANR.EGR:BMK02
Resource performance account 3 - LCI	ANR.EGR:BMK03
Resource performance account 4 - SCI	ANR.EGR:BMK04
Resource performance account 5 - IMN	ANR.EGR:BMK05
Resource performance account 6 - IMS	ANR.EGR:BMK06
Resource performance account 7 - SET	ANR.EGR:BMK07
Resource performance account 8 - STA	ANR.EGR:BMK08
Resource performance account 9 - U8	ANR.EGR:BMK09
Resource performance account 10 - U9	ANR.EGR:BMK10
Resource performance account 11 - MUT	ANR.EGR:BMK11
Resource performance account 12 - BKS	ANR.EGR:BMK12
Yield: base quantity unit	ANR.EGR:GUTB
Yield: primary quantity unit	ANR.EGR:GUTP / ANR.EGR:GUT
Yield: secondary quantity unit	ANR.EGR:GUTS
Yield: tertiary quantity unit	ANR.EGR:GUTT
Scrap: base quantity unit	ANR.EGR:AUSB
Scrap: primary quantity unit	ANR.EGR:AUSP / ANR.EGR:AUS
Scrap: secondary quantity unit	ANR.EGR:AUSS

Actual values at the operation (OP status)

Scrap: tertiary quantity unit	ANR.EGR:AUST
Rework quantity: base quantity unit	ANR.EGR:NCHB
Rework quantity: primary quantity unit	ANR.EGR:NCHP / ANR.EGR:NCH
Rework quantity: secondary quantity unit	ANR.EGR:NCHS
Rework quantity: tertiary quantity unit	ANR.EGR:NCHT
Problem quantity: base quantity unit	ANR.EGR:PRBB
Problem quantity: primary quantity unit	ANR.EGR:PRBP / ANR.EGR:PRB
Problem quantity: secondary quantity unit	ANR.EGR:PRBS
Problem quantity: tertiary quantity unit	ANR.EGR:PRBT
Actual cycle	ANR.IZY



We recommend defining the formulas in a template to allow for them to be assigned automatically (e.g. formula for remaining run time).



3 Basic KPIs

The following basic KPIs are available for the single objects to calculate key performance indicators in MES-Cockpit and can be used in formulas. The basic KPIs are exported from the connected HYDRA systems for the objects "workplace" and "operation" for each shift.

3.1 Object "workplaces"

Service: BOResource.list

Field name in XML	Description
w.target_yield	Calculated target quantity of individual machines
w.oeee_arith	Calculated effectiveness of individual machines
w.cycle.target	Target cycle of machines
w.strokes.total	Recorded strokes of machines
w.partitioning	Machine partitioning
wm.pulse_factor.target	Pulse factor of the machine
w.rpaX	Time posted onto individual resource performance accounts (RPA)
w.rpaX_count	The number of times a resource performance account has been posted
w.status_X	Time posted onto single statuses
w.status_X_count	The number of times a status has been posted
w.yield.base	Yield in the base quantity unit
w.yield.primary	Yield in the primary quantity unit
w.yield.secondary	Yield in the secondary quantity unit
w.yield.tertiary	Yield in the tertiary quantity unit
w.scrap.base	Scrap in the base quantity unit
w.scrap.primary	Scrap in the primary quantity unit
w.scrap.tertiary	Scrap in the secondary quantity unit
w.scrap.secondary	Scrap in the tertiary quantity unit
w.problem.base	Open quantity in the base quantity unit
w.problem.primary	Open quantity in the primary quantity unit

w.problem.secondary	Open quantity in the secondary quantity unit
w.problem.tertiary	Open quantity in the tertiary quantity unit
w.rework.base	Rework in the base quantity unit
w.rework.primary	Rework in the primary quantity unit
w.rework.secondary	Rework in the secondary quantity unit
w.rework.tertiary	Rework in the tertiary quantity unit

3.2 Object "order"

Service: BOOrder.overview

Field name in XML	Description
o.act.retension_period	Retention period of order
o.plan.yield.base	Planned yield in the base quantity unit
o.plan.yield.primary	Planned yield in the primary quantity unit
o.plan.yield.secondary	Planned yield in the secondary quantity unit
o.plan.yield.tertiary	Planned yield in the tertiary quantity unit
o.act.processing_time	Processing time of the order
o.no_recordable_op	Number of operations
o.no_finished_op	Number of operations not finished
o.act.occupancy_time	Occupancy time
o.plan.lead_time	Planned lead time
o.act.lead_time	Lead time
o.plan.total_setup_time	Planned setup time of the order
o.plan.processing_time	Planned processing time of the order
o.plan.execution_time	Planned lead time
o.act.standstill_period	Downtimes of the complete order
o.act.setup_time	Setup time of the complete order
o.act.wait_time	Wait time of the complete order

o.act.yield.base	Yield in the base quantity unit
o.act.yield.primary	Yield in the primary quantity unit
o.act.yield.secondary	Yield in the secondary quantity unit
o.act.yield.tertiary	Yield in the tertiary quantity unit
o.plan.labor_utilization	Target personnel deployment of all active OPs that can be collected
o.act.labor_utilization	Personnel time incurred in production
o.act.problem.base	Open quantity in the base quantity unit
o.act.problem.primary	Open quantity in the primary quantity unit
o.act.problem.secondary	Open quantity in the secondary quantity unit
o.act.problem.tertiary	Open quantity in the tertiary quantity unit
o.act.rework.base	Rework in the base quantity unit
o.act.rework.primary	Rework in the primary quantity unit
o.act.rework.secondary	Rework in the secondary quantity unit
o.act.rework.tertiary	Rework in the tertiary quantity unit
o.act.scrap.base	Scrap in the base quantity unit
o.act.scrap.primary	Scrap in the primary quantity unit
o.act.scrap.secondary	Scrap in the secondary quantity unit
o.act.scrap.tertiary	Scrap in the tertiary quantity unit
o.act.rpaX	Sum of all single resource performance accounts (RPA) of all active OPs that can be collected

3.3 Object "operation"

Service: BOOperation.list

Field name in XML	Description
opm.plan.yield.base	Planned yield in base quantity unit
opm.plan.yield.primary	Planned yield in primary quantity unit
opm.plan.yield.secondary	Planned yield in secondary quantity unit
opm.plan.yield.tertiary	Planned yield in tertiary quantity unit

opm.processing_time	Planned processing time of the operation
op.rpaX	Shift-related times posted on the single resource performance accounts 1-12
op.yield.base	Shift-related yield recorded in base quantity unit
op.yield.primary	Shift-related yield recorded in primary quantity unit
op.yield.secondary	Shift-related yield recorded in secondary quantity unit
op.yield.tertiary	Shift-related yield recorded in tertiary quantity unit
op.scrap.base	Shift-related scrap recorded in base quantity unit
op.scrap.primary	Shift-related scrap recorded in primary quantity unit
op.scrap.secondary	Shift-related scrap recorded in secondary quantity unit
op.scrap.tertiary	Shift-related scrap recorded in tertiary quantity unit
op.rework.base	Shift-related rework quantity recorded in base quantity unit
op.rework.primary	Shift-related rework quantity recorded in primary quantity unit
op.rework.secondary	Shift-related rework quantity recorded in secondary quantity unit
op.rework.tertiary	Shift-related rework quantity recorded in tertiary quantity unit
op.problem.base	Shift-related open quantity recorded in base quantity unit
op.problem.primary	Shift-related open quantity recorded in primary quantity unit
op.problem.secondary	Shift-related open quantity recorded in secondary quantity unit
op.problem.tertiary	Shift-related open quantity recorded in tertiary quantity unit
op.labor_utilization	Shift-related personnel times
op.scrap.reason_\$\$	Shift-related scrap quantity for each scrap reason
op.scrap.reason_\$\$\$_count	Shift-related number of scrap reasons occurred