

Manual

PCC module ARGBURG-SGM via serial interface PCC-SSA 8.1

Version 1.0.23049

Last changed on: 02.09.2020

Copyright

©Copyright 2020 All rights reserved.

SAP® and R/3® are registered trademarks of SAP AG.

WINDOWS® is a registered trademark of Microsoft Corporation.

MPDV® and HYDRA® are registered trademarks of MPDV Mikrolab GmbH.

ORACLE® is a registered trademark of ORACLE Corporation, California, USA.

Copying and distribution of this documentation or any part thereof, for any purpose or in any form, is prohibited without prior written permission from MPDV Mikrolab GmbH.

The information contained in this documentation is subject to change without prior notice.

Contents

1	Overview of the PCC-Module ARBURG-SGM via Serial Interface	4
---	--	---

1 Overview of the PCC-Module ARBURG-SGM via Serial Interface

Possible fields of application

There are different connection options to establish direct communication with Arburg machines. The Arburg Selogica protocol is supported, among others, using serial interface. The PCC-SSA module has been integrated as protocol module in HYDRA-PCC (Process Communication Controller). Using this client, generally all data fields of machines provided by the protocol can be read out. This approach can be used for data from the HYDRA modules

- MDE - Machine Data Collection (counter, cycle, status)
- PDV - Process Data Collection (process values)
- DNC - Direct Numerical Control (setting values)

Implementation notes

The function package is used if you:

- want Arburg machines to communicate with HYDRA using the machine's server interface.

Integration

The protocol module has been integrated in HYDRA-PCC. Please also see the documents dealing with the products [SCS-PCP](#) and [SCS-PCB](#).

Functions

Communication module to transfer process data and machine data from the control of an ARBURG injection molding machine or transfer of setting parameters (NC data) used for the control by serial interfaces; required once for each connected machine.

Prerequisite: machines have been equipped, parameters have been set for the control and the used protocols are available according to MPDV's availability list.