

# Predictive Quantization for MIMO-OFDM SVD Precoders using Reservoir Computing Framework

Agrim Gupta, Pranav Sankhe, Kumar Appaiah, Manoj Gopalkrishnan  
Department of Electrical Engineering, Indian Institute of Technology Bombay  
{agrim,pranavs,akumar,manojg}@ee.iitb.ac.in

**Abstract**—Precoding matrices obtained via SVD<sup>1</sup> of the MIMO channel matrix can be utilized at the transmitter for optimum power allocation and lower BER<sup>2</sup> transmissions. However, a key step enabling this improved performance is the feedback of these precoders to the transmitter from the receiver. Considering the limited bit budget for such CSI<sup>3</sup> feedback, the precoders need to be quantized with single digit number of bits. For a  $N_T \times N_R$ <sup>4</sup> MIMO system, this amounts to quantizing a  $N_T \times N_R$  complex valued matrix. This odious task is helped by the presence of an underlying manifold structure, and temporal/frequency correlations in the precoders. In this work, we introduce a reservoir computing framework for the task of prediction of new precoders upon observation of past such precoders, by utilizing temporal correlations. This is a departure from existing methods which exploit the non linear geometry endowed by the manifold structure to perform the same. Alternately, the non-linear relation is captured in our work via the dynamical reservoir state via the training process of the reservoir. Simulations reveal reduced quantization error, which results in lower BER as well as improved achievable rate, as compared to previous work.

## I. INTRODUCTION

In MIMO wireless systems, precoding matrices are used for matrix transformation of  $N_S$ -dimensional ( $N_S \leq \min(N_T, N_R)$ ) information vector onto the  $N_T$ -dimensional transmit vector, corresponding to the signal emanating out of the  $N_T$  antennas of the transmitter. The optimum precoding matrix, to achieve channel capacity via optimum power allocation is obtained via the SVD of the MIMO channel matrix. [1] The MIMO channel matrix is estimated at the receiver, and the transmitter has no a-priori knowledge of the same. Hence, to avail the said benefits of SVD precoders, the receiver needs to quantize and feedback the precoders it obtains from SVD of the MIMO channel matrix. To respect the bit budget imposed by limited feedback CSI schemes, the quantization needs to be performed only with a few single number of bits. Given the high dimensionality of the precoders (which form a  $N_T \times N_R$  complex valued matrix, viz.  $2 \times N_T \times N_R$  real numbers), effective quantization with just a few bits pose a significant challenge.

This challenge has been overcome in past work via two inherent properties of the precoders. Firstly, the precoders are not actually  $2 \times N_T \times N_R$  dimensional entities, and these actually have an underlying manifold structure which allows one to work with lower dimensions if one performs operations over the manifold directly. Secondly, these precoders are correlated nicely along both time and frequency. Capturing

temporal correlations allow for predictive quantization algorithms, which allow improvement of the quantization error with time. Exploiting frequency correlations allow for various interpolation algorithms, which in turn reduce the feedback overhead in a single OFDM frame, by feeding back only for certain subcarriers, and interpolating over the others. Although the underlying manifold structure allows one to work with effective lower dimensions, most of the naive linear algorithms to predict and interpolate don't work well here, owing to the inherent non-linear structure of the manifold. Hence, combining these two properties, viz. the underlying manifold structure and temporal-frequency correlations, require generalization of such linear algorithms to the manifold under consideration, by exploiting the differential geometry of the manifold. Relevant past work in this direction has been [2–8].

The manifold based approaches have provided significant performance benefits, given that they work with effective lower dimensions. However, these approaches are difficult to implement and require some familiarity with manifold geometry for a complete grasp. In this paper, we propose a reservoir computing based predictive quantizer to exploit the temporal correlations effectively. The proposed scheme offers a cleaner solution to the predictive quantization problem, which brings about both ease of implementability, and improved performance as well, when compared to [3], which proposed a manifold based method of predictive quantization.

Reservoir computing is a computational framework designed for sequential data processing. It's design takes inspiration from several frameworks of recurrent neural networks [9] including Liquid State Machines [10]. A reservoir computing system maps the inputs to spatio-temporal patterns in higher dimensional dynamical reservoir state. The pattern analysis over these spatio-temporal patterns is performed by an output coupler which maps the higher dimensional reservoir state back to the output dimension, generally having lower dimensionality than reservoir state. The major advantage of reservoir computing system is that its extremely easy to train in comparison to its counterparts like Deep Neural Networks. The input features can be efficiently read out by a simple learning algorithm because the reservoir non-linearly transforms sequential inputs into the higher dimensional reservoir state. Reservoir computing has been successfully used to solve problems like spoken digit recognition [11], handwritten digit image recognition [10] and climate prediction [12].

Reservoir computing has also been applied to solve prob-

<sup>1</sup> Singular Value Decomposition    <sup>2</sup> Bit Error Rate    <sup>3</sup> Channel State Information    <sup>4</sup>  $N_T(R)$ : Number of Transmit (Receive) Antennas

lems in the domain of wireless communications [9, 13, 14]. [9] used reservoir computing framework to harness channel nonlinearities in order for smarter channel equalization. [13, 14] utilized the same for OFDM symbol detection while tapping in channel, as well as power amplifier non-linearities. In our work, we utilize the reservoir computing framework to discover the underlying non-linear relations between previously observed precoding matrices, in order to predict the next precoder in series. Upon vectorizing the precoding matrices, this becomes analogous to time series prediction algorithms, which the reservoir computing framework has been known to work really well for [13].

## II. SYSTEM MODEL

We consider a point-to-point MIMO-OFDM wireless system that has  $N_T$  transmit antennas and  $N_R$  receive antennas. The available bandwidth is divided into  $N$  subcarriers, so that individually for each subcarrier, the channel can be considered flat fading. The transmitter communicates an  $N_s \times 1$  information data vector, where  $N_s \leq \min(N_T, N_R)$ , and the  $N_T \times N_s$  precoding matrix maps the  $N_s \times 1$  information data vector onto the  $N_T \times 1$  transmit vector emanating out of the transmitter.

In this discussion, we assume that  $N_T > N_R$  and  $N_s = N_R$ . Keeping notations consistent with [2, 3], the  $N_R \times 1$  data stream received is denoted by:

$$\mathbf{y}_{i,t} = \mathbf{H}_{i,t}^H \tilde{\mathbf{U}}_{i,t} \mathbf{x}_{i,t} + \mathbf{w}_{i,t} \quad (1)$$

Here  $\tilde{\mathbf{U}}_{i,t} \in \mathbb{C}^{N_T \times N_R}$  denotes the precoding matrix which is a function of quantized CSI fed back by the receiver,  $\mathbf{y}_{i,t} \in \mathbb{C}^{N_R \times 1}$  is the received data stream,  $\mathbf{x}_{i,t} \in \mathbb{C}^{N_R \times 1}$  denotes the transmitted signal, all at the  $i$ -th subcarrier of the  $t$ -th OFDM frame,  $\mathbf{H}_{i,t} \in \mathbb{C}^{N_T \times N_R}$  denotes the MIMO channel matrix and  $\mathbf{w}_{i,t}$  denotes the i.i.d. complex Gaussian noise with  $\mathbf{w}_{i,t} \sim \mathcal{N}_{\mathbb{C}}(0, N_0 \mathbf{I}_{N_R})$ ,  $N_0$  being the noise variance.

Provided an infinite bit budget for quantization, the transmitter can directly use the matrices obtained from SVD of  $\mathbf{H}_{i,t}^H$  as precoder  $\tilde{\mathbf{U}}_{i,t}$ . In particular, if  $\text{SVD}(\mathbf{H}_{i,t}) = \mathbf{U}_{i,t} \Sigma_{i,t} \mathbf{V}_{i,t}$ , then  $\tilde{\mathbf{U}}_{i,t} = \mathbf{U}_{i,t}$ . Notice that matrices  $\mathbf{U}_{i,t}$  reside on the Stiefel manifold  $\text{St}(N_T, N_R)$ , since the columns of  $\mathbf{U}_{i,t}$  form a set of  $N_R$  orthogonal vectors in  $N_T$  dimensions [2, 3]. Given practical limitations, only limited feedback is available from the receiver, and the objective is to find a ‘reasonable’ estimate of  $\mathbf{U}_{i,t}$ , given by  $\tilde{\mathbf{U}}_{i,t}$  using the available feedback bits.

Algorithms similar to Lloyd codebook algorithm have been studied for quantizing  $\text{St}(N_T, N_R)$  [15]. However, this method treats precoders close-by in time/frequency to each other as independent, since it doesn’t exploit any temporal/spectral correlations for quantization. Predictive quantization algorithms [2, 3] can be utilized to reduce the quantization error with time by tapping in available correlations.

We now discuss the basic mathematical model central to predictive quantization algorithms for precoding matrices. Consider that we predict based on past  $p$  observed precoding matrices, and hence  $\tilde{\mathbf{U}}_{i,t-p}, \tilde{\mathbf{U}}_{i,t-p+1}, \dots, \tilde{\mathbf{U}}_{i,t-2}, \tilde{\mathbf{U}}_{i,t-1}$

have been fed back and available at the transmitter. Using a prediction algorithm and exploiting time correlations among precoders at  $t-p, t-p+1, \dots, t-2, t-1$  time instances, the transmitter can predict  $\tilde{\mathbf{U}}_{i,t}$  to be some  $\mathbf{P}_{i,t} = f_P(\tilde{\mathbf{U}}_{i,t-p}, \tilde{\mathbf{U}}_{i,t-p+1}, \dots, \tilde{\mathbf{U}}_{i,t-2}, \tilde{\mathbf{U}}_{i,t-1})$ , where  $f_P : \text{St}(N_T, N_R)^p \rightarrow \text{St}(N_T, N_R)$  is a prediction function. Now since the transmitter already knows a coarse estimate of  $\tilde{\mathbf{U}}_{i,t}$  given by  $\mathbf{P}_{i,t}$ , the receiver just quantizes the local space of  $\text{St}(N_T, N_R)$  nearby  $\mathbf{P}_{i,t}$  to enable a refined estimate of  $\tilde{\mathbf{U}}_{i,t}$  at the transmitter. That is, the transmitter utilizes a quantization function  $q_P : \text{St}(N_T, N_R) \times \mathbb{N} \rightarrow \text{St}(N_T, N_R)$ , to obtain  $\tilde{\mathbf{U}}_{i,t} \leftarrow q_P(\mathbf{P}_{i,t}, \text{fb}_{i,t})$ , where  $\text{fb}_{i,t} \in \{1, 2, \dots, 2^{\mathcal{B}}\}$  is the feedback from the receiver for precoder at  $i$ -th subcarrier and  $t$ -th time instant, considering bit budget of  $\mathcal{B}$  bits. In [2–4],  $\text{fb}_{i,t}$  denotes the codeword index for the codebook obtained for quantizing the local tangent space at  $\mathbf{P}_{i,t}$ .

Since using predictive quantization scheme, quantization is on a smaller subspace as compared to the entire manifold in case of independent quantization, the quantization error is substantially lower as well. However, that being said, independent quantization algorithms are important for initialization the predictive quantization strategies. Observe that, predictive quantization algorithms for SVD precoders are typically the higher dimensional analogs of the well known approaches to reduce quantization error using Linear Prediction Codes and Delta PCM. In both LPC and Delta PCM, quantization error is reduced substantially by using a linear predictor and quantizing the scalar difference between the predicted and observed value. Analogous to this, for  $\text{St}(N_T, N_R)$  quantization error is reduced by quantizing a smaller subspace around predicted value, compared to the entire manifold.

In our work, we propose a reservoir computing based prediction framework, which predicts the new precoders by tapping the temporal correlations captured from past observed precoders ( $f_P$ ). We reuse the  $q_P$  algorithm from [2, 3], however, by incorporating the  $q_P$  in the prediction framework, as discussed in subsequent sections, the  $f_P$  function also exploits correlations in  $q_P$  (codebook locality correlations), along with temporal correlations. Previous work [2, 3] have  $f_P$  and  $q_P$  independent of each other. The detailed discussion on reservoir computing based model for  $f_P$  and  $q_P$  is presented in Section III. The proposed reservoir computing scheme is evaluated against the temporal predictive quantization scheme in [3], and the simulation results are discussed in Section IV. Finally, Section V concludes and presents future lines of work.

## III. RESERVOIR MODEL FOR PREDICTIVE QUANTIZATION

### A. Vectorizing matrices in Stiefel Manifold

### B. Prediction and Quantization

## IV. SIMULATION RESULTS

## V. CONCLUSIONS AND FUTURE WORK

## REFERENCES

- [1] D. J. Love, R. W. Heath, V. K. Lau, D. Gesbert, B. D. Rao, and M. Andrews, “An overview of limited feedback in wireless communication systems,” *IEEE J. Sel. Areas Commun.*, vol. 26, no. 8, 2008.

- [2] A. Gupta, K. Appaiah, and R. Vaze, "Predictive quantization and joint Time-Frequency interpolation technique for MIMO-OFDM precoding," in *2019 IEEE International Conference on Communications (ICC): Wireless Communications Symposium (IEEE ICC'19 - WC Symposium)*, Shanghai, P.R. China, May 2019.
- [3] S. Schwarz and M. Rupp, "Predictive Quantization on Stiefel Manifold," *IEEE Signal Process. Lett.*, vol. 22, no. 2, pp. 234–238, Feb 2015.
- [4] S. Schwarz, R. W. Heath, and M. Rupp, "Adaptive Quantization on a Grassmann-Manifold for Limited Feedback Beamforming Systems," *IEEE Trans. Signal Process.*, vol. 61, no. 18, pp. 4450–4462, Sept 2013.
- [5] Y. Chou and T. Sang, "Efficient interpolation of precoding matrices in MIMO-OFDM systems," in *SPAWC, 2010*, June 2010, pp. 1–4.
- [6] T. Li, F. Li, and C. Li, "Manifold-based predictive precoding for the time-varying channel using differential geometry," *Wireless Networks*, vol. 22, no. 8, pp. 2773–2783, Nov 2016.
- [7] N. Khaled, B. Mondal, R. W. Heath, G. Leus, and F. Petré, "Quantized multi-mode precoding for spatial multiplexing MIMO-OFDM systems," in *IEEE 62nd Vehic. Technol. Conf.*, vol. 2. IEEE, 2005, pp. 867–871.
- [8] R. T. Krishnamachari and M. K. Varanasi, "On the geometry and quantization of manifolds of positive semi-definite matrices," *IEEE Trans. Signal Process.*, vol. 61, no. 18, pp. 4587–4599, 2013.
- [9] H. Jaeger and H. Haas, "Harnessing nonlinearity: Predicting chaotic systems and saving energy in wireless communication," *science*, vol. 304, no. 5667, pp. 78–80, 2004.
- [10] A. Jalalvand, G. Van Wallendael, and R. Van de Walle, "Real-time reservoir computing network-based systems for detection tasks on visual contents," in *2015 7th International Conference on Computational Intelligence, Communication Systems and Networks*. IEEE, 2015, pp. 146–151.
- [11] D. Verstraeten, B. Schrauwen, D. Stroobandt, and J. Van Campenhout, "Isolated word recognition with the liquid state machine: a case study," *Information Processing Letters*, vol. 95, no. 6, pp. 521–528, 2005.
- [12] J. Pathak, Z. Lu, B. R. Hunt, M. Girvan, and E. Ott, "Using machine learning to replicate chaotic attractors and calculate lyapunov exponents from data," *Chaos: An Interdisciplinary Journal of Nonlinear Science*, vol. 27, no. 12, p. 121102, 2017.
- [13] S. Mosleh, L. Liu, C. Sahin, Y. R. Zheng, and Y. Yi, "Brain-inspired wireless communications: Where reservoir computing meets mimo-ofdm," *IEEE transactions on neural networks and learning systems*, no. 99, pp. 1–15, 2017.
- [14] R. Shafin, L. Liu, J. Ashdown, J. Matyjas, M. Medley, B. Wysocki, and Y. Yi, "Realizing green symbol detection via reservoir computing: An energy-efficiency perspective," in *2018 IEEE International Conference on Communications (ICC)*. IEEE, 2018, pp. 1–6.
- [15] R. Pitaval and O. Tirkkonen, "Joint Grassmann-Stiefel Quantization for MIMO Product Codebooks," *IEEE Trans. Wireless Commun.*, vol. 13, no. 1, pp. 210–222, January 2014.