

Indian drone landscape and the Icarus opportunity

Research brief | 17 September 2026 | Prepared for Agrim

The seven companies reviewed

- **Garuda Aerospace:** agricultural spraying platforms such as Kisan, plus the compact Droni camera drone and enterprise services. [1, 2]
- **ideaForge:** NETRA surveillance quadcopters, SWITCH fixed-wing/VTOL aircraft, mapping platforms and mission/data software. [3, 4]
- **DroneAcharya:** Arya 1.0 surveying/inspection aircraft, alongside drone services and training. [5]
- **Marut Drones:** AG365-family agricultural aircraft for spraying and related farm operations. [6]
- **Skylark Drones:** aerial-data analytics, mission management and fleet/dock workflows; not a single standard airframe. [7]
- **InsideFPV:** Elevate surveillance drones, Advik FPV aircraft, training products and specialised defence platforms. [8-10]
- **Apollyon Dynamics:** Nightshade ADX-1, a specialised jet-powered defence platform, and mobile drone infrastructure. [11]

Recommendation in brief

Position Icarus as a reusable, operator-supervised aircraft that turns a plain-language request into an approved mission and useful evidence. Start with AGX Orin 64GB and a quantised 8B mission model. Treat Thor 128GB as the higher-compute development option, not a requirement established by the current workload.

How to read this report

Company capabilities are public manufacturer claims unless stated otherwise. They are not independent test results, procurement approvals or proof of deployment maturity. Missing specifications are marked as unknown. Proposed Icarus sizes and performance goals are engineering targets, not validated aircraft specifications.

Focus: ideaForge, InsideFPV and Apollyon. Sources were reviewed during this research conversation; key hardware and product pages were checked again for this report. Numbered references are clickable on page 9.

ideaForge

Benchmark: navigation reliability, mission usability and complete field systems

Product families and their roles

NETRA 5 is a foldable surveillance quadcopter. The product page advertises daylight/thermal observation, obstacle avoidance, GPS-denied navigation and return, tracking, people detection/counting and terrain following. Its secondary payload interface supports up to 2kg. Exact external dimensions were not verified from the reviewed page. These features describe advertised capability, not measured reliability across every environment. [3]

NETRA V4 PRO addresses surveillance and security. **SWITCH / SWITCH V2** combine vertical takeoff with fixed-wing flight for longer surveillance missions. **Q4i / Q6** cover surveillance and mapping roles. The company portfolio presents multiple aircraft rather than one drone optimised for every mission. [4]

What a customer uses them for

Mission	Operational output
Surveillance and reconnaissance	Live aerial imagery for situational awareness; observation of a defined area.
Public safety and emergency response	Views of affected terrain, infrastructure and possible people requiring attention.
Mapping and change detection	Maps, terrain information and comparisons of sites over time.

NETRA 5 combines onboard functions with BlueFire Touch mission planning and BlueFire Live video distribution; its ecosystem also includes Flyght Cloud. Waypoint planning remains explicitly part of the advertised workflow. [3]

Size and endurance: avoid misleading comparisons

An older official NETRA V-series sheet specifies a vehicle smaller than 1.5 x 1.5m and under 6kg. That is historical context, **not a NETRA 5 specification**. Endurance figures across investor presentations use different conditions and generations; this report does not treat them as directly comparable loaded flight times. [4, 12]

Implication for Icarus

Obstacle avoidance and onboard AI are already competitive baseline features. Differentiate through measured reductions in mission preparation, operator interventions and time to useful findings. Do not claim better autonomy merely because Icarus carries a language model.

Questions to resolve through a product demonstration

Ask which functions work without GNSS or a data link, how failures are handled, which obstacle types are excluded, and what endurance is achieved with the selected payload. Request a configuration-specific datasheet and acceptance-test results rather than relying on headline claims.

InsideFPV

Benchmark: compact packaging, rapid deployment and product-specific capability

Elevate V1: a surveillance product

Elevate V1 is marketed for patrol support, border observation and disaster response. Its page lists a stabilised camera, obstacle avoidance, follow-me, AI-assisted tracking and automatic return after low battery or signal loss. These functions help an operator collect imagery; they do not establish open-ended mission reasoning. [8]

Published figures include a 5km range and 45km/h speed. The current product specification says "60+ mins (3 batteries)"; it should not be presented as a verified continuous 60-minute flight. Other marketing material has used different wording. External dimensions and loaded endurance need supplier confirmation. [8]

Advik: small FPV aircraft are a separate category

The Advik 5-inch page describes a lightweight FPV platform for training, surveillance and reconnaissance. It advertises 200+km/h maximum speed, up to 6km range, 20+ minutes flight time and 100g maximum payload. These are separate maxima, not a demonstrated simultaneous operating point. The page does not establish that this small FPV aircraft has Elevate's autonomy suite. [9]

The wider catalogue contains 7-, 10- and 15-inch Advik variants, including specialised defence products. Inch labels refer to propeller class, not total aircraft width or motor diagonal. They do not demonstrate that a complete AGX Orin or Thor stack fits inside the same platform. [8, 9]

Rakshak: a specialised counter-drone product

Rakshak is marketed for counter-drone defence, military-base security and critical-infrastructure protection. Its page advertises AI visual tracking and multi-unit coordination. This is a distinct mission category; this report does not assess engagement methods or translate those capabilities into an Icarus design. Independent performance evidence was not established in the reviewed material. [10]

Implication for Icarus

Benchmark the ease of carrying, setting up, repairing and operating the aircraft. Compete on validated autonomous task completion, not an assumption that a small FPV frame already includes enterprise-grade navigation and mission intelligence.

What must be compared fairly

Compare the same payload, battery reserve, wind conditions, link assumptions and mission duration. Separate manual FPV handling, camera tracking, automatic navigation and high-level decision-making: one feature does not imply the others.

Apollyon Dynamics

Benchmark: focused mission definition, not small-quad dimensions

Nightshade ADX-1

Apollyon describes Nightshade as a jet-powered autonomous strike platform for contested environments. The public product content advertises GPS-denied navigation and terrain-following, with a **70kg maximum takeoff weight**. Its published role is fundamentally different from a reusable inspection quadcopter. [11]

The current website lists 700km/h speed, 150km+ range and 45-minute endurance. Those headline figures do not establish a single simultaneous flight profile. Physical length and wingspan were not verified, and publicly advertised capability should not be treated as an independently demonstrated operational envelope. [11]

Other product direction

The company also presents mobile drone-lab infrastructure. This broadens its offering beyond an aircraft into field support and development infrastructure. The reviewed sources do not establish a comparable commercial roof-inspection product or a general-purpose prompt-to-mission interface. Absence from public material is not proof that a capability does not exist. [11]

Comparison	Why it matters
Aircraft purpose	Nightshade is advertised for a specialised combat role; Icarus is positioned here for reusable observation and inspection.
Size benchmark	A 70kg maximum-takeoff-weight platform does not validate dimensions or propulsion choices for a 7-15-inch quadcopter.
Autonomy claim	GPS-denied navigation is a capability claim, not evidence of unrestricted language-based reasoning.
Business lesson	A clear mission and acceptance test are more valuable than a broad list of AI features.

Implication for Icarus

Learn from mission focus, but do not imitate Nightshade's configuration or speed target. Define the repeatable job Icarus performs, the conditions under which it works, and the evidence a customer receives at the end.

Evidence limitations

This is a public-source competitive profile, not a technical audit. Website text was available through its publicly delivered page assets. No independent flight-test report, complete airframe drawing or verified autonomous-decision benchmark was obtained. Defence capabilities are summarised at a market level only.

Sell a completed task, not onboard RAM

Proposed first market: supervised outdoor inspection and observation

Proposed positioning

Icarus is a portable, reusable drone that turns an operator's plain-language request into a bounded, approved mission, adapts within those limits, and returns location-tagged evidence.

Why this position fits the competitive landscape

ideaForge already markets substantial navigation and sensing capabilities. InsideFPV covers compact aircraft and rapid deployment. Apollyon emphasises specialised mission platforms. The opportunity is therefore not simply "AI on a drone": it is a demonstrably easier, dependable workflow for a specific customer problem. The reviewed public sources do not prove an uncontested market gap.

Initial mission	Deliverable and value
Roof / facility inspection	Repeatable imagery and suspected defect locations; less manual mission setup.
Fence / site-condition inspection	Evidence of gaps, damage or changes for human review.
Disaster / rescue support	Approved-area imagery and candidate findings, with uncertainty clearly shown.

Start with one repeatable enterprise inspection workflow. Non-weapon defence-support uses, such as facility condition assessment or emergency response, can be evaluated separately. Customer access, data handling and procurement requirements should be established before expanding markets.

The mission experience

Request: "Inspect the approved roof area and show visible damage."

Plan: identify missing details, select a supported inspection skill and calculate coverage.

Approve: show the area, limits, estimated duration and return reserve.

Execute: navigate, capture evidence and revisit unclear views within approved bounds.

Report: return a location-tagged summary with images and confidence indicators.

What not to promise in version one

Do not bundle arbitrary tasks, acro flight, all-weather navigation, reliable wire detection, unrestricted GPS-denied flight and unattended operation into one launch promise. Each expands the validation burden. A prompt must never grant authority to exceed the approved mission boundaries.

The product advantage to build

Measure setup time, completed missions without intervention, usable inspection coverage, finding accuracy and time to report. Good training data, failure handling, serviceability and repeatable customer results are harder to copy than the choice of Jetson module.

Two configurations, one software architecture

Requested propeller ranges are hypotheses - not validated minimum aircraft sizes

	Thor configuration	Orin configuration
Compute	Jetson T5000 / Thor, 128GB	Jetson AGX Orin, 64GB
Proposed prop class	12-15 inches	7-10 inches
Interpretation	Larger prototype for compute and sensor headroom	Compact target; start packaging near 10 inches. Treat 7 inches as a stretch goal.
Module power range	40-130W [13]	15-60W [14]
Flight controller	Pixhawk 6X	Pixhawk 6X
Storage proposal	512GB NVMe; expand if recordings require it	512GB NVMe with capped recording retention
Best reason to choose	Orin misses required concurrent-workload deadlines	Baseline for a quantised 8B mission model and bounded perception workload

Power ranges above are published module configurations, not actual application consumption or total drone power. Battery sizing must include propulsion, carrier losses, SSD, sensors, communications and cooling. Lower configured power does not automatically mean better task-level energy efficiency. [13, 14]

Physical integration and size reality

Both concepts need a carrier, power conditioning, cooling, mechanically secured storage, sensor interfaces and vibration-managed flight-controller mounting. The previously discussed Forecr Thor carrier measures **140 x 125mm** and accepts 18-36V; it still needs the module, cooling and complete aircraft integration. It is not evidence that a finished drone meets a particular mass or size. [15]

An AGX Orin module is not an Orin NX module. Do not use an NX carrier or small-drone example as proof that AGX Orin 64GB fits. Likewise, do not assume the existing Mark4 V2 frame supports either complete configuration without checking mounting, stiffness, centre of gravity and propeller clearance.

Propeller inches are not aircraft width

For a square-X quad with motor diagonal D and propeller diameter P , its approximate rotor envelope is $D / \sqrt{2} + P$ per side. A hypothetical 450mm diagonal with 10-inch props spans about 572mm per side; 600mm with 15-inch props spans about 805mm. These are geometry examples, not approved frame dimensions.

Design constraint

No complete mass, thrust, battery or thermal budget has been closed for either version. If all-up mass remains near the earlier 6kg estimate, the compact Orin concept must be reassessed. Neither the requested size range nor dropping a 3:1 thrust target proves acceptable flight performance.

An 8B model is one part of the stack

Recommended baseline: AGX Orin 64GB, subject to concurrent-load testing

Layer	Role and execution approach
Voice input	Push-to-talk STT turns speech into text. Sarvam may run through a remote service; offline Jetson deployment remains unverified. [16]
Perception	YOLO-style detection plus selected depth / tracking models. YOLO belongs inside perception, not a duplicate layer.
Localisation and state	Fuse sensor data; track position, uncertainty, battery, map and mission progress. Validate stale or inconsistent observations.
8B mission model	Read bounded state summaries and propose structured, permitted mission actions. Run on mission events, not as the flight-control loop.
Safety and execution	Check permissions, geofences, energy reserve and action feasibility independently. Use an explicit mission executor and navigation planner.
Flight control	Pixhawk handles stabilisation and configured failsafes. Loss or failure of the language model must not remove safe flight control.
Storage and reporting	Record selected evidence, state and decisions; enforce retention limits and produce operator-reviewed findings.

Why recommend Orin 64GB first?

The proposed model receives structured observations, rather than continuously interpreting every camera frame. State handling and deterministic checks need not each be another large neural network. This makes Orin a reasonable baseline candidate, while 64GB provides more memory margin than smaller Orin variants. It does not guarantee the required perception frame rate or decision latency.

An 8B model at idealised 4-bit precision needs about **4GB for weights alone**. Quantisation metadata, context/KV cache, runtime buffers, vision models, maps and the OS increase this. There is no defensible complete RAM estimate until model variants, camera streams, context lengths and mapping limits are specified. Fine-tuning should be performed offboard; deploy the resulting inference model to the drone.

Model and speech choices

Use a pretrained, instruction-tuned 8B model with structured tool outputs; Qwen3-8B is one candidate, not a validated flight component. Evaluate before adding LoRA/QLoRA fine-tuning. Sarvam's documented self-hosting uses AWS SageMaker, which is not proof of local Jetson support. Cloud STT adds connectivity and data-handling dependencies. [16-18]

Keep manual hold/abort independent of speech and cloud availability. Require confirmation for takeoff and substantial mission changes; treat sensed text and audio as untrusted data, not privileged commands.

Choose Orin by evidence, not by optimism

Thor remains the fallback when measured workload demands it

Recommended development configuration

AGX Orin 64GB + compatible compact carrier + 512GB NVMe + Pixhawk 6X + a quantised 8B mission model. Begin a packaging study around the upper end of the requested 7-10-inch range. Do not purchase the final propulsion system based on propeller class alone.

Acceptance gates before committing the airframe

Gate	Evidence required
1. Define the workload	Fix camera count/resolution, perception frequency, map size, language-model context, response deadline and STT location.
2. Test simultaneous inference	Run cameras, localisation, mapping, recording and model decisions together. Measure worst-case / tail latency, not only average tokens per second.
3. Test sustained operation	Measure power, temperature, throttling and memory under representative ambient conditions and full mission duration.
4. Validate decision safety	Use unseen scenarios, malformed commands, stale sensors and model failures. Confirm independent rejection of invalid actions and safe fallback.
5. Close the aircraft budget	Weigh the entire installed stack. Validate motor/prop thrust and current, centre of gravity, vibration, cooling and loaded endurance with reserve.
6. Demonstrate customer value	Complete repeat inspections and measure interventions, usable coverage, finding quality and reporting time.

When to move to Thor 128GB

Choose Thor if Orin cannot meet the agreed perception and decision deadlines at the same time, if a required larger visual model cannot be accommodated, or if memory/thermal constraints remain unacceptable after reasonable optimisation. Test the intended Thor configuration too: additional hardware capacity is not a substitute for measurement.

When to shrink further

Only pursue the 7-inch end of the Orin concept after the integrated mass, power and cooling results support it. Reducing the language model, moving nonessential processing to the controller, or limiting camera workloads are possible trade-offs, not free improvements. Record exactly which offline capabilities are retained.

Final recommendation: use Orin 64GB as the baseline for the current 8B architecture, and Thor 128GB as the high-compute option. Market Icarus through verified mission outcomes. Keep both aircraft-size ranges explicitly provisional until engineering tests establish them.

References and evidence notes

Click a source title to open it. Manufacturer specifications can change.

- [1] [Garuda Droni specifications](#)
- [2] [Garuda agricultural brochure \(manufacturer material hosted by distributor\)](#)
- [3] [ideaForge NETRA 5: capabilities and mission software](#)
- [4] [ideaForge investor presentation, 7 June 2026](#)
- [5] [DroneAcharya Arya 1.0 official brochure](#)
- [6] [Marut AG365 agricultural product page](#)
- [7] [Skylark: drone-dock solar inspection workflows](#)
- [8] [InsideFPV Elevate V1 specifications and catalogue](#)
- [9] [InsideFPV Advik 5-inch product page](#)
- [10] [InsideFPV Rakshak product page](#)
- [11] [Apollyon Nightshade ADX-1 \(dynamic official website\)](#)
- [12] [Historical ideaForge NETRA V-series datasheet](#)
- [13] [NVIDIA Jetson Thor specifications](#)
- [14] [NVIDIA Jetson Orin specifications](#)
- [15] [Forecr DSBOARD-THRMAX Thor carrier](#)
- [16] [Sarvam: self-hosted deployment model](#)
- [17] [Qwen3: official function-calling documentation](#)
- [18] [Hugging Face: parameter-efficient fine-tuning](#)

Evidence and interpretation

Sources [1-12] support market and product descriptions, not independent certification of autonomy. Sources [13-16] support hardware and deployment facts. Sources [17-18] support model tooling, not suitability for safety-critical flight. Icarus positioning, architecture, storage choice and development gates are recommendations. The 12-15-inch Thor and 7-10-inch Orin concepts originate from the requested design direction and remain unvalidated.

No capability claim here establishes weapon-system performance or authorises unattended operation. Sensitive deployments require their own security, operational and procurement review.