# What Transfers to a New Benchmark? Priors, Not Item Estimates, for Label-Efficient LLM Evaluation

**Arshia Teymourtash**[*]
KTH Royal Institute of Technology
Stockholm, Sweden
arturt@kth.se

**Ankit Grover**[*]
KTH Royal Institute of Technology
Stockholm, Sweden
agrover@kth.se

## Abstract

Evaluating an LLM on every item of every benchmark is expensive, so predicting item outcomes from a few revealed answers is attractive, but only if what is learned from past benchmarks carries over to new ones. We ask what does, in a controlled comparison where the models, the evaluation tasks and the order in which answers are revealed are held fixed and only the source of the prior changes. A prior learned from past benchmarks *transfers* to a new benchmark. Estimates of individual item difficulty *do not*. The prior's benefit is small on average and depends on the benchmark: it helps on benchmarks of *typical* difficulty and hurts on much easier or much harder ones. A neural network that predicts item difficulty from item text adds little beyond the prior. Whether pooling answers across LLMs helps *remains open*, because our evaluation reveals answers from one LLM per benchmark. Our entry to the Predictive AI Evaluation Competition (Codabench submission 1005155) is a Beta-Binomial predictor. We release the simulation code, the fixed evaluation samples and every saved score on GitHub.

## 1 Introduction

Evaluating language models on every item of every benchmark is expensive, so a predictor that infers a model's per-item results from a handful of labelled answers is attractive. The natural recipe is to learn from past benchmarks how items behave and carry that to a new benchmark. Whether it carries is an empirical question, and the answer matters because new benchmarks and new models keep arriving. Most benchmark-prediction methods lose their advantage over random sampling when extrapolating to higher-performing models [35], and amortized item-response models learn item difficulty from item text [34]. We ask what, among the things one can fit offline, actually transfers to an unseen benchmark.

We use the Predictive AI Evaluation Competition's setting: a *task* is one subject (a model under given evaluation settings) answering one benchmark, labels are bought one at a time, and predictions are scored by Brier ALC at 0, 1, 3, 7, 15 and 31 labels. Our contributions:

- **A controlled comparison.** Models, tasks and label order are fixed and only the source of the prior changes, in an online simulation of the competition protocol (Section 4).
- **What transfers.** A learned prior transfers to a new benchmark and item-level estimates do not. The prior helps on benchmarks of typical difficulty and hurts on much easier or harder ones, and item text adds almost nothing beyond it (Section 5).

The simulation code, the fixed evaluation samples and every saved score are on GitHub.

[*]Work done equally.

40th Conference on Neural Information Processing Systems (NeurIPS 2026), The Predictive AI Evaluation Competition at NeurIPS 2026.

## 2 Related work

**Label-efficient evaluation.** Label-efficient methods estimate LLM performance from few responses, for example from curated item subsets and item-response models [23]. Most benchmark-prediction methods lose their advantage over random sampling when extrapolating to higher-performing models, while one estimator that combines predictions with random labels keeps it [35]. That shift is in which models are evaluated, ours is in which benchmark, and that work estimates aggregate scores and not per-item outcomes. Active evaluation acquisition learns which examples to label from a pool that stays visible [21], whereas our labels arrive in a random order.

**Item response theory.** It separates subject ability from item difficulty, with Rasch as its basic model [28]. A model trained on pooled responses can predict item difficulty from item text, so that new items need less calibration [34], and concurrent work finds that text embeddings carry almost no difficulty signal on unseen benchmarks [17]. We compare simple probes of this kind with priors that carry over only the typical accuracy of a task. Sharing labels across LLMs, where item response theory gains most, is not tested here because each draw reveals one LLM per benchmark.

**Empirical Bayes and shrinkage.** These carry population-level information to related tasks by learning a prior across them [29, 8, 27]. Only our prior fitted on training benchmarks is empirical Bayes. The Jeffreys prior [15] and the settings tuned on validation are separate prior sources, and robust mixture priors give a precedent for our adaptive priors [31].

## 3 Data and evaluation protocol

**Data.** The data are a binary response matrix $Y \in \{0,1\}^{N \times M}$ with $N$ subjects (rows, index $i$) and $M$ items (columns, index $j$): $Y_{ij} = 1$ if subject $i$ answers item $j$ correctly. Most entries are missing, since a subject answers only the items of the benchmarks it was evaluated on. Each item $j$ belongs to the dataset $d(j)$ of one of $D = 17$ benchmarks, so a benchmark is a block of columns, and a *task* is one row restricted to one block: subject $i$ on benchmark $d$.

Each item $j$ has an embedding $x_j \in \mathbb{R}^{1024}$ computed once from its text by the frozen BGE-M3 encoder [6] with a context of 8,192 tokens, and normalised to unit length. We use BGE-M3 because the corpus is multilingual (it includes Chinese, Russian and several African languages) and some items are long, which English-only and 512-token encoders handle poorly.

**Online simulation and splits.** The competition protocol is *online*: for each task, labels are revealed one at a time and the predictor updates from them. Whatever the predictor knows before the first label is *offline*, that is, fitted on the training benchmarks beforehand. Our *online simulation* runs this protocol on recorded responses, with disjoint column blocks for training, validation, and test (11, 3, and 3 benchmarks): priors are fitted offline on training, and validation selects settings. The validation and test benchmarks are *out of distribution* (OOD): their responses are excluded from offline fitting.

A *competition-shaped draw* samples one subject per benchmark, so a predictor cannot borrow labels from other subjects on the same benchmark; this simulates the competition protocol on public data. As a separate *in-distribution* (ID) evaluation, we hold out rows (subjects) within the training blocks, so its benchmarks and items have been seen during fitting, and retain the questions covered by the fit subjects. The offline comparator reuses its fitted benchmark rates and item difficulties where available, and its online update changes only the subject ability.

**Budgets and scoring.** For each subject–benchmark pair we freeze a split of distinct items into acquisition and evaluation pools, assigning the extra item to acquisition when the count is odd. A frozen random acquisition order supplies nested prefixes of 0, 1, 3, 7, 15, and 31 labels. At each budget the predictor conditions on the allowed prefix and predicts the same evaluation items.

Evaluation outcomes are used only to score those predictions. We average Brier scores over query items, then average repeated appearances within each task and give tasks equal weight. Brier ALC combines the six budgets with weights $(0.1, 0.2, 0.2, 0.2, 0.2, 0.1)$. Paired intervals resample whole tasks with their matched predictions.

# 4 Methodology

We first define the three predictors, then two ways of improving on them, adaptive priors and item-text probes, and finally the sources of the prior parameters that every predictor needs.

## 4.1 Models

The three predictors differ in what they model: a task's accuracy (Beta-Binomial), a subject's ability and each item's difficulty (Rasch), and the similarity between items (kernel Rasch).

**Beta-Binomial.** Let $p$ be a task's accuracy, with a Beta prior $p \sim \mathrm{Beta}(\alpha, \beta)$. After $n$ revealed labels, $k$ of them correct, the posterior is $\mathrm{Beta}(\alpha + k, \beta + n - k)$ and the prediction, the same for every item of the task, is its mean

$$\hat{p} = \frac{\alpha + k}{\alpha + \beta + n}. \tag{1}$$

The prior acts like $\alpha + \beta$ extra labels, $\alpha$ of them correct. The Jeffreys prior is $\alpha = \beta = \frac{1}{2}$ [15]. This is the exact Bayesian sequential update; nothing is learned.

**Rasch.** The probability that subject $i$ answers item $j$ correctly is

$$p_{ij} = \sigma(\theta_i - b_j), \qquad b_j = \delta_j - \mu_{d(j)}, \tag{2}$$

where $\sigma$ is the logistic function, $\theta_i$ is the subject's ability, and $b_j$ is the item's difficulty. This is the Rasch model [28] with the item difficulty split into a benchmark part and an item part: $\delta_j$ is the item's deviation from the average difficulty $-\mu_d$ of its benchmark $d = d(j)$, so a larger benchmark rate $\mu_d$ means an easier benchmark. The priors are $\mu_d \sim \mathcal{N}(m_0, \sigma_\mu^2)$, $\theta_i \sim \mathcal{N}(0, \sigma_\theta^2)$ and $\delta_j \sim \mathcal{N}(0, \sigma_\delta^2)$. At every budget we refit the maximum a posteriori (MAP) estimate from scratch on all labels revealed so far in the draw; an unlabelled item gets $\delta_j = 0$.

**Kernel Rasch.** Kernel Rasch keeps Equation (2) and correlates the item deviations $\boldsymbol{\delta}$ through the similarity of the item embeddings of Section 3, with a kernel weight $\rho$ and a temperature $T$. Appendix J gives the prior and how unlabelled items are predicted. With one subject per benchmark, as in the competition-shaped draws, no labels are shared across subjects, so Rasch there differs from the Beta-Binomial only in its prior.

**Offline model that keeps its fitted values.** For the ID evaluation, the offline Rasch keeps its fitted $\mu_d$ and $\delta_j$ for a benchmark and items it has seen and updates only the subject ability $\theta_i$ online (a one-dimensional MAP on the task's own labels). For an unseen benchmark or item it falls back to $m_0$ and 0, i.e. to the fitted prior alone.

## 4.2 Adaptive priors

The predictors above keep their prior fixed whatever labels arrive. An *adaptive prior* lets the first labels change it. We test three closed-form versions, each refit without any held-out benchmark.

**Beta mixture.** The prior is a mixture of $K \in \{2, 3\}$ Beta distributions with weights $w_c$, fitted by expectation maximisation on the accuracies of the training tasks. After $k$ of $n$ labels are correct, the weight of each component is updated by how well it explains them, and the prediction is the weighted mean of the components' posterior means,

$$w_c' \propto w_c \, \frac{\mathrm{B}(\alpha_c + k,\ \beta_c + n - k)}{\mathrm{B}(\alpha_c,\ \beta_c)}, \qquad \hat{p} = \sum_c w_c' \, \frac{\alpha_c + k}{\alpha_c + \beta_c + n}, \tag{3}$$

where B is the Beta function.

**Averaging over the prior.** Instead of one $(\alpha, \beta)$, we average the Beta-Binomial prediction over a grid of prior parameters, weighting each by the same factor $\mathrm{B}(\alpha + k, \beta + n - k)/\mathrm{B}(\alpha, \beta)$. We average over the prior's strength $\alpha + \beta$ at the fitted mean, or over its mean and strength together, in which case nothing is learned from training.

Table 1: Prior parameters by model and source. The prior mean of the Beta-Binomial is $\alpha/(\alpha+\beta)$ and its strength is $\alpha+\beta$. Kernel Rasch keeps $\rho$ and $T$ from validation, so its kernel is not fitted on training.

| Model | Fixed in advance | Fitted on training | Tuned on validation |
|---|---|---|---|
| Beta-Binomial | $\alpha=\beta=\frac{1}{2}$ | $\alpha=1.92, \beta=1.76$ | $\alpha=0.4, \beta=0.6$ |
| Rasch | $m_0=0$, $\sigma_\mu=\sigma_\theta=\sigma_\delta=1$ | $m_0=0.175, \sigma_\mu=0.75$, $\sigma_\theta=1.38, \sigma_\delta=1.49$ | $m_0=0.048, \sigma_\mu=2, \sigma_\theta=0.5$, $\sigma_\delta=1$ |
| Kernel Rasch | as Rasch, $\rho=0.5$, $T=0.1$ | as fitted Rasch, $\rho=0.8, T=0.2$ | $m_0=0.048, \sigma_\mu=2, \sigma_\theta=1$, $\sigma_\delta=1.4, \rho=0.8, T=0.2$ |

**Switch to Jeffreys.** Once at least $k_0 \in \{3, 7\}$ labels are revealed, we predict with the Jeffreys prior if the accuracy so far, $k/n$, lies more than $\eta$ from the fitted prior's mean $\alpha/(\alpha+\beta)$, and with the fitted prior otherwise. We choose $\eta$ on validation.

### 4.3 Probes

The predictors above ignore what an item says. A probe predicts an item's relative difficulty from its embedding before any response from that benchmark is available. We compare ridge regression on the embeddings, a probe using log character count, and a random score. We add ridge regression and a small neural network (MLP) that fit either the item pass rate or the negative fitted Rasch difficulty (easiness), each centred within its benchmark. The fitted probes use a fixed sample of 8,462 items from the 11 training benchmarks, at most 800 per benchmark, and choose their regularisation by five folds grouped by training benchmark. Appendix H gives the training details.

We score a probe on each benchmark by its Spearman correlation and its pairwise accuracy between predicted and observed item difficulty, averaged over benchmarks. Appendix H defines both.

To test whether a probe helps prediction, we give the item deviations of Rasch a prior mean taken from it,

$$\delta_j \sim \mathcal{N}\big(\gamma\, z_j,\ \sigma_\delta^2\big), \tag{4}$$

where $z_j$ is the probe's predicted difficulty of item $j$, centred within its benchmark (the benchmark rate $\mu_d$ absorbs the average), and $\gamma$ is a scale. Setting $\gamma=0$ gives the fitted Rasch. At prediction time the probes use only item features. Training outcomes supply supervision, and validation and test outcomes are used only for evaluation and for choosing $\gamma$ on validation.

### 4.4 Priors

Every predictor above needs prior parameters, and where they come from is the one thing our comparison changes. We set them from one of three sources. *Fixed in advance* means nothing is learned, so the Beta-Binomial uses Jeffreys and the Rasch models use unit widths. *Fitted on training* means estimated from the 11 training benchmarks only. *Tuned on validation* means the best setting on the three validation benchmarks from a grid. Table 1 lists the settings.

*Fitted on training* means estimated from the responses of the 11 training benchmarks, once, before any simulation starts. For the Beta-Binomial, we choose $(\alpha, \beta)$ to maximise the probability of the training tasks' counts, where a task with $k$ correct labels out of $n$ has probability proportional to $\mathrm{B}(\alpha+k, \beta+n-k)/\mathrm{B}(\alpha,\beta)$, and every benchmark counts equally. This gives a prior mean of $0.522$ worth $\alpha+\beta=3.68$ labels. For Rasch, we first fit the model to $4.34$ million training responses (4,809 subjects, 109,987 items) by maximum a posteriori estimation. We then set each prior parameter from the fitted values: $m_0$ is the mean of the benchmark rates $\mu_d$, and each width is the spread of the corresponding fitted quantity ($\mu_d$, $\theta_i$ or $\delta_j$), averaged per benchmark so that the benchmark with the most subjects does not dominate. We repeat the two steps until the values stop changing. Only these prior parameters transfer to a new benchmark. The fitted $\mu_d$, $\theta_i$ and $\delta_j$ belong to training benchmarks, subjects and items.

*Tuned on validation* is different, because nothing is estimated from a likelihood. We try a grid of settings, run the online simulation on the three validation benchmarks with each, and keep the setting with the lowest Brier ALC. The scale $\gamma$ of the probe prior mean (Section 4.3) is chosen the same way. The two sources differ in what they learn from and what they optimise. Fitting on training uses

Table 2: **A prior fitted on training helps on the test benchmarks and hurts on the validation benchmarks; a fixed prior with strong shrinkage does nearly as well on test.** Each cell is $\Delta_{m-\mathrm{J}}$ for the model $m$ in the row, competition-shaped draws. ID: held-out subjects on the 11 training benchmarks, 114 tasks, where the training-fitted Beta-Binomial prior is refit without those subjects. OOD validation: 3 unseen benchmarks, 80 tasks. OOD test: 3 unseen benchmarks, 45 tasks. Bold: best of the nine models in each column; underlined: second best.

| Model $m$ | ID | OOD validation | OOD test |
|---|---|---|---|
| *Fixed in advance* | | | |
| Beta-Binomial (Jeffreys) | 0 (reference) | 0 (reference) | 0 (reference) |
| Rasch | $-0.0073$ [$-0.0091$, $-0.0055$] | $+0.0031$ [$-0.0005$, $+0.0066$] | $-0.0102$ [$-0.0118$, $-0.0085$] |
| Kernel Rasch | $-0.0072$ [$-0.0087$, $-0.0058$] | $+0.0029$ [$-0.0008$, $+0.0065$] | $-0.0105$ [$-0.0121$, $-0.0088$] |
| *Tuned on validation* | | | |
| Beta-Binomial | $+0.0041$ [$+0.0027$, $+0.0055$] | $\mathbf{-0.0015}$ [$-0.0040$, $+0.0010$] | $+0.0055$ [$+0.0038$, $+0.0072$] |
| Rasch | $-0.0024$ [$-0.0028$, $-0.0019$] | $+0.0004$ [$-0.0006$, $+0.0014$] | $-0.0032$ [$-0.0035$, $-0.0029$] |
| Kernel Rasch | $+0.0001$ [$-0.0004$, $+0.0005$] | $\underline{-0.0003}$ [$-0.0010$, $+0.0004$] | $-0.0024$ [$-0.0027$, $-0.0021$] |
| *Fitted on training* | | | |
| Beta-Binomial | $\mathbf{-0.0090}$ [$-0.0115$, $-0.0063$] | $+0.0079$ [$+0.0024$, $+0.0136$] | $\mathbf{-0.0138}$ [$-0.0158$, $-0.0116$] |
| Rasch | $\underline{-0.0081}$ [$-0.0101$, $-0.0060$] | $+0.0052$ [$+0.0008$, $+0.0097$] | $\underline{-0.0119}$ [$-0.0133$, $-0.0106$] |
| Kernel Rasch | $-0.0063$ [$-0.0076$, $-0.0049$] | $+0.0036$ [$-0.0007$, $+0.0076$] | $-0.0118$ [$-0.0131$, $-0.0105$] |

many benchmarks and a likelihood and never sees validation or test outcomes. Tuning on validation uses three benchmarks and the score we care about and never sees test outcomes. Both are fixed before the test simulation starts, and the probes are trained on the training benchmarks' items only.

## 5 Results

Every difference is written $\Delta_{a-b}$, the Brier ALC of model $a$ minus that of model $b$, so negative favours $a$; paired 95% bootstrap intervals are over tasks. J is the Jeffreys Beta-Binomial; BB, R and KR are the Beta-Binomial, Rasch and kernel Rasch models, subscripted fix, tune or fit for the source of their prior, and R off is the offline Rasch that keeps its fitted values.

### 5.1 Prior source matters, and no source wins on every split

Table 2 compares the nine combinations. The validation-tuned Beta-Binomial prior is *worse* than Jeffreys on test ($\Delta_{\mathrm{BB\,tune-J}} = +0.0055$) though it is the best Beta-Binomial on validation. Every comparison between prior sources changes sign between test and validation (Appendix B); fresh draws change no result by more than $0.0007$ (Appendix C). The prior's source matters at zero to three labels and has faded by 31 (Figure 4, Appendix L). Other metrics tell the same story: log loss and calibration error give the same ordering of the prior sources on test and the same reversal on validation, and rank metrics are uninformative for a constant prediction (Appendix F).

### 5.2 Learned priors transfer to unseen benchmarks; item-level estimates do not

On the ID evaluation set the offline model that keeps its fitted values scores $\Delta_{\mathrm{R\,off-J}} = -0.0852$ [$-0.0955$, $-0.0747$] against $\Delta_{\mathrm{BB\,fit-J}} = -0.0090$ for the fitted Beta-Binomial prior and $\Delta_{\mathrm{R\,fit-J}} = -0.0081$ for the fitted Rasch prior (Figure 1); its item difficulties alone, at budget zero, reach a within-task AUC of $0.836$. On the unseen test benchmarks it equals the fitted prior ($\Delta_{\mathrm{R\,off-J}} = -0.0115$ against $\Delta_{\mathrm{R\,fit-J}} = -0.0119$): nothing it knows about particular items or benchmark rates is available. This is the seen-benchmark check the design requires, and it separates two things that are easy to conflate: item-level estimates transfer only to the items they were fitted on, while the prior's spreads carry over to new benchmarks.

### 5.3 Learned priors help benchmarks of typical difficulty and hurt much easier or harder ones

Figure 5 (Appendix L) shows the test and validation benchmarks separately: all three test benchmarks agree ($\Delta_{\mathrm{BB\,fit-J}}$ from $-0.013$ to $-0.015$), and on validation `ai2d_test` agrees while





Figure 1: **Offline estimates win on familiar benchmarks and have no edge on unfamiliar ones.** Brier score per label budget for the offline Rasch keeping its fitted benchmark rates and item difficulties and updating only ability (solid), against the online Rasch with the same fitted prior (dashed). Left: ID, held-out subjects on the 11 training benchmarks. Right: OOD test benchmarks, where the offline model has no fitted values and falls back to the prior.





Figure 2: **A fitted prior helps when a benchmark's accuracy is near the prior mean.** Each point is one of 17 benchmarks. For each of the 11 training benchmarks, the prior was refit without any of that benchmark's rows and scored on held-out subjects. The six validation and test benchmarks use the original training-only prior. The horizontal axis uses task accuracy on the evaluation items; the vertical axis shows $\Delta_{\mathrm{BB\,fit-J}}$, with 95% task-bootstrap intervals. This is an explanatory analysis using observed outcomes.

`bird_sql` goes the other way ($+0.025$). Over the 17 benchmarks (Figure 2; each training benchmark is held out in turn, Appendix D) the fitted prior significantly helps on 9, significantly hurts on 1 (`bird_sql`), and the macro mean $\Delta_{\mathrm{BB\,fit-J}}$ is $-0.0050$. What separates the benchmarks is not whether they lie inside the range of training benchmark rates (`alignment_faking` and `harmbench` lose while inside it) but how far their task accuracies sit from the prior mean: the Spearman correlation between the gain and that distance is $0.96$ over the 17 benchmarks ($0.93$ over the 11 training benchmarks), against $0.01$ over the 11 for the benchmark's mean accuracy. The prior is a starting guess that a task is answered correctly about $52\%$ of the time, and with few labels the predictor pulls its estimate toward it. If a benchmark's true accuracy is, say, $55\%$, the pull lands near the truth and the prediction improves; if it is $12\%$, as on `bird_sql`, the pull drags the estimate the wrong way

Table 3: Item-difficulty transfer: within-benchmark Spearman correlation and pairwise accuracy between predicted easiness and observed pass rate, averaged across benchmarks. ID: items held out within the 11 training benchmarks; OOD validation and OOD test: three unseen benchmarks each. The additional pass-rate and Rasch-target probes use benchmark-grouped selection and were not evaluated on ID (–).

| | ID | | OOD validation | | OOD test | |
|---|---|---|---|---|---|---|
| Probe | Spearman | Pairwise | Spearman | Pairwise | Spearman | Pairwise |
| Random score | $-0.003$ | $0.499$ | $-0.024$ | $0.490$ | $0.076$ | $0.529$ |
| Log character count | $0.107$ | $0.539$ | $0.058$ | $0.525$ | $0.061$ | $0.521$ |
| Ridge on embeddings | $0.400$ | $0.649$ | $0.196$ | $0.570$ | $-0.020$ | $0.494$ |
| Pass-rate ridge | – | – | $0.165$ | $0.557$ | $-0.035$ | $0.487$ |
| Rasch-target ridge | – | – | $0.130$ | $0.544$ | $-0.035$ | $0.487$ |
| Pass-rate MLP | – | – | $0.071$ | $0.523$ | $0.109$ | $0.539$ |
| Rasch-target MLP | – | – | $0.146$ | $0.550$ | $0.059$ | $0.522$ |

and it gets worse. So the prior helps on benchmarks of typical difficulty and hurts on much easier or much harder ones. The three test benchmarks (mean accuracy $0.54$–$0.68$) sit near the prior mean, which is why test looks good. A random choice of three held-out benchmarks would usually look worse: over all 680 choices, with the prior refit on the other 14 benchmarks, the mean $\Delta_{\mathrm{BB\,fit}-\mathrm{J}}$ is $-0.0037$ and the prior hurts in $17.5\%$ of them (Appendix E). We found this pattern after seeing the results, so it is an explanation and not a predictor.

Under the fitted priors, the simplest Rasch model is also the best on test and the worst on validation: with benchmark rate only $\Delta_{m-\mathrm{J}}$ is $-0.0172$ on test and $+0.0211$ on validation (Appendix A). The subject-ability term is what lets a benchmark far from the prior move away from it, at a cost in variance when the benchmark is near it. The kernel adds nothing on test.

### 5.4 Item content carries a small rank signal and a negligible gain for the prior

Embeddings show a clear signal on known benchmarks. On the six unseen benchmarks the two MLP probes pass the criterion we fixed in advance, with benchmark-macro Spearman $0.090$ and $0.103$ against $0.026$ for a random baseline and a positive correlation on 5 of 6 benchmarks; the ridge probes do not ($0.065$ and $0.047$). On the three test benchmarks alone, the pass-rate MLP reaches $0.109$, while the Rasch-target MLP reaches $0.059$, below the sampled random control's $0.076$. The aggregate rank criterion therefore does not establish a consistent test-only advantage.

The rank signal yields only a small gain at the validation-selected scale. In Table 10 (Appendix H), every $\gamma \geq 0.25$ is worse than $\gamma = 0$ on both splits. The scale selected on validation ($\gamma = 0.05$, Rasch-target MLP) improves Brier ALC by about $0.0004$ on each split in its matched replay; this comparison alone does not establish a reliable improvement. This tests these two probes only; a stronger difficulty predictor, for instance one trained through an item response likelihood on more items, could do better.

### 5.5 Priors that adapt to the first labels do not remove the harm

Table 11 (Appendix I) compares the adaptive priors of Section 4.2 with the fitted Beta-Binomial prior over the 17 benchmarks. They trade gain for safety and none dominates it. The mixtures give the largest average and test gains but leave the worst benchmark as bad as before. Averaging over the mean and strength nearly removes the worst case but halves the gain. The switch rule falls in between. We had fixed three criteria in advance: a worst benchmark of at most $+0.0120$, a mean within $0.0010$ of the fitted prior's $-0.0050$, and a test gain within $0.0020$ of its $-0.0138$. No adaptive prior meets all three.

Can the first labels warn that the prior will hurt? The distance of the accuracy so far from the prior's mean separates the tasks the prior hurts from the rest, with an area under the ROC curve (AUC) of $0.73$ from seven labels, but only $0.64$ within a benchmark, so most of the signal is between benchmarks. The harm sits at zero to three labels, which carry half of the ALC weight, before any such warning exists.

## 6 Limitations

**Evidence.** Our results rest on 17 benchmarks from the competition's public data, with random label acquisition, and three benchmarks serve as test. Intervals resample tasks, so they do not reflect which benchmarks are held out. Section 5 and Appendix E report the sensitivity to that choice, and the choices overlap.

**Selection.** All settings were chosen on validation. Test scores were visible during development, so we treat the test split as one of many possible splits and report the others. Our account of when the prior helps was formed after seeing the results and uses observed outcomes, so it explains them and does not select a prior for a new benchmark.

**Not tested.** Sharing labels across subjects, other label-selection policies, priors from subject metadata, reasoning-trace features (unavailable at test time) and stronger difficulty predictors. The conclusions are limited to the models and data above.

## 7 Conclusion

What transfers from offline fitting to an unseen benchmark is a shrinkage prior, not item-level estimates. Where fitted values apply, offline fitting is worth a very large gain, and where they do not, it is worth none. The prior itself helps only modestly and unevenly. It pulls predictions toward a typical accuracy, which helps benchmarks of typical difficulty and hurts much easier or much harder ones, so its benefit depends on which benchmarks a new evaluation contains. Two ways of doing better added little. Priors that adapt to the first labels traded gain for safety without beating the fixed prior, and probes that predict item difficulty from item text carry a small rank signal that barely improved prediction.

These findings concern the models and data we studied. Each of our evaluations reveals answers from one LLM per benchmark, so whether sharing labels across LLMs helps remains open, and a stronger difficulty predictor could change the picture. It also remains open whether tabular foundation models or meta-learning, which learn to predict from a few labelled examples, can carry across benchmarks information that a fixed prior cannot.

## Disclosure

**Training data.** All fitted quantities (the offline Rasch fit, the Beta-Binomial empirical-Bayes prior, the item probes) use only the responses of the 11 training benchmarks in the competition's measurement database after the filtering described in Section 3; no other response data is used.

**Pretrained models.** Item text is embedded with the frozen BGE-M3 model; nothing else is pretrained or fine-tuned.

**Author contributions and LLM assistance.** The authors formulated the research questions, directed the experiments, selected the final methods, and interpreted the results. Claude Code (Anthropic) and OpenAI Codex assisted with brainstorming and refining ideas, implementing code, preparing analyses and figures, and drafting and revising text. A colleague with training in statistical learning contributed to discussions of the mathematical formulation. LLM-assisted development at times became difficult to audit and steer; this was one reason we chose a simpler, more transparent predictor for the competition submission. All reported numerical results were generated by executing the repository code and checked by the authors. The authors retained responsibility for the methodological decisions, verification, and final manuscript.

## References


[1] HELM african MMLU and WinoGrande, version 1.1.0. Stanford Center for Research on Foundation Models benchmark release. URL https://crfm.stanford.edu/helm/mmlu-winogrande-afr/latest/. Accessed 7 November 2026; distinct from the general HELM framework paper.

[2] David Ifeoluwa Adelani, Jade Abbott, Graham Neubig, Daniel D'souza, Julia Kreutzer, Constantine Lignos, Chester Palen-Michel, Happy Buzaaba, Shruti Rijhwani, Sebastian Ruder, Stephen Mayhew, Israel Abebe Azime, Shamsuddeen H. Muhammad, Chris Chinenye Emezue, Joyce Nakatumba-Nabende, Perez Ogayo, Aremu Anuoluwapo, Catherine Gitau, Derguene Mbaye, Jesujoba Alabi, Seid Muhie Yimam, Tajuddeen Rabiu Gwadabe, Ignatius Ezeani, Rubungo Andre Niyongabo, Jonathan Mukiibi, Verrah Otiende, Iroro Orife, Davis David, Samba Ngom, Tosin Adewumi, Paul Rayson, Mofetoluwa Adeyemi, Gerald Muriuki, Emmanuel Anebi, Chiamaka Chukwuneke, Nkiruka Odu, Eric Peter Wairagala, Samuel Oyerinde, Clemencia Siro, Tobius Saul Bateesa, Temilola Oloyede, Yvonne Wambui, Victor Akinode, Deborah Nabagereka, Maurice Katusiime, Ayodele Awokoya, Mouhamadane MBOUP, Dibora Gebreyohannes, Henok Tilaye, Kelechi Nwaike, Degaga Wolde, Abdoulaye Faye, Blessing Sibanda, Orevaoghene Ahia, Bonaventure F. P. Dossou, Kelechi Ogueji, Thierno Ibrahima DIOP, Abdoulaye Diallo, Adewale Akinfaderin, Tendai Marengereke, and Salomey Osei. MasakhaNER: Named entity recognition for African languages. *Transactions of the Association for Computational Linguistics*, 9:1116–1131, 2021. doi: 10.1162/tacl_a_00416. URL https://aclanthology.org/2021.tacl-1.66/.

[3] David Ifeoluwa Adelani, Graham Neubig, Sebastian Ruder, Shruti Rijhwani, Michael Beukman, Chester Palen-Michel, Constantine Lignos, Jesujoba O. Alabi, Shamsuddeen H. Muhammad, Peter Nabende, Cheikh M. Bamba Dione, Andiswa Bukula, Rooweither Mabuya, Bonaventure F. P. Dossou, Blessing Sibanda, Happy Buzaaba, Jonathan Mukiibi, Godson Kalipe, Derguene Mbaye, Amelia Taylor, Fatoumata Kabore, Chris Chinenye Emezue, Anuoluwapo Aremu, Perez Ogayo, Catherine Gitau, Edwin Munkoh-Buabeng, Victoire Memdjokam Koagne, Allahsera Auguste Tapo, Tebogo Macucwa, Vukosi Marivate, Elvis Mboning, Tajuddeen Gwadabe, Tosin Adewumi, Orevaoghene Ahia, Joyce Nakatumba-Nabende, Neo L. Mokono, Ignatius Ezeani, Chiamaka Chukwuneke, Mofetoluwa Adeyemi, Gilles Q. Hacheme, Idris Abdulmumin, Odunayo Ogundepo, Oreen Yousuf, Tatiana Moteu Ngoli, and Dietrich Klakow. MasakhaNER 2.0: Africa-centric transfer learning for named entity recognition. In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang, editors, *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 4488–4508, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.298. URL https://aclanthology.org/2022.emnlp-main.298/.

[4] Tuka Alhanai, Adam Kasumovic, Mohammad Ghassemi, Aven Zitzelberger, Jessica Lundin, and Guillaume Chabot-Couture. Bridging the gap: Enhancing llm performance for low-resource african languages with new benchmarks, fine-tuning, and cultural adjustments, 2024. URL https://arxiv.org/abs/2412.12417.

[5] Lucas Bandarkar, Davis Liang, Benjamin Muller, Mikel Artetxe, Satya Narayan Shukla, Donald Husa, Naman Goyal, Abhinandan Krishnan, Luke Zettlemoyer, and Madian Khabsa. The belebele benchmark: a parallel reading comprehension dataset in 122 language variants, 2024. URL https://arxiv.org/abs/2308.16884.

[6] Jianlv Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. BGE M3-embedding: Multi-lingual, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. arXiv:2402.03216, 2024.

[7] Wayne Chi, Valerie Chen, Ryan Shar, Aditya Mittal, Jenny Liang, Wei-Lin Chiang, Anastasios Nikolas Angelopoulos, Ion Stoica, Graham Neubig, Ameet Talwalkar, and Chris Donahue. Edit-bench: Evaluating llm abilities to perform real-world instructed code edits, 2025. URL https://arxiv.org/abs/2511.04486.

[8] Bradley Efron and Carl Morris. Stein's estimation rule and its competitors—an empirical Bayes approach. *Journal of the American Statistical Association*, 68(341):117–130, 1973.

[9] Johannes Gasteiger, Vlad Mikulik, Hoagy Cunningham, Misha Wagner, Benjamin Wright, Jonathan Uesato, Joe Benton, Monte MacDiarmid, Fabien Roger, and Evan Hubinger. Towards training-time mitigations for alignment faking in RL. Anthropic Alignment Science Blog, December 2025. URL https://alignment.anthropic.com/2025/alignment-faking-mitigations/. Published 16 December 2025; source study for the alignment-faking-rl response release.

[10] Alex Gu, Baptiste Rozière, Hugh Leather, Armando Solar-Lezama, Gabriel Synnaeve, and Sida I. Wang. Cruxeval: A benchmark for code reasoning, understanding and execution, 2024. URL https://arxiv.org/abs/2401.03065.

[11] Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, Dinesh Manocha, and Tianyi Zhou. Hallusionbench: An advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models, 2024. URL https://arxiv.org/abs/2310.14566.

[12] Tianyu Guo, Hongyu Chen, Hao Liang, Meiyi Qiang, Bohan Zeng, Linzhuang Sun, Bin Cui, and Wentao Zhang. Brace: A benchmark for robust audio caption quality evaluation, 2025. URL https://arxiv.org/abs/2512.10403.

[13] Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding, 2021. URL https://arxiv.org/abs/2009.03300.

[14] Pranab Islam, Anand Kannappan, Douwe Kiela, Rebecca Qian, Nino Scherrer, and Bertie Vidgen. Financebench: A new benchmark for financial question answering, 2023. URL https://arxiv.org/abs/2311.11944.

[15] Harold Jeffreys. An invariant form for the prior probability in estimation problems. *Proceedings of the Royal Society A*, 186, 1946.

[16] Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. A diagram is worth a dozen images, 2016. URL https://arxiv.org/abs/1603.07396.

[17] Stefan Krsteski and Charlotte Meyer. Predicting task difficulty without rollouts, 2026. URL https://arxiv.org/abs/2608.05797.

[18] Insung Lee, Taeyoung Jeong, Haejun Yoo, Du-Seong Chang, and Myoung-Wan Koo. Caf-score: Calibrating clap with lalms for reference-free audio captioning evaluation, 2026. URL https://arxiv.org/abs/2603.19615.

[19] Haonan Li, Yixuan Zhang, Fajri Koto, Yifei Yang, Hai Zhao, Yeyun Gong, Nan Duan, and Timothy Baldwin. Cmmlu: Measuring massive multitask language understanding in chinese, 2024. URL https://arxiv.org/abs/2306.09212.

[20] Jinyang Li, Binyuan Hui, Ge Qu, Jiaxi Yang, Binhua Li, Bowen Li, Bailin Wang, Bowen Qin, Rongyu Cao, Ruiying Geng, Nan Huo, Xuanhe Zhou, Chenhao Ma, Guoliang Li, Kevin C. C. Chang, Fei Huang, Reynold Cheng, and Yongbin Li. Can llm already serve as a database interface? a big bench for large-scale database grounded text-to-sqls, 2023. URL https://arxiv.org/abs/2305.03111.

[21] Yang Li, Jie Ma, Miguel Ballesteros, Yassine Benajiba, and Graham Horwood. Active evaluation acquisition for efficient LLM benchmarking. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu, editors, *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 35581–35602. PMLR, 13–19 Jul 2025. URL https://proceedings.mlr.press/v267/li25bp.html.

[22] Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, Benjamin Newman, Binhang Yuan, Bobby Yan, Ce Zhang, Christian Cosgrove, Christopher D. Manning, Christopher Ré, Diana Acosta-Navas, Drew A. Hudson, Eric Zelikman, Esin Durmus, Faisal Ladhak, Frieda Rong, Hongyu Ren, Huaxiu Yao, Jue Wang, Keshav Santhanam, Laurel Orr, Lucia Zheng, Mert Yuksekgonul, Mirac Suzgun, Nathan Kim, Neel Guha, Niladri Chatterji, Omar Khattab, Peter Henderson, Qian Huang, Ryan Chi, Sang Michael Xie, Shibani Santurkar, Surya Ganguli, Tatsunori Hashimoto, Thomas Icard, Tianyi Zhang, Vishrav Chaudhary, William Wang, Xuechen Li, Yifan Mai, Yuhui Zhang, and Yuta Koreeda. Holistic evaluation of language models, 2023. URL https://arxiv.org/abs/2211.09110.

[23] Felipe Maia Polo, Lucas Weber, Leshem Choshen, Yuekai Sun, Gongjun Xu, and Mikhail Yurochkin. tinyBenchmarks: evaluating LLMs with fewer examples. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 34303–34326. PMLR, 2024. URL https://proceedings.mlr.press/v235/maia-polo24a.html.

[24] Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal, 2024. URL https://arxiv.org/abs/2402.04249.

[25] Charles Nimo, Tobi Olatunji, Abraham Toluwase Owodunni, Tassallah Abdullahi, Emmanuel Ayodele, Mardhiyah Sanni, Ezinwanne C. Aka, Folafunmi Omofoye, Foutse Yuehgoh, Timothy Faniran, Bonaventure F. P. Dossou, Moshood O. Yekini, Jonas Kemp, Katherine A Heller, Jude Chidubem Omeke, Chidi Asuzu Md, Naome A Etori, Aïmérou Ndiaye, Ifeoma Okoh, Evans Doe Ocansey, Wendy Kinara, Michael L. Best, Irfan Essa, Stephen Edward Moore, Chris Fourie, and Mercy Nyamewaa Asiedu. AfriMed-QA: A pan-African, multi-specialty, medical question-answering benchmark dataset. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar, editors, *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1948–1973, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.96. URL https://aclanthology.org/2025.acl-long.96/.

[26] Ori Press, Brandon Amos, Haoyu Zhao, Yikai Wu, Samuel K. Ainsworth, Dominik Krupke, Patrick Kidger, Touqir Sajed, Bartolomeo Stellato, Jisun Park, Nathanael Bosch, Eli Meril, Albert Steppi, Arman Zharmagambetov, Fangzhao Zhang, David Perez-Pineiro, Alberto Mercurio, Ni Zhan, Talor Abramovich, Kilian Lieret, Hanlin Zhang, Shirley Huang, Matthias Bethge, and Ofir Press. Algotune: Can language models speed up general-purpose numerical programs?, 2025. URL https://arxiv.org/abs/2507.15887.

[27] J. N. K. Rao and Isabel Molina. *Small Area Estimation*. Wiley, 2nd edition, 2015.

[28] Georg Rasch. *Probabilistic Models for Some Intelligence and Attainment Tests*. Danish Institute for Educational Research, 1960.

[29] Herbert Robbins. An empirical Bayes approach to statistics. In *Proceedings of the Third Berkeley Symposium on Mathematical Statistics and Probability*, volume 1, pages 157–163, 1956.

[30] Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale, 2019. URL https://arxiv.org/abs/1907.10641.

[31] Heinz Schmidli, Sandro Gsteiger, Satrajit Roychoudhury, Anthony O'Hagan, David Spiegelhalter, and Beat Neuenschwander. Robust meta-analytic-predictive priors in clinical trials with historical control information. *Biometrics*, 70(4):1023–1032, 2014. doi: 10.1111/biom.12242.

[32] Shuo Sun, Yimin Zhao, Christina Dao Wen Lee, Jiawei Sun, Chengran Yuan, Zefan Huang, Dongen Li, Justin KW Yeoh, Alok Prakash, Thomas W. Malone, and Marcelo H. Ang Jr. Agi-elo: How far are we from mastering a task?, 2025. URL https://arxiv.org/abs/2505.12844.

[33] Harsh Trivedi, Tushar Khot, Mareike Hartmann, Ruskin Manku, Vinty Dong, Edward Li, Shashank Gupta, Ashish Sabharwal, and Niranjan Balasubramanian. Appworld: A controllable world of apps and people for benchmarking interactive coding agents, 2024. URL https://arxiv.org/abs/2407.18901.

[34] Sang T. Truong, Yuheng Tu, Percy Liang, Bo Li, and Sanmi Koyejo. Reliable and efficient amortized model-based evaluation. In Aarti Singh, Maryam Fazel, Daniel Hsu, Simon Lacoste-Julien, Felix Berkenkamp, Tegan Maharaj, Kiri Wagstaff, and Jerry Zhu, editors, *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 60238–60265. PMLR, 13–19 Jul 2025. URL https://proceedings.mlr.press/v267/truong25c.html.

[35] Guanhua Zhang, Florian E. Dorner, and Moritz Hardt. How benchmark prediction from fewer data misses the mark, 2026. URL https://arxiv.org/abs/2506.07673.

## A Rasch terms under the fitted priors

Table 4: $\Delta_{m-\mathrm{J}}$ for Rasch with terms switched off (prior width $\sigma$ set near zero), under the training-fitted priors. Competition-shaped draws on OOD validation and OOD test. Bold: lowest in each column.

| Model $m$ | OOD validation | OOD test |
|---|---|---|
| Benchmark rate $\mu_d$ only | $+0.0211$<br>$[+0.0114, +0.0311]$ | $-0.0172$<br>$[-0.0202, -0.0142]$ |
| + subject ability $\theta_i$ | $\mathbf{+0.0029}$<br>$[-0.0003, +0.0060]$ | $-0.0089$<br>$[-0.0100, -0.0080]$ |
| + item deviation $\delta_j$ (Rasch) | $+0.0052$<br>$[+0.0007, +0.0098]$ | $-0.0119$<br>$[-0.0133, -0.0106]$ |
| + kernel | $+0.0036$<br>$[-0.0006, +0.0078]$ | $-0.0118$<br>$[-0.0131, -0.0105]$ |
| $\mu_d$ and $\delta_j$, no $\theta_i$ | $+0.0282$<br>$[+0.0164, +0.0401]$ | $\mathbf{-0.0174}$<br>$[-0.0208, -0.0139]$ |
| $\theta_i$ and $\delta_j$, no $\mu_d$ | $+0.0078$<br>$[+0.0022, +0.0135]$ | $-0.0140$<br>$[-0.0157, -0.0122]$ |

## B Paired comparisons between prior sources

Table 5: Paired $\Delta_{a-b}$ between prior sources, with 95% intervals over tasks. Each comparison changes sign between OOD test and OOD validation. A dash: not run on ID.

| Comparison | ID | OOD validation | OOD test |
|---|---|---|---|
| $\Delta_{\mathrm{R\,fit}-\mathrm{R\,fix}}$ | – | $+0.0021$<br>$[+0.0006, +0.0036]$ | $-0.0017$<br>$[-0.0028, -0.0005]$ |
| $\Delta_{\mathrm{KR\,fit}-\mathrm{R\,fit}}$ | – | $-0.0016$<br>$[-0.0021, -0.0012]$ | $+0.0001$<br>$[-0.0002, +0.0004]$ |
| $\Delta_{\mathrm{R\,fit}-\mathrm{BB\,fit}}$ | $+0.0009$<br>$[-0.0001, +0.0018]$ | $-0.0027$<br>$[-0.0041, -0.0012]$ | $+0.0019$<br>$[+0.0007, +0.0031]$ |

## C Draw-seed robustness

Table 6: $\Delta_{m-\mathrm{J}}$ on three fresh sets of 150 competition-shaped draws per role (seeds 20261201–03); results on the frozen draws are in Table 2.

| Model $m$ | OOD validation | OOD test |
|---|---|---|
| BB fit | $+0.0078$ / $+0.0083$ / $+0.0089$ | $-0.0137$ / $-0.0144$ / $-0.0139$ |
| R fit | $+0.0051$ / $+0.0054$ / $+0.0060$ | $-0.0120$ / $-0.0124$ / $-0.0123$ |
| BB tune | $-0.0015$ / $-0.0016$ / $-0.0018$ | $+0.0060$ / $+0.0059$ / $+0.0063$ |

## D The fitted prior on all 17 benchmarks

Table 7: $\Delta_{\mathrm{BB\,fit-J}}$ for each of the 17 benchmarks. Training benchmarks: the prior is refit without the held-out benchmark and scored on held-out-subject tasks. OOD validation and OOD test benchmarks: the original training-only prior. The last column is the mean distance of a benchmark's task accuracies from the prior mean $0.52$.

| Benchmark | Split | Tasks | $\Delta_{\mathrm{BB\,fit-J}}$ [95% CI] | Mean distance from $0.52$ |
|---|---|---|---|---|
| `hallusionbench` [11] | Training | 20 | $-0.0151$ [$-0.0165$, $-0.0137$] | 0.11 |
| `editbench` [7] | OOD test | 17 | $-0.0149$ [$-0.0171$, $-0.0127$] | 0.10 |
| `bridging_gap` [4, 13, 30, 5] | Training | 20 | $-0.0142$ [$-0.0168$, $-0.0116$] | 0.14 |
| `helm_afr` [4, 1, 22, 13, 30] | Training | 3 | $-0.0139$ [$-0.0168$, $-0.0108$] | 0.07 |
| `cmmlu` [19] | OOD test | 10 | $-0.0137$ [$-0.0187$, $-0.0096$] | 0.17 |
| `algotune` [26] | OOD test | 18 | $-0.0127$ [$-0.0166$, $-0.0085$] | 0.17 |
| `afrimedqa` [25] | Training | 6 | $-0.0121$ [$-0.0191$, $-0.0047$] | 0.15 |
| `afrieval` [2, 3] | Training | 20 | $-0.0111$ [$-0.0138$, $-0.0084$] | 0.18 |
| `ai2d_test` [16] | OOD validation | 29 | $-0.0107$ [$-0.0154$, $-0.0065$] | 0.19 |
| `cruxeval` [10] | Training | 5 | $-0.0055$ [$-0.0155$, $+0.0060$] | 0.17 |
| `brace` [12, 18] | Training | 6 | $-0.0042$ [$-0.0124$, $+0.0037$] | 0.22 |
| `agi_elo` [32, 13] | Training | 4 | $+0.0004$ [$-0.0069$, $+0.0076$] | 0.26 |
| `appworld` [33] | Training | 4 | $+0.0026$ [$-0.0087$, $+0.0120$] | 0.24 |
| `alignment_faking` [9] | Training | 20 | $+0.0043$ [$-0.0091$, $+0.0191$] | 0.24 |
| `financebench` [14] | OOD validation | 16 | $+0.0047$ [$-0.0041$, $+0.0134$] | 0.28 |
| `harmbench` [24] | Training | 6 | $+0.0070$ [$-0.0023$, $+0.0159$] | 0.31 |
| `bird_sql` [20] | OOD validation | 35 | $+0.0248$ [$+0.0161$, $+0.0334$] | 0.40 |
| Mean over the 17 benchmarks | | 239 | $-0.0050$ | 0.20 |
| Mean over the 11 training benchmarks | | 114 | $-0.0056$ | 0.19 |
| Spearman $\rho$ between gain and distance: $0.96$ over the 17 benchmarks, $0.93$ over the 11 training benchmarks. | | | | |

## E Sensitivity to the benchmark split

We held out each of the 680 triples, refitted the benchmark-weighted empirical Beta prior on the other 14 benchmarks, and rescored the frozen trajectories. The mean macro $\Delta_{\mathrm{BB\,fit-J}}$ was $-0.0037$, with 5th–95th percentiles [$-0.0095$, $+0.0099$]. The fitted prior hurt on 17.5% of splits. The original test benchmark names gave $-0.0087$ (percentile 13) under refitting. This refit includes the former validation benchmarks among the 14 eligible fit benchmarks for the original test triple, so its result differs from the original 11-benchmark fit. The 11 original training benchmarks are scored on held-out-subject tasks from the existing leave-one-out data. These overlapping triples describe split sensitivity within this dataset. The main text uses the prior fitted on the 11 training benchmarks only. Under that prior the mean macro $\Delta_{\mathrm{BB\,fit-J}}$ over the same triples is $-0.0050$, the prior hurts on 17.8% of them, and the original test benchmarks give $-0.0138$.





Figure 3: $\Delta_{\text{BB fit}-\text{J}}$ over all 680 triples. Each empirical prior is fitted on the 14 benchmarks outside its triple. The vertical line marks the original test benchmark names under this refitting protocol.

For 40 random triples we also refit the Rasch prior without the triple's training benchmarks. Table 8 compares it with the Beta-Binomial on the same triples.

Table 8: The fitted prior on 40 random triples of held-out benchmarks. Mean macro $\Delta_{m-\text{J}}$ over the triples, its 5th to 95th percentile, and the share of triples on which the prior hurts. The prior is refit without the triple's training benchmarks.

| Fitted prior | Triples | Mean macro $\Delta_{m-\text{J}}$ | 5th–95th percentile | Hurts |
|---|---|---|---|---|
| Beta-Binomial | 40 | $-0.0051$ | $[-0.0128, +0.0067]$ | 20.0% |
| Rasch | 40 | $-0.0041$ | $[-0.0095, +0.0037]$ | 22.5% |

## F Alternative evaluation metrics

Table 9: Competition-shaped online simulation; models are labelled as in Section 5. Brier, log loss, and ten-bin task ECE are averaged using the official budget weights; lower is better. AUC uses within-task item rankings at 31 labels, where higher is better. Dashes indicate no informative ranking; a constant prediction ties all items. Bold: best in each split (lowest loss, highest AUC). Per-budget AUC and alternative weights are reported in the accompanying CSVs.

| Split | Model $m$ | Brier | Log loss | ECE | AUC at 31 labels |
|---|---|---|---|---|---|
| ID | J | 0.2357 | 0.6681 | 0.1407 | – |
| | BB fit | 0.2268 | 0.6437 | 0.1235 | – |
| | R fit | 0.2276 | 0.6460 | 0.1245 | – |
| | KR fit | 0.2295 | 0.6506 | 0.1336 | 0.581 |
| | R off | **0.1506** | **0.4634** | **0.1161** | **0.836** |
| OOD validation | J | **0.1738** | **0.5159** | **0.1405** | – |
| | BB fit | 0.1817 | 0.5404 | 0.1677 | – |
| | R fit | 0.1790 | 0.5323 | 0.1580 | – |
| | KR fit | 0.1774 | 0.5279 | 0.1603 | **0.618** |
| OOD test | J | 0.2499 | 0.7045 | 0.1426 | – |
| | BB fit | **0.2362** | **0.6656** | **0.1113** | – |
| | R fit | 0.2380 | 0.6712 | 0.1164 | – |
| | KR fit | 0.2382 | 0.6717 | 0.1230 | **0.571** |

## G Solver convergence and compute

**Online solver.** At every budget the online Rasch fit is a Newton solve with a limit of 30 steps. In 6,300 audited fits, none reached the limit, none needed more than 7 steps, and the last step was below $10^{-6}$ in every one.

**Offline fit.** Our first offline fit stopped at its iteration limit of 400 in three of its four rounds. We refit it with a proper stopping rule. The hyperparameters moved by at most $1.2\%$, the benchmark rates by at most $0.011$ on the logit scale, and no Brier ALC changed by more than $0.0001$. The reported results use the first fit, and the refit leaves them unchanged.

**Compute.** All experiments ran on CPU only, with no GPU, on one machine with 12 logical cores (AMD Ryzen AI 5 340) and 15 GB of memory. One run of the online simulation takes under a minute, and the offline Rasch fit on the training responses takes under ten minutes. The longest jobs, such as the refits for the sampled choices of held-out benchmarks, ran in the background on the same machine. The item embeddings are a precomputed input.

## H Probe details

**Scores.** We score a probe on each benchmark $d$ by two numbers and average each over benchmarks. Let $y_j$ be the observed pass rate of item $j$ across recorded subjects and $\hat{y}_j$ its predicted easiness, so higher values mean easier items. The *Spearman correlation* $\rho_d = \operatorname{corr}\big(\operatorname{rank}(\hat{y}_j), \operatorname{rank}(y_j)\big)$ compares the two orderings of the items: it is 1 if the probe orders them perfectly, 0 if its order is unrelated to the truth, and $-1$ if it is reversed. The *pairwise accuracy* $A_d = \frac{1}{|P_d|}\sum_{(j,k)\in P_d} s_{jk}$ is the share of item pairs the probe orders correctly, where $P_d$ is the set of pairs with $y_j \neq y_k$ (observed ties are excluded), $s_{jk} = 1$ if $\hat{y}_j - \hat{y}_k$ has the same sign as $y_j - y_k$, $s_{jk} = \frac{1}{2}$ if the probe predicts a tie, and $s_{jk} = 0$ otherwise. A random score has $A_d = 0.5$ on average.

**Training.** Inputs are standardised using the fitting items only. The neural network has one hidden layer of 32 units and a limit of 100 epochs. The Rasch targets come from the offline Rasch fit.

**From predictions to $z_j$.** For the Rasch-target probe, the difficulty $z_j$ is the negative of the predicted easiness. For the pass-rate probe, the centred prediction $f(x_j)$ is converted to a logit-scale difficulty,

$$z_j = \operatorname{logit}(\bar{p}) - \operatorname{logit}\big(\operatorname{clip}(\bar{p} + f(x_j),\, 10^{-4},\, 1 - 10^{-4})\big),$$

where $\bar{p}$ is the benchmark-weighted mean pass rate of the sampled training items. Positive difficulty means harder.

**Probe prior mean.** Table 10 gives the effect of the scale $\gamma$ in Equation (4).

Table 10: Predicted item difficulty as the prior mean of the Rasch item deviation, Equation (4). Cells are $\Delta_{m-\mathrm{J}}$ of the fitted Rasch with scale $\gamma$, competition-shaped draws; $\gamma = 0$ is the fitted Rasch without a prior mean. Bold: lowest in each column.

| | Pass-rate MLP | | Rasch-target MLP | |
|---|---|---|---|---|
| Scale $\gamma$ | OOD validation | OOD test | OOD validation | OOD test |
| 0 | $\mathbf{+0.0052}$ | $-0.0119$ | $+0.0052$ | $-0.0119$ |
| 0.05 | $+0.0062$ | $\mathbf{-0.0119}$ | $\mathbf{+0.0048}$ | $\mathbf{-0.0123}$ |
| 0.1 | $+0.0103$ | $-0.0082$ | $+0.0051$ | $-0.0120$ |
| 0.25 | $+0.0332$ | $+0.0150$ | $+0.0099$ | $-0.0079$ |
| 0.5 | $+0.0690$ | $+0.0491$ | $+0.0273$ | $+0.0069$ |
| 1 | $+0.1065$ | $+0.0826$ | $+0.0704$ | $+0.0433$ |
| 1.5 | $+0.1326$ | $+0.1050$ | $+0.1040$ | $+0.0724$ |

# I Adaptive prior details

Table 12 gives the gain of each adaptive prior on every benchmark behind Table 11. Table 13 reports how well the first labels predict which tasks the fitted prior hurts, and Table 14 sweeps the switch threshold $\eta$. The threshold in Table 11 was chosen on validation, which picked the smallest value on the grid.

Table 11: $\Delta_{m-\mathrm{J}}$ for adaptive priors. Worst benchmark: the largest gain (a loss) over the 17 benchmarks. Mean: over the 17 benchmarks. The training benchmarks are held out one at a time, and the switch threshold is chosen on validation. Mixtures with 2 and 3 components differ by at most 0.0001 (the table shows 2). Bold: best of the adaptive priors in each column.

| Model $m$ | Worst benchmark | Mean over 17 benchmarks | OOD test |
|---|---|---|---|
| Fitted Beta-Binomial (reference) | $+0.0248$ | $-0.0050$ | $-0.0138$ |
| Beta mixture, 2 or 3 components | $+0.0269$ | $\mathbf{-0.0054}$ | $\mathbf{-0.0163}$ |
| Average over strength | $+0.0122$ | $-0.0045$ | $-0.0110$ |
| Average over mean and strength | $\mathbf{+0.0034}$ | $-0.0037$ | $-0.0063$ |
| Switch to Jeffreys, 3 labels | $+0.0136$ | $-0.0027$ | $-0.0078$ |
| Switch to Jeffreys, 7 labels | $+0.0202$ | $-0.0042$ | $-0.0114$ |

Table 12: $\Delta_{m-\mathrm{J}}$ per benchmark. Fitted BB: the fitted Beta-Binomial. Mixture: two components. Avg. strength and Avg. mean, strength: averaging over the prior's strength, or over its mean and strength. Switch: the switch to Jeffreys after 3 or 7 labels. Training benchmarks are held out in turn.

| Benchmark | Split | Fitted BB | Mixture | Avg. strength | Avg. mean, strength | Switch, 3 | Switch, 7 |
|---|---|---|---|---|---|---|---|
| `afrieval` | Training | $-0.0111$ | $-0.0146$ | $-0.0084$ | $-0.0053$ | $-0.0063$ | $-0.0096$ |
| `afrimedqa` | Training | $-0.0121$ | $-0.0152$ | $-0.0097$ | $-0.0056$ | $-0.0071$ | $-0.0105$ |
| `agi_elo` | Training | $+0.0004$ | $-0.0019$ | $+0.0015$ | $-0.0002$ | $+0.0002$ | $+0.0006$ |
| `alignment_faking` | Training | $+0.0043$ | $+0.0033$ | $-0.0011$ | $-0.0025$ | $+0.0017$ | $+0.0028$ |
| `appworld` | Training | $+0.0026$ | $+0.0085$ | $+0.0036$ | $-0.0032$ | $+0.0049$ | $+0.0037$ |
| `brace` | Training | $-0.0042$ | $-0.0053$ | $-0.0021$ | $-0.0019$ | $-0.0032$ | $-0.0035$ |
| `bridging_gap` | Training | $-0.0142$ | $-0.0130$ | $-0.0115$ | $-0.0078$ | $-0.0076$ | $-0.0122$ |
| `cruxeval` | Training | $-0.0055$ | $-0.0013$ | $-0.0035$ | $-0.0044$ | $-0.0026$ | $-0.0040$ |
| `hallusionbench` | Training | $-0.0151$ | $-0.0180$ | $-0.0130$ | $-0.0074$ | $-0.0086$ | $-0.0130$ |
| `harmbench` | Training | $+0.0070$ | $+0.0081$ | $+0.0054$ | $+0.0025$ | $+0.0043$ | $+0.0060$ |
| `helm_afr` | Training | $-0.0139$ | $-0.0139$ | $-0.0133$ | $-0.0085$ | $-0.0083$ | $-0.0119$ |
| `ai2d_test` | OOD validation | $-0.0107$ | $-0.0137$ | $-0.0082$ | $-0.0043$ | $-0.0069$ | $-0.0100$ |
| `bird_sql` | OOD validation | $+0.0248$ | $+0.0269$ | $+0.0122$ | $+0.0034$ | $+0.0136$ | $+0.0202$ |
| `financebench` | OOD validation | $+0.0047$ | $+0.0073$ | $+0.0038$ | $+0.0009$ | $+0.0033$ | $+0.0041$ |
| `algotune` | OOD test | $-0.0127$ | $-0.0159$ | $-0.0095$ | $-0.0051$ | $-0.0060$ | $-0.0100$ |
| `cmmlu` | OOD test | $-0.0138$ | $-0.0162$ | $-0.0102$ | $-0.0057$ | $-0.0085$ | $-0.0117$ |
| `editbench` | OOD test | $-0.0149$ | $-0.0166$ | $-0.0131$ | $-0.0079$ | $-0.0093$ | $-0.0126$ |

Table 13: Can the first labels warn that the fitted prior will hurt a task? The score is the distance of the accuracy so far from the prior's mean, and the AUC separates the tasks the prior hurts from the rest, pooled over benchmarks and as a mean within each benchmark.

| Pilot labels | Tasks hurt | AUC, pooled | AUC, within benchmark |
|---|---|---|---|
| 3 | 29.1% | 0.61 | 0.52 |
| 7 | 29.1% | 0.73 | 0.64 |

Table 14: Sweep of the switch threshold $\eta$ over the 17 benchmarks. The fitted prior is kept while the accuracy so far lies within $\eta$ of its mean, and $\eta = \infty$ never switches. Columns as in Table 11.

| Pilot labels $k_0$ | Threshold $\eta$ | Mean over 17 | Worst benchmark | OOD test |
|---|---|---|---|---|
| 3 | 0.1 | $-0.0027$ | $+0.0137$ | $-0.0077$ |
| 3 | 0.2 | $-0.0033$ | $+0.0141$ | $-0.0096$ |
| 3 | 0.3 | $-0.0033$ | $+0.0141$ | $-0.0096$ |
| 3 | 0.4 | $-0.0033$ | $+0.0141$ | $-0.0096$ |
| 3 | 0.5 | $-0.0047$ | $+0.0132$ | $-0.0122$ |
| 3 | 0.6 | $-0.0049$ | $+0.0252$ | $-0.0136$ |
| 3 | $\infty$ | $-0.0049$ | $+0.0252$ | $-0.0136$ |
| 7 | 0.1 | $-0.0042$ | $+0.0206$ | $-0.0114$ |
| 7 | 0.2 | $-0.0042$ | $+0.0205$ | $-0.0115$ |
| 7 | 0.3 | $-0.0043$ | $+0.0208$ | $-0.0118$ |
| 7 | 0.4 | $-0.0047$ | $+0.0206$ | $-0.0127$ |
| 7 | 0.5 | $-0.0051$ | $+0.0206$ | $-0.0134$ |
| 7 | 0.6 | $-0.0049$ | $+0.0252$ | $-0.0136$ |
| 7 | $\infty$ | $-0.0049$ | $+0.0252$ | $-0.0136$ |

# J Kernel Rasch details

Kernel Rasch keeps Equation (2) and changes only the prior on the item deviations $\boldsymbol{\delta} = (\delta_1, \ldots, \delta_M)^\top$. Rasch treats them as independent Gaussians, $\delta_j \sim \mathcal{N}(0, \sigma_\delta^2)$; kernel Rasch makes them jointly Gaussian, with covariance given by the similarity of the item embeddings:

$$\boldsymbol{\delta} \sim \mathcal{N}\big(\mathbf{0},\, K\big), \qquad K = \sigma_\delta^2\big[(1-\rho)\, I + \rho\, S\big], \quad S_{jj'} = \exp\Big(\frac{\cos(x_j, x_{j'}) - 1}{T}\Big), \tag{5}$$

where $x_j$ are the item embeddings of Section 3, $\rho \in [0, 1]$ weights the similarity part $S$ and $T$ is its temperature. At $\rho = 0$ the two priors coincide; for $\rho > 0$, similar items share difficulty, while items of different benchmarks stay independent. After the refit, a labelled item keeps its fitted deviation, and an unlabelled item $j$ receives the posterior mean given the labelled items $L$ of its benchmark, $\hat{\delta}_j = \rho\, \sigma_\delta^2\, S_{jL} K_{LL}^{-1} \hat{\boldsymbol{\delta}}_L$, which is 0 at $\rho = 0$ as in Rasch. With one subject per benchmark, as in the competition-shaped draws, no labels are shared across subjects: the joint fit equals independent per-task fits (maximum difference $10^{-14}$ in our check), so Rasch there differs from the Beta-Binomial only in its prior.

# K Licences and terms

**Data.** The response data come from the AI Measurement Data Bank (`aims-foundations/measurement-db` on the Hugging Face Hub, revision `54074453da7b9911be0f48e4c560be547bc84d21`), which is released under the Creative Commons Attribution-ShareAlike 4.0 licence with gated access. We use the 17 benchmarks only through this data bank and credit the original paper of each benchmark in the table of Appendix D. The fixed evaluation samples, saved scores and result tables we release are derived from it and carry the same licence.

**Model and code.** The BGE-M3 encoder is released under the MIT licence, and our code is released under the MIT licence.

## L Additional figures





Figure 4: **The prior's source matters at zero to three labels and has faded by 31.** Brier score (a) and $\Delta_{m-J}$ (b) per label budget on the three unseen test benchmarks, competition-shaped draws, for the Beta-Binomial with a fixed (Jeffreys, solid), validation-tuned (dashed) and training-fitted (dotted) prior. Jeffreys jumps to $0.75$ or $0.25$ after one answer, so the gap is largest at one label; at 31 labels the three differ by less than $0.001$.





Figure 5: **The training-fitted prior helps on all three test benchmarks and on one validation benchmark, and hurts on the hardest.** $\Delta_{\mathrm{BB\,fit}-J}$ for each unseen benchmark, with 95% intervals over tasks. The validation benchmark `bird_sql` has task accuracy $0.12$, far below every training benchmark.

## NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes]

   Justification: The abstract and introduction state the controlled benchmark-transfer comparison; Section 5 provides the supporting results. Section 6 and the conclusion restrict the findings to the evaluated models, benchmarks, and acquisition protocol.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes]

   Justification: Section 6 discusses the limited benchmark population, task-level uncertainty, repeated visibility of test scores, post-hoc explanations, and untested alternatives. Appendix E reports sensitivity to which benchmarks are held out.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [N/A]

Justification: The paper is an empirical comparison and does not claim new theoretical results. Its equations define the statistical predictors and evaluation procedure.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: Sections 3 and 4, the experimental appendices, and the linked repository specify the split, nested evidence, scoring, fitting procedures, and selected settings. The repository supplies replay and analysis code, frozen draws, and result tables; rerunning from responses requires authorised access to the competition data.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
  (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
  (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).

(d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes]

   Justification: The linked GitHub repository provides the code, dependency and execution instructions, the fixed evaluation samples, the saved scores and the aggregate result tables, so every table and figure in the paper can be rebuilt from them. The response data are the public AI Measurement Data Bank (CC BY-SA 4.0, gated access on the Hugging Face Hub). They are not copied into the repository, so a full rerun of the simulation needs access to that dataset at the pinned revision, as the repository's data documentation explains.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes]

   Justification: Sections 3 and 4 specify the benchmark split, label budgets, models, prior fitting, and validation selection. Appendices H and G, together with the released configurations and code, give probe and solver details.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: Section 3 defines paired resampling of whole tasks, and Section 5 reports 95% bootstrap intervals. Section 6 explains that these intervals do not capture benchmark-selection uncertainty; Appendix E reports split sensitivity separately.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: Appendix G states the compute: all experiments ran on CPU only, with no GPU, on one machine with 12 logical cores and 15 GB of memory. It gives the run time of the online simulation and of the offline fit, and notes that the item embeddings are a precomputed input.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

Answer: [Yes]

Justification: This study analyses existing AI-system responses without recruiting human participants, and the release excludes the restricted response data. The paper discloses test-score visibility, limits its generalisation claims, and documents author responsibility in the Disclosure.

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [No]

    Justification: The paper discusses statistical transfer failures and evaluation limitations, but does not explicitly analyse both positive and negative societal impacts. Lower-cost evaluation could broaden access, while inaccurate transferred estimates could mislead model-selection or deployment decisions.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
    - The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
    - The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
    - If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A]

    Justification: The release consists of evaluation code, statistical predictors, and derived research artifacts, rather than a new generative model or a high-risk scraped dataset. Restricted competition response data are not redistributed.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.

- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes]

    Justification: Appendix K states the licence of each asset: the AI Measurement Data Bank (CC BY-SA 4.0, revision pinned), BGE-M3 (MIT) and our code (MIT). The benchmarks are used only through the data bank and each is credited to its original paper.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.
    - The name of the license (e.g., CC-BY 4.0) should be included for each asset.
    - For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
    - If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
    - For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
    - If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes]

    Justification: The linked repository documents the replay and analysis code, configurations, frozen draws, and derived result tables alongside the artifacts, including their schemas and reproduction commands. Its README and contribution guidance state the code license and restrictions on redistributing inputs.

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A]

    Justification: This work does not involve crowdsourcing or newly recruited human participants. The subjects in the response matrix are AI systems, as defined in Section 3.

    Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A]

    Justification: The study uses existing AI-system evaluation records and does not conduct research with human participants. No participant intervention, recruitment, or compensation is involved.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [Yes]

    Justification: The Disclosure identifies Claude Code and OpenAI Codex as research-development assistants and describes author verification and responsibility. The reported evaluation pipeline uses statistical predictors and frozen BGE-M3 embeddings; it does not call a generative LLM to supply response labels or final predictions.

    Guidelines:

    - The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.