

Apply filters to SQL queries

Agus Hendra 04-20-2024

Project description

Analyze security issues, and retrieve and filter data using SQL.

Retrieve after-hours failed login attempts

```
MariaDB [organization]> clear
MariaDB [organization]> SELECT *
  -> FROM log_in_attempts
  -> WHERE login_time > '18:00' AND success = 0 ;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	astrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	astrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0

Here, I used SELECT * FROM log_in_attempts because I want to query data in every column on the login attempts table. Then, I use WHERE login_time > '18:00' because I only want to search login attempts that happen after 18.00 which is hours after working office time. Lastly, success = 0 which means failed login.

Retrieve login attempts on specific dates

```
MariaDB [organization]> SELECT *  
  -> FROM log_in_attempts  
  -> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08' ;
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
30	yappiah	2022-05-09	03:22:22	MEX	192.168.124.48	1
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1
38	sbaelish	2022-05-09	14:40:01	USA	192.168.60.42	1

In this case, I use `SELECT * FROM log_in_attempts` because I would like to see all the columns in the login attempts table. I use `WHERE login_date = '2022-05-09' OR login_date = '2022-05-08' ;` because I only specify those 2 dates which are the day issues occurred and 1 day before. OR means it will show all the information from those two dates.

Retrieve login attempts outside of Mexico

```
MariaDB [organization]> SELECT *  
  -> FROM log_in_attempts  
  -> WHERE NOT country = 'MEXICO' ;
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
9	yappiah	2022-05-11	13:47:29	MEX	192.168.59.136	1
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrah	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0

In this case, again I used `SELECT * FROM log_in_attempts` because I want to query all columns on the login attempts table. Then, I use `WHERE NOT country = 'Mexico'` ; because I am only looking for login attempts that occur in all countries except (NOT) Mexico.

Retrieve employees in Marketing

```
MariaDB [organization]> SELECT *
-> FROM employees
-> WHERE department = 'Marketing' AND office LIKE 'east%' ;
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

7 rows in set (0.001 sec)

In this case, I use SELECT * FROM employees because I want to retrieve all columns (*) on the employee's table. I used WHERE department = 'Marketing' AND office = 'East%' ; because I want to filter only Marketing employees in the East building that will be shown in queries.

Retrieve employees in Finance or Sales

```
MariaDB [organization]> SELECT *
-> FROM employees
-> WHERE department = 'Sales' OR department = 'Finance' ;
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1029	d336e475f676	ivelasco	Finance	East-156
1035	j236k303l245	bisles	Sales	South-171
1039	n253o917p623	cjackson	Sales	East-378
1041	p929q222r778	cgriffin	Sales	North-208
1044	s429t157u159	tbarnes	Finance	West-415
1045	t567u844v434	pwashing	Finance	East-115
1046	u429v921w138	daquino	Finance	West-280
1047	v109w587x644	cward	Finance	West-373
1048	w167x592y375	tmitchel	Finance	South-288
1049	NULL	jreckley	Finance	Central-295
1050	y132z930a114	csimmons	Finance	North-468
1057	f370g535h632	mscott	Sales	South-270
1062	k367l639m697	redwards	Finance	North-180
1063	l686m140n569	lpope	Sales	East-226
1066	o678p794q957	ttyrell	Sales	Central-444
1069	NULL	jpark	Finance	East-110
1071	t244u829v723	zdutchma	Sales	West-348
1072	u905v920w694	esmith	Sales	East-421
1076	y347z204a710	fgarcia	Finance	Central-270

In this case, I use SELECT * FROM employees to retrieve all columns in the employee's table. Then, use WHERE department = 'Sales' OR department = 'Finance' ; to show only Sales or Finance employees in the organization.

Retrieve all employees not in the IT

```
MariaDB [organization]> SELECT*
```

```
-> FROM employees
```

```
-> WHERE NOT department = 'Information Technology' ;
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p611q262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1020	u899v381w363	arutley	Marketing	South-351
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1026	a998b568c863	apatel	Human Resources	West-320
1027	b806c503d354	mrroh	Marketing	West-246
1028	c603d749e374	aestrada	Human Resources	West-121
1029	d336e475f676	ivelasco	Finance	East-156
1030	e391f189g913	mabadi	Marketing	West-375
1031	f419g188h578	dkot	Marketing	West-408
1034	i679j565k940	bsand	Human Resources	East-484
1035	j236k303l245	bisles	Sales	South-171
1036	k550l533m205	rjensen	Marketing	Central-239
1038	m873n636o225	btang	Human Resources	Central-260
1039	n253o917p623	cjackson	Sales	East-378
1040	o783p832q294	dtarly	Human Resources	East-237

Again I use SELECT * FROM employees to show all columns on the employees table. Finally, I used WHERE NOT department = 'Information Technology' ; because I want to see all employees except for the IT department.

Summary

Here we can see how useful SQL is when we understand how to use it to retrieve data, filter data, analyze any security issues and make a decision.

