


Introducción a la Inteligencia Artificial


Clase 4






Clase 5

1. Regularización
 - a. Caso general
 - b. Ridge
 - c. Lasso
2. Gradient descent
 - a. GD
 - b. GD Estocástico
 - c. GD Mini-Batch
3. Entrenamiento de modelos
 - a. Selección de modelos
 - b. Cross-Validation





Regularización - Motivación



$$E_D(\mathbf{w}) = \frac{1}{2} \sum_{n=1}^N \{t_n - \mathbf{w}^T \phi(\mathbf{x}_n)\}^2$$


Observado - Predicción



\mathbf{w} está “libre”

$$\frac{1}{2} \sum_{n=1}^N \{t_n - \mathbf{w}^T \phi(\mathbf{x}_n)\}^2 + \boxed{\frac{\lambda}{2} \sum_{j=1}^M |w_j|^q}$$

Término de regularización "weight decay" → w afecta la pérdida



Lasso

Ridge

$$\mathbf{w} = (\Phi^T \Phi + \lambda I)^{-1} \Phi^T \mathbf{y}$$

Maximum A Posteriori como regularización

Distribución “a priori” de los parámetros \longrightarrow Observar data \longrightarrow Actualizar distribución (Posterior)

$$p(w) \sim D(\theta)$$

$$(\mathcal{X}, \mathcal{Y})$$

$$p(w|\mathcal{X}, \mathcal{Y}) = \frac{p(\mathcal{Y}|\mathcal{X}, w)p(w)}{p(\mathcal{Y}|\mathcal{X})}$$

$$w_{map} = (\Phi^T \Phi + \frac{\sigma^2}{b^2} I)^{-1} \Phi^T y$$

Gaussian prior con varianza b^2


Maximum A Posteriori como regularización - Ridge (L2)

$$\hat{\beta}_{\text{MAP}} = \arg \max_{\beta} \underbrace{\log p(\{Y_i\}_{i=1}^n | \beta, \sigma^2, \{X_i\}_{i=1}^n)}_{\text{Conditional log likelihood}} + \underbrace{\log p(\beta)}_{\text{log prior}}$$

I) Gaussian Prior

$$\beta \sim \mathcal{N}(0, \tau^2 \mathbf{I})$$

$$p(\beta) \propto e^{-\beta^T \beta / 2\tau^2}$$



$$\hat{\beta}_{\text{MAP}} = \arg \min_{\beta} \sum_{i=1}^n (Y_i - X_i \beta)^2 + \lambda \|\beta\|_2^2 \quad \text{Ridge Regression}$$

↓
constant(σ^2, τ^2)

$$\hat{\beta}_{\text{MAP}} = (\mathbf{A}^T \mathbf{A} + \lambda \mathbf{I})^{-1} \mathbf{A}^T \mathbf{Y}$$


Maximum A Posteriori como regularización - LASSO (L1)

$$\hat{\beta}_{\text{MAP}} = \arg \max_{\beta} \underbrace{\log p(\{Y_i\}_{i=1}^n | \beta, \sigma^2, \{X_i\}_{i=1}^n)}_{\text{Conditional log likelihood}} + \underbrace{\log p(\beta)}_{\text{log prior}}$$

II) Laplace Prior

$$\beta_i \stackrel{iid}{\sim} \text{Laplace}(0, t)$$

$$p(\beta_i) \propto e^{-|\beta_i|/t}$$





$$\hat{\beta}_{\text{MAP}} = \arg \min_{\beta} \sum_{i=1}^n (Y_i - X_i \beta)^2 + \lambda \|\beta\|_1$$

\downarrow
constant(σ^2, t)


Lasso

Regularización




Regularización

(a) L1 Constraint Diamond



(b) L2 Constraint Circle





ElasticNet

$$(\alpha\lambda\|\beta\|_1 + \frac{1}{2}(1 - \alpha)\|\beta\|_2^2)$$

¿Qué β se reduce más?

Regularización




Gradiente Descendente

Implementación de Gradiente Descendente

Solucion analitica

$$\min_W \|Y - XW\|_2^2$$

$$W = (X^T X)^{-1} X^T Y$$




Implementación de Gradiente Descendente


Solución numérica

$$\min_W \|Y - XW\|_2^2 \implies \min_W \sum_i (y_i - X_i \cdot W)^2$$

$$W \leftarrow W - \alpha \nabla \left(\sum_i (y_i - X_i \cdot W)^2 \right)$$




Gradiente Descendente




Andrew Ng

Gradiente Descendente



Large learning rate: Overshooting.



Small learning rate: Many iterations until convergence and trapping in local minima.

Implementación de Gradiente Descendente

Solución numérica

$$\begin{aligned}\nabla_w J(w) &= \nabla_w \left(\sum_i (y_i - X_i W)^2 \right) \\ &= \sum_i \left(\nabla_w (y_i - X_i W)^2 \right) \\ &= \sum_i \left(\nabla_w (y_i - (x_{i1}w_1 + x_{i2}w_2 + \cdots + x_{im}w_m))^2 \right) \\ &= \sum_i \left(-2(y_i - \hat{y}_i)x_{ij} \right) \quad \forall j \in (1 \cdots m)\end{aligned}$$

Implementación de Gradiente Descendente

Solución numérica

$$\nabla \left(\sum_{\text{all samples}} (y_i - f_W(X_i))^2 \right)$$

Gradient Descent algorithm

for epoch in n_epochs:

- compute the predictions for **all the samples**
- compute the error between truth and predictions
- compute the gradient using **all the samples**
- update the parameters of the model

Implementación de Gradiente Descendente Estocástico

Solución numérica

$$\nabla ((y_i - f_W(X_i))^2)$$


Stochastic Gradient Descent algorithm

for epoch in n_epochs:

- shuffle the samples
- **for sample in n_samples:**
 - compute the predictions for **the sample**
 - compute the error between truth and predictions
 - compute the gradient using **the sample**
 - update the parameters of the model

Implementación de Gradiente Descendente Estocástico

Solución numérica



Implementación de Gradiente Descendente Mini-Batch

Solución numérica

$$\nabla \left(\sum_{\text{batch samples}} (y_i - f_W(X_i))^2 \right)$$

Mini-Batch Gradient Descent algorithm

for epoch in n_epochs:


- shuffle the batches
- **for batch in n_batches:**
 - compute the predictions for **the batch**
 - compute the error for the batch
 - compute the gradient for **the batch**
 - update the parameters of the model

Comparativa de gradientes


	Gradient Descent	Stochastic Gradient Descent	Mini-Batch Gradient Descent
Gradient	$\nabla \left(\sum_{\text{all samples}} (y_i - f_W(X_i))^2 \right)$	$\nabla \left((y_i - f_W(X_i))^2 \right)$	$\nabla \left(\sum_{\text{batch samples}} (y_i - f_W(X_i))^2 \right)$
Speed	Very Fast (vectorized)	Slow (compute sample by sample)	Fast (vectorized)
Memory	O(dataset)	O(1)	O(batch)
Convergence	Needs more epochs	Needs less epochs	Middle point between GD and SGD
Gradient Stability	Smooth updates in params	Noisy updates in params	Middle point between GD and SGD

Selección de modelos


Selección de modelos




Selección de modelos



Cross-Validation



Entrenamiento numérico del modelo seleccionado - Obtención de parámetros




Mini-Batch Gradient Descent

for epoch in n_epochs:

- shuffle the batches
- **for batch in n_batches:**
 - compute the predictions for **the batch**
 - compute the error for the batch
 - compute the gradient for **the batch**
 - update the parameters of the model
- plot error vs epoch

Selección de los hiper parámetros



Grid Search

Random Search

Bibliografía

- The Elements of Statistical Learning | Trevor Hastie | Springer
- An Introduction to Statistical Learning | Gareth James | Springer
- Deep Learning | Ian Goodfellow | <https://www.deeplearningbook.org/>
- Mathematics for Machine Learning | Deisenroth, Faisal, Ong
- Artificial Intelligence, A Modern Approach | Stuart J. Russell, Peter Norvig
- A visual explanation for regularization of linear models - Terence Parr
- A Complete Tutorial on Ridge and Lasso Regression in Python - Aarshay Jain