

Distribuidora App

One-page repo summary of the current application

React 19 + Vite

Supabase

Offline + Realtime

What It Is

Private web app for running a food distributor's daily operations. The repo shows a React single-page application that centralizes customers, products, orders, deliveries, payments, and reporting on top of Supabase.

Who It's For

Primary persona: an admin or preventista at a food distribution company. Transportistas are a supported secondary role with delivery-focused views.

What It Does

- Role-based auth and routing for admin, preventista, and transportista users.
- Manage customers, products, suppliers, purchases, users, price groups, and promotions.
- Create, edit, cancel, and track orders with payment state, history, and transport assignment.
- Plan recorridos, save routes, and optimize delivery order via optional n8n + Google integrations.
- Work offline with IndexedDB queues for pending orders and mermas, then sync/retry when online.
- Produce operational outputs: PDFs, Excel exports, reports, analytics, commissions, renditions, transfers, and salvados.

How It Works

- UI: React 19 SPA with React Router, container/view/modal structure, Tailwind CSS, and Radix UI components.
- App state: TanStack Query plus custom hooks and Auth, Theme, Notification, and data contexts.
- Backend: Supabase Auth + Postgres from env vars; code queries tables such as pedidos, clientes, productos, and perfiles.
- Transactions/live updates: services and query hooks call RPCs like crear_pedido_completo and actualizar_pedido_items; realtime invalidates pedidos/productos.
- Offline/integrations: Dexie stores pending ops, offline cache, and saved routes; optional n8n + Google support route optimization.

Browser UI -> hooks/services -> Supabase Auth/DB/RPC/Realtime Offline actions -> IndexedDB queue -> sync manager -> Supabase when online

How To Run

1. Install Node.js 20+ and npm 10+.
2. Create a Supabase project and apply repo migrations if starting from a blank DB.
3. Run `npm install`.
4. Copy `.env.example` to `.env`; set `VITE_SUPABASE_URL` and `VITE_SUPABASE_ANON_KEY`.
5. Start with `npm run dev` and open `http://localhost:5173`.

Optional vars: `VITE_GOOGLE_API_KEY`, `VITE_N8N_WEBHOOK_URL`, `VITE_N8N_FACTURA_WEBHOOK_URL`, `VITE_SENTRY_DSN`.

Repo Gaps

- Demo/seed credentials: Not found in repo.
- Hosted production URL: Not found in repo.