

Autenticación

ASP.NET

WebApplication1 - Microsoft Visual Studio

File Edit View Project Build Debug Team Tools Test Analyze Window Help

Debug Any CPU Google Chrome

Solution Explorer

Search Solution Explorer (Ctrl+)

Solution 'WebApplication1' (1 project)

- WebApplication1
 - Connected Services
 - Properties
 - References
 - App_Data
 - Database1.mdf
 - Database1_log.ldf
 - App_Start
 - Content
 - Controllers
 - AccountController.cs
 - HomeController.cs
 - ManageController.cs
 - fonts
 - Models
 - Scripts
 - Views
 - Account
 - _ExternalLoginsListPartial.cshtml
 - ConfirmEmail.cshtml
 - ExternalLoginConfirmation.cshtml
 - ExternalLoginFailure.cshtml
 - ForgotPassword.cshtml
 - ForgotPasswordConfirmation.cshtml
 - Login.cshtml
 - Register.cshtml**
 - ResetPassword.cshtml
 - ResetPasswordConfirmation.cshtml
 - SendCode.cshtml
 - VerifyCode.cshtml

WebApplication1

```
1 @model WebApplication1.Models.RegisterViewModel
2 @{
3     ViewBag.Title = "Register";
4 }
5
6 <h2>@ViewBag.Title.</h2>
7
8 @using (Html.BeginForm("Register", "Account", FormMethod.Post))
9 {
10     @Html.AntiForgeryToken()
11     <h4>Create a new account.</h4>
12     <hr />
13     @Html.ValidationSummary("", new { class = "text-danger" })
14     <div class="form-group">
15         @Html.LabelFor(m => m.Email, "Email")
16         <div class="col-md-10">
17             @Html.TextBoxFor(m => m.Email, new { class = "form-control" })
18         </div>
19     </div>
20     <div class="form-group">
21         @Html.LabelFor(m => m.Password, "Password")
22         <div class="col-md-10">
23             @Html.PasswordFor(m => m.Password, new { class = "form-control" })
24         </div>
25     </div>
26     <div class="form-group">
27         @Html.LabelFor(m => m.ConfirmPassword, "Confirm password")
28         <div class="col-md-10">
29             @Html.PasswordFor(m => m.ConfirmPassword, new { @class = "form-control" })
30         </div>
31     </div>
32     <div class="form-group">
33         <div class="col-md-offset-2 col-md-10">
34             <input type="submit" class="btn btn-default" value="Register" />
35         </div>
36     </div>
37 }
```

Register - My ASP.NET Application

localhost:62152/Account/Register

Application name Home About Contact Register Log in

Register.




Create a new account.

Email

Password

Confirm password

© 2017 - My ASP.NET Application



WebApplication1 - Microsoft Visual Studio

File Edit View Project Build Debug Team Tools Test Analyze Window Help

Debug Any CPU Google Chrome

Server Explorer

- Azure
- Data Connections
 - Database.mdf
 - Tables
 - AspNetUsers
- Views
- Stored Procedures
- Functions
- Synonyms
- Types
- Assemblies
- Default Connection (WebApplication1)
- Servers

dbo.AspNetUsers [Data] Web.config WebApplication1

Max Rows: 1000

	Id	Email	EmailConfirmed	PasswordHash
▶	ad69fd8a-88fa-4076-8000-31190c9d615f	juan_carrillog@my.unitec.edu.mx	False	AADGU3TbzH5ona6E6mjUcTzbky0/m6UKd7SMSBTnyOOS2MmPYyGvWrOWFqM4ujavew==
⊞	NULL	NULL	NULL	NULL

SecurityStamp	PhoneNumber	PhoneNumberConfirmed	TwoFactorEnabled	LockoutEndDateUtc	LockoutEnabled	AccessFailedCount	UserName
b91d2925-fdfb-4af5-8461-ba69bbe5ec77	NULL	False	False	NULL	True	0	juan_carrillog@my.unitec.edu.mx
NULL	NULL	NULL	NULL	NULL	NULL	NULL	NULL

En criptografía, MD5 (abreviatura de Message-Digest Algorithm 5, Algoritmo de Resumen del Mensaje 5) es un algoritmo de reducción criptográfico de 128 bits ampliamente usado.

Server Explorer

- Azure
- Data Connections
 - Database.mdf
 - Tables
 - AspNetRoles
 - AspNetUserClaims
 - AspNetUserLogins
 - AspNetUserRoles
 - AspNetUsers
 - Views
 - Stored Procedures
 - Functions
 - Synonyms
 - Types
 - Assemblies
 - DefaultConnection (WebApplication1)
- Servers

SQLQuery1.sql * dbo.AspNetRoles [Data] dbo.AspNetUsers [Data]

Max Rows: 1000

	Id	Name
	FC7219E8-30D4-453B-8891-9045CCC24DD1	admin
	NULL	NULL

AspNetUserRoles (dbo)

	Column Name	Data Type	Allow Nulls
	UserId	nvarchar(450)	<input type="checkbox"/>
	RoleId	nvarchar(450)	<input type="checkbox"/>

AspNetRoles (dbo)

	Column Name	Data Type	Allow Nulls
	Id	nvarchar(450)	<input type="checkbox"/>
	Name	nvarchar(256)	<input checked="" type="checkbox"/>
	NormalizedName	nvarchar(256)	<input checked="" type="checkbox"/>
	ConcurrencyStamp	nvarchar(MAX)	<input checked="" type="checkbox"/>

AspNetUsers (dbo)

	Column Name	Data Type	Allow Nulls
	Id	nvarchar(450)	<input type="checkbox"/>
	UserName	nvarchar(256)	<input checked="" type="checkbox"/>
	NormalizedUserName	nvarchar(256)	<input checked="" type="checkbox"/>
	Email	nvarchar(256)	<input checked="" type="checkbox"/>
	NormalizedEmail	nvarchar(256)	<input checked="" type="checkbox"/>
	EmailConfirmed	bit	<input type="checkbox"/>
	PasswordHash	nvarchar(MAX)	<input checked="" type="checkbox"/>
	SecurityStamp	nvarchar(MAX)	<input checked="" type="checkbox"/>
	ConcurrencyStamp	nvarchar(MAX)	<input checked="" type="checkbox"/>
	PhoneNumber	nvarchar(MAX)	<input checked="" type="checkbox"/>
	PhoneNumberConfirmed	bit	<input type="checkbox"/>
	TwoFactorEnabled	bit	<input type="checkbox"/>
	LockoutEnd	datetimeoffset(7)	<input checked="" type="checkbox"/>
	LockoutEnabled	bit	<input type="checkbox"/>
	AccessFailedCount	int	<input type="checkbox"/>

WebApplication1 - Microsoft Visual Studio

File Edit View Project Build Debug Team Tools Test Analyze Window Help

Debug Any CPU Google Chrome

Server Explorer

- Azure
- Data Connections
 - Database.mdf
 - Tables
 - AspNetUserRoles
 - AspNetUsers
 - Views
 - Stored Procedures
 - Functions
 - Synonyms
 - Types
 - Assemblies
 - DefaultConnection (WebApplication1)
 - Servers

dbo.AspNetUserRoles [Data] | dbo.AspNetRoles [Data]

Max Rows: 1000

	UserId	RoleId
▶	ad69fd8a-88fa-4076-8000-31190c9d615f	FC7219E8-30D4-453B-8891-9045CCC24DD1
⊕	NULL	NULL

	Id	Name
▶	FC7219E8-30D4-453B-8891-9045CCC24DD1	admin
⊕	NULL	NULL

	Id	Email
▶	ad69fd8a-88fa-4076-8000-31190c9d615f	juan_carrillog@my.unitec.edu.mx
⊕	NULL	NULL

Autorización

ASP.NET

[Authorize]

```
public class HomeController : Controller  
{
```

```
    public ActionResult Index()  
    {  
        return View();  
    }
```

```
    public ActionResult About()  
    {  
        return View();  
    }
```

```
    public ActionResult Contact()  
    {  
        return View();  
    }
```

```
}
```



Solo usuarios autenticados

The diagram consists of a vertical orange line that spans the width of the three action methods (Index, About, and Contact). From the center of this vertical line, a horizontal orange line extends to the right, pointing towards the text 'Solo usuarios autenticados'. This indicates that the [Authorize] attribute applies to all three methods.


```
public class HomeController : Controller
{
```

```
    public ActionResult Index()
    {
        return View();
    }
```

```
    [Authorize]
    public ActionResult About()
    {
        return View();
    }
```

```
    [Authorize]
    public ActionResult Contact()
    {
        return View();
    }
}
```

Cualquiera

Solo usuarios autenticados

[Authorize]

```
public class HomeController : Controller
```

```
{
```

```
    [AllowAnonymous]
```

```
    public ActionResult Index()
```

```
    {
```

```
        return View();
```

```
    }
```

Cualquiera

```
    public ActionResult About()
```

```
    {
```

```
        return View();
```

```
    }
```

```
    public ActionResult Contact()
```

```
    {
```

```
        return View();
```

```
    }
```

Solo usuarios autenticados

```
}
```

```
public class HomeController : Controller
{
    [Authorize(Users = "luis@mail.com, pedro@mail.com")]
    public ActionResult Index()
    {
        return View();
    }
    [Authorize(Roles = "Admin")]
    public ActionResult About()
    {
        return View();
    }
    [Authorize(Roles = "Editor, Admin")]
    public ActionResult Contact()
    {
        return View();
    }
}
```

Solo usuarios:

- luis@mail.com
- pedro@mail.com

Solo usuarios con el rol:

- admin

Solo usuarios los roles:

- editor
- admin

```
@* .\Views\Shared\_LoginPartial.cshtml *
```

```
@using Microsoft.AspNetCore.Identity
@inject SignInManager<IdentityUser> SignInManager
@inject UserManager<IdentityUser> UserManager
```

```
<ul class="navbar-nav">
  @if (SignInManager.IsSignedIn(User))
  {
    if (User.IsInRole("Admin"))
    {
      <li class="nav-item">
        <a class="nav-link text-dark" asp-area="" asp-controller="Products" asp-action="Index">Products</a>
      </li>
      <li class="nav-item">
        <a class="nav-link text-dark" asp-area="" asp-controller="Sales" asp-action="Index">Sales</a>
      </li>
    }
    <li class="nav-item">
      <a class="nav-link text-dark" asp-area="Identity" asp-page="/Account/Manage/Index" title="Manage">@User.Identity.Name</a>
    </li>
    <li class="nav-item">
      <form class="form-inline" asp-area="Identity" asp-page="/Account/Logout" asp-route-returnUrl="@Url.Action("Index", "Home", new { area = "" })">
        <button type="submit" class="nav-link btn btn-link text-dark">Logout</button>
      </form>
    </li>
  }
  else
  {
    <li class="nav-item">
      <a class="nav-link text-dark" asp-area="Identity" asp-page="/Account/Register">Register</a>
    </li>
    <li class="nav-item">
      <a class="nav-link text-dark" asp-area="Identity" asp-page="/Account/Login">Login</a>
    </li>
  }
</ul>
```

Home Privacy

Register Login

Home Privacy

user@unitec.mx Logout

Home Privacy

Products Sales admin@unitec.mx Logout

Usuario	Rol	Contraseña
admin@unitec.mx	Admin	Admin123
user@unitec.mx		User123

Crear usuarios en la aplicación:

Implementar la autorización a los controladores y las vistas necesarias:

```
[Authorize]
[Authorize(Roles = "Admin")]

if (User.IsInRole("Admin"))
{
}
}
```




Ejercicio

Transaccion

ACID

Conjunto de propiedades que garantizan que las transacciones de una Base de Datos se procesan de manera fiable:

- **Atomicidad**: un cambio debe **completarse en su totalidad**, es decir, si consiste en una serie de pasos, o se ejecutan todos o ninguno.
- **Consistencia (Integridad)**: asegura que sólo se empieza aquello que se puede acabar, es decir, cualquier cambio debe conducir de un estado válido a otro estado válido.
- **Aislamiento (Isolation)**: un cambio no debe afectar a otros cambios que se estén ejecutando al mismo tiempo, es decir, dos transacciones sobre la misma información deben ser independientes y no generen ningún tipo de error.
- **Durabilidad (Persistencia)**: una vez completado el cambio, éste debe conservarse, aunque se produzcan fallos en la base de datos o el sistema completo.



Models>UserProducts.cs

```
/*
CREATE TABLE [UserProducts](
    [Id] [uniqueidentifier] PRIMARY KEY NOT NULL,

    [UserId] [nvarchar](450) NOT NULL,
    [UserName] [nvarchar](256) NULL,

    [ProductId] [uniqueidentifier] NOT NULL,
    [Name] [nvarchar](128) NOT NULL,

    [Date] [smalldatetime] NOT NULL,

    FOREIGN KEY([ProductId]) REFERENCES [Products] ([Id]),
    FOREIGN KEY([UserId]) REFERENCES [AspNetUsers] ([Id])
);
*/
```

using System;

```
public class UserProducts
{
    public Guid Id { get; set; }

    public string UserId { get; set; }
    public string UserName { get; set; }

    public Guid ProductId { get; set; }
    public string Name { get; set; }

    public DateTime Date { get; set; }
}
```

```
CREATE TABLE [AspNetUsers](
    [Id] [nvarchar](450) PRIMARY KEY NOT NULL,
    [UserName] [nvarchar](256) NULL,

    [NormalizedUserName] [nvarchar](256) NULL,
    [Email] [nvarchar](256) NULL,
    [NormalizedEmail] [nvarchar](256) NULL,
    [EmailConfirmed] [bit] NOT NULL,
    [PasswordHash] [nvarchar](max) NULL,
    [SecurityStamp] [nvarchar](max) NULL,
    [ConcurrencyStamp] [nvarchar](max) NULL,
    [PhoneNumber] [nvarchar](max) NULL,
    [PhoneNumberConfirmed] [bit] NOT NULL,
    [TwoFactorEnabled] [bit] NOT NULL,
    [LockoutEnd] [datetimeoffset](7) NULL,
    [LockoutEnabled] [bit] NOT NULL,
    [AccessFailedCount] [int] NOT NULL
);
```

```
CREATE TABLE [Products] (
    [Id] [uniqueidentifier] PRIMARY KEY NOT NULL,
    [Name] [nvarchar](128) NOT NULL,

    [Price] [float] NOT NULL,
    [Stock] [int] NOT NULL DEFAULT(0),
    [Photo] [varchar](max) NULL
);
```

Controllers>HomeController.cs

```
public IActionResult Purchase(Guid id)
{
    var data = new Products();

    var con = new SqlConnection(_connectionString);
    con.Open();

    var sqlt = con.BeginTransaction();

    try
    {
        using (var cmd = new SqlCommand("SELECT [Id], [Name], [Price], [Stock], [Photo] FROM [Products] WHERE [Id] = @id", con, sqlt))
        {
            cmd.Parameters.Add("@id", SqlDbType.UniqueIdentifier).Value = id;
            var dr = cmd.ExecuteReader();
            if (dr.Read())
            {
                data.Id = (Guid)dr["Id"];
                data.Name = (string)dr["Name"];
                data.Price = (double)dr["Price"];
                data.Stock = (int)dr["Stock"];
                data.Photo = (string)dr["Photo"];
            }
            dr.Close();
            if (data.Stock <= 0)
            {
                return BadRequest();
            }
        }

        using (var cmd = new SqlCommand(@"UPDATE [Products] SET [Stock] = @stock WHERE [Id] = @id;", con, sqlt))
        {
            cmd.Parameters.Add("@id", SqlDbType.UniqueIdentifier).Value = id;
            cmd.Parameters.Add("@stock", SqlDbType.Int).Value = data.Stock - 1;
            cmd.ExecuteNonQuery();
        }

        sqlt.Commit();

        return View(data);
    }
    catch (Exception)
    {
        sqlt.Rollback();
        throw;
    }
    finally { con.Close(); }
```

Controllers>HomeController.cs

```
public IActionResult Purchase(Guid id)
{
    var data = new Products();
    var userId = new Guid(User.FindFirst(ClaimTypes.NameIdentifier)?.Value);
    var userName = User.Identity.Name;
    var con = new SqlConnection(_connectionString);
    con.Open();
    var sqlt = con.BeginTransaction();
    try
    {
        using (var cmd = new SqlCommand("SELECT [Id], [Name], [Price], [Stock], [Photo] FROM [Products] WHERE [Id] = @id", con, sqlt))
        {
            cmd.Parameters.Add("@id", SqlDbType.UniqueIdentifier).Value = id;
            var dr = cmd.ExecuteReader();
            if (dr.Read())
            {
                data.Id = (Guid)dr["Id"];
                data.Name = (string)dr["Name"];
                data.Price = (double)dr["Price"];
                data.Stock = (int)dr["Stock"];
                data.Photo = (string)dr["Photo"];
            }
            dr.Close();
            if (data.Stock <= 0)
            {
                return BadRequest();
            }
        }
        using (var cmd = new SqlCommand(@"UPDATE [Products] SET [Stock] = @stock WHERE [Id] = @id;", con, sqlt))
        {
            cmd.Parameters.Add("@id", SqlDbType.UniqueIdentifier).Value = id;
            cmd.Parameters.Add("@stock", SqlDbType.Int).Value = data.Stock - 1;
            cmd.ExecuteNonQuery();
        }
        using (var cmd = new SqlCommand(@"INSERT INTO [UserProducts] ([Id], [UserId], [UserName], [ProductId], [Name], [Date]) VALUES (NEWID(), @userId, @userName, @productId, @name, @date);", con, sqlt))
        {
            cmd.Parameters.Add("@userId", SqlDbType.UniqueIdentifier).Value = userId;
            cmd.Parameters.Add("@userName", SqlDbType.NVarChar, 450).Value = userName;
            cmd.Parameters.Add("@productId", SqlDbType.UniqueIdentifier).Value = id;
            cmd.Parameters.Add("@name", SqlDbType.NVarChar, 128).Value = data.Name;
            cmd.Parameters.Add("@date", SqlDbType.SmallDateTime).Value = DateTime.Now;
            cmd.ExecuteNonQuery();
        }
        SendMail.Send(userName, "Compra realizada", "Gracias por la compra");
        sqlt.Commit();
        return View(data);
    }
    catch (Exception)
    {
        sqlt.Rollback();
        throw;
    }
    finally { con.Close(); }
}
```

Proyecto Bimestral

Primer entregable Bimestral

<https://github.com/jlcarrillog/im221bim>