Answer: (penalty regime: 0 %)

```
#include<stdio.h>
    int main()
 3 ▼
    {
        int T,n,t;
4
 5
        scanf("%d",&T);
        while(T--){
6 🔻
            scanf("%d",&n);
8
            t=n/4;
9
            printf("%s\n",(t%2==n%2)?"No":"Yes");
10
11
                                             GULZHAR AHAMAD VM
                                             ECE-B
                                             240801090
```

	Input	Expected	Got	
~	3 1 6	Yes Yes No	Yes Yes No	~
	7			

GULZHAR AHAMAD VM ECE-B 240801090

Passed all tests! 🗸



```
#include<stdio.h>
    int main()
 2
 3 ▼
 4
        int a,b,n=0;
 5
        scanf("%d",&a);
        while(a>0){
 6 ▼
            b=a%10;
 8
            n+=(b==8)?2:(b==0||b==4||b==6||b==9)?1:0;
 9
            a/=10;
10
        printf("%d",n);
11
12
13
                                               GULZHAR AHAMAD VM
                                               ECE-B
                                               240801090
```

	Input	Expected	Got	
~	630	2	2	~
~	1288	4	4	~

Passed all tests! 🗸

GULZHAR AHAMAD VM ECE-B 240801090

```
#include<stdio.h>
    int main()
 4
         int n,r=0;
         scanf("%d",&n);
 6
         while(n!=0)
 8
             n=n/2;
                              GULZHAR AHAMAD VM
             r=r+1;
                              ECE-B
10
                              240801090
11
         printf("%d",r);
12
```

	Input	Expected	Got	
~	10	4	4	~
~	5	3	3	~
~	20	5	5	~
~	500	9	9	~
~	1000	10	10	~

Passed all tests! 🗸

GULZHAR AHAMAD VM ECE-B 240801090

```
#include<stdio.h>
    int main()
 3 ▼
 4
        int n, x=0;
 5 ▼
        while(scanf("%d",&n)==1){
 6 ₹
            if(n%2!=0){
                 X++;
 8
 9
10
        printf("%d",x);
                                            GULZHAR AHAMAD VM
11
        return 0;
                                            ECE-B
12
                                            240801090
```

	Input	Expected	Got	
~	5 10 15 20 25 30 35 40 45 50	5	5	~

Passed all tests! 🗸

GULZHAR AHAMAD VM

ECE-B

240801090

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
   int main()
3 ▼
       int n;
       scanf("%d",&n);
       while(n&&n%10!=2&&n%10!=3&&n%10!=4&&n%10!=7)
6
       n/=10;
8
       printf("%s",n?"false":"true");
9
                               GULZHAR AHAMAD VM
                               ECE-B
                               240801090
```

	Input	Expected	Got	
~	6	true	true	~
~	89	true	true	~
~	25	false	false	~

GULZHAR AHAMAD VM ECE-B 240801090

Passed all tests! 🗸

```
#include<stdio.h>
   int main()
3 ▼
4
        long long int n,t,i,nut=0;
        scanf("%lld %lld",&n,&t);
        for(i=1;i<=n;i++){
6 ▼
            nut=nut+i;
            if(nut==t){
8
                nut=nut-1;
10
11
                                           GULZHAR AHAMAD VM
        printf("%lld", nut%100000007);
12
                                           ECE-B
13
                                           240801090
```

	Input	Expected	Got	
~	2	3	3	~
~	2	2	2	~
~	3	5	5	~

GULZHAR AHAMAD VM ECE-B 240801090

Passed all tests! 🗸