

# Zomato Food Delivery

## 15 Solved SQL Business Questions

A portfolio-ready record of SQL analysis performed on a simulated Zomato-style food delivery database using MySQL.

|                         |                                                                              |
|-------------------------|------------------------------------------------------------------------------|
| <b>Project</b>          | Zomato Food Delivery SQL Analysis                                            |
| <b>Database</b>         | MySQL                                                                        |
| <b>Solved questions</b> | 15                                                                           |
| <b>Core skills</b>      | Joins • Aggregation • GROUP BY • HAVING • CASE • Date functions • Subqueries |

### Question 1

Find the full order-to-delivery journey for a specific order (end-to-end join).

#### SQL Solution

```
SELECT
  o.order_id,
  c.coustomer_name,
  r.restaurant_name,
  o.order_item,
  o.order_date,
  o.order_time,
  o.total_amount,
  o.order_status,
  d.rider_id,
  rd.rider_name,
  d.delivery_status,
  d.delivery_time
FROM
  orders o
  JOIN
  customers c ON o.customer_id = c.customer_id
  JOIN
  restaurants r ON o.restaurant_id = r.restaurant_id
  LEFT JOIN
  deliveries d ON o.order_id = d.order_id
  LEFT JOIN
  riders rd ON d.rider_id = rd.rider_id
WHERE
  o.order_id = 1;
```

### Question 2

Find restaurants that generated the highest total revenue

#### SQL Solution

```
SELECT
  R.restaurant_id,
  R.restaurant_name,
  O.order_id,
  SUM(O.total_amount) AS toalat_revenue
FROM
  orders AS O
  JOIN
  restaurants AS R ON R.restaurant_id = O.restaurant_id
WHERE
  order_status = 'delivered'
GROUP BY R.restaurant_id , O.order_id, R.restaurant_name
ORDER BY toalat_revenue DESC
LIMIT 5;
```

### Question 3

Identify customers who have never placed an order.

#### SQL Solution

```
SELECT
    C.customer_id, C.coustomer_name
FROM
    customers AS C
    LEFT JOIN
    orders AS O
    ON C.customer_id = O.customer_id
WHERE
    O.order_id IS NULL;
```

### Question 4

List all restaurants located in a specific city (e.g. Mumbai).

#### SQL Solution

```
SELECT
    *
FROM
    restaurants
WHERE
    city = 'pune';
```

### Question 5

Find the number of restaurants per city.

#### SQL Solution

```
SELECT
    city, COUNT(*) AS total_restarurant
FROM
    restaurants
GROUP BY city
ORDER BY total_restarurant DESC;
```

### Question 6

Find the total number of orders by order\_status.

#### SQL Solution

```
SELECT
    order_status, COUNT(*) AS order_count
FROM
    orders
GROUP BY order_status
;
```

### Question 7

Find the busiest day of the week (by number of orders).

#### SQL Solution

```
SELECT DAYNAME(order_date) AS day_of_week, COUNT(*) AS order_count
FROM orders
GROUP BY DAYNAME(order_date)
ORDER BY order_count DESC;
```

### Question 8

Identify riders who have completed more than 10 deliveries.

#### SQL Solution

```
SELECT
    rider_id, COUNT(*) AS delivery_completed
```

```

FROM
    deliveries
WHERE
    delivery_status = 'completed'
GROUP BY rider_id
HAVING COUNT(*) > 10
ORDER BY delivery_completed DESC;

```

## Question 9

Find riders who joined in a specific year (e.g. 2024) and their delivery count.

### SQL Solution

```

SELECT
    r.rider_name,
    r.rider_id,
    r.joining_date,
    COUNT(d.delivery_id) AS delivery_done
FROM
    riders AS r
    LEFT JOIN
    deliveries AS d ON r.rider_id = d.rider_id
WHERE
    YEAR(r.joining_date) = 2024
GROUP BY r.rider_name , r.rider_id , r.joining_date;

```

## Question 10

Find the average age of customers.

### SQL Solution

```

SELECT
    ROUND(AVG(age), 2)
FROM
    customers;

```

## Question 11

Find the customer(s) with the highest average order value.

### SQL Solution

```

SELECT
    customer_id, ROUND(AVG(total_amount), 2) AS avg_total_amount
FROM
    orders
WHERE
    order_status = 'delivered'
GROUP BY customer_id
ORDER BY avg_total_amount DESC
LIMIT 5;

```

## Question 12

Identify restaurants that have never received an order.

### SQL Solution

```

SELECT
    r.restaurant_id, r.restaurant_name
FROM
    restaurants r
    LEFT JOIN
    orders o ON r.restaurant_id = o.restaurant_id
WHERE
    o.order_id IS NULL;

```

## Question 13

Calculate the total revenue generated (delivered orders only).

### SQL Solution

```
SELECT
    ROUND(SUM(total_amount), 2) AS total_delivered_revenue
FROM
    orders
WHERE
    order_status = 'delivered';
```

## Question 14

List the top 5 cities with the highest number of customers who signed up in the last year of the dataset (2025).

### SQL Solution

```
SELECT
    city, COUNT(*) AS new_signup
FROM
    customers
WHERE
    YEAR(signup_date) = '2025'
GROUP BY city
LIMIT 5;
```

## Question 15

Calculate each customer's total spend and total number of completed deliveries received.

### SQL Solution

```
SELECT
    c.customer_id,
    c.coustomer_name,
    ROUND(SUM(o.total_amount), 2) total_spend,
    COUNT(DISTINCT CASE
        WHEN d.delivery_status = 'Completed' THEN d.delivery_id
    END) AS completed_deliveries
FROM
    customers c
    JOIN
    orders o ON c.customer_id = o.customer_id
    LEFT JOIN
    deliveries d ON o.order_id = d.order_id
GROUP BY c.customer_id , c.coustomer_name
ORDER BY total_spend DESC;
```

**Portfolio note:** This document records the 15 SQL questions currently solved in the project. The underlying dataset is simulated for educational and portfolio purposes and does not represent proprietary Zomato data.