

# Repository Mirror Scripts for IBM Resilient App Host

---

## Table of Contents

- [About this Package](#)
  - [mirror-all-images.sh](#)
  - [mirror-images.sh](#)
  - [App Host Configuration](#)
- 

## History

7/20 - Initial Documentation

## About this Package:

This branch contains scripts which can be used to mirror App Host container images for local registry use. This is necessary when customers need to maintain their own apps for use in App Host along with those officially published on the App Exchange or to replicate containers for air-gapped environments.

Two scripts are provided:

- [mirror-all-images.sh](#)
- [mirror-images.sh](#)

## Initialization

- Ensure that the local container tool, docker or podman, is accessible. If root permissions are needed to run these commands, use **sudo** or **su** to access that login account in advance.
- Login to each registry using the **docker login** or **podman login** commands.

## [mirror-all-images.sh](#)

This script is used to copy all container images from the IBM official registry, [quay.io](#), to a customer's private registry. It uses local container tools such as **docker** or **podman** to pull containers down from [quay.io](#) and then push them to the private registry.

## Usage

```
/bin/bash mirror-all-images fqdn.registry.io [docker | podman]
```

- [fqdn.registry.io](#) - name or ip address of the replication registry
- [docker | podman] - optional reference to the tool to perform the container transfer. If missing, the script will attempt to determine which tool exists.

## Example

/bin/bash mirror-all-images [834299573936.dkr.ecr.us-east-2.amazonaws.com](https://834299573936.dkr.ecr.us-east-2.amazonaws.com) podman

## mirror-images.sh

This script is used to copy a select number of container images from the IBM official registry, [quay.io](https://quay.io), to a customer's private registry. It uses local container tools such as [docker](#) or [podman](#) to pull containers down from [quay.io](https://quay.io) and then push them to the private registry. Two additional files are used to control the behavior of the script:

- `repo_quay.conf` - a list of container names and versions, one per line, to replicate. The format of a line is: `container_name:x.x.x` where `x.x.x` is the tagged version.
- `preserved_images.conf` - a list of container names and versions, one per line, to retain in the local docker or podman image container environment. Format of a line is the same as used in the `repo_quay.conf` file: `container_name:x.x.x`.

### Usage

/bin/bash mirror-all-images [fqdn.registry.io](https://fqdn.registry.io) [docker | podman]

- [fqdn.registry.io](https://fqdn.registry.io) - name or ip address of the replication registry
- [docker | podman] - optional reference to the tool to perform the container transfer. If missing, the script will attempt to determine which tool exists.

### Example

/bin/bash mirror-images 192.168.12.186:5000

`repo_quay.conf`

```
fn_utilities:1.14.0
fn_xforce:1.0.0
```

`preserved_images.conf`

```
fn_utilities:1.14.0
```

## App Host Configuration

Refer to the [Configuring a private repository](#) document on how to develop Apps and configure App Host for your private registry.