

Modeling Geometry with Assemblies in SysML *

May 16, 2014

Abstract

In this module a preliminary concept implementation is provided for the possible introduction of a novel kind of 3D diagram in SysML. Such “Assembly” Diagram is used to specify an operable description of the 3D geometry of a system part.

Contents

1	Introduction	2
1.1	bbbbbbbbb	2
2	Implementation	2
2.1	Diagram initialization	2
2.2	Cell numbering	3
2.3	Diagram segmentation	3
2.4	Subdiagram mapping	4
3	Library export	5
3.1	Exporting the library	5
4	Tests	6
4.1	Diagram initialization	6
4.2	Diagram merging	6
4.3	Diagram visualization	7
A	Utilities	9
A.1	Initial import of modules	10

*This document is part of the *Linear Algebraic Representation with CoChains* (LAR-CC) framework [CL13]. May 16, 2014

1 Introduction

1.1 bbbbbbbb

2 Implementation

2.1 Diagram initialization

Uniform cell sizing A cuboidal 3-complex is generated by the script below, where the cells have uniform dimension on each coordinate direction.

```
⟨Diagram initialization 1⟩ ≡  
    """ Diagram initialization """  
    def assemblyDiagramInit(shape):  
        print "\n shape =",shape  
        # shape must be 3D, i.e. a python array with 3 indices  
        assert len(shape) == 3  
        diagram = larCuboids(shape)  
        return diagram  
    ◇
```

Macro never referenced.

Non-uniform cell sizing The parameter `quoteList` is used here to generate the new vertices of the `diagram`, previously generated with uniform spacing between the cell vertices in every coordinate direction. Each `pattern` in `quoteList` is a list of positive numbers, each corresponding to the size of the corresponding "coordinate stripe".

```
⟨Diagram initialization (non-uniform sizing) 2a⟩ ≡  
    """ Diagram initialization """  
    def assemblyDiagramInit (shape):  
        def assemblyDiagram (quoteList):  
            print "\n shape =",shape  
            # shape and quoteList must be 3D, i.e. a python array with 3 indices  
            assert (len(shape) == 3) and (len(quoteList) == 3)  
            coordList = [list(cumsum([0]+pattern)) for pattern in quoteList]  
            verts = CART(coordList)  
            _,CV = larCuboids(shape)  
            return verts,CV  
        return assemblyDiagram  
    ◇
```

Macro referenced in 5a.

Diagram scaling to cuboid of given size The `size` parameter is the array of lateral dimensions to which to scale the `diagram` parameter. `size` must be an array of 3 numbers; `diagram` is a LAR model

```

⟨Diagram scaling to sized cuboid 2b⟩ ≡
    """ Diagram scaling to given size """
    def unitDiagram(diagram, size=[1,1,1]):
        V,CV = diagram
        print "\n shape =",shape
        # size must be a python array with 3 numbers
        assert (len(size) == 3) and (AND(AA(ISNUM)(size)) == True)
        V_ = array(V) / AA(float)(max(V))
        V = (V_ * size).tolist()
        diagram = V,CV
        return diagram
    ◇

```

Macro referenced in 5a.

2.2 Cell numbering

Drawing numbers of cells

```

⟨Drawing numbers of cells 2c⟩ ≡
    """ Drawing numbers of cells """
    def cellNumbering (larModel,hpcModel):
        V,CV = larModel
        def cellNumbering0 (cellSubset,color=WHITE,scalingFactor=1):
            text = TEXTWITHATTRIBUTES (TEXTALIGNMENT='centre', TEXTANGLE=0,
                                         TEXTWIDTH=0.1*scalingFactor,
                                         TEXTHEIGHT=0.2*scalingFactor,
                                         TEXTSPACING=0.025*scalingFactor)
            hpcList = [hpcModel]
            for cell in cellSubset:
                point = CCOMB([V[v] for v in CV[cell]])
                hpcList.append(T([1,2,3])(point)(COLOR(color)(text(str(cell)))))
            return STRUCT(hpcList)
        return cellNumbering0
    ◇

```

Macro referenced in 5a.

2.3 Diagram segmentation

Boundary cells ($3D \rightarrow 2D$) computation The computations of boundary cells is executed by calling the `boundaryCells` from the `larcc` module.

```

⟨Boundary cells ( $3D \rightarrow 2D$ ) computation 3a⟩ ≡

```

```

def lar2boundaryFaces(CV,FV):
    """ Boundary cells computation """
    return boundaryCells(CV,FV)

```

Macro referenced in 5a.

Interior partitions ($3D \rightarrow 2D$) computation The indices of the boundary 2-cells are returned in `boundarychain2D`, and subtracted from the set $\{0, 1, \dots, |E| - 1\}$ in order to return the indices of the `interiorCells`.

\langle Interior partitions ($3D \rightarrow 2D$) computation 3b $\rangle \equiv$

```

def lar2InteriorFaces(CV,FV):
    """ Boundary cells computation """
    boundarychain2D = boundaryCells(CV,FV)
    totalChain2D = range(len(FV))
    interiorCells = set(totalChain2D).difference(boundarychain2D)
    return interiorCells

```

Macro referenced in 5a.

2.4 Subdiagram mapping

The aim of this section is to allow for separate development of subdiagrams of a geometric diagram. When satisfied with the current design situation, the developer may map a whole diagram into a single 3D cell of the upper-level diagram — in the following called the *master* diagram. Of course, such nesting may happen several times within a (father) master, producing a hierarchical decomposition (of any depth) of the geometry diagrams.

Task decomposition The procedure to map a diagram to a sub diagram is described below in a top-down manner, decomposing the task into an ordered set of subtasks.

\langle Subdiagram to diagram mapping 4a $\rangle \equiv$

\langle 3D window to viewport transformation 4b \rangle

```

def diagram2cell(diagram, master, cell):
    mat = diagram2cellMatrix(diagram)(master, cell)
    diagram = larApply(mat)(diagram)

    """
    # yet to finish coding
    V, CV1, CV2, n12 = vertexSieve(master, diagram)
    masterBoundaryFaces = boundaryOfChain(CV, FV)([cell])
    diagramBoundaryFaces = lar2boundaryFaces(CV, FV)

```

```

"""
V = master[0] + diagram[0]
offset = len(master[0])
CV = [c for k,c in enumerate(master[1]) if k != cell] + [
    [v+offset for v in c] for c in diagram[1]]
master = V, CV
return master

```

◇

Macro referenced in 5a.

3D window to viewport transformation

⟨3D window to viewport transformation 4b⟩ ≡

```

""" 3D window to viewport transformation """
def diagram2cellMatrix(diagram):
    def diagramToCellMatrix0(master,cell):
        wdw = min(diagram[0]) + max(diagram[0])          # window3D
        cV = [master[0][v] for v in master[1][cell]]
        vpt = min(cV) + max(cV)                          # viewport3D
        print "\n window3D =",wdw
        print "\n viewport3D =",vpt

        mat = zeros((4,4))
        mat[0,0] = (vpt[3]-vpt[0])/(wdw[3]-wdw[0])
        mat[0,3] = vpt[0] - mat[0,0]*wdw[0]
        mat[1,1] = (vpt[4]-vpt[1])/(wdw[4]-wdw[1])
        mat[1,3] = vpt[1] - mat[1,1]*wdw[1]
        mat[2,2] = (vpt[5]-vpt[2])/(wdw[5]-wdw[2])
        mat[2,3] = vpt[2] - mat[2,2]*wdw[2]
        mat[3,3] = 1
        print "\n mat =",mat
        return mat
    return diagramToCellMatrix0

```

◇

Macro referenced in 4a.

3 Library export

3.1 Exporting the library

"lib/py/sysml.py" 5a ≡

- ⟨Initial import of modules 9b⟩
- ⟨To compute the boundary (d-1)-chain of a given d-chain 9a⟩
- ⟨Diagram initialization (non-uniform sizing) 2a⟩
- ⟨Boundary cells ($3D \rightarrow 2D$) computation 3a⟩

```

⟨Interior partitions ( $3D \rightarrow 2D$ ) computation 3b⟩
⟨Diagram scaling to sized cuboid 2b⟩
from myfont import *
⟨Drawing numbers of cells 2c⟩
⟨Subdiagram to diagram mapping 4a⟩
◇

```

4 Tests

4.1 Diagram initialization

```

"test/py/sysml/test01.py" 5b ≡
    """ testing initial steps of Assembly Diagram construction """
    ⟨Initial import of modules 9b⟩
    from sysml import *

    shape = [1,2,2]
    sizePatterns = [[1],[2,1],[0.8,0.2]]
    diagram = assemblyDiagramInit(shape)(sizePatterns)
    print "\n diagram =",diagram
    VIEW(SKEL_1(STRUCT(MKPOLS(diagram))))

    VV,EV,FV,CV = gridSkeletons(shape)
    boundaryFaces = lar2boundaryFaces(CV,FV)
    interiorFaces = list(set(range(len(FV))).difference(boundaryFaces))
    print "\n boundary faces =",boundaryFaces
    print "\n interior faces =",interiorFaces
    diagram1 = unitDiagram(diagram)
    VIEW(SKEL_1(STRUCT(MKPOLS(diagram1))))

    hpc = SKEL_1(STRUCT(MKPOLS(diagram1)))
    V = diagram1[0]
    hpc = cellNumbering ((V,FV),hpc)(interiorFaces,YELLOW,.5)
    VIEW(hpc)
    hpc = cellNumbering ((V,EV),hpc)([for f in interiorFaces],GREEN,.4)
    VIEW(hpc)
    hpc = cellNumbering ((V,VV),hpc)(range(len(VV)),RED,.3)
    VIEW(hpc)

    ◇

```

4.2 Diagram merging

```

"test/py/sysml/test02.py" 6a ≡
    """ definition and merging of two diagrams into a single diagram """
    ⟨Initial import of modules 9b⟩

```

```

from sysml import *

master = assemblyDiagramInit([2,2,2])([.4,.6],[.4,.6],[.4,.6]))
diagram = assemblyDiagramInit([3,3,3])([.4,.2,.4],[.4,.2,.4],[.4,.2,.4]))
VIEW(SKEL_1(STRUCT([DRAW(master),T(2)(1),DRAW(diagram)])))

hpc = SKEL_1(STRUCT(MKPOLS(master)))
hpc = cellNumbering (master,hpc)(range(len(master[1])),WHITE,.5)
VIEW(hpc)

master = diagram2cell(diagram,master,7)
VIEW(SKEL_1(STRUCT( MKPOLS(master) )))

◇

```

4.3 Diagram visualization

```

"test/py/sysml/test03.py" 6b ≡
""" definition and merging of two diagrams into a single diagram """
<Initial import of modules 9b>
from sysml import *

master = assemblyDiagramInit([2,2,2])([.4,.6],[.4,.6],[.4,.6]))
diagram = assemblyDiagramInit([3,3,3])([.4,.2,.4],[.4,.2,.4],[.4,.2,.4]))

VV,EV,FV,CV = gridSkeletons([2,2,2])
V,CV = master
hpc = SKEL_1(STRUCT(MKPOLS(master)))
hpc = cellNumbering (master,hpc)(range(len(CV)),CYAN,.5)
VIEW(hpc)

master = diagram2cell(diagram,master,7)
VIEW(SKEL_1(STRUCT( MKPOLS(master) )))

VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLS(larFacets(master))))

masterBoundaryFaces = boundaryOfChain(CV,FV)([7])
diagramBoundaryFaces = lar2boundaryFaces(CV,FV)

◇

```

progressive refinement of a block diagram In this example, a step-by step generation of a simple apartment is produced, using `assemblyDiagramInit` to produce a block diagram of given `shape` and `size`, the `cellNumbering` function to generate an `hpc` value with the numbers of 3-cells in the current "master" diagram, the `diagram2cell` function to map and merge a `diagram` into a `cell` of the `master`.




Figure 1: Example of a geometry diagram merged in a master diagram

Remember that in `lar-cc` the numbering of cells in a model is 0-based (like in python). Conversely, in `pyplasm` the numbering of cells (for example of vertex indices in MKPOL) is 1-based, like in Fortran or MATLAB.

```
"test/py/sysml/test04.py" 8 ≡
    """ progressive refinement of a block diagram """
    (Initial import of modules 9b)
    from sysml import *
    DRAW = COMP([VIEW,STRUCT,MKPOLS])

    master = assemblyDiagramInit([5,5,2])([.3,3.2,.1,5,.3],[.3,4,.1,2.9,.3],[.3,2.7])
    V,CV = master
    hpc = SKEL_1(STRUCT(MKPOLS(master)))
    hpc = cellNumbering (master,hpc)(range(len(CV)),CYAN,2)
    VIEW(hpc)

    toRemove = [13,33,17,37]
    master = V,[cell for k,cell in enumerate(CV) if not (k in toRemove)]
    DRAW(master)

    hpc = SKEL_1(STRUCT(MKPOLS(master)))
    hpc = cellNumbering (master,hpc)(range(len(master[1])),CYAN,2)
    VIEW(hpc)

    toMerge = 29
```



```

cell = MKPOL([master[0],[[v+1 for v in master[1][toMerge]]],None])
VIEW(STRUCT([hpc,cell]))

diagram = assemblyDiagramInit([3,1,2])([[2,1,2],[.3],[2.2,.5]])
master = diagram2cell(diagram,master,toMerge)
hpc = SKEL_1(STRUCT(MKPOLS(master)))
hpc = cellNumbering (master,hpc)(range(len(master[1])),CYAN,2)
VIEW(hpc)

toRemove = [47]
master = master[0], [cell for k,cell in enumerate(master[1]) if not (k in toRemove)]
DRAW(master)

hpc = SKEL_1(STRUCT(MKPOLS(master)))
hpc = cellNumbering (master,hpc)(range(len(master[1])),CYAN,2)
VIEW(hpc)

toMerge = 34
cell = MKPOL([master[0],[[v+1 for v in master[1][toMerge]]],None])
VIEW(STRUCT([hpc,cell]))

diagram = assemblyDiagramInit([5,1,3])([[1.5,0.9,.2,.9,1.5],[.3],[1,1.4,.3]])
master = diagram2cell(diagram,master,toMerge)
hpc = SKEL_1(STRUCT(MKPOLS(master)))
hpc = cellNumbering (master,hpc)(range(len(master[1])),CYAN,2)
VIEW(hpc)

toRemove = [53,59]
master = master[0], [cell for k,cell in enumerate(master[1]) if not (k in toRemove)]
DRAW(master)
◇

```

A Utilities

⟨ To compute the boundary (d-1)-chain of a given d-chain 9a ⟩ ≡

```

def boundaryOfChain(cells,facets):
    csrBoundaryMat = boundary(cells,facets)
    csrChain = zeros((len(cells),1))
    def boundaryOfChain0(chain):
        for cell in chain: csrChain[cell,0]=1.0
        csrBoundaryChain = matrixProduct(csrBoundaryMat, csrChain)
        boundaryCells = [k for k,val in enumerate(csrBoundaryChain.tolist())
                        if val == [1.0]]
        return boundaryCells
    return boundaryOfChain0

```

◇

Macro referenced in 5a.

A.1 Initial import of modules

Initial import of modules

⟨Initial import of modules 9b⟩ ≡

```
from pyplasm import *
from scipy import *
import os,sys
""" import modules from larcc/lib """
sys.path.insert(0, 'lib/py/')
from lar2psm import *
from simplexn import *
from larcc import *
from largrid import *
from mapper import *
from boolean import *
```

◇

Macro referenced in 5ab, 6ab, 8.

References

- [CL13] CVD-Lab, *Linear algebraic representation*, Tech. Report 13-00, Roma Tre University, October 2013.