

The basic `larcc` module *

The LARCC team

May 22, 2014

Contents

1	Basic representations	2
1.1	BRC (Binary Row Compressed)	2
1.2	Format conversions	2
2	Matrix operations	5
3	Topological operations	10
3.1	Incidence and adjacency operators	10
3.2	Boundary and coboundary operators	10
4	Exporting the library	19
4.1	MIT licence	19
4.2	Importing of modules or packages	19
4.3	Writing the library file	20
5	Unit tests	20
A	Appendix: Tutorials	21
A.1	Model generation, skeleton and boundary extraction	21
A.2	Boundary of 3D simplicial grid	25
A.3	Oriented boundary of a random simplicial complex	25
A.4	Oriented boundary of a simplicial grid	27
A.5	Skeletons and oriented boundary of a simplicial complex	27
A.6	Boundary of random 2D simplicial complex	28
A.7	Assemblies of simplices and hypercubes	31

*This document is part of the *Linear Algebraic Representation with CoChains* (LAR-CC) framework [CL13]. May 22, 2014

1 Basic representations

A few basic representation of topology are used in LARCC. They include some common sparse matrix representations: CSR (Compressed Sparse Row), CSC (Compressed Sparse Column), COO (Coordinate Representation), and BRC (Binary Row Compressed).

1.1 BRC (Binary Row Compressed)

We denote as BRC (Binary Row Compressed) the standard input representation of our LARCC framework. A BRC representation is an array of arrays of integers, with no requirement of equal length for the component arrays. The BRC format is used to represent a (normally sparse) binary matrix. Each component array corresponds to a matrix row, and contains the indices of columns that store a 1 value. No storage is used for 0 values.

BRC format example Let $A = (a_{i,j} \in \{0,1\})$ be a binary matrix. The notation $\text{BRC}(A)$ is used for the corresponding data structure.

$$A = \begin{pmatrix} 0, 1, 0, 0, 0, 0, 0, 1, 0, 0 \\ 0, 0, 1, 0, 0, 0, 0, 0, 0, 0 \\ 1, 0, 0, 1, 0, 0, 0, 0, 0, 1 \\ 1, 0, 0, 0, 0, 0, 1, 0, 0, 0 \\ 0, 0, 0, 0, 0, 1, 1, 1, 0, 0 \\ 0, 0, 1, 0, 1, 0, 0, 0, 1, 0 \\ 0, 0, 0, 0, 0, 0, 0, 0, 0, 0 \\ 0, 1, 0, 0, 0, 0, 0, 1, 0, 1 \\ 0, 0, 0, 1, 0, 0, 0, 0, 1, 0 \\ 0, 1, 1, 0, 1, 0, 0, 0, 0, 0 \end{pmatrix} \mapsto \text{BRC}(A) = \begin{array}{l} [[1,7], \\ [2], \\ [0,3,9], \\ [0,6], \\ [5,6,7], \\ [2,4,8], \\ [], \\ [1,7,9], \\ [3,8], \\ [1,2,4]] \end{array}$$

1.2 Format conversions

First we give the function `triples2mat` to make the transformation from the sparse matrix, given as a list of triples *row,column,value* (non-zero elements), to the `scipy.sparse` format corresponding to the `shape` parameter, set by default to "csr", that stands for *Compressed Sparse Row*, the normal matrix format of the LARCC framework.

⟨ From list of triples to scipy.sparse 3a ⟩ ≡

```
def triples2mat(triples, shape="csr"):
    n = len(triples)
    data = arange(n)
    ij = arange(2*n).reshape(2,n)
    for k,item in enumerate(triples):
        ij[0][k],ij[1][k],data[k] = item
    return scipy.sparse.coo_matrix((data, ij)).asformat(shape)
```

◇

Macro referenced in 20a.

The function `brc2Coo` transforms a BRC representation in a list of triples (*row, column, 1*) ordered by row.

⟨ Brc to Coo transformation 3b ⟩ ≡

```
def brc2Coo(ListOfListOfInt):
    COOm = [[k,col,1] for k,row in enumerate(ListOfListOfInt)
            for col in row ]
    return COOm
```

◇

Macro referenced in 20a.

Two coordinate compressed sparse matrices `cooFV` and `cooEV` are created below, starting from the BRC representation `FV` and `EV` of the incidence of vertices on faces and edges, respectively, for a very simple plane triangulation.

⟨ Test example of Brc to Coo transformation 3c ⟩ ≡

```
print "\n>>> brc2Coo"
V = [[0, 0], [1, 0], [2, 0], [0, 1], [1, 1], [2, 1]]
FV = [[0, 1, 3], [1, 2, 4], [1, 3, 4], [2, 4, 5]]
EV = [[0,1],[0,3],[1,2],[1,3],[1,4],[2,4],[2,5],[3,4],[4,5]]
cooFV = brc2Coo(FV)
cooEV = brc2Coo(EV)
assert cooFV == [[0,0,1],[0,1,1],[0,3,1],[1,1,1],[1,2,1],[1,4,1],[2,1,1],
[2,3,1],[2,4,1],[3,2,1],[3,4,1],[3,5,1]]
assert cooEV == [[0,0,1],[0,1,1],[1,0,1],[1,3,1],[2,1,1],[2,2,1],[3,1,1],
[3,3,1],[4,1,1],[4,4,1],[5,2,1],[5,4,1],[6,2,1],[6,5,1],[7,3,1],[7,4,1],
[8,4,1],[8,5,1]]
```

◇

Macro referenced in 20b.

⟨Coo to Csr transformation 4a⟩ ≡

```
def coo2Csr(COOm):
    CSRm = triples2mat(COOm,"csr")
    return CSRm
```

◇

Macro referenced in 20a.

Two CSR sparse matrices `csrFV` and `csrEV` are generated (by *scipy.sparse*) in the following example:

⟨Test example of Coo to Csr transformation 4b⟩ ≡

```
csrFV = coo2Csr(cooFV)
csrEV = coo2Csr(cooEV)
print "\ncsr(FV) =\n", repr(csrFV)
print "\ncsr(EV) =\n", repr(csrEV)
```

◇

Macro referenced in 20b.

The *scipy* printout of the last two lines above is the following:

```
csr(FV) = <4x6 sparse matrix of type '<type 'numpy.int64'>'
with 12 stored elements in Compressed Sparse Row format>
csr(EV) = <9x6 sparse matrix of type '<type 'numpy.int64'>'
with 18 stored elements in Compressed Sparse Row format>
```

The transformation from BRC to CSR format is implemented slightly differently, according to the fact that the matrix dimension is either unknown (`shape=(0,0)`) or known.

⟨Brc to Csr transformation 4c⟩ ≡

```
def csrCreate(BRCmatrix,shape=(0,0)):
    triples = brc2Coo(BRCmatrix)
    if shape == (0,0):
        CSRmatrix = coo2Csr(triples)
    else:
        CSRmatrix = scipy.sparse.csr_matrix(shape)
        for i,j,v in triples: CSRmatrix[i,j] = v
    return CSRmatrix
```

◇

Macro referenced in 20a.

The conversion to CSR format of the characteristic matrix *faces-vertices* FV is given below for our simple example made by four triangle of a manifold 2D space, graphically shown in Figure 1a. The LAR representation with CSR matrices does not make difference between manifolds and non-manifolds, conversely than most modern solid modelling representation schemes, as shown by removing from FV the third triangle, giving the model in Figure 1b.

⟨ Test example of Brc to Csr transformation 5a ⟩ ≡

```
print "\n>>> brc2Csr"
V = [[0, 0], [1, 0], [2, 0], [0, 1], [1, 1], [2, 1]]
FV = [[0, 1, 3], [1, 2, 4], [1, 3, 4], [2, 4, 5]]
EV = [[0,1],[0,3],[1,2],[1,3],[1,4],[2,4],[2,5],[3,4],[4,5]]
csrFV = csrCreate(FV)
csrEV = csrCreate(EV)
print "\ncsrCreate(FV) =\n", csrFV
VIEW(STRUCT(MKPOLS((V,FV))))
VIEW(STRUCT(MKPOLS((V,EV))))
◇
```

Macro referenced in [6d](#), [20b](#).




Figure 1: (a) Manifold two-dimensional space; (b) non-manifold space.

2 Matrix operations

As we know, the LAR representation of topology is based on CSR representation of sparse binary (and integer) matrices. Two Utility functions allow to query the number of rows and columns of a CSR matrix, independently from the low-level implementation (that in the following is provided by *scipy.sparse*).

⟨ Query Matrix shape 5b ⟩ ≡

```
def csrGetNumberOfRows(CSRmatrix):
    Int = CSRmatrix.shape[0]
    return Int

def csrGetNumberOfColumns(CSRmatrix):
    Int = CSRmatrix.shape[1]
    return Int
◇
```

Macro referenced in [20a](#).

⟨ Test examples of Query Matrix shape 6a ⟩ ≡

```
print "\n>>> csrGetNumberOfRows"
print "\ncsrGetNumberOfRows(csrFV) =", csrGetNumberOfRows(csrFV)
print "\ncsrGetNumberOfRows(csrEV) =", csrGetNumberOfRows(csrEV)
print "\n>>> csrGetNumberOfColumns"
print "\ncsrGetNumberOfColumns(csrFV) =", csrGetNumberOfColumns(csrFV)
print "\ncsrGetNumberOfColumns(csrEV) =", csrGetNumberOfColumns(csrEV)
◇
```

Macro referenced in 20b.

⟨ Sparse to dense matrix transformation 6b ⟩ ≡

```
def csr2DenseMatrix(CSRm):
    nrows = csrGetNumberOfRows(CSRm)
    ncolumns = csrGetNumberOfColumns(CSRm)
    ScipyMat = zeros((nrows,ncolumns),int)
    C = CSRm.tocoo()
    for triple in zip(C.row,C.col,C.data):
        ScipyMat[triple[0],triple[1]] = triple[2]
    return ScipyMat
◇
```

Macro referenced in 20a.

⟨ Test examples of Sparse to dense matrix transformation 6c ⟩ ≡

```
print "\n>>> csr2DenseMatrix"
print "\nFV =\n", csr2DenseMatrix(csrFV)
print "\nEV =\n", csr2DenseMatrix(csrEV)
◇
```

Macro referenced in 6d, 20b.

Characteristic matrices Let us compute and show in dense form the characteristic matrices of 2- and 1-cells of the simple manifold just defined. By running the file `test/py/larcc/test08.py` the reader will get the two matrices shown in Example 2

"test/py/larcc/test08.py" 6d ≡

```
import sys
sys.path.insert(0, 'lib/py/')
from larcc import *
⟨ Test example of Brc to Csr transformation 5a ⟩
⟨ Test examples of Sparse to dense matrix transformation 6c ⟩
◇
```

Example 1 (Dense Characteristic matrices). *Let us notice that the two matrices below have the same numbers of columns (indexed by vertices of the cell decomposition). This very fact allows to multiply one matrix for the other transposed, and hence to compute the*

matrix form of linear operators between the spaces of cells of various dimensions.

$$\begin{aligned}
 FV &= \begin{bmatrix} 1 & 1 & 0 & 1 & 0 & 0 \\ 0 & 1 & 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 & 1 \end{bmatrix} \\
 EV &= \begin{bmatrix} 1 & 1 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 1 & 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 1 & 1 & 0 \\ 0 & 0 & 0 & 0 & 1 & 1 \end{bmatrix}
 \end{aligned}$$

Matrix product and transposition The following macro provides the IDE interface for the two main matrix operations required by LARCC, the binary product of compatible matrices and the unary transposition of matrices.

```

⟨Matrix product and transposition 7⟩ ≡
def matrixProduct(CSRm1,CSRm2):
    CSRm = CSRm1 * CSRm2
    return CSRm

def csrTranspose(CSRm):
    CSRm = CSRm.T
    return CSRm

```

Macro referenced in 20a.

Example 2 (Operators from edges to faces and vice-versa). *As a general rule for operators between two spaces of chains of different dimensions supported by the same cellular complex, we use names made by two characters, whose first letter correspond to the target space, and whose second letter to the domain space. Hence FE must be read as the operator from edges to faces. Of course, since this use correspond to see the first letter as the space generated by rows, and the second letter as the space generated by columns. Notice that the element (i, j) of such matrices stores the number of vertices shared between the (row-)cell i and the*

(column-)cell j .

$$FE = FV EV^\top = \begin{bmatrix} 2 & 2 & 1 & 2 & 1 & 0 & 0 & 1 & 0 \\ 1 & 0 & 2 & 1 & 2 & 2 & 1 & 1 & 1 \\ 1 & 1 & 1 & 2 & 2 & 1 & 0 & 2 & 1 \\ 0 & 0 & 1 & 0 & 1 & 2 & 2 & 1 & 2 \end{bmatrix}$$

$$EF = EV FV^\top = \begin{bmatrix} 2 & 1 & 1 & 0 \\ 2 & 0 & 1 & 0 \\ 1 & 2 & 1 & 1 \\ 2 & 1 & 2 & 0 \\ 1 & 2 & 2 & 1 \\ 0 & 2 & 1 & 2 \\ 0 & 1 & 0 & 2 \\ 1 & 1 & 2 & 1 \\ 0 & 1 & 1 & 2 \end{bmatrix}$$




Figure 2: example caption

⟨Matrix filtering to produce the boundary matrix 8⟩ ≡

```
def csrBoundaryFilter(CSRm, facetLengths):
    maxs = [max(CSRm[k].data) for k in range(CSRm.shape[0])]
    inputShape = CSRm.shape
    coo = CSRm.tocoo()
    for k in range(len(coo.data)):
        if coo.data[k] == maxs[coo.row[k]]: coo.data[k] = 1
        else: coo.data[k] = 0
    mtx = coo_matrix((coo.data, (coo.row, coo.col)), shape=inputShape)
    out = mtx.tocsr()
    return out
```

◇

Macro referenced in 20a.

⟨ Test example of Matrix filtering to produce the boundary matrix 9a ⟩ ≡

```
print "\n>>> csrBoundaryFilter"
csrEF = matrixProduct(csrFV, csrTranspose(csrEV)).T
facetLengths = [csrCell.getnnz() for csrCell in csrEV]
CSRm = csrBoundaryFilter(csrEF, facetLengths).T
print "\ncsrMaxFilter(csrFE) =\n", csr2DenseMatrix(CSRm)
◇
```

Macro referenced in 20b.

⟨ Matrix filtering via a generic predicate 9b ⟩ ≡

```
def csrPredFilter(CSRm, pred):
    # can be done in parallel (by rows)
    coo = CSRm.tocoo()
    triples = [[row,col,val] for row,col,val
                in zip(coo.row,coo.col,coo.data) if pred(val)]
    i, j, data = TRANS(triples)
    CSRm = scipy.sparse.coo_matrix((data,(i,j)),CSRm.shape).tocsr()
    return CSRm
◇
```

Macro referenced in 20a.

⟨ Test example of Matrix filtering via a generic predicate 9c ⟩ ≡

```
print "\n>>> csrPredFilter"
CSRm = csrPredFilter(matrixProduct(csrFV, csrTranspose(csrEV)).T, GE(2)).T
print "\nccsrPredFilter(csrFE) =\n", csr2DenseMatrix(CSRm)
◇
```

Macro referenced in 20b.

3 Topological operations

3.1 Incidence and adjacency operators

3.2 Boundary and coboundary operators

⟨ From cells and facets to boundary operator 10a ⟩ ≡

```
def boundary(cells,facets):
    csrCV = csrCreate(cells)
    csrFV = csrCreate(facets)
    csrFC = matrixProduct(csrFV, csrTranspose(csrCV))
    facetLengths = [csrCell.getnnz() for csrCell in csrCV]
    return csrBoundaryFilter(csrFC,facetLengths)

def coboundary(cells,facets):
    Boundary = boundary(cells,facets)
    return csrTranspose(Boundary)

◇
```

Macro referenced in 20a.

⟨ Test examples of From cells and facets to boundary operator 10b ⟩ ≡

```
V = [[0.0, 0.0, 0.0], [1.0, 0.0, 0.0], [0.0, 1.0, 0.0], [1.0, 1.0, 0.0],
      [0.0, 0.0, 1.0], [1.0, 0.0, 1.0], [0.0, 1.0, 1.0], [1.0, 1.0, 1.0]]

CV = [[0, 1, 2, 4], [1, 2, 4, 5], [2, 4, 5, 6], [1, 2, 3, 5], [2, 3, 5, 6],
       [3, 5, 6, 7]]

FV = [[0, 1, 2], [0, 1, 4], [0, 2, 4], [1, 2, 3], [1, 2, 4], [1, 2, 5],
       [1, 3, 5], [1, 4, 5], [2, 3, 5], [2, 3, 6], [2, 4, 5], [2, 4, 6], [2, 5, 6],
       [3, 5, 6], [3, 5, 7], [3, 6, 7], [4, 5, 6], [5, 6, 7]]

EV = [[0, 1], [0, 2], [0, 4], [1, 2], [1, 3], [1, 4], [1, 5], [2, 3], [2, 4],
       [2, 5], [2, 6], [3, 5], [3, 6], [3, 7], [4, 5], [4, 6], [5, 6], [5, 7],
       [6, 7]]

print "\ncoboundary_2 =\n", csr2DenseMatrix(coboundary(CV,FV))
print "\ncoboundary_1 =\n", csr2DenseMatrix(coboundary(FV,EV))
print "\ncoboundary_0 =\n", csr2DenseMatrix(coboundary(EV,AA(LIST)(range(len(V))))))

◇
```

Macro referenced in 20b.

```

⟨ From cells and facets to boundary cells 11a ⟩ ≡
def zeroChain(cells):
    pass

def totalChain(cells):
    return csrCreate([[0] for cell in cells]) # ??? zero ??

def boundaryCells(cells,facets):
    csrBoundaryMat = boundary(cells,facets)
    csrChain = totalChain(cells)
    csrBoundaryChain = matrixProduct(csrBoundaryMat, csrChain)
    for k,value in enumerate(csrBoundaryChain.data):
        if value % 2 == 0: csrBoundaryChain.data[k] = 0
    boundaryCells = [k for k,val in enumerate(csrBoundaryChain.data.tolist()) if val == 1]
    return boundaryCells
◇

```

Macro referenced in 20a.

```

⟨ Test examples of From cells and facets to boundary cells 11b ⟩ ≡
boundaryCells_2 = boundaryCells(CV,FV)
boundaryCells_1 = boundaryCells([FV[k] for k in boundaryCells_2],EV)

print "\nboundaryCells_2 =\n", boundaryCells_2
print "\nboundaryCells_1 =\n", boundaryCells_1

boundaryModel = (V,[FV[k] for k in boundaryCells_2])
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs(boundaryModel)))
◇

```

Macro referenced in 20b.

Signed boundary matrix for simplicial complexes The computation of the *signed* boundary matrix starts with enumerating the non-zero elements of the mod two (unoriented) boundary matrix. In particular, the `pairs` variable contains all the pairs of incident $((d-1)\text{-cell}, d\text{-cell})$, corresponding to all the 1 elements in the binary boundary matrix. Of course, their number equates the product of the number of d -cells, times the number of $(d-1)$ -facets on the boundary of each d -cell. For the case of a 3-simplicial complex CV , we have $4|CV|$ `pairs` elements. The actual goal of the function `signedBoundary`, in the macro below, is to compute a sign for each of them.

The `pairs` values must be interpreted as (i, j) values in the incidence matrix FC (*facets-cells*), and hence as pairs of indices f and c into the characteristic matrices $FV = CSR(M_{d-1})$ and $CV = CSR(M_d)$, respectively.

For each incidence pair f, c , the list `vertLists` contains the two lists of vertices associated to f and to c , called respectively the `face` and the `coface`. For each `face`, `coface`

pair (i.e. for each unit element in the unordered boundary matrix), the `missingVertIndices` list will contain the index of the `coface` vertex not contained in the incident `face`. Finally the ± 1 (signed) incidence coefficients are computed and stored in the `faceSigns`, and then located in their actual positions within the `csrSignedBoundaryMat`. The sign of the incidence coefficient associated to the pair (facet,cell), also called (face,coface) in the implementation below, is computed as the sign of $(-1)^k$, where k is the position index of the removed vertex in the facet $\langle v_0, \dots, v_{k-1}, v_{k+1}, \dots, v_d \rangle$. of the $\langle v_0, \dots, v_d \rangle$ cell.

\langle Signed boundary matrix for simplicial models 12 $\rangle \equiv$

```
def signedBoundary (CV,FV):
    # compute the set of pairs of indices to [boundary face,incident coface]
    coo = boundary(CV,FV).tocoo()
    pairs = [[coo.row[k],coo.col[k]] for k,val in enumerate(coo.data) if val != 0]

    # compute the [face, coface] pair as vertex lists
    vertLists = [[FV[f], CV[c]] for f,c in pairs]

    # compute the local (interior to the coface) indices of missing vertices
    def missingVert(face,coface): return list(set(coface).difference(face))[0]
    missingVertIndices = [c.index(missingVert(f,c)) for f,c in vertLists]

    # signed incidence coefficients
    faceSigns = AA(C(POWER)(-1))(missingVertIndices)

    # signed boundary matrix
    csrSignedBoundaryMat = csr_matrix( (faceSigns, TRANS(pairs)) )
    return csrSignedBoundaryMat
```

◇

Macro referenced in [20a](#).

Computation of signed boundary cells Two simplices are said *coherently oriented* when their common facets have opposite orientations. If the boundary cells give a decomposition of the boundary of an orientable solid, that partitionates the embedding space in two subsets corresponding to the *interior* and the *exterior* of the solid, then the boundary cells can be coherently oriented. This task is performed by the function `signedBoundaryCells` below.

The matrix of the signed boundary operator, with elements in $\{-1, 0, 1\}$, is computed in compressed sparse row (CSR) format, and stored in `csrSignedBoundaryMat`. In order to be able to return a list of `signedBoundaryCells` having a coherent orientation, we need to compute the coface of each boundary facet, i.e. the single d -cell having the facet on its boundary, and provide a coherent orientation to such chain of d -cells. The goal is obtained computing the sign of the determinant of the coface matrices, i.e. of square matrices having as rows the vertices of a coface, in normalised homogeneous coordinates.

The chain of boundary facets `boundaryCells`, obtained by multiplying the signed matrix of the boundary operator by the coordinate representation of the total d -chain, is coherently oriented by multiplication times the determinants of the `cofaceMats`.

The `cofaceMats` list is filled with the matrices having per row the position vectors of vertices of a coface, in normalized homogeneous coordinates. The list of signed face indices `orientedBoundaryCells` is returned by the function.

⟨ Oriented boundary cells for simplicial models 13 ⟩ \equiv

```
def signedBoundaryCells(verts,cells,facets):
    csrSignedBoundaryMat = signedBoundary(cells,facets)

    csrTotalChain = totalChain(cells)
    csrBoundaryChain = matrixProduct(csrSignedBoundaryMat, csrTotalChain)
    cooCells = csrBoundaryChain.tocoo()

    boundaryCells = []
    for k,v in enumerate(cooCells.data):
        if abs(v) == 1:
            boundaryCells += [int(cooCells.row[k] * cooCells.data[k])]

    boundaryCocells = []
    for k,v in enumerate(boundaryCells):
        boundaryCocells += list(csrSignedBoundaryMat[abs(v)].tocoo().col)

    boundaryCofaceMats = [[verts[v]+[1] for v in cells[c]] for c in boundaryCocells]
    boundaryCofaceSigns = AA(SIGN)(AA(np.linalg.det)(boundaryCofaceMats))

    def swap(mylist): return [mylist[1]]+[mylist[0]]+mylist[2:]
    orientedBoundaryCells = list(array(boundaryCells)*array(boundaryCofaceSigns))

    return orientedBoundaryCells
```

◇

Macro defined by [13](#), [15](#).
Macro referenced in [20a](#).

Orienting polytopal cells

input : "cell" indices of a convex and solid polytopes and "V" vertices;

output : biggest "simplex" indices spanning the polytope.

m : number of cell vertices

d : dimension (number of coordinates) of cell vertices

d+1 : number of simplex vertices

vcell : cell vertices

vsimplex : simplex vertices

Id : identity matrix

basis : orthonormal spanning set of vectors e_k

vector : position vector of a simplex vertex in translated coordinates

unUsedIndices : cell indices not moved to simplex

⟨ Oriented boundary cells for simplicial models 15 ⟩ ≡

```
def pivotSimplices(V,CV,d=3):
    simplices = []
    for cell in CV:
        vcell = np.array([V[v] for v in cell])
        m, simplex = len(cell), []
        # translate the cell: for each k, vcell[k] -= vcell[0], and simplex[0] := cell[0]
        for k in range(m-1,-1,-1): vcell[k] -= vcell[0]
        # simplex = [0], basis = [], tensor = Id(d+1)
        simplex += [cell[0]]
        basis = []
        tensor = np.array(IDNT(d))
        # look for most far cell vertex
        dists = [SUM([SQR(x) for x in v])**0.5 for v in vcell]
        maxDistIndex = max(enumerate(dists),key=lambda x: x[1])[0]
        vector = np.array([vcell[maxDistIndex]])
        # normalize vector
        den=(vector**2).sum(axis=-1) **0.5
        basis = [vector/den]
        simplex += [cell[maxDistIndex]]
        unUsedIndices = [h for h in cell if h not in simplex]

        # for k in {2,d+1}:
        for k in range(2,d+1):
            # update the orthonormal tensor
            e = basis[-1]
            tensor = tensor - np.dot(e.T, e)
            # compute the index h of a best vector
            # look for most far cell vertex
            dists = [SUM([SQR(x) for x in np.dot(tensor,v)])**0.5
                    if h in unUsedIndices else 0.0
                    for (h,v) in zip(cell,vcell)]
            # insert the best vector index h in output simplex
            maxDistIndex = max(enumerate(dists),key=lambda x: x[1])[0]
            vector = np.array([vcell[maxDistIndex]])
            # normalize vector
            den=(vector**2).sum(axis=-1) **0.5
            basis += [vector/den]
            simplex += [cell[maxDistIndex]]
            unUsedIndices = [h for h in cell if h not in simplex]
        simplices += [simplex]
    return simplices

def simplexOrientations(V,simplices):
    vcells = [[V[v]+[1.0] for v in simplex] for simplex in simplices]
    return [SIGN(np.linalg.det(vcell)) for vcell in vcells]
◇
```

Macro defined by 13, 15.
Macro referenced in 20a.

⟨ Computation of cell adjacencies 16a ⟩ ≡

```
def larCellAdjacencies(CSRm):  
    CSRm = matrixProduct(CSRm,csrTranspose(CSRm))  
    return CSRm  
◇
```

Macro referenced in 20a.

⟨ Test examples of Computation of cell adjacencies 16b ⟩ ≡

```
print "\n>>> larCellAdjacencies"  
adj_2_cells = larCellAdjacencies(csrFV)  
print "\nadj_2_cells =\n", csr2DenseMatrix(adj_2_cells)  
adj_1_cells = larCellAdjacencies(csrEV)  
print "\nadj_1_cells =\n", csr2DenseMatrix(adj_1_cells)  
◇
```

Macro referenced in 20b.

⟨Extraction of facets of a cell complex 17⟩ ≡

```
def setup(model,dim):
    V, cells = model
    csr = csrCreate(cells)
    csrAdjSquareMat = larCellAdjacencies(csr)
    csrAdjSquareMat = csrPredFilter(csrAdjSquareMat, GE(dim)) # ? HOWTODO ?
    return V,cells,csr,csrAdjSquareMat

def larFacets(model,dim=3,emptyCellNumber=0):
    """
        Estraction of (d-1)-cellFacets from "model" := (V,d-cells)
        Return (V, (d-1)-cellFacets)
    """
    V,cells,csr,csrAdjSquareMat = setup(model,dim)
    solidCellNumber = len(cells) - emptyCellNumber
    cellFacets = []
    # for each input cell i
    for i in range(len(cells)):
        adjCells = csrAdjSquareMat[i].tocoo()
        cell1 = csr[i].tocoo().col
        pairs = zip(adjCells.col,adjCells.data)
        for j,v in pairs:
            if (i<j) and (i<solidCellNumber):
                cell2 = csr[j].tocoo().col
                cell = list(set(cell1).intersection(cell2))
                cellFacets.append(sorted(cell))
    # sort and remove duplicates
    cellFacets = sorted(AA(list)(set(AA(tuple)(cellFacets))))
    return V,cellFacets
```

◇

Macro referenced in [20a](#).

```

⟨ Test examples of Extraction of facets of a cell complex 18 ⟩ ≡
V = [[0.,0.],[3.,0.],[0.,3.],[3.,3.],[1.,2.],[2.,2.],[1.,1.],[2.,1.]]
FV = [[0,1,6,7],[0,2,4,6],[4,5,6,7],[1,3,5,7],[2,3,4,5],[0,1,2,3]]

_,EV = larFacets((V,FV),dim=2)
print "\nEV =",EV
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs((V,EV))))

FV = [[0,1,3],[1,2,4],[2,4,5],[3,4,6],[4,6,7],[5,7,8], # full
      [1,3,4],[4,5,7], # empty
      [0,1,2],[6,7,8],[0,3,6],[2,5,8]] # exterior

_,EV = larFacets((V,FV),dim=2)
print "\nEV =",EV
◇

```

Macro referenced in [20b](#).

4 Exporting the library

4.1 MIT licence

⟨ The MIT Licence 19a ⟩ ≡

```
"""
The MIT License
=====

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
"""
◇
```

Macro referenced in 20a.

4.2 Importing of modules or packages

⟨ Importing of modules or packages 19b ⟩ ≡

```
from pyplasm import *
import collections
import scipy
import numpy as np
from scipy import zeros, arange, mat, amin, amax, array
from scipy.sparse import vstack, hstack, csr_matrix, coo_matrix, lil_matrix, triu

from lar2psm import *
◇
```

Macro referenced in 20a.

4.3 Writing the library file

```
"lib/py/larcc.py" 20a ≡
# -*- coding: utf-8 -*-
""" Basic LARCC library """
⟨ The MIT Licence 19a ⟩
⟨ Importing of modules or packages 19b ⟩
⟨ From list of triples to scipy.sparse 3a ⟩
⟨ Brc to Coor transformation 3b ⟩
⟨ Coor to Csr transformation 4a ⟩
⟨ Brc to Csr transformation 4c ⟩
⟨ Query Matrix shape 5b ⟩
⟨ Sparse to dense matrix transformation 6b ⟩
⟨ Matrix product and transposition 7 ⟩
⟨ Matrix filtering to produce the boundary matrix 8 ⟩
⟨ Matrix filtering via a generic predicate 9b ⟩
⟨ From cells and facets to boundary operator 10a ⟩
⟨ From cells and facets to boundary cells 11a ⟩
⟨ Signed boundary matrix for simplicial models 12 ⟩
⟨ Oriented boundary cells for simplicial models 13, ... ⟩
⟨ Computation of cell adjacencies 16a ⟩
⟨ Extraction of facets of a cell complex 17 ⟩

if __name__ == "__main__":
    ⟨ Test examples 20b ⟩
◇
```

5 Unit tests

```
⟨ Test examples 20b ⟩ ≡

⟨ Test example of Brc to Coor transformation 3c ⟩
⟨ Test example of Coor to Csr transformation 4b ⟩
⟨ Test example of Brc to Csr transformation 5a ⟩
⟨ Test examples of Query Matrix shape 6a ⟩
⟨ Test examples of Sparse to dense matrix transformation 6c ⟩
⟨ Test example of Matrix filtering to produce the boundary matrix 9a ⟩
⟨ Test example of Matrix filtering via a generic predicate 9c ⟩
⟨ Test examples of From cells and facets to boundary operator 10b ⟩
⟨ Test examples of From cells and facets to boundary cells 11b ⟩
⟨ Test examples of Computation of cell adjacencies 16b ⟩
⟨ Test examples of Extraction of facets of a cell complex 18 ⟩
◇
```

Macro referenced in 20a.

Comparing oriented and unoriented boundary

"test/py/larcc/test09.py" 20c ≡

```
""" comparing oriented boundary and unoriented boundary extraction on a simple example """
import sys
sys.path.insert(0, 'lib/py/')
from largrid import *
from larcc import *

V,CV = larSimplexGrid1([1,1,1])
FV = larSimplexFacets(CV)

orientedBoundary = signedBoundaryCells(V,CV,FV)
def swap(mylist): return [mylist[1]]+[mylist[0]]+mylist[2:]
orientedBoundaryFV = [FV[-k] if k<0 else swap(FV[k]) for k in orientedBoundary]
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs((V,orientedBoundaryFV))))

BF = boundaryCells(CV,FV)
boundaryCellsFV = [FV[k] for k in BF]
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs((V,boundaryCellsFV))))
◇
```

A Appendix: Tutorials

A.1 Model generation, skeleton and boundary extraction

"test/py/larcc/test01.py" 21 ≡

```
import sys
sys.path.insert(0, 'lib/py/')
from larcc import *
from largrid import *
⟨input of 2D topology and geometry data 22a⟩
⟨characteristic matrices 22b⟩
⟨incidence matrix 22c⟩
⟨boundary and coboundary operators 22d⟩
⟨product of cell complexes 23a⟩
⟨2-skeleton extraction 23b⟩
⟨1-skeleton extraction 23c⟩
⟨0-coboundary computation 24a⟩
⟨1-coboundary computation 24b⟩
⟨2-coboundary computation 24c⟩
⟨boundary chain visualisation 24d⟩
◇
```

⟨input of 2D topology and geometry data 22a⟩ ≡

```
# input of geometry and topology
V2 = [[4,10],[8,10],[14,10],[8,7],[14,7],[4,4],[8,4],[14,4]]
EV = [[0,1],[1,2],[3,4],[5,6],[6,7],[0,5],[1,3],[2,4],[3,6],[4,7]]
FV = [[0,1,3,5,6],[1,2,3,4],[3,4,6,7]]
◇
```

Macro referenced in 21.

⟨characteristic matrices 22b⟩ ≡

```
# characteristic matrices
csrFV = csrCreate(FV)
csrEV = csrCreate(EV)
print "\nFV =\n", csr2DenseMatrix(csrFV)
print "\nEV =\n", csr2DenseMatrix(csrEV)
◇
```

Macro referenced in 21.

⟨incidence matrix 22c⟩ ≡

```
# product
csrEF = matrixProduct(csrEV, csrTranspose(csrFV))
print "\nEF =\n", csr2DenseMatrix(csrEF)
◇
```

Macro referenced in 21.

⟨boundary and coboundary operators 22d⟩ ≡

```
# boundary and coboundary operators
facetLengths = [csrCell.getnnz() for csrCell in csrEV]
boundary = csrBoundaryFilter(csrEF,facetLengths)
coboundary_1 = csrTranspose(boundary)
print "\ncoboundary_1 =\n", csr2DenseMatrix(coboundary_1)
◇
```

Macro referenced in 21.

$\langle \text{product of cell complexes 23a} \rangle \equiv$

```
# product operator
mod_2D = (V2,FV)
V1,topol_0 = [[0.],[1.],[2.]], [[0],[1],[2]]
topol_1 = [[0,1],[1,2]]
mod_0D = (V1,topol_0)
mod_1D = (V1,topol_1)
V3,CV = larModelProduct([mod_2D,mod_1D])
mod_3D = (V3,CV)
VIEW(EXPLODE(1.2,1.2,1.2)(MKPOLs(mod_3D)))
print "\nk_3 =", len(CV), "\n"
◇
```

Macro referenced in 21.

$\langle \text{2-skeleton extraction 23b} \rangle \equiv$

```
# 2-skeleton of the 3D product complex
mod_2D_1 = (V2,EV)
mod_3D_h2 = larModelProduct([mod_2D,mod_0D])
mod_3D_v2 = larModelProduct([mod_2D_1,mod_1D])
_,FV_h = mod_3D_h2
_,FV_v = mod_3D_v2
FV3 = FV_h + FV_v
SK2 = (V3,FV3)
VIEW(EXPLODE(1.2,1.2,1.2)(MKPOLs(SK2)))
print "\nk_2 =", len(FV3), "\n"
◇
```

Macro referenced in 21.

$\langle \text{1-skeleton extraction 23c} \rangle \equiv$

```
# 1-skeleton of the 3D product complex
mod_2D_0 = (V2,AA(LIST)(range(len(V2))))
mod_3D_h1 = larModelProduct([mod_2D_1,mod_0D])
mod_3D_v1 = larModelProduct([mod_2D_0,mod_1D])
_,EV_h = mod_3D_h1
_,EV_v = mod_3D_v1
EV3 = EV_h + EV_v
SK1 = (V3,EV3)
VIEW(EXPLODE(1.2,1.2,1.2)(MKPOLs(SK1)))
print "\nk_1 =", len(EV3), "\n"
◇
```

Macro referenced in 21.

⟨ 0-coboundary computation 24a ⟩ ≡

```
# boundary and coboundary operators
np.set_printoptions(threshold=sys.maxint)
csrFV3 = csrCreate(FV3)
csrEV3 = csrCreate(EV3)
csrVE3 = csrTranspose(csrEV3)
facetLengths = [csrCell.getnnz() for csrCell in csrEV3]
boundary = csrBoundaryFilter(csrVE3,facetLengths)
coboundary_0 = csrTranspose(boundary)
print "\ncoboundary_0 =\n", csr2DenseMatrix(coboundary_0)
◇
```

Macro referenced in 21.

⟨ 1-coboundary computation 24b ⟩ ≡

```
csrEF3 = matrixProduct(csrEV3, csrTranspose(csrFV3))
facetLengths = [csrCell.getnnz() for csrCell in csrFV3]
boundary = csrBoundaryFilter(csrEF3,facetLengths)
coboundary_1 = csrTranspose(boundary)
print "\ncoboundary_1.T =\n", csr2DenseMatrix(coboundary_1.T)
◇
```

Macro referenced in 21.

⟨ 2-coboundary computation 24c ⟩ ≡

```
csrCV = csrCreate(CV)
csrFC3 = matrixProduct(csrFV3, csrTranspose(csrCV))
facetLengths = [csrCell.getnnz() for csrCell in csrCV]
boundary = csrBoundaryFilter(csrFC3,facetLengths)
coboundary_2 = csrTranspose(boundary)
print "\ncoboundary_2 =\n", csr2DenseMatrix(coboundary_2)
◇
```

Macro referenced in 21.

⟨ boundary chain visualisation 24d ⟩ ≡

```
# boundary chain visualisation
boundaryCells_2 = boundaryCells(CV,FV3)
boundary = (V3,[FV3[k] for k in boundaryCells_2])
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs(boundary)))
◇
```

Macro referenced in 21.

A.2 Boundary of 3D simplicial grid

"test/py/larcc/test02.py" 25a \equiv

```
import sys
sys.path.insert(0, 'lib/py/')
⟨boundary of 3D simplicial grid 25b⟩
◇
```

⟨boundary of 3D simplicial grid 25b⟩ \equiv

```
from simplexn import *
from larcc import *

V,CV = larSimplexGrid1([10,10,3])
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs((V,CV))))
SK2 = (V,larSimplexFacets(CV))
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs(SK2)))
_,FV = SK2
SK1 = (V,larSimplexFacets(FV))
_,EV = SK1
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs(SK1)))

boundaryCells_2 = boundaryCells(CV,FV)
boundary = (V,[FV[k] for k in boundaryCells_2])
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs(boundary)))
print "\nboundaryCells_2 =\n", boundaryCells_2

boundaryCells_2 = signedBoundaryCells(V,CV,FV)
def swap(mylist): return [mylist[1]]+[mylist[0]]+mylist[2:]
boundaryFV = [FV[-k] if k<0 else swap(FV[k]) for k in boundaryCells_2]

VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs((V,boundaryFV))))
print "\nboundaryCells_2 =\n", boundaryFV
◇
```

Macro referenced in 25a.

A.3 Oriented boundary of a random simplicial complex

"test/py/larcc/test03.py" 25c \equiv

```
⟨Importing external modules 26a⟩
⟨Generating and viewing a random 3D simplicial complex 26b⟩
⟨Computing and viewing its non-oriented boundary 26c⟩
⟨Computing and viewing its oriented boundary 26d⟩
◇
```

⟨ Importing external modules 26a ⟩ ≡

```
import sys
sys.path.insert(0, 'lib/py/')
from simplexn import *
from larcc import *
from scipy import *
from scipy.spatial import Delaunay
import numpy as np
◇
```

Macro referenced in 25c.

⟨ Generating and viewing a random 3D simplicial complex 26b ⟩ ≡

```
verts = np.random.rand(10000, 3) # 1000 points in 3-d
verts = [AA(lambda x: 2*x)(VECTDIFF([vert,[0.5,0.5,0.5]])) for vert in verts]
verts = [vert for vert in verts if VECTNORM(vert) < 1.0]
tetra = Delaunay(verts)
cells = [cell for cell in tetra.vertices.tolist()
         if ((verts[cell[0]][2]<0) and (verts[cell[1]][2]<0)
             and (verts[cell[2]][2]<0) and (verts[cell[3]][2]<0) ) ]
V, CV = verts, cells
VIEW(MKPOL([V,AA(AA(lambda k:k+1))(CV),[]]))
◇
```

Macro referenced in 25c.

⟨ Computing and viewing its non-oriented boundary 26c ⟩ ≡

```
FV = larSimplexFacets(CV)
VIEW(MKPOL([V,AA(AA(lambda k:k+1))(FV),[]]))
boundaryCells_2 = boundaryCells(CV,FV)
print "\nboundaryCells_2 =\n", boundaryCells_2
bndry = (V,[FV[k] for k in boundaryCells_2])
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOL(bndry)))
◇
```

Macro referenced in 25c.

⟨ Computing and viewing its oriented boundary 26d ⟩ ≡

```
boundaryCells_2 = signedBoundaryCells(V,CV,FV)
print "\nboundaryCells_2 =\n", boundaryCells_2
def swap(mylist): return [mylist[1]]+[mylist[0]]+mylist[2:]
boundaryFV = [FV[-k] if k<0 else swap(FV[k]) for k in boundaryCells_2]
boundaryModel = (V,boundaryFV)
VIEW(EXPLODE(1.5,1.5,1.5)(MKPOL(boundaryModel)))
◇
```

Macro referenced in 25c.

A.4 Oriented boundary of a simplicial grid

```
"test/py/larcc/test04.py" 27a ≡  
    ⟨Generate and view a 3D simplicial grid 27b⟩  
    ⟨Computing and viewing the 2-skeleton of simplicial grid 27c⟩  
    ⟨Computing and viewing the oriented boundary of simplicial grid 27d⟩  
    ◇
```

```
⟨Generate and view a 3D simplicial grid 27b⟩ ≡  
    import sys  
    sys.path.insert(0, 'lib/py/')  
    from simplexn import *  
    from larcc import *  
    V,CV = larSimplexGrid1([4,4,4])  
    VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLLS((V,CV))))  
    ◇
```

Macro referenced in 27a.

```
⟨Computing and viewing the 2-skeleton of simplicial grid 27c⟩ ≡  
    FV = larSimplexFacets(CV)  
    EV = larSimplexFacets(FV)  
    VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLLS((V,FV))))  
    ◇
```

Macro referenced in 27a.

```
⟨Computing and viewing the oriented boundary of simplicial grid 27d⟩ ≡  
    csrSignedBoundaryMat = signedBoundary (CV,FV)  
    boundaryCells_2 = signedBoundaryCells(V,CV,FV)  
    def swap(l): return [l[1],l[0],l[2]]  
    boundaryFV = [FV[-k] if k<0 else swap(FV[k]) for k in boundaryCells_2]  
    boundary = (V,boundaryFV)  
    VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLLS(boundary)))  
    ◇
```

Macro referenced in 27a.

A.5 Skeletons and oriented boundary of a simplicial complex

```
"test/py/larcc/test05.py" 27e ≡  
    import sys  
    sys.path.insert(0, 'lib/py/')  
  
    ⟨Skeletons computation and visualization 28a⟩  
    ⟨Oriented boundary matrix visualization 28b⟩  
    ⟨Computation of oriented boundary cells 28c⟩  
    ◇
```

```

⟨ Skeletons computation and visualisation 28a ⟩ ≡
    from simplexn import *
    from larcc import *
    V,FV = larSimplexGrid1([3,3])
    VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs((V,FV))))
    EV = larSimplexFacets(FV)
    VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs((V,EV))))
    VV = larSimplexFacets(EV)
    VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs((V,VV))))
    ◇

```

Macro referenced in 27e.

```

⟨ Oriented boundary matrix visualization 28b ⟩ ≡
    np.set_printoptions(threshold='nan')
    csrSignedBoundaryMat = signedBoundary (FV,EV)
    Z = csr2DenseMatrix(csrSignedBoundaryMat)
    print "\ncsrSignedBoundaryMat =\n", Z
    from pylab import *
    matshow(Z)
    show()
    ◇

```

Macro referenced in 27e.

```

⟨ Computation of oriented boundary cells 28c ⟩ ≡
    boundaryCells_1 = signedBoundaryCells(V,FV,EV)
    print "\nboundaryCells_1 =\n", boundaryCells_1
    def swap(mylist): return [mylist[1]]+[mylist[0]]+mylist[2:]
    boundaryEV = [EV[-k] if k<0 else swap(EV[k]) for k in boundaryCells_1]
    bndry = (V,boundaryEV)
    VIEW(EXPLODE(1.5,1.5,1.5)(MKPOLs(bndry)))
    ◇

```

Macro referenced in 27e.

A.6 Boundary of random 2D simplicial complex

```

"test/py/larcc/test06.py" 28d ≡
    import sys
    sys.path.insert(0, 'lib/py/')
    from simplexn import *
    from larcc import *
    from scipy.spatial import Delaunay
    ⟨ Test for quasi-equilateral triangles 29a ⟩
    ⟨ Generation and selection of random triangles 29b ⟩
    ⟨ Boundary computation and visualisation 30a ⟩
    ◇

```




Figure 3: example caption

```

⟨ Test for quasi-equilateral triangles 29a ⟩ ≡
def quasiEquilateral(tria):
    a = VECTNORM(VECTDIFF(tria[0:2]))
    b = VECTNORM(VECTDIFF(tria[1:3]))
    c = VECTNORM(VECTDIFF([tria[0],tria[2]]))
    m = max(a,b,c)
    if m/a < 1.7 and m/b < 1.7 and m/c < 1.7: return True
    else: return False
◇

```

Macro referenced in 28d.

```

⟨ Generation and selection of random triangles 29b ⟩ ≡
verts = np.random.rand(20,2)
verts = (verts - [0.5,0.5]) * 2
triangles = Delaunay(verts)
cells = [ cell for cell in triangles.vertices.tolist()
          if (not quasiEquilateral([verts[k] for k in cell])) ]
V, FV = AA(list)(verts), cells
EV = larSimplexFacets(FV)
pols2D = MKPOLS((V,FV))
VIEW(EXPLODE(1.5,1.5,1.5)(pols2D))
◇

```

Macro referenced in 28d.

⟨ Boundary computation and visualisation 30a ⟩ ≡

```
boundaryCells_1 = signedBoundaryCells(V,FV,EV)
print "\nboundaryCells_1 =\n", boundaryCells_1
def swap(mylist): return [mylist[1]]+[mylist[0]]+mylist[2:]
boundaryEV = [EV[-k] if k<0 else swap(EV[k]) for k in boundaryCells_1]
bndry = (V,boundaryEV)
VIEW(STRUCT(MKPOLS(bndry) + pols2D))
VIEW(COLOR(RED)(STRUCT(MKPOLS(bndry))))
◇
```

Macro referenced in 28d.

⟨ Compute the topologically ordered chain of boundary vertices 30b ⟩ ≡

◇

Macro never referenced.

⟨ Decompose a permutation into cycles 30c ⟩ ≡

```
def permutationOrbits(List):
    d = dict((i,int(x)) for i,x in enumerate(List))
    out = []
    while d:
        x = list(d)[0]
        orbit = []
        while x in d:
            orbit += [x],
            x = d.pop(x)
        out += [CAT(orbit)+orbit[0]]
    return out

if __name__ == "__main__":
    print [2, 3, 4, 5, 6, 7, 0, 1]
    print permutationOrbits([2, 3, 4, 5, 6, 7, 0, 1])
    print [3,9,8,4,10,7,2,11,6,0,1,5]
    print permutationOrbits([3,9,8,4,10,7,2,11,6,0,1,5])
◇
```

Macro never referenced.

A.7 Assemblies of simplices and hypercubes

```
"test/py/larcc/test07.py" 31a ≡
import sys
sys.path.insert(0, 'lib/py/')
from simplexn import *
from larcc import *
from largrid import *
⟨Definition of 1-dimensional LAR models 31b⟩
⟨Assembly generation of squares and triangles 31c⟩
⟨Assembly generation of cubes and tetrahedra 32⟩
◇
```




Figure 4: (a) Assemblies of squares and triangles; (b) assembly of cubes and tetrahedra.

```
⟨Definition of 1-dimensional LAR models 31b⟩ ≡
geom_0,topol_0 = [[0.],[1.],[2.],[3.],[4.],[[0,1],[1,2],[3,4]]
geom_1,topol_1 = [[0.],[1.],[2.],[[0,1],[1,2]]
mod_0 = (geom_0,topol_0)
mod_1 = (geom_1,topol_1)
◇
```

Macro referenced in 31a.

```
⟨Assembly generation of squares and triangles 31c⟩ ≡
squares = larModelProduct([mod_0,mod_1])
V,FV = squares
simplices = pivotSimplices(V,FV,d=2)
VIEW(STRUCT([ MKPOL([V,AA(AA(C(SUM)(1)))(simplices),[]]),
                SKEL_1(STRUCT(MKPOLS((V,FV)))) ]))
◇
```

Macro referenced in 31a.

```

⟨ Assembly generation of cubes and tetrahedra 32 ⟩ ≡
  cubes = larModelProduct([squares,mod_0])
  V,CV = cubes
  simplices = pivotSimplices(V,CV,d=3)
  VIEW(STRUCT([ MKPOL([V,AA(AA(C(SUM)(1)))(simplices),[]]),
                SKEL_1(STRUCT(MKPOLS((V,CV)))) ]))
  ◇

```

Macro referenced in [31a](#).

References

- [CL13] CVD-Lab, *Linear algebraic representation*, Tech. Report 13-00, Roma Tre University, October 2013.