

Q vs DDPG - Stat Tests

Aheer Sravon

June 12, 2026

1 Imports

```
[1]: import numpy as np
import pandas as pd
from scipy.stats import permutation_test
import itertools
```

2 Data Loading

```
[2]: models = [
    "logit", # row 0
    "hotelling", # row 1
    "linear" # row 2
]

firm1 = "q"
firm2 = "ddpg"

shock_none_data = {
    model: {
        "avg_prices": {
            firm1: [],
            firm2: []
        },
        "deltas": {
            firm1: [],
            firm2: []
        },
        "rpdis": {
            firm1: [],
            firm2: []
        }
    } for model in models
}

shock_a_data = {
```

```

model: {
  "avg_prices": {
    firm1: [],
    firm2: []
  },
  "deltas": {
    firm1: [],
    firm2: []
  },
  "rpdis": {
    firm1: [],
    firm2: []
  }
} for model in models
}

shock_b_data = {
  model: {
    "avg_prices": {
      firm1: [],
      firm2: []
    },
    "deltas": {
      firm1: [],
      firm2: []
    },
    "rpdis": {
      firm1: [],
      firm2: []
    }
  }
  for model in models
}

shock_c_data = {
  model: {
    "avg_prices": {
      firm1: [],
      firm2: []
    },
    "deltas": {
      firm1: [],
      firm2: []
    },
    "rpdis": {
      firm1: [],
      firm2: []
    }
  }
}

```

```

    } for model in models
}

for i in range(1,8):
    shock_none_df = pd.read_csv(f"../results/run_{i}/shock_none/
    ↪{firm1}_vs_{firm2}.csv")
    shock_a_df = pd.read_csv(f"../results/run_{i}/shock_a/{firm1}_vs_{firm2}.
    ↪csv")
    shock_b_df = pd.read_csv(f"../results/run_{i}/shock_b/{firm1}_vs_{firm2}.
    ↪csv")
    shock_c_df = pd.read_csv(f"../results/run_{i}/shock_c/{firm1}_vs_{firm2}.
    ↪csv")

    # Map each dataframe to its corresponding data storage dictionary
    shock_mappings = [
        (shock_none_df, shock_none_data),
        (shock_a_df, shock_a_data),
        (shock_b_df, shock_b_data),
        (shock_c_df, shock_c_data)
    ]

    for df, data_dict in shock_mappings:
        for idx, model in enumerate(models):
            # Access the row matching the current model by its index (0, 1, or
            ↪2)

            row = df.iloc[idx]

            # Dynamically look up columns based on firm name capitalization (e.
            ↪g., "Q" and "PSQ")
            f1_upper = firm1.upper()
            f2_upper = firm2.upper()

            # Append Average Prices
            data_dict[model]["avg_prices"][firm1].append(row[f"{f1_upper} Avg.
            ↪Prices"])
            data_dict[model]["avg_prices"][firm2].append(row[f"{f2_upper} Avg.
            ↪Prices"])

            # Append Extra-profits  $\Delta$  (deltas)
            data_dict[model]["deltas"][firm1].append(row[f"{f1_upper}
            ↪Extra-profits  $\Delta$ "])
            data_dict[model]["deltas"][firm2].append(row[f"{f2_upper}
            ↪Extra-profits  $\Delta$ "])

            # Append RPDI
            data_dict[model]["rpdis"][firm1].append(row[f"{f1_upper} RPDI"])

```

```
data_dict[model]["rpdis"][firm2].append(row[f"{f2_upper} RPDI"])
```

```
[3]: def paired_mean_diff(x, y, axis=0):
      return np.mean(x - y, axis=axis)
```

3 Logit

3.1 Shock None

3.1.1 Average Prices

```
[4]: array1 = np.array(shock_none_data['logit']['avg_prices'][firm1])
      array2 = np.array(shock_none_data['logit']['avg_prices'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)
```

```

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0900
Exact P-value:           0.01562
95% Test-Inverted CI:     [-0.1250, -0.0550]
=====

```

3.1.2 Deltas

```

[5]: array1 = np.array(shock_none_data['logit']['deltas'][firm1])
     array2 = np.array(shock_none_data['logit']['deltas'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

```

```

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If  $p > 0.05$ , this shift magnitude is statistically plausible (inside the CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.6357
Exact P-value:           0.01562
95% Test-Inverted CI:     [0.4700, 0.5000]
=====

```

3.1.3 RPDIs

```
[6]: array1 = np.array(shock_none_data['logit']['rpdis'][firm1])
array2 = np.array(shock_none_data['logit']['rpdis'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
    ↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the_
    ↪CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
```

```
# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")
```

```
=====
EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.1957
Exact P-value:           0.01562
95% Test-Inverted CI:    [-0.2700, -0.1250]
=====
```

3.2 Shock A

3.2.1 Average Prices

```
[7]: array1 = np.array(shock_a_data['logit']['avg_prices'][firm1])
array2 = np.array(shock_a_data['logit']['avg_prices'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
```



```

        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    ↪CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0671
Exact P-value:           0.01562
95% Test-Inverted CI:     [-0.0850, -0.0400]
=====

```

3.2.2 Deltas

```

[8]: array1 = np.array(shock_a_data['logit']['deltas'][firm1])
     array2 = np.array(shock_a_data['logit']['deltas'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

```

```

)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-1.8, 1.8, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the CI)
    ↪CI
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
EXACT PAIRED PERMUTATION TEST REPORT
=====

```

Observed Mean Difference: 1.5686
Exact P-value: 0.01562
95% Test-Inverted CI: [1.2902, 1.7798]
=====

3.2.3 RPDIs

```
[9]: array1 = np.array(shock_a_data['logit']['rpdis'][firm1])
array2 = np.array(shock_a_data['logit']['rpdis'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    ↪CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
```

```

        ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
    else:
        ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.2414
Exact P-value:           0.01562
95% Test-Inverted CI:    [-0.3050, -0.1600]
=====

```

3.3 Shock B

3.3.1 Average Prices

```

[10]: array1 = np.array(shock_b_data['logit']['avg_prices'][firm1])
      array2 = np.array(shock_b_data['logit']['avg_prices'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

```

```

perm_res = permutation_test(
    data=(shifted_array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',
    alternative='two-sided',
    n_resamples=np.inf
)

# If p > 0.05, this shift magnitude is statistically plausible (inside the
↪ CI)
if perm_res.pvalue > 0.05:
    ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.1057
Exact P-value:           0.01562
95% Test-Inverted CI:     [-0.1350, -0.0800]
=====

```

3.3.2 Deltas

```

[11]: array1 = np.array(shock_b_data['logit']['deltas'][firm1])
      array2 = np.array(shock_b_data['logit']['deltas'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,

```

```

    permutation_type='samples',      # 'samples' handles paired data structural
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
    ↪05
shifts = np.linspace(-1, 1, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If  $p > 0.05$ , this shift magnitude is statistically plausible (inside the
    ↪CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```
=====
EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.8914
Exact P-value:          0.01562
95% Test-Inverted CI:   [0.7300, 1.0000]
=====
```

3.3.3 RPDIs

```
[12]: array1 = np.array(shock_b_data['logit']['rpdis'][firm1])
      array2 = np.array(shock_b_data['logit']['rpdis'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
```

```

if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.2643
Exact P-value:           0.01562
95% Test-Inverted CI:     [-0.3400, -0.1950]
=====

```

3.4 Shock C

3.4.1 Average Prices

```

[13]: array1 = np.array(shock_c_data['logit']['avg_prices'][firm1])
      array2 = np.array(shock_c_data['logit']['avg_prices'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

```



```

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If  $p > 0.05$ , this shift magnitude is statistically plausible (inside the CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:    {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0443
Exact P-value:           0.01562
95% Test-Inverted CI:    [-0.0650, -0.0250]
=====

```

3.4.2 Deltas

```
[14]: array1 = np.array(shock_c_data['logit']['deltas'][firm1])
      array2 = np.array(shock_c_data['logit']['deltas'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-1.6, 1.6, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
      if len(ci_values) > 0:
          lower_bound = np.min(ci_values)
          upper_bound = np.max(ci_values)
          ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
      else:
          ci_str = "Outside defined search grid"
```

```
# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")
```

```
=====
EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 1.5557
Exact P-value:           0.01562
95% Test-Inverted CI:     [1.1853, 1.6000]
=====
```

3.4.3 RPDIs

```
[15]: array1 = np.array(shock_c_data['logit']['rpdis'][firm1])
      array2 = np.array(shock_c_data['logit']['rpdis'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
```

```

        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    ↪ CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.1586
Exact P-value:           0.01562
95% Test-Inverted CI:     [-0.2400, -0.0750]
=====

```

4 Hotelling

4.1 Shock None

4.1.1 Average Prices

```

[16]: array1 = np.array(shock_none_data['hotelling']['avg_prices'][firm1])
      array2 = np.array(shock_none_data['hotelling']['avg_prices'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪ dependencies

```

```

        alternative='two-sided',
        n_resamples=np.inf
    )

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the CI)
    ↪CI
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```
=====
EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0157
Exact P-value:          0.12500
95% Test-Inverted CI:   [-0.0350, 0.0100]
=====
```

4.1.2 Deltas

```
[17]: array1 = np.array(shock_none_data['hotelling']['deltas'][firm1])
      array2 = np.array(shock_none_data['hotelling']['deltas'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
```

```

if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.1286
Exact P-value:           0.01562
95% Test-Inverted CI:    [0.0300, 0.2200]
=====

```

4.1.3 RPDIs

```

[18]: array1 = np.array(shock_none_data['hotelling']['rpdis'][firm1])
      array2 = np.array(shock_none_data['hotelling']['rpdis'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:

```

```

# Shift sample x by a hypothetical effect size delta
shifted_array1 = array1 - shift

perm_res = permutation_test(
    data=(shifted_array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',
    alternative='two-sided',
    n_resamples=np.inf
)

# If p > 0.05, this shift magnitude is statistically plausible (inside the CI)
if perm_res.pvalue > 0.05:
    ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0729
Exact P-value:           0.10938
95% Test-Inverted CI:     [-0.1500, 0.0100]
=====

```


4.2 Shock A

4.2.1 Average Prices

```
[19]: array1 = np.array(shock_a_data['hotelling']['avg_prices'][firm1])
      array2 = np.array(shock_a_data['hotelling']['avg_prices'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If  $p > 0.05$ , this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
      if len(ci_values) > 0:
          lower_bound = np.min(ci_values)
          upper_bound = np.max(ci_values)
          ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
      else:
          ci_str = "Outside defined search grid"
```

```
# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")
```

```
=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0086
Exact P-value:           0.28125
95% Test-Inverted CI:     [-0.0200, 0.0050]
=====
```

4.2.2 Deltas

```
[20]: array1 = np.array(shock_a_data['hotelling']['deltas'][firm1])
      array2 = np.array(shock_a_data['hotelling']['deltas'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
```

```

        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    ↪CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.0543
Exact P-value:           0.07812
95% Test-Inverted CI:     [-0.0100, 0.1000]
=====

```

4.2.3 RPDIs

```

[21]: array1 = np.array(shock_a_data['hotelling']['rpdis'][firm1])
      array2 = np.array(shock_a_data['hotelling']['rpdis'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

```

```

)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    ↪CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
EXACT PAIRED PERMUTATION TEST REPORT
=====

```

```

Observed Mean Difference: -0.0271
Exact P-value:           0.32812
95% Test-Inverted CI:    [-0.0800, 0.0300]
=====

```

4.3 Shock B

4.3.1 Average Prices

```

[22]: array1 = np.array(shock_b_data['hotelling']['avg_prices'][firm1])
      array2 = np.array(shock_b_data['hotelling']['avg_prices'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
      if len(ci_values) > 0:
          lower_bound = np.min(ci_values)

```

```

upper_bound = np.max(ci_values)
ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:      {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0071
Exact P-value:           0.62500
95% Test-Inverted CI:      [-0.0400, 0.0200]
=====

```

4.3.2 Deltas

```

[23]: array1 = np.array(shock_b_data['hotelling']['deltas'][firm1])
      array2 = np.array(shock_b_data['hotelling']['deltas'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta

```

```

shifted_array1 = array1 - shift

perm_res = permutation_test(
    data=(shifted_array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',
    alternative='two-sided',
    n_resamples=np.inf
)

# If p > 0.05, this shift magnitude is statistically plausible (inside the
CI)
if perm_res.pvalue > 0.05:
    ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.0629
Exact P-value:           0.34375
95% Test-Inverted CI:     [-0.1000, 0.2000]
=====

```

4.3.3 RPDIs

```

[24]: array1 = np.array(shock_b_data['hotelling']['rpdis'][firm1])
      array2 = np.array(shock_b_data['hotelling']['rpdis'][firm2])

main_test = permutation_test(
    data=(array1, array2),

```

```

    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
    ↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    ↪CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")

```



```
print("=====")
```

```
=====
EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0286
Exact P-value:           0.50000
95% Test-Inverted CI:    [-0.1400, 0.0550]
=====
```

4.4 Shock C

4.4.1 Average Prices

```
[25]: array1 = np.array(shock_c_data['hotelling']['avg_prices'][firm1])
      array2 = np.array(shock_c_data['hotelling']['avg_prices'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
```

```

        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:                {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:         {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0071
Exact P-value:            0.62500
95% Test-Inverted CI:     [-0.0300, 0.0100]
=====

```

4.4.2 Deltas

```

[26]: array1 = np.array(shock_c_data['hotelling']['deltas'][firm1])
      array2 = np.array(shock_c_data['hotelling']['deltas'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)

```

```

ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.1171
Exact P-value:           0.04688
95% Test-Inverted CI:     [0.0100, 0.2350]
=====

```

4.4.3 RPDIs

```
[27]: array1 = np.array(shock_c_data['hotelling']['rpdis'][firm1])
      array2 = np.array(shock_c_data['hotelling']['rpdis'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If  $p > 0.05$ , this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
      if len(ci_values) > 0:
          lower_bound = np.min(ci_values)
          upper_bound = np.max(ci_values)
          ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
      else:
          ci_str = "Outside defined search grid"
```

```
# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")
```

```
=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0329
Exact P-value:           0.43750
95% Test-Inverted CI:     [-0.1150, 0.0350]
=====
```

5 Linear

5.1 Shock None

5.1.1 Average Prices

```
[28]: array1 = np.array(shock_none_data['linear']['avg_prices'][firm1])
      array2 = np.array(shock_none_data['linear']['avg_prices'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
```

```

        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    ↪ CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0029
Exact P-value:           0.62500
95% Test-Inverted CI:     [-0.0100, 0.0050]
=====

```

5.1.2 Deltas

```

[29]: array1 = np.array(shock_none_data['linear']['deltas'][firm1])
      array2 = np.array(shock_none_data['linear']['deltas'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
    ↪ dependencies

```

```

        alternative='two-sided',
        n_resamples=np.inf
    )

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the CI)
    ↪CI
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

=====

EXACT PAIRED PERMUTATION TEST REPORT

```
=====
Observed Mean Difference: 0.0186
Exact P-value:           0.15625
95% Test-Inverted CI:    [-0.0050, 0.0400]
=====
```

5.1.3 RPDIs

```
[30]: array1 = np.array(shock_none_data['linear']['rpdis'][firm1])
      array2 = np.array(shock_none_data['linear']['rpdis'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
      if len(ci_values) > 0:
          lower_bound = np.min(ci_values)
```



```

upper_bound = np.max(ci_values)
ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0114
Exact P-value:           0.76562
95% Test-Inverted CI:     [-0.1100, 0.0800]
=====

```

5.2 Shock A

5.2.1 Average Prices

```

[31]: array1 = np.array(shock_a_data['linear']['avg_prices'][firm1])
      array2 = np.array(shock_a_data['linear']['avg_prices'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↳dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↳05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta

```

```

shifted_array1 = array1 - shift

perm_res = permutation_test(
    data=(shifted_array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',
    alternative='two-sided',
    n_resamples=np.inf
)

# If  $p > 0.05$ , this shift magnitude is statistically plausible (inside the
CI)
if perm_res.pvalue > 0.05:
    ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0100
Exact P-value:           0.01562
95% Test-Inverted CI:     [-0.0100, -0.0100]
=====

```

5.2.2 Deltas

```

[32]: array1 = np.array(shock_a_data['linear']['deltas'][firm1])
      array2 = np.array(shock_a_data['linear']['deltas'][firm2])

      main_test = permutation_test(

```

```

    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
    ↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If  $p > 0.05$ , this shift magnitude is statistically plausible (inside the_
    ↪CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:                {main_test.pvalue:.5f}")

```

```
print(f"95% Test-Inverted CI:      {ci_str}")
print("=====")
```

```
=====
EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.0014
Exact P-value:           1.00000
95% Test-Inverted CI:    [-0.0400, 0.0500]
=====
```

5.2.3 RPDIs

```
[33]: array1 = np.array(shock_a_data['linear']['rpdis'][firm1])
      array2 = np.array(shock_a_data['linear']['rpdis'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)
```

```

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0829
Exact P-value:           0.01562
95% Test-Inverted CI:     [-0.1150, -0.0500]
=====

```

5.3 Shock B

5.3.1 Average Prices

```

[34]: array1 = np.array(shock_b_data['linear']['avg_prices'][firm1])
      array2 = np.array(shock_b_data['linear']['avg_prices'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)

```

```

ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0014
Exact P-value:           1.00000
95% Test-Inverted CI:     [-0.0100, 0.0050]
=====

```

5.3.2 Deltas

```
[35]: array1 = np.array(shock_b_data['linear']['deltas'][firm1])
      array2 = np.array(shock_b_data['linear']['deltas'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
      if len(ci_values) > 0:
          lower_bound = np.min(ci_values)
          upper_bound = np.max(ci_values)
          ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
      else:
          ci_str = "Outside defined search grid"
          print(f"{array1 = }, {array2 = }")
```

```
# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")
```

```
=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.0629
Exact P-value:           0.03125
95% Test-Inverted CI:    [0.0100, 0.1100]
=====
```

5.3.3 RPDIs

```
[36]: array1 = np.array(shock_b_data['linear']['rpdis'][firm1])
      array2 = np.array(shock_b_data['linear']['rpdis'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
```



```

)

# If p > 0.05, this shift magnitude is statistically plausible (inside the
↪CI)
if perm_res.pvalue > 0.05:
    ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.0114
Exact P-value:           0.75000
95% Test-Inverted CI:    [-0.1000, 0.0900]
=====

```

5.4 Shock C

5.4.1 Average Prices

```

[37]: array1 = np.array(shock_c_data['linear']['avg_prices'][firm1])
      array2 = np.array(shock_c_data['linear']['avg_prices'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural
↪dependencies
    alternative='two-sided',
    n_resamples=np.inf

```

```

)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(
        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the CI)
    ↪CI
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
EXACT PAIRED PERMUTATION TEST REPORT
=====

```

```

Observed Mean Difference: -0.0071
Exact P-value:           0.06250
95% Test-Inverted CI:    [-0.0100, 0.0000]
=====

```

5.4.2 Deltas

```

[38]: array1 = np.array(shock_c_data['linear']['deltas'][firm1])
      array2 = np.array(shock_c_data['linear']['deltas'][firm2])

      main_test = permutation_test(
          data=(array1, array2),
          statistic=paired_mean_diff,
          permutation_type='samples',      # 'samples' handles paired data structural_
          ↪dependencies
          alternative='two-sided',
          n_resamples=np.inf
      )

      # --- 4. Compute the Test-Inverted 95% Confidence Interval ---
      # We run a fine grid search to map exactly where the p-value transitions past 0.
      ↪05
      shifts = np.linspace(-0.5, 0.5, 10001)
      ci_values = []

      for shift in shifts:
          # Shift sample x by a hypothetical effect size delta
          shifted_array1 = array1 - shift

          perm_res = permutation_test(
              data=(shifted_array1, array2),
              statistic=paired_mean_diff,
              permutation_type='samples',
              alternative='two-sided',
              n_resamples=np.inf
          )

          # If p > 0.05, this shift magnitude is statistically plausible (inside the_
          ↪CI)
          if perm_res.pvalue > 0.05:
              ci_values.append(shift)

      # Extract boundaries from the valid grid values
      if len(ci_values) > 0:
          lower_bound = np.min(ci_values)
          upper_bound = np.max(ci_values)
          ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"

```

```

else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: 0.0786
Exact P-value:           0.59375
95% Test-Inverted CI:    [-0.1900, 0.4000]
=====

```

5.4.3 RPDIs

```

[39]: array1 = np.array(shock_c_data['linear']['rpdis'][firm1])
      array2 = np.array(shock_c_data['linear']['rpdis'][firm2])

main_test = permutation_test(
    data=(array1, array2),
    statistic=paired_mean_diff,
    permutation_type='samples',      # 'samples' handles paired data structural_
    ↪dependencies
    alternative='two-sided',
    n_resamples=np.inf
)

# --- 4. Compute the Test-Inverted 95% Confidence Interval ---
# We run a fine grid search to map exactly where the p-value transitions past 0.
↪05
shifts = np.linspace(-0.5, 0.5, 10001)
ci_values = []

for shift in shifts:
    # Shift sample x by a hypothetical effect size delta
    shifted_array1 = array1 - shift

    perm_res = permutation_test(

```

```

        data=(shifted_array1, array2),
        statistic=paired_mean_diff,
        permutation_type='samples',
        alternative='two-sided',
        n_resamples=np.inf
    )

    # If p > 0.05, this shift magnitude is statistically plausible (inside the
    CI)
    if perm_res.pvalue > 0.05:
        ci_values.append(shift)

# Extract boundaries from the valid grid values
if len(ci_values) > 0:
    lower_bound = np.min(ci_values)
    upper_bound = np.max(ci_values)
    ci_str = f"[{lower_bound:.4f}, {upper_bound:.4f}]"
else:
    ci_str = "Outside defined search grid"
    print(f"{array1 = }, {array2 = }")

# --- 5. Report Results ---
print("=====")
print("  EXACT PAIRED PERMUTATION TEST REPORT  ")
print("=====")
print(f"Observed Mean Difference: {main_test.statistic:.4f}")
print(f"Exact P-value:           {main_test.pvalue:.5f}")
print(f"95% Test-Inverted CI:     {ci_str}")
print("=====")

```

```

=====
  EXACT PAIRED PERMUTATION TEST REPORT
=====
Observed Mean Difference: -0.0571
Exact P-value:           0.03125
95% Test-Inverted CI:     [-0.0900, -0.0050]
=====

```