



HTML Form Attributes

[< Previous](#)[Next >](#)

This chapter describes the different attributes for the HTML `<form>` element.

The Action Attribute

The `action` attribute defines the action to be performed when the form is submitted.

Usually, the form data is sent to a file on the server when the user clicks on the submit button.

In the example below, the form data is sent to a file called "action_page.php". This file contains a server-side script that handles the form data:

Example

On submit, send form data to "action_page.php":

```
<form action="/action_page.php">
  <label for="fname">First name:</label><br>
  <input type="text" id="fname" name="fname" value="John"><br>
  <label for="lname">Last name:</label><br>
  <input type="text" id="lname" name="lname" value="Doe"><br><br>
  <input type="submit" value="Submit">
</form>
```

Try it Yourself »

Tip: If the `action` attribute is omitted, the action is set to the current page.

The Target Attribute

The `target` attribute specifies where to display the response that is received after submitting the form.

The `target` attribute can have one of the following values:

Value	Description
<code>_blank</code>	The response is displayed in a new window or tab
<code>_self</code>	The response is displayed in the current window
<code>_parent</code>	The response is displayed in the parent frame
<code>_top</code>	The response is displayed in the full body of the window

framename

The response is displayed in a named iframe

The default value is `_self` which means that the response will open in the current window.

Example

Here, the submitted result will open in a new browser tab:

```
<form action="/action_page.php" target="_blank">
```

[Try it Yourself »](#)

The Method Attribute

The `method` attribute specifies the HTTP method to be used when submitting the form data.

The form-data can be sent as URL variables (with `method="get"`) or as HTTP post transaction (with `method="post"`).

The default HTTP method when submitting form data is GET.

Example

This example uses the GET method when submitting the form data:

```
<form action="/action_page.php" method="get">
```

[Try it Yourself »](#)

Example

This example uses the POST method when submitting the form data:

```
<form action="/action_page.php" method="post">
```

[Try it Yourself »](#)

Notes on GET:

- Appends the form data to the URL, in name/value pairs
- NEVER use GET to send sensitive data! (the submitted form data is visible in the URL!)
- The length of a URL is limited (2048 characters)
- Useful for form submissions where a user wants to bookmark the result
- GET is good for non-secure data, like query strings in Google

Notes on POST:

- Appends the form data inside the body of the HTTP request (the submitted form data is not shown in the URL)
- POST has no size limitations, and can be used to send large amounts of data.
- Form submissions with POST cannot be bookmarked

Tip: Always use POST if the form data contains sensitive or personal information!

The Autocomplete Attribute

The `autocomplete` attribute specifies whether a form should have autocomplete on or off.

When autocomplete is on, the browser automatically complete values based on values that the user has entered before.

Example

A form with autocomplete on:

```
<form action="/action_page.php" autocomplete="on">
```

Try it Yourself »

The Novalidate Attribute

The `novalidate` attribute is a boolean attribute.

When present, it specifies that the form-data (input) should not be validated when submitted.

Example

A form with a novalidate attribute:

```
<form action="/action_page.php" novalidate>
```

[Try it Yourself »](#)

HTML Exercises

Test Yourself With Exercises

Exercise:

Add a submit button, and specify that the form should go to `"/action_page.php"`.

```
<form ="/action_page.php">  
Name: <input type="text" name="name">  
<  >  
</form>
```

[Submit Answer »](#)[Start the Exercise](#)

List of All <form> Attributes

Attribute	Description
<u>accept-charset</u>	Specifies the character encodings used for form submission
<u>action</u>	Specifies where to send the form-data when a form is submitted
<u>autocomplete</u>	Specifies whether a form should have autocomplete on or off
<u>enctype</u>	Specifies how the form-data should be encoded when submitting it to the server (only for method="post")
<u>method</u>	Specifies the HTTP method to use when sending form-data
<u>name</u>	Specifies the name of the form
<u>novalidate</u>	Specifies that the form should not be validated when submitted
<u>rel</u>	Specifies the relationship between a linked resource and the current document
<u>target</u>	Specifies where to display the response that is received after submitting the form

[< Previous](#)[Next >](#)



COLOR PICKER



SHOP

HOW TO


Tabs
Dropdowns
Accordions
Side Navigation
Top Navigation
Modal Boxes
Progress Bars
Parallax
Login Form
HTML Includes
Google Maps
Range Sliders
Tooltips
Slideshow
Filter List
Sort List

SHARE



Certificates
HTML
CSS
JavaScript
Python
SQL
PHP
And more





[REPORT ERROR](#)

[FORUM](#)

[ABOUT](#)

[SHOP](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)

- JavaScript Tutorial
- How To Tutorial
- SQL Tutorial
- Python Tutorial
- W3.CSS Tutorial
- Bootstrap Tutorial
- PHP Tutorial
- Java Tutorial
- C++ Tutorial
- jQuery Tutorial

Top Examples

- HTML Examples
- CSS Examples
- JavaScript Examples
- How To Examples
- SQL Examples
- Python Examples
- W3.CSS Examples
- Bootstrap Examples
- PHP Examples
- Java Examples
- XML Examples
- jQuery Examples

- JavaScript Reference
- SQL Reference
- Python Reference
- W3.CSS Reference
- Bootstrap Reference
- PHP Reference
- HTML Colors
- Java Reference
- Angular Reference
- jQuery Reference

Web Certificates

- HTML Certificate
- CSS Certificate
- JavaScript Certificate
- SQL Certificate
- Python Certificate
- PHP Certificate
- Bootstrap Certificate
- XML Certificate
- jQuery Certificate

[Get Certified »](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2020 by Refsnes Data. All Rights Reserved.
W3Schools is Powered by W3.CSS.

