

CONTRIBUTE



In this article you will learn about Html.Action and Html.RenderAction in ASP.NET MVC.



Sandeep Singh Shekhawat

Jul 27 2017

8

15

251.6k

Download Free .NET & JAVA Files API

This article introduces both @Html.Action and @Html.RenderAction. These are used to call a partial view in another view by action method. As we have other options such as @Html.Partial and @Html.RenderPartial to call a partial view in other views then why do we use @Html.Action and @Html.RenderAction? We use these two html helper methods in the following scenarios.

- 1. To call partial view in another view.
- 2. Partial view is independent to corresponding view in other words partial view model in not related to corresponding view model in strongly typed views.
- 3. We need some operations over data of partial view before it render in corresponding view
- 4. We call a partial view from ChildActionOnly action methods in another view by GET request.

Whenever we got above situation in our application then we prefer to use these Html helper methods. Now let's have a look on summery information of these Html helper methods.

## @Html.Action

This Html.Action renders partial view as an HTML string so we can store it in another string variable. It is string return type method so first it returns result as a string then renders result to response.



This is also same as Html.Action but main differer ASK A QUESTION st CONTRIBUTE response that's why it is more efficient if the action returns a large amount of HTML over @Html.Action.

Now we will have a look on particle implementation of these two.

## **Using Code**

We create an MVC application which has a view for employee login and employee registration as both employee login and employee registration are independent to each other. To combine these on single view, we create two partial views, one for Employee login and another for employee registration. As these two views are also independent to corresponding views in which these call.




Figure 1: Partial View in corresponding View

First of all we create two view models one for Employee Login (EmployeeLoginViewModel) and another for Employee Registration (EmployeeViewModel). The following code snippet shows both.

```
CONTRIBUTE
      #Corner
using System.ComponentModel.DataAnn
                                              ASK A OUESTION
11.
12.
     namespace EFOperation.Models
13.
     {
          public class EmployeeViewModel
14.
15.
16.
              public string Name { get; set; }
              public string Email { get; set; }
17.
18.
              public string Password { get; set; }
19.
              [Display(Name="Confirm Password")]
20.
              public string ConfirmPassword { get; set; }
21.
          }
     }
22.
```

As per figure 1, we create an Index view which has both employee login and employee registration partial view so we define a controller that has three action methods. The "Index" action method returns main view and other two child action methods "EmployeeLogin" and "EmployeeRegistration". The following code snippet shows EmployeeController.

```
03.
04.
     namespace EFOperation.Controllers
05.
          public class EmployeeController : Controller
06.
07.
08.
09.
              public ActionResult Index()
10.
11.
                  return View("Index");
12.
13.
              [ChildActionOnly]
14.
              public ActionResult EmployeeLogin()
15.
16.
                  EmployeeLoginViewModel model = new EmployeeLoginViewModel();
17.
                  return PartialView("_EmployeeLogin", model);
18.
19.
20.
              [ChildActionOnly]
21.
              public ActionResult EmployeeRegistration()
22.
              {
23.
                  EmployeeViewModel model = new EmployeeViewModel();
                  return PartialView(" EmployeeRegistration", model);
24.
25.
              }
26.
          }
     }
27.
```

Mitmle Render Action, we can use independent m ASK A QUESTION IC CONTRIBUTE how partial views are called in corresponding view. The Tollowing code snippet for Employee Login partial view.

```
01.
     @model EFOperation.Models.EmployeeLoginViewModel
02.
03.
     <section id="loginForm">
04.
          @using (Html.BeginForm("EmployeeLogin", "Employee", new { ReturnUrl =
     horizontal", role = "form" }))
05.
          {
06.
              @Html.AntiForgeryToken()
              <h4>Use a local account to log in.</h4>
07.
              <hr />
08.
              <div class="form-group">
09.
                  @Html.LabelFor(m => m.Email, new { @class = "col-md-
10.
     2 control-label" })
                  <div class="col-md-10">
11.
12.
                      @Html.TextBoxFor(m => m.Email, new { @class = "form-
     control" })
13.
                  </div>
                  (WHTMI.Labelfor(M => M.Password, new { (WClass = COl-Md-
To.
     2 control-label" })
                  <div class="col-md-10">
17.
18.
                      @Html.PasswordFor(m => m.Password, new { @class = "form-
     control" })
19.
                      @Html.ValidationMessageFor(m => m.Password)
                  </div>
20.
              </div>
21.
              <div class="form-group">
22.
                  <div class="col-md-offset-2 col-md-10">
23.
24.
                       <input type="submit" value="Log in" class="btn btn-</pre>
     default" />
25.
                  </div>
              </div>
26.
27.
28.
     </section>
```

The following code snippet for Employee registration view.

```
<div class="col-md-10">
                  @Html.TextBoxFor(m => m ASK A QUESTION
                                                                   CONTRIBUTE
      #Corner
     control" })
              </div>
12.
13.
          </div>
          <div class="form-group">
14.
              @Html.LabelFor(m => m.Email, new { @class = "col-md-2 control-
15.
     label" })
              <div class="col-md-10">
16.
17.
                  @Html.TextBoxFor(m => m.Email, new { @class = "form-
     control" })
              </div>
18.
19.
         </div>
          <div class="form-group">
20.
              @Html.LabelFor(m => m.Password, new { @class = "col-md-
21.
     2 control-label" })
              <div class="col-md-10">
22.
                  @Html.PasswordFor(m => m.Password, new { @class = "form-
23.
     control" })
              </div>
24.
25.
          </div>
     Z CONCLOT-TANCT 1)
28.
              <div class="col-md-10">
29.
                  @Html.PasswordFor(m => m.ConfirmPassword, new { @class = "forr
     control" })
30.
              </div>
          </div>
31.
          <div class="form-group">
32.
              <div class="col-md-offset-2 col-md-10">
33.
                  <input type="submit" class="btn btn-</pre>
34.
     default" value="Register" />
              </div>
35.
36.
         </div>
     }
37.
```

Now we call both partial views with help of @Html.Action and @Html.RenderAction in main index view. The following code snippet is for the same.

```
01.
     @{
02.
          ViewBag.Title = "Index";
     }
03.
04.
     <div class="row">
05.
06.
          <div class="col-lg-6">
07.
              @Html.Action("EmployeeLogin")
08.
09.
          </div>
          <div class="col-lg-6">
10.
              @{Html.RenderAction("EmployeeRegistration");}
```



CONTRIBUTE

Now run the application and we get the same result as figure 2.




Figure 2: Index view

Read more articles on ASP.NET,

• Get IP Address In ASP.NET ASP.NET MVC Html.RenderAction Html.Action



Sandeep Singh Shekhawat 70P 100

Microsoft Tech Net Guru | C# Corner MVP | Code Project MVP | Associate Lead, Technology

**78** 15.1m 5

**View Previous Comments** 





Corner ASK A QUESTION
Type your comment here and press Enter Key (will in 1907) and access to the comment have an access.

CONTRIBUTE

2

How to pass parameter in RenderAction

Sribin Kumar Oct 10, 2018

1713 50 0 0 Reply



How to do wire framing because you posted a sample prototype picture....which tool you used to create that?

Tridip Bhattacharjee Jul 27, 2017

**843 1.2k 16.4k** 0 0 Reply



How can we put javascript in a @Html.Action partial view, pls? This pw load after the view and I put the script in a section but it does not load. Maybe I should import jQuery and my script in partial view in case of Action? Thank you in advance.

Sándor Hatvani May 27, 2017

**1742 21 0** 0 Reply



1760 3 0

0 0 Reply



After clicking login or register, i am not able to perform "RediretToRoute" or "Redirect" in the controller

Vishal Kotecha Jan 05, 2017

**1760 3 0** 0 Reply



Great article.

Bikesh Srivastava Jul 28, 2016

**79 20k 1.6m** 0 Reply



very nice

sreenivasa k Apr 25, 2016

**1206 570 8.3k** 0 Reply



Thanks:)

Sandeep Singh Shekhawat Apr 24, 2016

**78 20k 15.1m** 0 0 Reply



Interesting

Bhavik Patel Apr 24, 2016

**658 1.9k 417.4k** 0 0 Reply



Thanks for Sharing

Hari Shanker Apr 24

**1518 245 13k** 0 0



CONTRIBUTE

## **OUR TRAINING**



Mastering Xamarin Forms Development Learn how to build cross-platform mobile apps using Xamarin Forms.



CONTRIBUTE

## TRENDING UP

- 01 GraphQL In .NET Core Web API With Entity Framework Core Part Three
- 02 C# Coding Standards ©
- 03 Why Agile Is Important In Software Development
- 04 ASP.NET MVC Request Life Cycle
- 05 CRUD Operations On CosmosDB Mongo API Using ASP.NET Core
- 06 Create Registration And Login Page Using Angular 7 And Web API
- 07 GraphQL In .NET Core Web API With Entity Framework Core Part One
- 08 What Does "var" Mean In C#?
- 09 Upload Files ☐ In Azure Blob Storage Using ASP.NET Core



VIEW AII ( )
CONTRIBUTE

About Us Contact Us Privacy Policy Terms Media Kit Sitemap Report a Bug FAQ Partners C# Tutorials

©2019 C# Corner. All contents are copyright of their authors.