

# Minimum Absolute Difference in an Array in Algorithm | HackerRank Programming Solutions | HackerRank Problem Solving Solutions in Java [ Correct]

December 13, 2021 by [Techno-RJ](#)





Hello **Programmers/Coders**, Today we are going to share **solutions of Programming problems of HackerRank, *Algorithm Solutions of Problem Solving Section in Java***. At Each Problem with Successful submission with **all Test Cases Passed**, you will get an score or marks. And after solving maximum problems, you will be getting stars. This will highlight your profile to the recruiters.

In this post, you will find the solution for **Minimum Absolute Difference in an Array in Java-HackerRank Problem**. We are providing the **correct and tested solutions** of coding problems present on **HackerRank**. If you are not able to solve any problem, then you can take help from our Blog/website.

Use "Ctrl+F" To Find Any Questions Answer. & For Mobile User, You Just Need To Click On Three dots In Your Browser & You Will Get A "Find" Option There. Use These Option to Get Any Random Questions Answer.

## Introduction To Algorithm

The word **Algorithm** means "a process or set of rules to be followed in calculations or other problem-solving operations". Therefore Algorithm refers to a set of rules/instructions that step-by-step define how a work is to be executed upon in order to get the expected results.

## Advantages of Algorithms:

- It is easy to understand.
- Algorithm is a step-wise representation of a solution to a given problem.
- In Algorithm the problem is broken down into smaller pieces or steps hence, it is easier for the programmer to convert it into an actual program.

**Link for the Problem** – [Minimum Absolute Difference in an Array – Hacker Rank Solution](#)

### **Minimum Absolute Difference in an Array – Hacker Rank Solution**

## **Problem:**

The absolute difference is the positive difference between two values  $a$  and  $b$ , is written  $|a - b|$  or  $|b - a|$  and they are equal. If  $a = 3$  and  $b = 2$ ,  $|3 - 2| = |2 - 3| = 1$ . Given an array of integers, find the minimum absolute difference between any two elements in the array.

**Example.**  $arr = [-2, 2, 4]$

There are 3 pairs of numbers:  $[-2, 2]$ ,  $[-2, 4]$  and  $[2, 4]$ . The absolute differences for these pairs are  $|(-2) - 2| = 4$ ,  $|(-2) - 4| = 6$  and  $|2 - 4| = 2$ . The minimum absolute difference is 2.

## **Function Description**

Complete the *minimumAbsoluteDifference* function in the editor below. It should return an integer that represents the minimum absolute difference between any pair of elements.

*minimumAbsoluteDifference* has the following parameter(s):

- *int arr[n]*: an array of integers

## **Returns**

- *int*: the minimum absolute difference found

### Input Format

The first line contains a single integer  $n$ , the size of *arr*.

The second line contains  $n$  space-separated integers, *arr*[ $i$ ].

### Constraints

- $2 \leq n \leq 10^5$
- $-10^9 \leq arr[i] \leq 10^9$

### Sample Input 0

```
3
3 -7 0
```

### Sample Output 0

```
3
```

### Explanation 0



The first line of input is the number of array elements. The array,  $arr = [3, -7, 0]$

There are three pairs to test:  $(3, -7)$ ,  $(3, 0)$ , and  $(-7, 0)$ . The absolute differences are:

- $|3 - -7| \Rightarrow 10$
- $|3 - 0| \Rightarrow 3$
- $|-7 - 0| \Rightarrow 7$

Remember that the order of values in the subtraction does not influence the result.

The smallest of these absolute differences is **3**.

### Sample Input 1

```
10
-59 -36 -13 1 -53 -92 -2 -96 -54 75
```

### Sample Output 1

```
1
```

### Explanation 1

The smallest absolute difference is  $|-54 - -53| = 1$ .

### Sample Input 2

```
5
1 -3 71 68 17
```

### Sample Output 2

```
3
```

### Explanation 2

The minimum absolute difference is  $|71 - 68| = 3$ .

### Minimum Absolute Difference in an Array – Hacker Rank Solution

```
1. import java.io.*;
2. import java.util.*;
3. import java.text.*;
4. import java.math.*;
5. import java.util.regex.*;
6.
7. public class Solution {
8.
9.     public static void main(String[] args) {
10.         Scanner in = new Scanner(System.in);
11.         int n = in.nextInt();
12.         int[] a = new int[n];
13.         for(int a_i=0; a_i < n; a_i++){
14.             a[a_i] = in.nextInt();
15.         }
16.         Arrays.sort(a);
17.         int min = 2000000000;
```



```
18.     for (int i = 1; i < n; i++) {
19.         min = Math.min(Math.abs(a[i]-a[i-1]), min);
20.     }
21.     System.out.println(min);
22. }
23. }
```

- ◀ [Common Child in Algorithm | HackerRank Programming Solutions | HackerRank Problem Solving Solutions in Java \[🏆 Correct\]](#)
- ▶ [Marc's Cakewalk in Algorithm | HackerRank Programming Solutions | HackerRank Problem Solving Solutions in Java \[🏆 Correct\]](#)

## Leave a Comment

☐ Save my name, email, and website in this browser for the next time I comment.

Post Comment



## Recent Posts

[Database Management System DBMS Notes 2022](#)

[Best Operating System Notes in 2022 | Last Minute Notes | Operating System Overview](#)

[Best Tips To Crack Any Interview in 2022 | HR Interview Tips To Get The Job In Your Hand \[Latest Update!!\]](#)

[Combine Two Tables LeetCode Programming Solutions 2022 | LeetCode Problem Solutions in SQL \[🏆 Correct\]](#)

[Dungeon Game LeetCode Programming Solutions 2022 | LeetCode Problem Solutions in C++, Java, & Python \[🏆 Correct\]](#)

[About Us](#) [Contact Us](#) [Disclaimer](#) [DMCA](#) [Notes](#) [Privacy Policy](#) [Terms and Conditions](#)

Copyright © Techno-RJ, 2022

