

[Home](#) [About](#) [Contact](#) [Privacy policy](#) [DMCA](#) [computer science](#)

CLOSE ADS

CLOSE ADS

Programmingoneone[Home](#) [C++ solutions](#) [Java solutions](#) [Data structures](#) [30 days of code](#) [HackerRank Python Solutions](#) [100+ C programs](#)[Home](#) > [coding problems](#) > [Leetcode Two sum problem solution](#)

Leetcode Two sum problem solution

 YASH PAL  July 22, 2021

In this **Leetcode Two sum problem solution**, we have given an array of integers nums and an integer target. we need to return the indices of the two numbers such that they add up to the target.

Search Your favorite topic

Subscribe if you like my work and i will help you to learn new things

CLOSE ADS

CLOSE ADS



LeetCode

Two Sum

Problem solution in Python.

Code

```
class Solution:
    def twoSum(self, nums: List[int], target: int) -> List[int]:
        x = len(nums)
        for i in range(x-1):
            for j in range(1,x):
                if i == j:
                    continue
                if nums[i] + nums[j] == target:
                    return [i,j]
```

  **tion in Java.**

CLOSE ADS

CLOSE ADS

Code

```
class Solution {  
    public int[] twoSum(int[] nums, int target) {  
  
        HashMap<Integer,Integer> map = new HashMap<>();  
        int noToFind = 0;  
        for(int i = 0; i < nums.length; i++)  
        {  
            if(map.containsKey(nums[i]))  
            {  
                int[] arr = {map.get(nums[i]), i};  
                return arr;  
            }  
            noToFind = target - nums[i];  
            map.put(noToFind, i);  
        }  
        return null;  
    }  
}
```

Problem solution in C++.

Code

```
class Solution {  
public:
```

```

vector<int> twoSum(vector<int>& nums, int target) {
    int n,i,j,ind,ind2;
    ze();
    vector<int> ans;
    unordered_map<int, int> mp;
    for (int i = 0; i < n; i++)
    {
        if (mp.find(target - nums[i]) != mp.end())
        {
            ans.push_back(mp[target - nums[i]]);
            ans.push_back(i);
            return ans;
        }
        mp[nums[i]] = i;
    }

    return ans;
}
};

```

CLOSE ADS

Problem solution in C.

Code

```

int* twoSum(int* nums, int numsSize, int target, int* returnSize){
    *returnSize=2;
    int *arr=(int *)malloc((*returnSize)*sizeof(int));
    for(int i=0;i<numsSize;i++){
        for(int j=i+1;j<numsSize;j++){

```

```
if (nums[i]+nums[j]==target) {  
    arr[0]=i;  
    break;  
}  
}  
}  
return arr;  
}
```

[CLOSE ADS](#)[CLOSE ADS](#)

Tags: [coding problems](#)

[Facebook](#)[Twitter](#)

Post a Comment

1 Comments



UNKNOWN

🕒 January 24, 2022 at 7:17 AM

Pretty sure there is a better way to do the two sum in C with a hash map

[Reply](#)[Delete](#)

▼ **Replies**

[Reply](#)

[Add comment](#)



Enter your comment...

CLOSE ADS

CLOSE ADS

Crafted with ❤️ by [TemplatesYard](#) | Distributed by [Blogger](#)