

Data Structures Algorithms Interview Preparation Topic-wise Practice C++ Java Python Competitive Programming Machi

Find minimum difference between any two elements

Difficulty Level : Basic • Last Updated : 21 Jan, 2022

Given an unsorted array, find the minimum difference between any pair in given array.

Examples:

```
Input : {1, 5, 3, 19, 18, 25};
Output : 1
Minimum difference is between 18 and 19

Input : {30, 5, 20, 9};
Output : 4
Minimum difference is between 5 and 9

Input : {1, 19, -4, 31, 38, 25, 100};
Output : 5
Minimum difference is between 1 and -4
```

Login

Register

Method i (Simple, O(II-)

A simple solution is to use two loops.

C++

```
// C++ implementation of simple method to find
// minimum difference between any pair
#include <bits/stdc++.h>
using namespace std;
// Returns minimum difference between any pair
int findMinDiff(int arr[], int n)
// Initialize difference as infinite
int diff = INT_MAX;
// Find the min diff by comparing difference
// of all possible pairs in given array
for (int i=0; i<n-1; i++)</pre>
    for (int j=i+1; j<n; j++)</pre>
        if (abs(arr[i] - arr[j]) < diff)</pre>
                diff = abs(arr[i] - arr[j]);
// Return min diff
return diff;
```

Login

```
return 0;
Java
// Java implementation of simple method to find
// minimum difference between any pair
class GFG
    // Returns minimum difference between any pair
    static int findMinDiff(int[] arr, int n)
        // Initialize difference as infinite
         int diff = Integer.MAX_VALUE;
        // Find the min diff by comparing difference
        // of all possible pairs in given array
         for (int i=0; i<n-1; i++)</pre>
             for (int j=i+1; j<n; j++)</pre>
                 if (Math.abs((arr[i] - arr[j]) )< diff)</pre>
                     diff = Math.abs((arr[i] - arr[j]));
         // Return min diff
         return diff;
```

Login

Register

```
}
```

Python3

```
# Python implementation of simple method to find
# minimum difference between any pair
# Returns minimum difference between any pair
def findMinDiff(arr, n):
    # Initialize difference as infinite
    diff = 10**20
    # Find the min diff by comparing difference
   # of all possible pairs in given array
   for i in range(n-1):
        for j in range(i+1,n):
            if abs(arr[i]-arr[j]) < diff:</pre>
                diff = abs(arr[i] - arr[j])
    # Return min diff
    return diff
# Driver code
arr = [1, 5, 3, 19, 18, 25]
n = len(arr)
```

Login

Register

class GFG { // Returns minimum difference between any pair static int findMinDiff(int []arr, int n) // Initialize difference as infinite int diff = int.MaxValue; // Find the min diff by comparing difference // of all possible pairs in given array for (int i = 0; i < n-1; i++) for (int j = i+1; j < n; j++)if (Math.Abs((arr[i] - arr[j])) < diff)</pre> diff = Math.Abs((arr[i] - arr[j])); // Return min diff return diff; // Driver method to test the above function public static void Main()

// C# implementation of simple method to find

// minimum difference between any pair

using System;

Login

Register

// This code is contributed by nitin mittal.

PHP

```
<?php
// PHP implementation of simple
// method to find minimum
// difference between any pair
// Returns minimum difference
// between any pair
function findMinDiff($arr, $n)
// Initialize difference
// as infinite
$diff = PHP INT MAX;
// Find the min diff by comparing
// difference of all possible
// pairs in given array
for ($i = 0; $i < $n - 1; $i++)
    for (\$j = \$i + 1; \$j < \$n; \$j++)
        if (abs($arr[$i] - $arr[$j]) < $diff)</pre>
                $diff = abs($arr[$i] - $arr[$j]);
// Return min diff
return $diff;
```

Login

Register

```
findMinDiff($arr, $n);

// This code is contributed by ajit
?>
```

Javascript

```
<script>
// JavaScript program implementation of simple method to find
// minimum difference between any pair
    // Returns minimum difference between any pair
   function findMinDiff( arr, n)
        // Initialize difference as infinite
        let diff = Number.MAX VALUE;
        // Find the min diff by comparing difference
        // of all possible pairs in given array
        for (let i=0; i<n-1; i++)</pre>
            for (let j=i+1; j<n; j++)</pre>
                if (Math.abs((arr[i] - arr[j]) )< diff)</pre>
                    diff = Math.abs((arr[i] - arr[j]));
        // Return min diff
        return diff;
```

Login

Register

findMinDiff(arr, arr.length));

</script>

Output:

Minimum difference is 1

Method 2 (Efficient: O(n Log n)

The idea is to use sorting. Below are steps.

- 1) Sort array in ascending order. This step takes O(n Log n) time.
- 2) Initialize difference as infinite. This step takes O(1) time.
- 3) Compare all adjacent pairs in sorted array and keep track of minimum difference. This step takes O(n) time.

Below is implementation of above idea.

C++



```
// C++ program to find minimum difference between
// any pair in an unsorted array
```

Login

```
// Sort array in non-decreasing order
   sort(arr, arr+n);
   // Initialize difference as infinite
   int diff = INT MAX;
   // Find the min diff by comparing adjacent
   // pairs in sorted array
   for (int i=0; i<n-1; i++)</pre>
      if (arr[i+1] - arr[i] < diff)</pre>
          diff = arr[i+1] - arr[i];
   // Return min diff
   return diff;
// Driver code
int main()
   int arr[] = {1, 5, 3, 19, 18, 25};
   int n = sizeof(arr)/sizeof(arr[0]);
   cout << "Minimum difference is " << findMinDiff(arr, n);</pre>
   return 0;
```



Login

```
{
   // Returns minimum difference between any pair
   static int findMinDiff(int[] arr, int n)
           // Sort array in non-decreasing order
           Arrays.sort(arr);
           // Initialize difference as infinite
           int diff = Integer.MAX_VALUE;
           // Find the min diff by comparing adjacent
           // pairs in sorted array
           for (int i=0; i<n-1; i++)</pre>
              if (arr[i+1] - arr[i] < diff)</pre>
                  diff = arr[i+1] - arr[i];
           // Return min diff
           return diff;
   // Driver method to test the above function
   public static void main(String[] args)
        int arr[] = new int[]{1, 5, 3, 19, 18, 25};
        System.out.println("Minimum difference is "+
                              findMinDiff(arr, arr.length));
```

Login

Register

```
# any pair in an unsorted array
# Returns minimum difference between any pair
def findMinDiff(arr, n):
   # Sort array in non-decreasing order
   arr = sorted(arr)
   # Initialize difference as infinite
   diff = 10**20
   # Find the min diff by comparing adjacent
   # pairs in sorted array
   for i in range(n-1):
        if arr[i+1] - arr[i] < diff:</pre>
            diff = arr[i+1] - arr[i]
   # Return min diff
   return diff
# Driver code
arr = [1, 5, 3, 19, 18, 25]
n = len(arr)
print("Minimum difference is " + str(findMinDiff(arr, n)))
# This code is contributed by Pratik Chhajer
```

C#

Login

```
CIASS OFG
   // Returns minimum difference
   // between any pair
   static int findMinDiff(int[] arr,
                            int n)
        // Sort array in
        // non-decreasing order
        Array.Sort(arr);
        // Initialize difference
        // as infinite
        int diff = int.MaxValue;
        // Find the min diff by
        // comparing adjacent pairs
        // in sorted array
        for (int i = 0; i < n - 1; i++)</pre>
            if (arr[i + 1] - arr[i] < diff)</pre>
                diff = arr[i + 1] - arr[i];
        // Return min diff
        return diff;
   // Driver Code
   public static void Main()
```

Login

Register

//This code is contributed by anuj_67.

PHP

```
<?php
// PHP program to find minimum
// difference between any pair
// in an unsorted array
// Returns minimum difference
// between any pair
function findMinDiff($arr, $n)
// Sort array in
// non-decreasing order
sort($arr);
// Initialize difference
// as infinite
$diff = PHP INT MAX;
// Find the min diff by
// comparing adjacent
// pairs in sorted array
for ($i = 0; $i < $n - 1; $i++)
```

Login

Register

Javascript

```
// Javascript program to find minimum
// difference between any pair
// in an unsorted array

// Returns minimum difference
// between any pair
function findMinDiff(arr, n)
{

    // Sort array in
    // non-decreasing order
    arr.sort(function(a, b)
    {return a - b});
```

Login

Register

```
// in sorted array
for (let i = 0; i < n - 1; i++)
    if (arr[i + 1] - arr[i] < diff)
        diff = arr[i + 1] - arr[i];

// Return min diff
return diff;
}

let arr = [1, 5, 3, 19, 18, 25];
document.write("Minimum difference is "
+ findMinDiff(arr, arr.length));

</script>
```

Output:

Minimum difference is 1



Login

Register

Asked in: Amazon

This article is contributed by **Harshit Agrawal**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Login

Register

Previous

Next

Size of The Subarray With Maximum Sum

Space optimization using bit manipulations

RECOMMENDED ARTICLES

Page:

Article Contributed By:





Vote for difficulty

Login

Register

Improved By: nitin mittal, vt_m, jit_t, chinmoy1997pal, divyesh072019, amartyaniel20

Article Tags: Amazon, Arrays, Sorting

Practice Tags: Amazon, Arrays, Sorting

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments



5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org



Login

Register

Careers

In Media

Contact Us

Data Structures

SDE Cheat Sheet

Machine learning

Copyright Policy

CS Subjects Video Tutorials

News

Top News

Technology

Work & Career

Business

Finance

Lifestyle

Languages

Python

Java

CPP

Golang

C#

SQL

Web Development

Web Tutorials

Django Tutorial

HTML

CSS

JavaScript

Contribute

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships



Login

