

[Array](#) [Matrix](#) [Strings](#) [Hashing](#) [Linked List](#) [Stack](#) [Queue](#) [Binary Tree](#) [Binary Search Tree](#) [Heap](#) [Graph](#) [Searching](#) [Sorting](#)

Beat the competition and land yourself a top job. [Register for Job-a-thon now!](#)

# Inorder Successor in Binary Search Tree


Difficulty Level : Medium • Last Updated : 17 Jun, 2022

In Binary Tree, Inorder successor of a node is the next node in Inorder traversal of the Binary Tree. Inorder Successor is NULL for the last node in Inorder traversal.

In Binary Search Tree, Inorder Successor of an input node can also be defined as the node with the smallest key greater than the key of the input node. So, it is sometimes important to find next node in sorted order.



# Start Your Coding Journey Now!

[Login](#)[Register](#)

In the above diagram, inorder successor of **8** is **10**, inorder successor of **10** is **12** and inorder successor of **14** is **20**.

[Recommended Practice](#)[Inorder Successor in BST](#)[Try It!](#)

## Method 1 (Uses Parent Pointer)



# Start Your Coding Journey Now!

[Login](#)[Register](#)

In this method, we assume that every node has a parent pointer.

The Algorithm is divided into two cases on the basis of the right subtree of the input node being empty or not.

**Input:** *node, root* // *node* is the node whose Inorder successor is needed.

**Output:** *succ* // *succ* is Inorder successor of *node*.

1. If right subtree of *node* is not *NULL*, then *succ* lies in right subtree. Do the following.  
Go to right subtree and return the node with minimum key value in the right subtree.
2. If right subtree of *node* is *NULL*, then *succ* is one of the ancestors. Do the following.  
Travel up using the parent pointer until you see a node which is left child of its parent. The parent of such a node is the *succ*.

## Implementation:

Note that the function to find InOrder Successor is highlighted (with gray background) in below code.

### C++

```
#include <iostream>
using namespace std;

/* A binary tree node has data,
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
int data;
struct node* left;
struct node* right;
struct node* parent;
};

struct node* minValue(struct node* node);

struct node* inOrderSuccessor(
    struct node* root,
    struct node* n)
{
    // step 1 of the above algorithm
    if (n->right != NULL)
        return minValue(n->right);

    // step 2 of the above algorithm
    struct node* p = n->parent;
    while (p != NULL && n == p->right) {
        n = p;
        p = p->parent;
    }
    return p;
}

/* Given a non-empty binary search tree,
   return the minimum data
   value found in that tree. Note that
   the entire tree does not need
   to be searched. */
struct node* minValue(struct node* node)
{
    struct node* current = node;
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        current = current->left;
    }
    return current;
}

/* Helper function that allocates a new
   node with the given data and
   NULL left and right pointers. */
struct node* newNode(int data)
{
    struct node* node = (struct node*)
        malloc(sizeof(
            struct node));
    node->data = data;
    node->left = NULL;
    node->right = NULL;
    node->parent = NULL;

    return (node);
}

/* Give a binary search tree and
   a number, inserts a new node with
   the given number in the correct
   place in the tree. Returns the new
   root pointer which the caller should
   then use (the standard trick to
   avoid using reference parameters). */
struct node* insert(struct node* node,
                    int data)
{
    /* 1. If the tree is empty, return a new,
       single node */
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
struct node* temp;

/* 2. Otherwise, recur down the tree */
if (data <= node->data) {
    temp = insert(node->left, data);
    node->left = temp;
    temp->parent = node;
}
else {
    temp = insert(node->right, data);
    node->right = temp;
    temp->parent = node;
}

/* return the (unchanged) node pointer */
return node;
}
}

/* Driver program to test above functions*/
int main()
{
    struct node *root = NULL, *temp, *succ, *min;

    // creating the tree given in the above diagram
    root = insert(root, 20);
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
    temp = root->left->right->right;
```



## Start Your Coding Journey Now!

[Login](#)
[Register](#)

```
cout << "\n Inorder Successor of " << temp->data << " is " << succ->data;
else
    cout << "\n Inorder Successor doesn't exist";

    getchar();
    return 0;
}

// this code is contributed by shivanisinghss2110
```

### C

```
#include <stdio.h>
#include <stdlib.h>

/* A binary tree node has data,
the pointer to left child
and a pointer to right child */
struct node {
    int data;
    struct node* left;
    struct node* right;
    struct node* parent;
};

struct node* minValue(struct node* node);

struct node* inOrderSuccessor(
    struct node* root,
    struct node* n)
{
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// step 2 of the above algorithm
struct node* p = n->parent;
while (p != NULL && n == p->right) {
    n = p;
    p = p->parent;
}
return p;
}

/* Given a non-empty binary search tree,
return the minimum data
value found in that tree. Note that
the entire tree does not need
to be searched. */
struct node* minValue(struct node* node)
{
    struct node* current = node;

    /* loop down to find the leftmost leaf */
    while (current->left != NULL) {
        current = current->left;
    }
    return current;
}

/* Helper function that allocates a new
node with the given data and
NULL left and right pointers. */
struct node* newNode(int data)
{
    struct node* node = (struct node*)
        malloc(sizeof(
```





## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
node->right = NULL;
node->parent = NULL;

return (node);
}

/* Give a binary search tree and
a number, inserts a new node with
the given number in the correct
place in the tree. Returns the new
root pointer which the caller should
then use (the standard trick to
avoid using reference parameters). */
struct node* insert(struct node* node,
                    int data)
{
    /* 1. If the tree is empty, return a new,
    single node */
    if (node == NULL)
        return (newNode(data));
    else {
        struct node* temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node->data) {
            temp = insert(node->left, data);
            node->left = temp;
            temp->parent = node;
        }
        else {
            temp = insert(node->right, data);
            node->right = temp;
            temp->parent = node;
        }
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        return node;
    }
}

/* Driver program to test above functions*/
int main()
{
    struct node *root = NULL, *temp, *succ, *min;

    // creating the tree given in the above diagram
    root = insert(root, 20);
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
    temp = root->left->right->right;

    succ = inOrderSuccessor(root, temp);
    if (succ != NULL)
        printf(
            "\n Inorder Successor of %d is %d ",
            temp->data, succ->data);
    else
        printf("\n Inorder Successor doesn't exist");

    getchar();
    return 0;
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Java program to find minimum
// value node in Binary Search Tree

// A binary tree node
class Node {

    int data;
    Node left, right, parent;

    Node(int d)
    {
        data = d;
        left = right = parent = null;
    }
}

class BinaryTree {

    static Node head;

    /* Given a binary search tree and a number,
    inserts a new node with the given number in
    the correct place in the tree. Returns the new
    root pointer which the caller should then use
    (the standard trick to avoid using reference
    parameters). */
    Node insert(Node node, int data)
    {
        /* 1. If the tree is empty, return a new,
        single node */
        if (node == null) {
            return (new Node(data));
        }
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
Node temp = null;

/* 2. Otherwise, recur down the tree */
if (data <= node.data) {
    temp = insert(node.left, data);
    node.left = temp;
    temp.parent = node;
}
else {
    temp = insert(node.right, data);
    node.right = temp;
    temp.parent = node;
}

/* return the (unchanged) node pointer */
return node;
}
}

Node inOrderSuccessor(Node root, Node n)
{
    // step 1 of the above algorithm
    if (n.right != null) {
        return minValue(n.right);
    }

    // step 2 of the above algorithm
    Node p = n.parent;
    while (p != null && n == p.right) {
        n = p;
        p = p.parent;
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
/* Given a non-empty binary search
   tree, return the minimum data
   value found in that tree. Note that
   the entire tree does not need
   to be searched. */
Node minValue(Node node)
{
    Node current = node;

    /* loop down to find the leftmost leaf */
    while (current.left != null) {
        current = current.left;
    }
    return current;
}

// Driver program to test above functions
public static void main(String[] args)
{
    BinaryTree tree = new BinaryTree();
    Node root = null, temp = null, suc = null, min = null;
    root = tree.insert(root, 20);
    root = tree.insert(root, 8);
    root = tree.insert(root, 22);
    root = tree.insert(root, 4);
    root = tree.insert(root, 12);
    root = tree.insert(root, 10);
    root = tree.insert(root, 14);
    temp = root.left.right.right;
    suc = tree.inOrderSuccessor(root, temp);
    if (suc != null) {
        System.out.println(
            "Inorder successor of "
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        System.out.println(  
            "Inorder successor does not exist");  
    }  
}  
}  
  
// This code has been contributed by Mayank Jaiswal
```

### Python3

```
# Python program to find the inorder successor in a BST  
  
# A binary tree node  
class Node:  
  
    # Constructor to create a new node  
    def __init__(self, key):  
        self.data = key  
        self.left = None  
        self.right = None  
  
def inOrderSuccessor(n):  
  
    # Step 1 of the above algorithm  
    if n.right is not None:  
        return minValue(n.right)  
  
    # Step 2 of the above algorithm  
    p = n.parent  
    while( p is not None):  
        if n != p.right :
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
return p
```

```
# Given a non-empty binary search tree, return the  
# minimum data value found in that tree. Note that the  
# entire tree doesn't need to be searched
```

```
def minValue(node):  
    current = node  
  
    # loop down to find the leftmost leaf  
    while(current is not None):  
        if current.left is None:  
            break  
        current = current.left  
  
    return current
```

```
# Given a binary search tree and a number, inserts a  
# new node with the given number in the correct place  
# in the tree. Returns the new root pointer which the  
# caller should then use( the standard trick to avoid  
# using reference parameters)
```

```
def insert( node, data):  
  
    # 1) If tree is empty then return a new singly node  
    if node is None:  
        return Node(data)  
    else:  
  
        # 2) Otherwise, recur down the tree  
        if data <= node.data:  
            temp = insert(node.left, data)  
            node.left = temp
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
node.right = temp
temp.parent = node

# return the unchanged node pointer
return node

# Driver program to test above function

root = None

# Creating the tree given in the above diagram
root = insert(root, 20)
root = insert(root, 8);
root = insert(root, 22);
root = insert(root, 4);
root = insert(root, 12);
root = insert(root, 10);
root = insert(root, 14);
temp = root.left.right.right

succ = inOrderSuccessor(temp)
if succ is not None:
    print ("\nInorder Successor of % d is % d"%(temp.data, succ.data))
else:
    print ("\nInorder Successor doesn't exist")

# This code is contributed by Nikhil Kumar Singh(nickzuck_007)
```

**C#**



# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// A binary tree node
public
class Node
{
    public
    int data;
    public
    Node left, right, parent;
    public
    Node(int d)
    {
        data = d;
        left = right = parent = null;
    }
}

public class BinaryTree
{
    static Node head;

    /* Given a binary search tree and a number,
    inserts a new node with the given number in
    the correct place in the tree. Returns the new
    root pointer which the caller should then use
    (the standard trick to avoid using reference
    parameters). */
    Node insert(Node node, int data)
    {
        /* 1. If the tree is empty, return a new,
        single node */
        if (node == null)
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
else
{
    Node temp = null;

    /* 2. Otherwise, recur down the tree */
    if (data <= node.data)
    {
        temp = insert(node.left, data);
        node.left = temp;
        temp.parent = node;
    }
    else
    {
        temp = insert(node.right, data);
        node.right = temp;
        temp.parent = node;
    }

    /* return the (unchanged) node pointer */
    return node;
}
}

Node inOrderSuccessor(Node root, Node n)
{
    // step 1 of the above algorithm
    if (n.right != null)
    {
        return minValue(n.right);
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
{
    n = p;
    p = p.parent;
}
return p;
}

/* Given a non-empty binary search
   tree, return the minimum data
   value found in that tree. Note that
   the entire tree does not need
   to be searched. */
Node minValue(Node node)
{
    Node current = node;

    /* loop down to find the leftmost leaf */
    while (current.left != null)
    {
        current = current.left;
    }
    return current;
}

// Driver program to test above functions
public static void Main(String[] args)
{
    BinaryTree tree = new BinaryTree();
    Node root = null, temp = null, suc = null, min = null;
    root = tree.insert(root, 20);
    root = tree.insert(root, 8);
    root = tree.insert(root, 22);
    root = tree.insert(root, 4);
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
temp = root.left.right.right;
suc = tree.inOrderSuccessor(root, temp);
if (suc != null) {
    Console.WriteLine(
        "Inorder successor of "
        + temp.data + " is " + suc.data);
}
else {
    Console.WriteLine(
        "Inorder successor does not exist");
}
}
```

// This code is contributed by aashish1995

## Javascript

```
<script>

// JavaScript program to find minimum
// value node in Binary Search Tree

// A binary tree node
class Node {
    constructor(val) {
        this.data = val;
        this.left = null;
        this.right = null;
        this.parent = null;
    }
}
```

# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
var head;

/*
 * Given a binary search tree and a number,
 * inserts a new node with the given
 * number in the correct place in the tree.
 * Returns the new root pointer which
 * the caller should then use
 * (the standard trick to a function using reference
 * parameters).
 */
function insert(node , data) {

    /*
     * 1. If the tree is empty,
     * return a new, single node
     */
    if (node == null) {
        return (new Node(data));
    } else {

        var temp = null;

        /* 2. Otherwise, recur down the tree */
        if (data <= node.data) {
            temp = insert(node.left, data);
            node.left = temp;
            temp.parent = node;
        } else {
            temp = insert(node.right, data);
            node.right = temp;
            temp.parent = node;
        }
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
}  
}  
  
function inOrderSuccessor(root, n) {  
  
    // step 1 of the above algorithm  
    if (n.right != null) {  
        return minValue(n.right);  
    }  
  
    // step 2 of the above algorithm  
    var p = n.parent;  
    while (p != null && n == p.right) {  
        n = p;  
        p = p.parent;  
    }  
    return p;  
}  
  
/*  
 * Given a non-empty binary search tree,  
 * return the minimum data value found in  
 * that tree. Note that the entire tree  
 * does not need to be searched.  
 */  
function minValue(node) {  
    var current = node;  
  
    /* loop down to find the leftmost leaf */  
    while (current.left != null) {  
        current = current.left;  
    }  
    return current;  
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
var root = null, temp = null,
    suc = null, min = null;
root = insert(root, 20);
root = insert(root, 8);
root = insert(root, 22);
root = insert(root, 4);
root = insert(root, 12);
root = insert(root, 10);
root = insert(root, 14);
temp = root.left.right.right;
suc = inOrderSuccessor(root, temp);
if (suc != null) {
    document.write("Inorder successor of " +
        temp.data + " is " + suc.data);
} else {
    document.write(
        "Inorder successor does not exist"
    );
}
```

// This code contributed by gauravrajput1

</script>

### Output

Inorder Successor of 14 is 20

### Complexity Analysis:

## Start Your Coding Journey Now!

[Login](#)[Register](#)

As in the second case (suppose skewed tree) we have to travel all the way towards the root.

- **Auxiliary Space:**  $O(1)$ .

Due to no use of any data structure for storing values.

### Method 2 (Search from root)

Parent pointer is NOT needed in this algorithm. The Algorithm is divided into two cases on the basis of right subtree of the input node being empty or not.

**Input:** *node, root* // *node* is the node whose Inorder successor is needed.

**Output:** *succ* // *succ* is Inorder successor of *node*.

1. If right subtree of *node* is not *NULL*, then *succ* lies in right subtree. Do the following.  
Go to right subtree and return the node with minimum key value in the right subtree.
2. If right subtree of *node* is *NULL*, then start from the root and use search-like technique. Do the following.  
Travel down the tree, if a node's data is greater than root's data then go right side, otherwise, go to left side.

Below is the implementation of the above approach:

### C++

```
// C++ program for above approach
#include <iostream>
using namespace std;

/* A binary tree node has data,
the pointer to left child
and a pointer to right child */
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
struct node* left;
struct node* right;
struct node* parent;
};

struct node* minValue(struct node* node);

struct node* inOrderSuccessor(struct node* root,
                             struct node* n)
{
    // Step 1 of the above algorithm
    if (n->right != NULL)
        return minValue(n->right);

    struct node* succ = NULL;

    // Start from root and search for
    // successor down the tree
    while (root != NULL)
    {
        if (n->data < root->data)
        {
            succ = root;
            root = root->left;
        }
        else if (n->data > root->data)
            root = root->right;
        else
            break;
    }

    return succ;
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// return the minimum data value found
// in that tree. Note that the entire
// tree does not need to be searched.
struct node* minValue(struct node* node)
{
    struct node* current = node;

    // Loop down to find the leftmost leaf
    while (current->left != NULL)
    {
        current = current->left;
    }
    return current;
}
```

```
// Helper function that allocates a new
// node with the given data and NULL left
// and right pointers.
struct node* newNode(int data)
{
    struct node* node = (struct node*)
    malloc(sizeof(struct node));
    node->data = data;
    node->left = NULL;
    node->right = NULL;
    node->parent = NULL;

    return (node);
}
```

```
// Give a binary search tree and a
// number, inserts a new node with
// the given number in the correct
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// avoid using reference parameters).
struct node* insert(struct node* node,
                  int data)
{
    /* 1. If the tree is empty, return a new,
       single node */
    if (node == NULL)
        return (newNode(data));
    else
    {
        struct node* temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node->data)
        {
            temp = insert(node->left, data);
            node->left = temp;
            temp->parent = node;
        }
        else
        {
            temp = insert(node->right, data);
            node->right = temp;
            temp->parent = node;
        }

        /* Return the (unchanged) node pointer */
        return node;
    }
}

// Driver code
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Creating the tree given in the above diagram
root = insert(root, 20);
root = insert(root, 8);
root = insert(root, 22);
root = insert(root, 4);
root = insert(root, 12);
root = insert(root, 10);
root = insert(root, 14);
temp = root->left->right->right;

// Function Call
succ = inOrderSuccessor(root, temp);
if (succ != NULL)
    cout << "\n Inorder Successor of "
         << temp->data << " is " << succ->data;
else
    cout << "\n Inorder Successor doesn't exist";

getchar();
return 0;
}

// This code is contributed by shivanisinghss2110
```

**C**

```
// C program for above approach
#include <stdio.h>
#include <stdlib.h>
```

# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
struct node
{
    int data;
    struct node* left;
    struct node* right;
    struct node* parent;
};

struct node* minValue(struct node* node);

struct node* inOrderSuccessor(
    struct node* root,
    struct node* n)
{
    // step 1 of the above algorithm
    if (n->right != NULL)
        return minValue(n->right);

    struct node* succ = NULL;

    // Start from root and search for
    // successor down the tree
    while (root != NULL)
    {
        if (n->data < root->data)
        {
            succ = root;
            root = root->left;
        }
        else if (n->data > root->data)
            root = root->right;
        else
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
    return succ;
}

/* Given a non-empty binary search tree,
   return the minimum data
   value found in that tree. Note that
   the entire tree does not need
   to be searched. */
struct node* minValue(struct node* node)
{
    struct node* current = node;

    /* loop down to find the leftmost leaf */
    while (current->left != NULL)
    {
        current = current->left;
    }
    return current;
}

/* Helper function that allocates a new
   node with the given data and
   NULL left and right pointers. */
struct node* newNode(int data)
{
    struct node* node = (struct node*)
        malloc(sizeof(
            struct node));
    node->data = data;
    node->left = NULL;
    node->right = NULL;
    node->parent = NULL;
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
/* Give a binary search tree and
a number, inserts a new node with
the given number in the correct
place in the tree. Returns the new
root pointer which the caller should
then use (the standard trick to
avoid using reference parameters). */
struct node* insert(struct node* node,
                   int data)
{
    /* 1. If the tree is empty, return a new,
    single node */
    if (node == NULL)
        return (newNode(data));
    else
    {
        struct node* temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node->data)
        {
            temp = insert(node->left, data);
            node->left = temp;
            temp->parent = node;
        }
        else
        {
            temp = insert(node->right, data);
            node->right = temp;
            temp->parent = node;
        }

        /* return the (unchanged) node pointer */
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
/* Driver program to test above functions*/
int main()
{
    struct node *root = NULL, *temp, *succ, *min;

    // creating the tree given in the above diagram
    root = insert(root, 20);
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
    temp = root->left->right->right;

    // Function Call
    succ = inOrderSuccessor(root, temp);
    if (succ != NULL)
        printf(
            "\n Inorder Successor of %d is %d ",
            temp->data, succ->data);
    else
        printf("\n Inorder Successor doesn't exist");

    getchar();
    return 0;
}

// Thanks to R.Srinivasan for suggesting this method.
```





## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Java program for above approach
class GFG
{
    /* A binary tree node has data,
       the pointer to left child
       and a pointer to right child */
    static class node
    {
        int data;
        node left;
        node right;
        node parent;
    };

    static node inOrderSuccessor(
        node root,
        node n)
    {
        // step 1 of the above algorithm
        if (n.right != null)
            return minValue(n.right);

        node succ = null;

        // Start from root and search for
        // successor down the tree
        while (root != null)
        {
            if (n.data < root.data)
            {
                succ = root;
            }
        }
    }
}
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        root = root.right;
    else
        break;
}
return succ;
}

/* Given a non-empty binary search tree,
return the minimum data
value found in that tree. Note that
the entire tree does not need
to be searched. */
static node minValue(node node)
{
    node current = node;

    /* loop down to find the leftmost leaf */
    while (current.left != null)
    {
        current = current.left;
    }
    return current;
}

/* Helper function that allocates a new
node with the given data and
null left and right pointers. */
static node newNode(int data)
{
    node node = new node();
    node.data = data;
    node.left = null;
    node.right = null;
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
}

/* Give a binary search tree and
a number, inserts a new node with
the given number in the correct
place in the tree. Returns the new
root pointer which the caller should
then use (the standard trick to
astatic void using reference parameters). */
static node insert(node node,
                   int data)
{
    /* 1. If the tree is empty, return a new,
    single node */
    if (node == null)
        return (newNode(data));
    else
    {
        node temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node.data)
        {
            temp = insert(node.left, data);
            node.left = temp;
            temp.parent = node;
        }
        else
        {
            temp = insert(node.right, data);
            node.right = temp;
            temp.parent = node;
        }
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        return node;
    }
}

/* Driver program to test above functions*/
public static void main(String[] args)
{
    node root = null, temp, succ, min;

    // creating the tree given in the above diagram
    root = insert(root, 20);
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
    temp = root.left.right.right;

    // Function Call
    succ = inOrderSuccessor(root, temp);
    if (succ != null)
        System.out.printf(
            "\n Inorder Successor of %d is %d ",
            temp.data, succ.data);
    else
        System.out.printf("\n Inorder Successor doesn't exist");
}
}

// This code is contributed by gauravrajput1
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
# Python program to find
# the inorder successor in a BST

# A binary tree node
class Node:

    # Constructor to create a new node
    def __init__(self, key):
        self.data = key
        self.left = None
        self.right = None

def inOrderSuccessor(root, n):

    # Step 1 of the above algorithm
    if n.right is not None:
        return minValue(n.right)

    # Step 2 of the above algorithm
    succ=None

    while( root):
        if(root.data<n.data):
            root=root.right
        elif(root.data>n.data):
            succ=root
            root=root.left
        else:
            break
    return succ

# Given a non-empty binary search tree,
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
def minValue(node):
    current = node

    # loop down to find the leftmost leaf
    while(current is not None):
        if current.left is None:
            break
        current = current.left

    return current

# Given a binary search tree
# and a number, inserts a
# new node with the given
# number in the correct place
# in the tree. Returns the
# new root pointer which the
# caller should then use
# (the standard trick to avoid
# using reference parameters)
def insert( node, data):

    # 1) If tree is empty
    # then return a new singly node
    if node is None:
        return Node(data)
    else:

        # 2) Otherwise, recur down the tree
        if data <= node.data:
            temp = insert(node.left, data)
            node.left = temp
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        node.right = temp
        temp.parent = node

    # return the unchanged node pointer
    return node

# Driver program to test above function
if __name__ == "__main__":
    root = None

    # Creating the tree given in the above diagram
    root = insert(root, 20)
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
    temp = root.left.right

    succ = inOrderSuccessor( root, temp)
    if succ is not None:
        print("Inorder Successor of" ,
              temp.data , "is" , succ.data)
    else:
        print("InInorder Successor doesn't exist")
```

**C#**

// C# program for above approach

# Start Your Coding Journey Now!

[Login](#)[Register](#)

{

```
/* A binary tree node has data,  
the pointer to left child  
and a pointer to right child */
```

```
public
```

```
class node
```

```
{
```

```
public
```

```
int data;
```

```
public
```

```
node left;
```

```
public
```

```
node right;
```

```
public
```

```
node parent;
```

```
};
```

```
static node inOrderSuccessor(  
node root,  
node n)
```

```
{
```

```
// step 1 of the above algorithm
```

```
if (n.right != null)
```

```
return minValue(n.right);
```

```
node succ = null;
```

```
// Start from root and search for
```

```
// successor down the tree
```

```
while (root != null)
```

```
{
```





## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        root = root.left;
    }
    else if (n.data > root.data)
        root = root.right;
    else
        break;
}
return succ;
}

/* Given a non-empty binary search tree,
return the minimum data
value found in that tree. Note that
the entire tree does not need
to be searched. */
static node minValue(node node)
{
    node current = node;

    /* loop down to find the leftmost leaf */
    while (current.left != null)
    {
        current = current.left;
    }
    return current;
}

/* Helper function that allocates a new
node with the given data and
null left and right pointers. */
static node newNode(int data)
{
    node node = new node();
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
node.parent = null;

return (node);
}

/* Give a binary search tree and
a number, inserts a new node with
the given number in the correct
place in the tree. Returns the new
root pointer which the caller should
then use (the standard trick to
astatic void using reference parameters). */
static node insert(node node,
                   int data)
{

    /* 1. If the tree is empty, return a new,
    single node */
    if (node == null)
        return (newNode(data));
    else
    {
        node temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node.data)
        {
            temp = insert(node.left, data);
            node.left = temp;
            temp.parent = node;
        }
        else
        {

```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
}

/* return the (unchanged) node pointer */
return node;
}
}

/* Driver program to test above functions*/
public static void Main(String[] args)
{
    node root = null, temp, succ;

    // creating the tree given in the above diagram
    root = insert(root, 20);
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
    temp = root.left.right.right;

    // Function Call
    succ = inOrderSuccessor(root, temp);
    if (succ != null)
        Console.Write(
            "\n Inorder Successor of {0} is {1} ",
            temp.data, succ.data);
    else
        Console.WriteLine("\n Inorder Successor doesn't exist");
}
}
```



# Start Your Coding Journey Now!

[Login](#)[Register](#)

## Javascript

```
<script>

class Node
{
    constructor(data)
    {
        this.data=data;;
        this.left=this.right=this.parent=null;
    }
}

function inOrderSuccessor(root,n)
{
    // step 1 of the above algorithm
    if (n.right != null)
        return minValue(n.right);

    let succ = null;

    // Start from root and search for
    // successor down the tree
    while (root != null)
    {
        if (n.data < root.data)
        {
            succ = root;
            root = root.left;
        }
        else if (n.data > root.data)
            root = root.right;
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
    return succ;
}

function minValue(node)
{
    let current = node;

    /* loop down to find the leftmost leaf */
    while (current.left != null)
    {
        current = current.left;
    }
    return current;
}

function insert(node,data)
{
    /* 1. If the tree is empty, return a new,
       single node */
    if (node == null)
        return (new Node(data));
    else
    {
        let temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node.data)
        {
            temp = insert(node.left, data);
            node.left = temp;
            temp.parent = node;
        }
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        node.right = temp;
        temp.parent = node;
    }

    /* return the (unchanged) node pointer */
    return node;
}

let root = null, temp, succ, min;

// creating the tree given in the above diagram
root = insert(root, 20);
root = insert(root, 8);
root = insert(root, 22);
root = insert(root, 4);
root = insert(root, 12);
root = insert(root, 10);
root = insert(root, 14);
temp = root.left.right.right;

// Function Call
succ = inOrderSuccessor(root, temp);
if (succ != null)
    document.write(
        "<br> Inorder Successor of "+temp.data+" is "+
        succ.data);
else
    document.write("<br> Inorder Successor doesn't exist");

// This code is contributed by unknown2108

</script>
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

Inorder Successor of 14 is 20

### Complexity Analysis:

- **Time Complexity:**  $O(h)$ , where  $h$  is the height of the tree.  
In the worst case as explained above we travel the whole height of the tree
- **Auxiliary Space:**  $O(1)$ .  
Due to no use of any data structure for storing values.

**Method 3 (Inorder traversal)** An inorder transversal of BST produces a sorted sequence. Therefore, we perform an inorder traversal. The first encountered node with value greater than the node is the inorder successor.

**Input:** node, root // node is the node whose inorder successor is needed.

**Output:** succ // succ is Inorder successor of node.

Below is the implementation of the above approach:

### C++

```
// C++ program for above approach
#include <iostream>
using namespace std;

/* A binary tree node has data,
the pointer to left child
and a pointer to right child */
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
struct node* left;
struct node* right;
struct node* parent;
};
struct node* newNode(int data);

void inorderTraversal(struct node* root,
                    struct node* n,
                    struct node* succ)
{
    if(root==nullptr) { return; }

    inorderTraversal(root->left, n, succ);
    if(root->data>n->data && !succ->left) { succ->left = root; return; }
    inorderTraversal(root->right, n, succ);
}

struct node* inorderSuccessor(struct node* root,
                             struct node* n)
{
    struct node* succ = newNode(0);
    inorderTraversal(root, n, succ);
    return succ->left;
}

// Helper function that allocates a new
// node with the given data and NULL left
// and right pointers.
struct node* newNode(int data)
{
    struct node* node = (struct node*)
        malloc(sizeof(struct node));
    node->data = data;
```





## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
    return (node);
}

// Give a binary search tree and a
// number, inserts a new node with
// the given number in the correct
// place in the tree. Returns the new
// root pointer which the caller should
// then use (the standard trick to
// avoid using reference parameters).
struct node* insert(struct node* node,
                    int data)
{
    /* 1. If the tree is empty, return a new,
       single node */
    if (node == NULL)
        return (newNode(data));
    else
    {
        struct node* temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node->data)
        {
            temp = insert(node->left, data);
            node->left = temp;
            temp->parent = node;
        }
        else
        {
            temp = insert(node->right, data);
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        /* Return the (unchanged) node pointer */
        return node;
    }
}

// Driver code
int main()
{
    struct node *root = NULL, *temp, *succ, *min;

    // Creating the tree given in the above diagram
    root = insert(root, 20);
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
    temp = root->left->right->right;

    // Function Call
    succ = inOrderSuccessor(root, temp);
    if (succ != NULL)
        cout << "\n Inorder Successor of "
              << temp->data << " is " << succ->data;
    else
        cout << "\n Inorder Successor doesn't exist";

    //getchar();
    return 0;
}
```



# Start Your Coding Journey Now!

[Login](#)[Register](#)

## Java

```
// Java program for above approach
import java.util.*;

class GFG {

    /*
     * A binary tree node has data, the pointer to left child and a pointer to right
     * child
     */
    static class node {
        int data;
        node left;
        node right;
        node parent;
    };

    static void inOrderTraversal(node root) {
        if (root == null) {
            return;
        }

        inOrderTraversal(root.left);
        System.out.print(root.data);
        inOrderTraversal(root.right);
    }

    static void inOrderTraversal(node root, node n, node succ) {
        if (root == null) {
            return;
        }

        inOrderTraversal(root.left, n, succ);
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
}
inOrderTraversal(root.right, n, succ);
}

static node inOrderSuccessor(node root, node n) {
    node succ = newNode(0);
    inOrderTraversal(root, n, succ);
    return succ.left;
}

// Helper function that allocates a new
// node with the given data and null left
// and right pointers.
static node newNode(int data) {
    node node = new node();

    node.data = data;
    node.left = null;
    node.right = null;
    node.parent = null;

    return (node);
}

// Give a binary search tree and a
// number, inserts a new node with
// the given number in the correct
// place in the tree. Returns the new
// root pointer which the caller should
// then use (the standard trick to
// astatic void using reference parameters).
static node insert(node node, int data) {
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
if (node == null)
    return (newNode(data));
else {
    node temp;

    /* 2. Otherwise, recur down the tree */
    if (data <= node.data) {
        temp = insert(node.left, data);
        node.left = temp;
        temp.parent = node;
    } else {
        temp = insert(node.right, data);
        node.right = temp;
        temp.parent = node;
    }

    /* Return the (unchanged) node pointer */
    return node;
}

// Driver code
public static void main(String[] args) {
    node root = null, temp, succ, min;

    // Creating the tree given in the above diagram
    root = insert(root, 20);
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
succ = inOrderSuccessor(root, temp);
if (succ != null)
    System.out.print("\n Inorder Successor of " + temp.data + " is " + succ.data);
else
    System.out.print("\n Inorder Successor doesn't exist");
}
}
```

// This code is contributed by Rajput-Ji

### C#

```
// C# program for above approach
using System;
using System.Collections.Generic;

public class GFG {

    /*
     * A binary tree node has data, the pointer to left child and a pointer to right
     * child
     */
    public class node {
        public int data;
        public node left;
        public node right;
        public node parent;
    };

    static void inOrderTraversal(node root) {
        if (root == null) {
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
inOrderTraversal(root.left);
Console.WriteLine(root.data);
inOrderTraversal(root.right);
}
static void inOrderTraversal(node root, node n, node succ) {
    if (root == null) {
        return;
    }

    inOrderTraversal(root.left, n, succ);
    if (root.data > n.data && succ.left == null) {
        succ.left = root;
        return;
    }
    inOrderTraversal(root.right, n, succ);
}

static node inOrderSuccessor(node root, node n) {
    node succ = newNode(0);
    inOrderTraversal(root, n, succ);
    return succ.left;
}

// Helper function that allocates a new
// node with the given data and null left
// and right pointers.
static node newNode(int data) {
    node node = new node();

    node.data = data;
    node.left = null;
    node.right = null;
    node.parent = null;
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Give a binary search tree and a
// number, inserts a new node with
// the given number in the correct
// place in the tree. Returns the new
// root pointer which the caller should
// then use (the standard trick to
// astatic void using reference parameters).
static node insert(node node, int data) {

    /*
     * 1. If the tree is empty, return a new, single node
     */
    if (node == null)
        return (newNode(data));
    else {
        node temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node.data) {
            temp = insert(node.left, data);
            node.left = temp;
            temp.parent = node;
        } else {
            temp = insert(node.right, data);
            node.right = temp;
            temp.parent = node;
        }

        /* Return the (unchanged) node pointer */
        return node;
    }
}
```





## Start Your Coding Journey Now!

[Login](#)[Register](#)


```
node root = null, temp, succ, min;

// Creating the tree given in the above diagram
root = insert(root, 20);
root = insert(root, 8);
root = insert(root, 22);
root = insert(root, 4);
root = insert(root, 12);
root = insert(root, 10);
root = insert(root, 14);
temp = root.left.right.right;

// Function Call
succ = inOrderSuccessor(root, temp);
if (succ != null)
    Console.WriteLine("\n Inorder Successor of " + temp.data + " is " + succ.data);
else
    Console.WriteLine("\n Inorder Successor doesn't exist");
}
}
```

// This code contributed by Rajput-Ji

## Javascript



```
<script>
// javascript program for above approach

/*
 * A binary tree node has data, the pointer to left child and a pointer to right
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
    constructor(){
    this.data = 0;
    this.left = null;
    this.right = null;
    this.parent = null;
}
}

function inOrderTraversal( root) {
    if (root == null) {
        return;
    }

    inOrderTraversal(root.left);
    document.write(root.data);
    inOrderTraversal(root.right);
}

function inOrderTraversal( root, n, succ) {
    if (root == null) {
        return;
    }

    inOrderTraversal(root.left, n, succ);
    if (root.data > n.data && succ.left == null) {
        succ.left = root;
        return;
    }
    inOrderTraversal(root.right, n, succ);
}

function inOrderSuccessor( root, n) {
    var succ = newNode(0);
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Helper function that allocates a new
// node with the given data and null left
// and right pointers.
function newNode(data) {
    var node = new Node();

    node.data = data;
    node.left = null;
    node.right = null;
    node.parent = null;

    return (node);
}

// Give a binary search tree and a
// number, inserts a new node with
// the given number in the correct
// place in the tree. Returns the new
// root pointer which the caller should
// then use (the standard trick to
// afunction using reference parameters).
function insert( node , data) {

    /*
     * 1. If the tree is empty, return a new, single node
     */
    if (node == null)
        return (newNode(data));
    else {
        var temp;

        /* 2. Otherwise, recur down the tree */
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        temp.parent = node;
    } else {
        temp = insert(node.right, data);
        node.right = temp;
        temp.parent = node;
    }

    /* Return the (unchanged) node pointer */
    return node;
}
}
```

// Driver code

```
var root = null, temp, succ, min;

// Creating the tree given in the above diagram
root = insert(root, 20);
root = insert(root, 8);
root = insert(root, 22);
root = insert(root, 4);
root = insert(root, 12);
root = insert(root, 10);
root = insert(root, 14);
temp = root.left.right.right;

// Function Call
succ = inOrderSuccessor(root, temp);
if (succ != null)
    document.write("\n Inorder Successor of " + temp.data +
        " is " + succ.data);
else
    document.write("\n Inorder Successor doesn't exist");
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

### Output

Inorder Successor of 14 is 20

### Complexity Analysis:

- **Time Complexity:**  $O(h)$ , where  $h$  is the height of the tree. In the worst case as explained above we travel the whole height of the tree.
- **Auxiliary Space:**  $O(1)$ . Due to no use of any data structure for storing values.

**Method 4 (Inorder traversal iterative)** this method is inspired from the method 3 but with iterative and easy to understand approach.

**Input:** node, root // node is the node whose inorder successor is needed.

**Output:** succ // succ is Inorder successor of node.

Below is the implementation of the above approach:

### Java

```
// Java program for above approach
import java.util.*;

class GFG {

    /*
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
static class node {
    int data;
    node left;
    node right;
    node parent;
};

static void inOrderTraversal(node root) {
    if (root == null) {
        return;
    }

    inOrderTraversal(root.left);
    System.out.print(root.data);
    inOrderTraversal(root.right);
}

public static node inOrderSuccessor(node root, int key) {
    Deque<node> stack = new ArrayDeque<>();
    while(root != null || !stack.isEmpty()){
        while(root != null){
            stack.push(root);
            root = root.left;
        }
        root = stack.pop();
        if(root.data > key)
            return root;
        root = root.right;
    }
    return null;
}

// Helper function that allocates a new
// node with the given data and null left
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
node.data = data;
node.left = null;
node.right = null;
node.parent = null;

return (node);
}

// Give a binary search tree and a
// number, inserts a new node with
// the given number in the correct
// place in the tree. Returns the new
// root pointer which the caller should
// then use (the standard trick to
// astatic void using reference parameters).
static node insert(node node, int data) {

    /*
     * 1. If the tree is empty, return a new, single node
     */
    if (node == null)
        return (newNode(data));
    else {
        node temp;

        /* 2. Otherwise, recur down the tree */
        if (data <= node.data) {
            temp = insert(node.left, data);
            node.left = temp;
            temp.parent = node;
        } else {
            temp = insert(node.right, data);
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        /* Return the (unchanged) node pointer */
        return node;
    }
}

// Driver code
public static void main(String[] args) {
    node root = null, temp, succ, min;

    // Creating the tree given in the above diagram
    root = insert(root, 20);
    root = insert(root, 8);
    root = insert(root, 22);
    root = insert(root, 4);
    root = insert(root, 12);
    root = insert(root, 10);
    root = insert(root, 14);
    temp = root.left.right.right;

    // Function Call
    succ = inOrderSuccessor(root, temp.data);
    if (succ != null)
        System.out.print("\n Inorder Successor of " + temp.data + " is " + succ.data);
    else
        System.out.print("\n Inorder Successor doesn't exist");

}
}
```

// This code is contributed by Nitin Dhamija





# Start Your Coding Journey Now!

[Login](#)[Register](#)

Inorder Successor of 14 is 20

## Complexity Analysis:

- **Time Complexity:**  $O(h)$ , where  $h$  is the height of the tree. In the worst case as explained above we travel the whole height of the tree
- **Auxiliary Space:**  $O(1)$ . Due to no use of any data structure for storing values.

**AMAZON TEST SERIES**  
To Help Crack Your SDE Interview

[Enrol Now](#)

Like 71

Next

Inorder predecessor and successor for a  
given key in BST



# Start Your Coding Journey Now!

[Login](#)[Register](#)

## 01 Inorder predecessor and successor for a given key in BST | Iterative Approach

25, Jun 18

## 02 Inorder predecessor and successor for a given key in BST

25, Jul 14

## 03 Pre-Order Successor of all nodes in Binary Search Tree

14, Aug 19

## 04 Check if an array represents Inorder of Binary Search tree or not

29, Jun 17

## 05 Construct a Binary Tree from Postorder and Inorder

26, May 16

## 06 Binary Tree to Binary Search Tree Conversion using STL set

22, Mar 18

## 07 Binary Tree to Binary Search Tree Conversion

15, Jun 12

## 08 Difference between Binary Tree and Binary Search Tree

31, Oct 19



Article Contributed By :



GeeksforGeeks

Vote for difficulty

Current difficulty : [Medium](#)

Easy

Normal

Medium

Hard

Expert

## Start Your Coding Journey Now!

[Login](#)[Register](#)

**Improved By :** [bidibaaz123](#), [vipinyadav15799](#), [reapedjuggler](#), [pancudaniel](#), [aashish1995](#), [GauravRajput1](#), [unknown2108](#), [surinderdawra388](#), [shivanisinghss2110](#), [as5853535](#), [jaisw7](#), [amartyaghoshgfg](#), [Rajput-Ji](#), [nitin dhamija](#), [hardikkoriintern](#)

**Article Tags :** [Amazon](#), [Morgan Stanley](#), [Binary Search Tree](#)

**Practice Tags :** [Morgan Stanley](#), [Amazon](#), [Binary Search Tree](#)

[Improve Article](#)[Report Issue](#)

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

[Load Comments](#)

A-143, 9th Floor, Sovereign Corporate Tower,  
Sector-136, Noida, Uttar Pradesh - 201305

[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)



## Start Your Coding Journey Now!

[Login](#)[Register](#)

### Company

[About Us](#)[Careers](#)[In Media](#)[Contact Us](#)[Privacy Policy](#)[Copyright Policy](#)

### Learn

[Algorithms](#)[Data Structures](#)[SDE Cheat Sheet](#)[Machine learning](#)[CS Subjects](#)[Video Tutorials](#)[Courses](#)

### News

[Top News](#)[Technology](#)[Work & Career](#)[Business](#)[Finance](#)[Lifestyle](#)[Knowledge](#)

### Languages

[Python](#)[Java](#)[CPP](#)[Golang](#)[C#](#)[SQL](#)[Kotlin](#)

### Web Development

[Web Tutorials](#)[Django Tutorial](#)[HTML](#)[JavaScript](#)[Bootstrap](#)[ReactJS](#)[NodeJS](#)

### Contribute

[Write an Article](#)[Improve an Article](#)[Pick Topics to Write](#)[Write Interview Experience](#)[Internships](#)[Video Internship](#)

@geeksforgeeks , Some rights reserved

