


Array Matrix Strings Hashing Linked List Stack Queue Binary Tree Binary Search Tree Heap Graph Searching Sorting D

Find the closest element in Binary Search Tree

Difficulty Level: Medium • Last Updated: 28 Jun, 2021

Given a <u>binary search tree</u> and a target node K. The task is to find the node with minimum absolute difference with given target value K.





Login

Register

Input: k = 18

Output: 17

Input: k = 12

Output: 9

Recommended: Please solve it on "*PRACTICE*" first, before moving on to the solution.

A **simple solution** for this problem is to store Inorder traversal of given binary search tree in an auxiliary array and then by taking absolute difference of each element find the node having minimum absolute difference with given target value K in linear time.

An **efficient solution** for this problem is to take advantage of characteristics of BST. Here is the algorithm to solve this problem :

- If target value K is present in given <u>BST</u>, then it's the node having minimum absolute difference.
- If target value K is less than the value of current node then move to the left child.
- If target value K is greater than the value of current node then move to the right child.



Java

Python3

C#

Login

```
#include<bits/stdc++.h>
using namespace std;
/* A binary tree node has key, pointer to left child
and a pointer to right child */
struct Node
    int key;
    struct Node* left, *right;
};
/* Utility that allocates a new node with the
  given key and NULL left and right pointers. */
struct Node* newnode(int key)
    struct Node* node = new (struct Node);
    node->key = key;
    node->left = node->right = NULL;
    return (node);
// Function to find node with minimum absolute
// difference with given K
// min diff --> minimum difference till now
// min diff key --> node having minimum absolute
                     difference with K
void maxDiffUtil(struct Node *ptr, int k, int &min_diff,
                                      int &min_diff_key)
    if (ptr == NULL)
```

Login

```
return;
   // update min diff and min diff key by checking
   // current node value
   if (min diff > abs(ptr->key - k))
       min diff = abs(ptr->key - k);
       min diff key = ptr->key;
   // if k is less than ptr->key then move in
   // left subtree else in right subtree
   if (k < ptr->key)
       maxDiffUtil(ptr->left, k, min diff, min diff key);
    else
       maxDiffUtil(ptr->right, k, min diff, min diff key);
}
// Wrapper over maxDiffUtil()
int maxDiff(Node *root, int k)
{
   // Initialize minimum difference
   int min diff = INT MAX, min diff key = -1;
   // Find value of min diff key (Closest key
   // in tree with k)
   maxDiffUtil(root, k, min_diff, min_diff_key);
    return min_diff_key;
```

Login

Register

```
root->left = newnode(4);
root->right = newnode(17);
root->left->left = newnode(3);
root->left->right = newnode(6);
root->left->right->left = newnode(5);
root->left->right->right = newnode(7);
root->right->right = newnode(22);
root->right->right->left = newnode(20);
int k = 18;
cout << maxDiff(root, k);
return 0;</pre>
```

Java

```
// Recursive Java program to find key closest to k
// in given Binary Search Tree.

class solution
{
    static int min_diff, min_diff_key;

/* A binary tree node has key, pointer to left child and a pointer to right child */
static class Node
{
    int key;
```

Login

```
static Node newnode(int key)
    Node node = new Node();
    node.key = key;
    node.left = node.right = null;
    return (node);
// Function to find node with minimum absolute
// difference with given K
// min diff -. minimum difference till now
// min diff key -. node having minimum absolute
                     difference with K
static void maxDiffUtil(Node ptr, int k)
    if (ptr == null)
       return ;
   // If k itself is present
    if (ptr.key == k)
       min diff key = k;
        return;
    // update min_diff and min_diff_key by checking
    // current node value
    if (min_diff > Math.abs(ptr.key - k))
```

Login

```
// left subtree else in right subtree
   if (k < ptr.key)</pre>
       maxDiffUtil(ptr.left, k);
   else
       maxDiffUtil(ptr.right, k);
// Wrapper over maxDiffUtil()
static int maxDiff(Node root, int k)
   // Initialize minimum difference
   // Find value of min diff key (Closest key
   // in tree with k)
   maxDiffUtil(root, k);
   return min_diff_key;
// Driver program to run the case
public static void main(String args[])
    Node root = newnode(9);
               = newnode(4);
    root.left
   root.right = newnode(17);
   root.left.left = newnode(3);
   root.left.right = newnode(6);
   root.left.right.left = newnode(5);
```

Login

Register

```
}
}
//contributed by Arnab Kundu
```

Python3

```
# Recursive Python program to find key
# closest to k in given Binary Search Tree.
# Utility that allocates a new node with the
# given key and NULL left and right pointers.
class newnode:
    # Constructor to create a new node
    def init (self, data):
        self.key = data
        self.left = None
        self.right = None
# Function to find node with minimum
# absolute difference with given K
# min diff --> minimum difference till now
# min diff key --> node having minimum absolute
                    difference with K
def maxDiffUtil(ptr, k, min_diff, min_diff_key):
    if ptr == None:
        return
```

Login

```
# checking current node value
    if min diff > abs(ptr.key - k):
       min diff = abs(ptr.key - k)
       min diff key[0] = ptr.key
   # if k is less than ptr->key then move
   # in left subtree else in right subtree
    if k < ptr.key:</pre>
       maxDiffUtil(ptr.left, k, min diff,
                                 min diff key)
    else:
       maxDiffUtil(ptr.right, k, min diff,
                                  min diff key)
# Wrapper over maxDiffUtil()
def maxDiff(root, k):
   # Initialize minimum difference
   min diff, min diff key = 99999999999, [-1]
    # Find value of min diff key (Closest
   # key in tree with k)
   maxDiffUtil(root, k, min diff, min diff key)
    return min_diff_key[0]
# Driver Code
if __name__ == '__main__':
    root = newnode(9)
    root.left = newnode(4)
```

Login

Register

```
root.right.right.left = newnode(20)
k = 18
print(maxDiff(root, k))

# This code is contributed by PranchalK
```

C#

```
using System;
// Recursive C# program to find key closest to k
// in given Binary Search Tree.
public class solution
     public static int min_diff, min_diff_key;
/* A binary tree node has key, pointer to left child
and a pointer to right child */
public class Node
    public int key;
     public Node left, right;
  Utility that allocates a new node with the
```

Login

```
node.key = key;
    node.left = node.right = null;
    return (node);
// Function to find node with minimum absolute
// difference with given K
// min diff -. minimum difference till now
// min diff key -. node having minimum absolute
                     difference with K
//
public static void maxDiffUtil(Node ptr, int k)
    if (ptr == null)
        return;
   // If k itself is present
   if (ptr.key == k)
       min_diff_key = k;
       return;
    // update min_diff and min_diff_key by checking
    // current node value
    if (min_diff > Math.Abs(ptr.key - k))
       min_diff = Math.Abs(ptr.key - k);
       min_diff_key = ptr.key;
```

Login

```
maxDiffUtil(ptr.left, k);
   else
       maxDiffUtil(ptr.right, k);
// Wrapper over maxDiffUtil()
public static int maxDiff(Node root, int k)
   // Initialize minimum difference
   min diff = 999999999;
   min diff key = -1;
   // Find value of min diff key (Closest key
   // in tree with k)
   maxDiffUtil(root, k);
    return min_diff_key;
// Driver program to run the case
public static void Main(string[] args)
    Node root = newnode(9);
    root.left = newnode(4);
    root.right = newnode(17);
    root.left.left = newnode(3);
```

Login

Register

```
Console.WriteLine(maxDiff(root, k));
}
}
// This code is contributed by Shrikant13
```

Output:

17

Time complexity: O(h) where h is height of given Binary Search Tree.

Reference:

<u>http://stackoverflow.com/questions/6209325/how-to-find-the-closest-element-to-a-given-key-value-in-a-binary-search-tree</u>



Login

Register

This article is contributed by <u>Shashank Mishra (Gullu)</u>. If you like GeeksforGeeks and would like to contribute, you can also write an article using <u>write.geeksforgeeks.org</u> or mail your article to review-team@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Login

Register

To Help Crack Your SDE Interview

Enrol Now



Like 17

Previous

Find pairs with given sum such that pair elements lie in different BSTs

Next

Find the closest element in Binary Search Tree | Space Efficient Method



Login

Register

| Space Efficient Method

18, Jun 18

using SIL set

22, Mar 18

- Complexity of different operations in Binary tree, Binary Search Tree and AVL tree 19, Jan 18
- Binary Tree to Binary Search Tree Conversion 15, Jun 12

Find the closest leaf in a Binary Tree 21, Dec 14

- Minimum swap required to convert binary tree to binary search tree 28, Jan 17
- Difference between Binary Tree and Binary Search Tree

Binary Search Tree | Set 1 (Search and Insertion)

31, Oct 19

30, Jan 14

Article Contributed By:

Vote for difficulty

Current difficulty: Medium

GeeksforGeeks

Easy

Normal

Medium

Hard

Expert

Login

Register

Improve Article

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments



5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

Learn

News

Languages

Web Development

Contribute

About Us

Algorithms

Python

Web Tutorials

Write an Article

Login

Register

Copyright Policy Video Tutorials Finance SQL Bootstrap Video Internship

@geeksforgeeks, Some rights reserved

