



[Data Structures](#) [Algorithms](#) [Interview Preparation](#) [Topic-wise Practice](#) [C++](#) [Java](#) [Python](#) [Competitive Programming](#) [Machi](#)

Print all pairs with given sum

Difficulty Level : Easy • Last Updated : 01 Jul, 2021

Given an array of integers, and a number 'sum', print all pairs in the array whose sum is equal to 'sum'.

Examples :

Input : arr[] = {1, 5, 7, -1, 5},
sum = 6

Output : (1, 5) (7, -1) (1, 5)

Input : arr[] = {2, 5, 17, -1},
sum = 7

Output : (2, 5)

[Recommended: Please solve it on "**PRACTICE**" first, before moving on to the solution.](#)



A **simple solution** is to traverse each element and check if there's another number in the array which can be added to it to give sum.

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
using namespace std;

// Returns number of pairs in arr[0..n-1]
// with sum equal to 'sum'
int printPairs(int arr[], int n, int sum)
{
    int count = 0; // Initialize result

    // Consider all possible pairs and check
    // their sums
    for (int i = 0; i < n; i++)
        for (int j = i + 1; j < n; j++)
            if (arr[i] + arr[j] == sum)
                cout << "(" << arr[i] << ", "
                    << arr[j] << ")" << endl;
}

// Driver function to test the above function
int main()
{
    int arr[] = { 1, 5, 7, -1, 5 };
    int n = sizeof(arr) / sizeof(arr[0]);
    int sum = 6;
    printPairs(arr, n, sum);
    return 0;
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Print pairs with given sum.
```

```
class GFG {  
  
    // Returns number of pairs  
    // in arr[0..n-1] with sum  
    // equal to 'sum'  
    static void printPairs(int arr[],  
                           int n, int sum)  
    {  
        // int count = 0;  
  
        // Consider all possible pairs  
        // and check their sums  
        for (int i = 0; i < n; i++)  
            for (int j = i + 1; j < n; j++)  
                if (arr[i] + arr[j] == sum)  
                    System.out.println("(" + arr[i] + ", " + arr[j] + ")");  
    }  
  
    // Driver Code  
    public static void main(String[] arg)  
    {  
        int arr[] = { 1, 5, 7, -1, 5 };  
        int n = arr.length;  
        int sum = 6;  
        printPairs(arr, n, sum);  
    }  
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
# Python 3 implementation
# of simple method to find
# print pairs with given sum.

# Returns number of pairs
# in arr[0..n-1] with sum
# equal to 'sum'
def printPairs(arr, n, sum):

    # count = 0

    # Consider all possible
    # pairs and check their sums
    for i in range(0, n):
        for j in range(i + 1, n):
            if (arr[i] + arr[j] == sum):
                print("(", arr[i],
                    ", ", arr[j],
                    ")", sep = "")

# Driver Code
arr = [1, 5, 7, -1, 5]
n = len(arr)
sum = 6
printPairs(arr, n, sum)

# This code is contributed
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// C# implementation of simple
// method to find print pairs
// with given sum.
using System;

class GFG {
    // Returns number of pairs
    // in arr[0..n-1] with sum
    // equal to 'sum'
    static void printPairs(int[] arr,
                           int n, int sum)
    {
        // int count = 0;

        // Consider all possible pairs
        // and check their sums
        for (int i = 0; i < n; i++)
            for (int j = i + 1; j < n; j++)
                if (arr[i] + arr[j] == sum)
                    Console.WriteLine("(" + arr[i] + ", " + arr[j] + ") "
                                      + "\n");
    }

    // Driver Code
    public static void Main()
    {
        int[] arr = { 1, 5, 7, -1, 5 };
        int n = arr.Length;
        int sum = 6;
    }
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

PHP

```
<?php
// PHP implementation of simple
// method to find print pairs
// with given sum.

// Returns number of pairs in
// arr[0..n-1] with sum equal
// to 'sum'
function printPairs($arr, $n, $sum)
{
    // Initialize result
    $count = 0;

    // Consider all possible
    // pairs and check their sums
    for ($i = 0; $i < $n; $i++)
        for ( $j = $i + 1; $j < $n; $j++)
            if ($arr[$i] + $arr[$j] == $sum)
                echo "(", $arr[$i], ", ",
                    $arr[$j], ")", "\n";
}

// Driver Code
$arr = array (1, 5, 7, -1, 5);
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

Javascript

```
<script>
```

```
// JavaScript implementation of simple method to  
// find print pairs with given sum.
```

```
// Returns number of pairs in arr[0..n-1]  
// with sum equal to 'sum'
```

```
function printPairs(arr, n, sum)  
{  
    let count = 0; // Initialize result  
  
    // Consider all possible pairs and check  
    // their sums  
    for (let i = 0; i < n; i++)  
        for (let j = i + 1; j < n; j++)  
            if (arr[i] + arr[j] == sum)  
                document.write("(" + arr[i] + ", " +  
                    + arr[j] + ")" + "<br>");  
}
```

```
// Driver function to test the above function
```

```
let arr = [ 1, 5, 7, -1, 5 ];  
let n = arr.length;
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

</script>

Output :

(1, 5)
(1, 5)
(7, -1)

Method 2 (Use hashing).

We create an empty hash table. Now we traverse through the array and check for pairs in the hash table. If a matching element is found, we print the pair number of times equal to the number of occurrences of the matching element.

Note that the worst case of time complexity of this solution is **$O(c + n)$** where c is the count of pairs with a given sum.

C++

```
// C++ implementation of simple method to  
// find count of pairs with given sum.  
#include <bits/stdc++.h>  
using namespace std;
```


Start Your Coding Journey Now!

[Login](#)[Register](#)

```
void printPairs(int arr[], int n, int sum) {  
  
    // Traverse through all elements  
    for (int i = 0; i < n; i++) {  
  
        // Search if a pair can be formed with  
        // arr[i].  
        int rem = sum - arr[i];  
        if (m.find(rem) != m.end()) {  
            int count = m[rem];  
            for (int j = 0; j < count; j++)  
                cout << "(" << rem << ", "  
                    << arr[i] << ")" << endl;  
        }  
        m[arr[i]]++;  
    }  
}  
  
// Driver function to test the above function  
int main()  
{  
    int arr[] = { 1, 5, 7, -1, 5 };  
    int n = sizeof(arr) / sizeof(arr[0]);  
    int sum = 6;  
    printPairs(arr, n, sum);  
    return 0;  
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
import java.util.*;

class GFG{

// Returns number of pairs in arr[0..n-1]
// with sum equal to 'sum'
static void printPairs(int arr[], int n,
                      int sum)
{

// Store counts of all elements in map m
HashMap<Integer,
Integer> mp = new HashMap<Integer,
Integer>();

// Traverse through all elements
for(int i = 0; i < n; i++)
{

// Search if a pair can be formed with
// arr[i].
int rem = sum - arr[i];
if (mp.containsKey(rem))
{
    int count = mp.get(rem);

    for(int j = 0; j < count; j++)
        System.out.print("(" + rem +
                        ", " + arr[i] +
                        ")" + "\n");
}
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        {  
            mp.put(arr[i], 1);  
        }  
    }  
}  
  
// Driver code  
public static void main(String[] args)  
{  
    int arr[] = { 1, 5, 7, -1, 5 };  
    int n = arr.length;  
    int sum = 6;  
  
    printPairs(arr, n, sum);  
}  
  
// This code is contributed by Princi Singh
```

Python3

```
# Python3 implementation of simple method to  
# find count of pairs with given sum.
```

```
# Returns number of pairs in arr[0..n-1]  
# with sum equal to 'sum'  
def printPairs(arr, n, sum):
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
for i in range(n):

    # Search if a pair can be
    # formed with arr[i]
    temp = sum - arr[i]

    if temp in mydict:
        count = mydict[temp]
        for j in range(count):
            print("(", temp, ", ", arr[i],
                  ")", sep = "", end = '\n')

    if arr[i] in mydict:
        mydict[arr[i]] += 1
    else:
        mydict[arr[i]] = 1

# Driver code
if __name__ == '__main__':

    arr = [ 1, 5, 7, -1, 5 ]
    n = len(arr)
    sum = 6

    printPairs(arr, n, sum)
```

This code is contributed by MuskanKalra1

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
using System;
using System.Collections;
using System.Collections.Generic;

class GFG{

// Returns number of pairs in arr[0..n-1]
// with sum equal to 'sum'
static void printPairs(int []arr, int n, int sum)
{

    // Store counts of all elements in map m
    Dictionary<int,
        int> m = new Dictionary<int,
            int>();

    // Traverse through all elements
    for(int i = 0; i < n; i++)
    {

        // Search if a pair can be formed with
        // arr[i].
        int rem = sum - arr[i];

        if (m.ContainsKey(rem))
        {
            int count = m[rem];

            for(int j = 0; j < count; j++)
            {
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
... printPairs(arr, n, sum);
{
    m[arr[i]]++;
}
else
{
    m[arr[i]] = 1;
}
}
}

// Driver code
public static void Main(string[] args)
{
    int []arr = { 1, 5, 7, -1, 5 };
    int n = arr.Length;
    int sum = 6;

    printPairs(arr, n, sum);
}
}

// This code is contributed by rutvik_56
```

Javascript



<script>

// JavaScript implementation of simple method to

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Traverse through all elements
for (var i = 0; i < n; i++) {
    // Search if a pair can be formed with
    // arr[i].
    var rem = sum - arr[i];

    if (m.hasOwnProperty(rem)) {
        var count = m[rem];

        for (var j = 0; j < count; j++) {
            document.write("(" + rem + ", " + arr[i] + ")" + "<br>");
        }
    }

    if (m.hasOwnProperty(arr[i])) {
        m[arr[i]]++;
    } else {
        m[arr[i]] = 1;
    }
}

// Driver code
var arr = [1, 5, 7, -1, 5];
var n = arr.length;
var sum = 6;

printPairs(arr, n, sum);
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

(1, 5)
(7, -1)
(1, 5)

Method 3.

Another method to Print all pairs with the given sum is given as follows:

C++

```
// C++ code to implement
// the above approach
#include<bits/stdc++.h>
using namespace std;

void pairedElements(int arr[],
                    int sum, int n)
{
    int low = 0;
    int high = n - 1;

    while (low < high)
    {
        if (arr[low] + arr[high] == sum)
        {
```




Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        high--;\n    }\n    else\n    {\n        low++;\n    }\n}\n}\n\n// Driver code\nint main()\n{\n    int arr[] = {2, 3, 4, -2,\n                 6, 8, 9, 11};\n    int n = sizeof(arr) / sizeof(arr[0]);\n    sort(arr, arr + n);\n    pairedElements(arr, 6, n);\n}\n\n// This code is contributed by Rajput-Ji
```

Java



```
import java.util.Arrays;\n\n/**\n * Created by sampat.
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
...
int high = arr.length - 1;

while (low < high) {
    if (arr[low] + arr[high] == sum) {
        System.out.println("The pair is : ("
                            + arr[low] + ", " + arr[high] + ")");
    }
    if (arr[low] + arr[high] > sum) {
        high--;
    }
    else {
        low++;
    }
}

}

public static void main(String[] args)
{
    int arr[] = { 2, 3, 4, -2, 6, 8, 9, 11 };
    Arrays.sort(arr);

    SumOfPairs sp = new SumOfPairs();
    sp.pairedElements(arr, 6);
}
}
```



Python3

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
high = len(arr) - 1;
```

```
while (low < high):  
    if (arr[low] +  
        arr[high] == sum):  
        print("The pair is : (", arr[low],  
              ", ", arr[high], ")");  
    if (arr[low] + arr[high] > sum):  
        high -= 1;  
    else:  
        low += 1;
```

Driver code

```
if __name__ == '__main__':
```

```
    arr = [2, 3, 4, -2,  
           6, 8, 9, 11];  
    arr.sort();  
    pairedElements(arr, 6);
```

This code contributed by shikhasingrajput

C#



```
// C# program to find triplets in a given  
// array whose sum is equal to given sum.  
using System;
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
int high = arr.Length - 1;

while (low < high)
{
    if (arr[low] + arr[high] == sum)
    {
        Console.WriteLine("The pair is : ("
                           + arr[low] + ", " + arr[high] + ")");
    }
    if (arr[low] + arr[high] > sum)
    {
        high--;
    }
    else
    {
        low++;
    }
}

// Driver code
public static void Main(String[] args)
{
    int []arr = { 2, 3, 4, -2, 6, 8, 9, 11 };
    Array.Sort(arr);

    SumOfPairs sp = new SumOfPairs();
    sp.pairedElements(arr, 6);
}
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

Javascript

<script>

```
// Javascript code to implement
// the above approach
function pairedElements(arr, sum, n) {
    var low = 0;
    var high = n - 1;

    while (low < high) {
        if (arr[low] + arr[high] == sum) {
            document.write("The pair is : (" +
                arr[low] + ", " +
                arr[high] + ")<br>");
        }
        if (arr[low] + arr[high] > sum) {
            high--;
        }
        else {
            low++;
        }
    }
}

// Driver code
var arr = [ 2, 3, 4, -2, 6, 8, 9, 11]
var n = arr.length;
arr.sort(function(a,b){return a-b;});
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

Output :

The pair is : (-2, 8)

The pair is : (2, 4)

[Like](#)[Previous](#)[Next](#)


Start Your Coding Journey Now!

[Login](#)[Register](#)

RECOMMENDED ARTICLES

Page :

Article Contributed By :



kartik

@kartik

Vote for difficulty

Current difficulty : Easy

Easy

Normal

Medium

Hard

Expert



Improved By : [jit_t](#), [Smitha Dinesh Semwal](#), [SampatKumar1](#), [princi singh](#), [rutvik_56](#), [Rajput-Ji](#),

Start Your Coding Journey Now!

[Login](#)[Register](#)[Report Issue](#)

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

[Load Comments](#)

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

[Company](#)[Learn](#)

Start Your Coding Journey Now!

[Login](#)[Register](#)[Copyright Policy](#)[Video Tutorials](#)

Web Development

[Web Tutorials](#)[HTML](#)[CSS](#)[JavaScript](#)[Bootstrap](#)

Contribute

[Write an Article](#)[Write Interview Experience](#)[Internships](#)[Videos](#)

@geeksforgeeks , Some rights reserved

