



[Data Structures](#) [Algorithms](#) [Interview Preparation](#) [Topic-wise Practice](#) [C++](#) [Java](#) [Python](#) [Competitive Programming](#) [Mac](#)

Given two unsorted arrays, find all pairs whose sum is x

Difficulty Level : Easy • Last Updated : 25 Jan, 2022

Given two unsorted arrays of distinct elements, the task is to find all pairs from both arrays whose sum is equal to **X**.

Examples:

```
Input : arr1[] = {-1, -2, 4, -6, 5, 7}
        arr2[] = {6, 3, 4, 0}
        x = 8
```

```
Output : 4 4
         5 3
```

```
Input : arr1[] = {1, 2, 4, 5, 7}
        arr2[] = {5, 6, 3, 4, 8}
        x = 9
```

```
Output : 1 8
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

Recommended: Please solve it on "**PRACTICE**" first, before moving on to the solution.

A **Naive approach** is to simply run two loops and pick elements from both arrays. One by one check that both elements sum is equal to given value x or not.

C++

```
// C++ program to find all pairs in both arrays
// whose sum is equal to given value x
#include <bits/stdc++.h>

using namespace std;

// Function to print all pairs in both arrays
// whose sum is equal to given value x
void findPairs(int arr1[], int arr2[], int n,
               int m, int x)
{
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            if (arr1[i] + arr2[j] == x)
                cout << arr1[i] << " "
                    << arr2[j] << endl;
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
int arr2[] = { 0, 7, 4, 3, 2, 1 };
int n = sizeof(arr1) / sizeof(int);
int m = sizeof(arr2) / sizeof(int);
int x = 8;
findPairs(arr1, arr2, n, m, x);
return 0;
}
```

Java

```
// Java program to find all pairs in both arrays
// whose sum is equal to given value x
import java.io.*;

class GFG {

    // Function to print all pairs in both arrays
    // whose sum is equal to given value x
    static void findPairs(int arr1[], int arr2[], int n,
                          int m, int x)
    {
        for (int i = 0; i < n; i++)
            for (int j = 0; j < m; j++)
                if (arr1[i] + arr2[j] == x)
                    System.out.println(arr1[i] + " "
                                       + arr2[j]);
    }
}
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
int x = 8;
findPairs(arr1, arr2, arr1.length, arr2.length, x);
}
}
```

// This code is contributed
// by sunnysingh

Python3

```
# Python 3 program to find all
# pairs in both arrays whose
# sum is equal to given value x

# Function to print all pairs
# in both arrays whose sum is
# equal to given value x
def findPairs(arr1, arr2, n, m, x):

    for i in range(0, n):
        for j in range(0, m):
            if (arr1[i] + arr2[j] == x):
                print(arr1[i], arr2[j])

# Driver code
arr1 = [1, 2, 3, 7, 5, 4]
arr2 = [0, 7, 4, 3, 2, 1]
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

C#

```
// C# program to find all
// pairs in both arrays
// whose sum is equal to
// given value x
using System;

class GFG {

    // Function to print all
    // pairs in both arrays
    // whose sum is equal to
    // given value x
    static void findPairs(int[] arr1, int[] arr2,
                          int n, int m, int x)
    {
        for (int i = 0; i < n; i++)
            for (int j = 0; j < m; j++)
                if (arr1[i] + arr2[j] == x)
                    Console.WriteLine(arr1[i] + " " + arr2[j]);
    }

    // Driver code
    static void Main()
    {
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
}  
}  
  
// This code is contributed  
// by Sam007
```

PHP

```
<?php  
// PHP program to find all pairs  
// in both arrays whose sum is  
// equal to given value x  
  
// Function to print all pairs  
// in both arrays whose sum is  
// equal to given value x  
function findPairs($arr1, $arr2,  
                  $n, $m, $x)  
{  
    for ($i = 0; $i < $n; $i++)  
        for ($j = 0; $j < $m; $j++)  
            if ($arr1[$i] + $arr2[$j] == $x)  
                echo $arr1[$i] . " " .  
                    $arr2[$j] . "\n";  
}  
  
// Driver code
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
function findPairs(arr1, arr2, n, m, x) {
```

```
// This code is contributed  
// by Sam007  
?>
```

Javascript

```
<script>
```

```
// Javascript program to find all pairs in both arrays  
// whose sum is equal to given value x
```

```
// Function to print all pairs in both arrays  
// whose sum is equal to given value x
```

```
function findPairs(arr1, arr2, n, m, x)  
{  
    for (let i = 0; i < n; i++)  
        for (let j = 0; j < m; j++)  
            if (arr1[i] + arr2[j] == x)  
                document.write(arr1[i] + " "  
                    + arr2[j] + "<br>");  
}
```

```
// Driver code
```

```
let arr1 = [ 1, 2, 3, 7, 5, 4 ];  
let arr2 = [ 0, 7, 4, 3, 2, 1 ];
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// This code is contributed by Surbhi Tyagi.
```

```
</script>
```

Output:

```
1 7
7 1
5 3
4 4
```

Time Complexity : $O(n^2)$

Auxiliary Space : $O(1)$

Searching Approach : As we know sorting algorithms can sort data in $O(n \log n)$ time. So we will choose a $O(n \log n)$ time algorithm like : Quick Sort or Heap Sort. For each element of second array , we will subtract it from K and search it in the first array.

Steps:



1. First sort the given array using a $O(n \log n)$ algorithm like Heap Sort or Quick Sort.
2. Run a loop for each element of array-B (0 to n).
3. Inside the loop, use a temporary variable say temp, and $temp = K - B[i]$.

Start Your Coding Journey Now!

[Login](#)[Register](#)

C++

```
#include<bits/stdc++.h>
using namespace std;

void heapify(int a[] , int n , int i)
{
    int rootLargest = i;
    int lchild = 2 * i;
    int rchild = (2 * i) + 1;

    if (lchild < n && a[lchild] > a[rootLargest])
        rootLargest = lchild;

    if (rchild < n && a[rchild] > a[rootLargest])
        rootLargest = rchild;

    if (rootLargest != i)
    {
        swap(a[i] , a[rootLargest]);

        //Recursion
        heapify(a , n , rootLargest);
    }
}

int binarySearch(int a[] , int l , int r , int x)
```

Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

    return m;

    if (a[m] < x)
        l = m + 1;

    else
        r = m - 1;
}
return -1;
}

int main()
{
    int A[] = {1,2,1,3,4};
    int B[] = {3,1,5,1,2};

    int K = 8;

    int n = sizeof(A) / sizeof(A[0]);

    // Building the heap
    for (int i = n / 2 - 1 ; i >= 1; i--)
        heapify(A , n , i);

    for(int i=0 ; i<n ; i++)                //O(n)
    {
        int temp = K - B[i];                //O(1)

        if(binarySearch(A , 0 , n-1 , temp)) //O(logn)
    }
}

```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
    return 0;  
}
```

Java

```
import java.util.*;  
  
class GFG{  
    static int A[] = {1,2,1,3,4};  
    static void heapify( int n , int i)  
    {  
        int rootLargest = i;  
        int lchild = 2 * i;  
        int rchild = (2 * i) + 1;  
  
        if (lchild < n && A[lchild] > A[rootLargest])  
            rootLargest = lchild;  
  
        if (rchild < n && A[rchild] > A[rootLargest])  
            rootLargest = rchild;  
  
        if (rootLargest != i)  
        {  
            int t = A[i];  
            A[i] = A[rootLargest];  
            A[rootLargest] = t;  
            //Recursion  
        }  
    }  
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
while (l <= r)
{
    int m = l + (r - l) / 2;

    if (A[m] == x)
        return m;

    if (A[m] < x)
        l = m + 1;

    else
        r = m - 1;
}
return -1;
}

public static void main(String[] args)
{

    int B[] = {3,1,5,1,2};

    int K = 8;

    int n = A.length;

    // Building the heap
    for (int i = n / 2 - 1 ; i >= 1; i--)
        heapify( n , i);
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        System.out.print("\nFound the elements.\n");
        break;
    }
}
}
```

// This code is contributed by Rajput-Ji

Python3

```
A = [ 1, 2, 1, 3, 4 ];
```

```
def heapify(n, i):
    rootLargest = i;
    lchild = 2 * i;
    rchild = (2 * i) + 1;

    if (lchild < n and A[lchild] > A[rootLargest]):
        rootLargest = lchild;

    if (rchild < n and A[rchild] > A[rootLargest]):
        rootLargest = rchild;

    if (rootLargest != i):
        t = A[i];
        A[i] = A[rootLargest];
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
def binarySearch(l, r, x):  
    while (l <= r):  
        m = l + (r - l) // 2;  
  
        if (A[m] == x):  
            return m;  
  
        if (A[m] < x):  
            l = m + 1;  
  
        else:  
            r = m - 1;  
  
    return -1;  
  
if __name__ == '__main__':  
  
    B = [ 3, 1, 5, 1, 2 ];  
  
    K = 8;  
  
    n = len(A);  
  
    # Building the heap  
    for i in range(n// 2 - 1, 0, -1):  
        heapify(n, i);  
  
    for i in range(n):  
        temp = K - B[i];
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

C#

```
using System;
public class GFG {
    static int []A = { 1, 2, 1, 3, 4 };

    static void heapify(int n, int i) {
        int rootLargest = i;
        int lchild = 2 * i;
        int rchild = (2 * i) + 1;

        if (lchild < n && A[lchild] > A[rootLargest])
            rootLargest = lchild;

        if (rchild < n && A[rchild] > A[rootLargest])
            rootLargest = rchild;

        if (rootLargest != i) {
            int t = A[i];
            A[i] = A[rootLargest];
            A[rootLargest] = t;
            // Recursion
            heapify(n, rootLargest);
        }
    }

    static int binarySearch(int l, int r, int x) {
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        if (A[m] < x)
            l = m + 1;

        else
            r = m - 1;
    }
    return -1;
}

public static void Main(String[] args) {

    int []B = { 3, 1, 5, 1, 2 };
    int K = 8;
    int n = A.Length;

    // Building the heap
    for (int i = n / 2 - 1; i >= 1; i--)
        heapify(n, i);

    for (int i = 0; i < n; i++) // O(n)
    {
        int temp = K - B[i]; // O(1)

        if (binarySearch(0, n - 1, temp - 1) != -1) // O(logn)
        {
            Console.WriteLine("\nFound the elements.\n");
            break;
        }
    }
}
```


Start Your Coding Journey Now!

[Login](#)[Register](#)

Javascript

```
<script>
function heapify(a,n,i)
{
    let rootLargest = i;
    let lchild = 2 * i;
    let rchild = (2 * i) + 1;

    if (lchild < n && a[lchild] > a[rootLargest])
        rootLargest = lchild;

    if (rchild < n && a[rchild] > a[rootLargest])
        rootLargest = rchild;

    if (rootLargest != i)
    {
        swap(a[i] , a[rootLargest]);

        //Recursion
        heapify(a , n , rootLargest);
    }
}

function binarySearch(a,l,r,x)
{
    while (l <= r)
    {
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        l = m + 1;

    else
        r = m - 1;
    }
    return -1;
}

let A = [1,2,1,3,4];
let B = [3,1,5,1,2];

let K = 8;

let n = A.length;

// Building the heap
for (let i = n / 2 - 1 ; i >= 1; i--)
    heapify(A , n , i);

for(let i=0 ; i<n ; i++)                //O(n)
{
    let temp = K - B[i];                //O(1)

    if(binarySearch(A , 0 , n-1 , temp)) //O(logn)
    {
        document.write("\nFound the elements.\n");
        break;
    }
}
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

Found the elements

Time Complexity: $O(n \log n)$.

$O(\log n + n \log n)$

So, Overall time complexity = $O(n \log n)$.

An **Efficient solution** of this problem is to [hashing](#). Hash table is implemented using [unordered_set in C++](#).

- We store all first array elements in hash table.
- For elements of second array, we subtract every element from x and check the result in hash table.
- If result is present, we print the element and key in hash (which is an element of first array).

C++

```
// C++ program to find all pair in both arrays
// whose sum is equal to given value x
#include <bits/stdc++.h>
using namespace std;
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// ... ..  
unordered_set<int> s;  
for (int i = 0; i < n; i++)  
    s.insert(arr1[i]);  
  
// Subtract sum from second array elements one  
// by one and check it's present in array first  
// or not  
for (int j = 0; j < m; j++)  
    if (s.find(x - arr2[j]) != s.end())  
        cout << x - arr2[j] << " "  
            << arr2[j] << endl;  
}  
  
// Driver code  
int main()  
{  
    int arr1[] = { 1, 0, -4, 7, 6, 4 };  
    int arr2[] = { 0, 2, 4, -3, 2, 1 };  
    int x = 8;  
    int n = sizeof(arr1) / sizeof(int);  
    int m = sizeof(arr2) / sizeof(int);  
    findPairs(arr1, arr2, n, m, x);  
    return 0;  
}
```

**Java**

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Function to find all pairs in both arrays
// whose sum is equal to given value x
public static void findPairs(int arr1[], int arr2[],
                             int n, int m, int x)
{
    // Insert all elements of first array in a hash
    HashMap<Integer, Integer> s = new HashMap<Integer, Integer>();

    for (int i = 0; i < n; i++)
        s.put(arr1[i], 0);

    // Subtract sum from second array elements one
    // by one and check it's present in array first
    // or not
    for (int j = 0; j < m; j++)
        if (s.containsKey(x - arr2[j]))
            System.out.println(x - arr2[j] + " " + arr2[j]);
}

/* Driver program to test above function */
public static void main(String[] args)
{
    int arr1[] = { 1, 0, -4, 7, 6, 4 };
    int arr2[] = { 0, 2, 4, -3, 2, 1 };
    int x = 8;

    findPairs(arr1, arr2, arr1.length, arr2.length, x);
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
# Python3 program to find all
# pair in both arrays whose
# sum is equal to given value x

# Function to find all pairs
# in both arrays whose sum is
# equal to given value x
def findPairs(arr1, arr2, n, m, x):

    # Insert all elements of
    # first array in a hash
    s = set()
    for i in range(0, n):
        s.add(arr1[i])

    # Subtract sum from second
    # array elements one by one
    # and check it's present in
    # array first or not
    for j in range(0, m):
        if ((x - arr2[j]) in s):
            print((x - arr2[j]), ' ', arr2[j])

# Driver code
arr1 = [1, 0, -4, 7, 6, 4]
arr2 = [0, 2, 4, -3, 2, 1]
x = 8

n = len(arr1)
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

C#

```
// C# Code for Given two unsorted arrays,
// find all pairs whose sum is x
using System;
using System.Collections.Generic;

class GFG {

    // Function to find all pairs in
    // both arrays whose sum is equal
    // to given value x
    public static void findPairs(int[] arr1, int[] arr2,
                                int n, int m, int x)
    {
        // Insert all elements of first
        // array in a hash
        Dictionary<int,
            int>
        s = new Dictionary<int,
            int>();

        for (int i = 0; i < n; i++) {
            s[arr1[i]] = 0;
        }

        // Subtract sum from second array
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        }
    }
}

// Driver Code
public static void Main(string[] args)
{
    int[] arr1 = new int[] { 1, 0, -4, 7, 6, 4 };
    int[] arr2 = new int[] { 0, 2, 4, -3, 2, 1 };
    int x = 8;

    findPairs(arr1, arr2, arr1.Length,
              arr2.Length, x);
}

// This code is contributed by Shrikant13
```

Javascript

<script>

// Javascript Code for Given two unsorted arrays,
// find all pairs whose sum is x

// Function to find all pairs in both arrays
// whose sum is equal to given value x

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
... \set(arr1[i], 0);

// Subtract sum from second array elements one
// by one and check it's present in array first
// or not
for (let j = 0; j < m; j++)
    if (s.has(x - arr2[j]))
        document.write(x - arr2[j] + " " + arr2[j] + "<br/>");
}

// Driver code

let arr1 = [ 1, 0, -4, 7, 6, 4 ];
let arr2 = [ 0, 2, 4, -3, 2, 1 ];
let x = 8;

findPairs(arr1, arr2, arr1.length, arr2.length, x);

</script>
```

Output:



6 2

4 4


Start Your Coding Journey Now!

[Login](#)[Register](#)

Auxiliary Space: $O(n)$

This article is contributed by [DANISH_RAZA](#). If you like GeeksforGeeks and would like to contribute, you can also write an article using write.geeksforgeeks.org or mail your article to review-team@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Like 30

Start Your Coding Journey Now!

[Login](#)[Register](#)

RECOMMENDED ARTICLES

Page : [1](#) [2](#) [3](#)

01 **Given two arrays count all pairs whose sum is an odd number**
26, Apr 19

02 **Count pairs from two sorted arrays whose sum is equal to a given value x**
23, Jun 17

03 **Find Union and Intersection of two unsorted arrays**
01, May 15

04 **Print all pairs in an unsorted array with equal sum**
22, Nov 18

05 **Find XOR sum of Bitwise AND of all pairs from given two Arrays**
21, Jun 21

06 **Smallest Difference pair of values between two unsorted Arrays**
11, May 17

07 **Merging two unsorted arrays in sorted order**
29, Jul 17

08 **Count pairs from two arrays whose modulo operation yields K**
22, Nov 18



Start Your Coding Journey Now!

[Login](#)[Register](#)**GeeksforGeeks**

Vote for difficulty

Current difficulty : [Easy](#)

[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)

Improved By : [Sam007](#), [namankatuva](#), [ihritik](#), [shrikanth13](#), [Mayuri Gupta 4](#), [sp999](#), [RishabhAgnihotri](#), [surbhityagi15](#), [imsushant12](#), [avijitmondal1998](#), [vaibhavrabadiya3](#), [Rajput-Ji](#)

Article Tags : [Amazon](#), [Facebook](#), [Arrays](#), [Hash](#)

Practice Tags : [Amazon](#), [Facebook](#), [Arrays](#), [Hash](#)

[Improve Article](#)[Report Issue](#)

Start Your Coding Journey Now!

Login

Register



GeeksforGeeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh – 201305

feedback@geeksforgeeks.org

Company

About Us

Careers

Privacy Policy

Contact Us

Copyright Policy

Learn

Algorithms

Data Structures

Languages

CS Subjects

Video Tutorials

Web Development

Web Tutorials

HTML

CSS

JavaScript

Contribute

Write an Article

Write Interview Experience

Internships

Videos



Start Your Coding Journey Now!

Login

Register

