

Data Structures Algorithms Interview Preparation Topic-wise Practice C++ Java Python Competitive Programming Machi

Smallest Difference pair of values between two unsorted Arrays

Difficulty Level: Easy • Last Updated: 18 May, 2021

Given two arrays of integers, compute the pair of values (one value in each array) with the smallest (non-negative) difference. Return the difference.

Examples:

Login

Register

by iterating through the arrays using the approach discussed in below post.

Find the closest pair from two sorted arrays

Consider the following two arrays:

A: {l, 2, 11, 15}

B: {4, 12, 19, 23, 127, 235}

- **1.** Suppose a pointer a points to the beginning of A and a pointer b points to the beginning of B. The current difference between a and bis 3. Store this as the min.
- **2.** How can we (potentially) make this difference smaller? Well, the value at bis bigger than the value at a, so moving b will only make the difference larger. Therefore, we want to move a.
- **3.** Now a points to 2 and b (still) points to 4. This difference is 2, so we should update min. Move a, since it is smaller.
- **4.** Now a points to 11 and b points to 4. Move b.
- 5. Now a points to 11 and b points to 12. Update min to 1. Move b. And so on.

Below is the implementation of the idea.

C++



```
// C++ Code to find Smallest
// Difference between two Arrays
#include <bits/stdc++.h>
```

Login

```
{
    // Sort both arrays using
   // sort function
    sort(A, A + m);
    sort(B, B + n);
   int a = 0, b = 0;
   // Initialize result as max value
    int result = INT_MAX;
    // Scan Both Arrays upto
    // sizeof of the Arrays
    while (a < m && b < n)
        if (abs(A[a] - B[b]) < result)</pre>
            result = abs(A[a] - B[b]);
        // Move Smaller Value
        if (A[a] < B[b])
            a++;
        else
            b++;
    // return final sma result
    return result;
```

Login

Register

```
// Input given array B
int B[] = {4, 12, 19, 23, 127, 235};

// Calculate size of Both arrays
int m = sizeof(A) / sizeof(A[0]);
int n = sizeof(B) / sizeof(B[0]);

// Call function to print
// smallest result
cout << findSmallestDifference(A, B, m, n);
return 0;
}</pre>
```

Java

```
// Java Code to find Smallest
// Difference between two Arrays
import java.util.*;

class GFG
{
    // function to calculate Small
    // result between two arrays
```

Login

```
.... -, - - - - - - - - - - , , ,
    Arrays.sort(B);
    int a = 0, b = 0;
    // Initialize result as max value
    int result = Integer.MAX_VALUE;
    // Scan Both Arrays upto
    // sizeof of the Arrays
    while (a < m && b < n)
        if (Math.abs(A[a] - B[b]) < result)</pre>
             result = Math.abs(A[a] - B[b]);
        // Move Smaller Value
        if (A[a] < B[b])
             a++;
        else
             b++;
    // return final sma result
    return result;
// Driver Code
public static void main(String[] args)
```

Login

Register

Python3

```
# Python 3 Code to find
# Smallest Difference between
# two Arrays
import sys

# function to calculate
# Small result between
# two arrays
def findSmallestDifference(A, B, m, n):
```

Login

```
b = 0
    # Initialize result as max value
    result = sys.maxsize
    # Scan Both Arrays upto
    # sizeof of the Arrays
    while (a < m and b < n):</pre>
        if (abs(A[a] - B[b]) < result):</pre>
            result = abs(A[a] - B[b])
        # Move Smaller Value
        if (A[a] < B[b]):</pre>
            a += 1
        else:
            b += 1
    # return final sma result
    return result
# Driver Code
# Input given array A
A = [1, 2, 11, 5]
# Input given array B
B = [4, 12, 19, 23, 127, 235]
```

Login

```
print(findSmallestDifference(A, B, m, n))
# This code is contributed by
# Smitha Dinesh Semwal
C#
// C# Code to find Smallest
// Difference between two Arrays
using System;
class GFG
    // function to calculate Small
    // result between two arrays
    static int findSmallestDifference(int []A, int []B,
                                      int m, int n)
    {
        // Sort both arrays using
        // sort function
        Array.Sort(A);
        Array.Sort(B);
        int a = 0, b = 0;
```

Login

```
if (Math.Abs(A[a] - B[b]) < result)</pre>
            result = Math.Abs(A[a] - B[b]);
        // Move Smaller Value
        if (A[a] < B[b])
            a++;
        else
            b++;
    }
    // return final sma result
    return result;
// Driver Code
public static void Main()
    // Input given array A
    int []A = {1, 2, 11, 5};
    // Input given array B
    int []B = {4, 12, 19, 23, 127, 235};
    // Calculate size of Both arrays
    int m = A.Length;
```

Login

Register

```
}

// This code is contributed
// by nitin mittal.
```

PHP

}

Start Your Coding Journey Now!

Login

```
// Scan Both Arrays upto
   // sizeof of the Arrays
    while ($a < $m && $b < $n)
        if (abs($A[$a] - $B[$b]) < $result)</pre>
            $result = abs($A[$a] - $B[$b]);
        // Move Smaller Value
        if ($A[$a] < $B[$b])</pre>
            $a++;
        else
            $b++;
    // return final sma result
    return $result;
// Driver Code
    // Input given array A
   $A = array(1, 2, 11, 5);
   // Input given array B
   $B = array(4, 12, 19, 23, 127, 235);
```

Login

Register

```
return 0;
}
// This code is contributed by nitin mittal.
?>
```

Javascript

```
// JavaScript Code to find Smallest
// Difference between two Arrays

// function to calculate Small
// result between two arrays
function findSmallestDifference(A, B, m, n)
{

    // Sort both arrays using
    // sort function
    A.sort((a, b) => a - b);
    B.sort((a, b) => a - b);

    let a = 0, b = 0;

    // Initialize result as max value
```

Login

```
if (Math.abs(A[a] - B[b]) < result)</pre>
            result = Math.abs(A[a] - B[b]);
        // Move Smaller Value
        if (A[a] < B[b])
            a++;
        else
            b++;
    // Return final sma result
    return result;
}
// Driver Code
// Input given array A
let A = [ 1, 2, 11, 5 ];
// Input given array B
let B = [ 4, 12, 19, 23, 127, 235 ];
// Calculate size of Both arrays
let m = A.length;
let n = B.length;
// Call function to print
// smallest result
document.write(findSmallestDifference(
```

Login

Register

Output:

1

This algorithm takes $O(m \log m + n \log n)$ time to sort and O(m + n) time to find the minimum difference. Therefore, the overall runtime is $O(m \log m + n \log n)$.

This article is contributed by **Mr. Somesh Awasthi**. If you like GeeksforGeeks and would like to contribute, you can also write an article using <u>write.geeksforgeeks.org</u> or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Login

Register

-111

Next

Find minimum difference between any two elements

RECOMMENDED ARTICLES

Page:

Article Contributed By:





Vote for difficulty

Current difficulty : <u>Easy</u>

Login

Register

Article Tags: Arrays, Sorting

Practice Tags: Arrays, Sorting

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments



5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org



Login

Register

In Media

Contact Us

Privacy Policy

Copyright Policy

SDE Cheat Sheet

Machine learning

CS Subjects

Video Tutorials

News

Top News

Technology

Work & Career

Business

Finance

Lifestyle

Languages

Python

Java

CPP

Golang

C#

SQL

Web Development

Web Tutorials

Django Tutorial

HTML

CSS

JavaScript

Bootstrap

Contribute

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships

Video Internship



Login

