



Sort array after converting elements to their squares

Difficulty Level : Medium • Last Updated : 24 Nov, 2021

Given an array of both positive and negative integers 'arr[]' which are sorted. The task is to sort the square of the numbers of the Array.

Examples:

Input : arr[] = {-6, -3, -1, 2, 4, 5}

Output : 1, 4, 9, 16, 25, 36

Input : arr[] = {-5, -4, -2, 0, 1}

Output : 0, 1, 4, 16, 25

[Recommended: Please try your approach on {IDE} first, before moving on to the solution.](#)



Simple solution is to first convert each array element into its square and then apply any " $O(n \log n)$ " sorting algorithm to sort the array elements.

Below is the implementation of the above idea

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
#include <bits/stdc++.h>
using namespace std;

// Function to sort an square array
void sortSquares(int arr[], int n)
{
    // First convert each array elements
    // into its square
    for (int i = 0; i < n; i++)
        arr[i] = arr[i] * arr[i];

    // Sort an array using "sort STL function "
    sort(arr, arr + n);
}

// Driver program to test above function
int main()
{
    int arr[] = { -6, -3, -1, 2, 4, 5 };
    int n = sizeof(arr) / sizeof(arr[0]);

    cout << "Before sort " << endl;
    for (int i = 0; i < n; i++)
        cout << arr[i] << " ";
    sortSquares(arr, n);

    cout << "\nAfter Sort " << endl;
    for (int i = 0; i < n; i++)
        cout << arr[i] << " ";
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

Java

```
// Java program to Sort square of the numbers
// of the array
import java.util.*;
import java.io.*;

class GFG {
    // Function to sort an square array
    public static void sortSquares(int arr[])
    {
        int n = arr.length;

        // First convert each array elements
        // into its square
        for (int i = 0; i < n; i++)
            arr[i] = arr[i] * arr[i];

        // Sort an array using "inbuild sort function"
        // in Arrays class.
        Arrays.sort(arr);
    }

    // Driver program to test above function
    public static void main(String[] args)
    {
        int arr[] = { -6, -3, -1, 2, 4, 5 };
        int n = arr.length;
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// .....  
System.out.println("After Sort ");  
for (int i = 0; i < n; i++)  
    System.out.print(arr[i] + " ");  
}  
}
```

Python3

```
# Python program to Sort square  
# of the numbers of the array  
  
# Function to sort an square array  
def sortSquare(arr, n):  
  
    # First convert each array  
    # elements into its square  
    for i in range(n):  
        arr[i]= arr[i] * arr[i]  
    arr.sort()  
  
# Driver code  
arr = [-6, -3, -1, 2, 4, 5]  
n = len(arr)  
  
print("Before sort")  
for i in range(n):  
    print(arr[i], end = " ")
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
for i in range(n):  
    print(arr[i], end = " ")
```

```
# This code is contributed by  
# Shrikant13
```

C#

```
// C# program to Sort square  
// of the numbers of the array  
using System;  
  
class GFG {  
  
    // Function to sort  
    // an square array  
    public static void sortSquares(int[] arr)  
    {  
        int n = arr.Length;  
  
        // First convert each array  
        // elements into its square  
        for (int i = 0; i < n; i++)  
            arr[i] = arr[i] * arr[i];  
  
        // Sort an array using  
        // "inbuild sort function"
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// This code is contributed by anuj_67.
{
    int[] arr = { -6, -3, -1,
                 2, 4, 5 };
    int n = arr.Length;

    Console.WriteLine("Before sort ");
    for (int i = 0; i < n; i++)
        Console.Write(arr[i] + " ");

    sortSquares(arr);
    Console.WriteLine("");
    Console.WriteLine("After Sort ");

    for (int i = 0; i < n; i++)
        Console.Write(arr[i] + " ");
}
```

// This code is contributed by anuj_67.

Javascript

<script>

// JavaScript program for the above approach

// Function to sort an square array

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// ... ..  
for (let i = 0; i < n; i++)  
    arr[i] = arr[i] * arr[i];  
  
// Sort an array using "inbuild sort function"  
// in Arrays class.  
arr.sort();  
}  
  
// Driver Code  
let arr = [ -6, -3, -1, 2, 4, 5 ];  
let n = arr.length;  
  
document.write("Before sort " + "<br/>");  
for (let i = 0; i < n; i++)  
    document.write(arr[i] + " ");  
  
sortSquares(arr);  
document.write(" " + "<br/>");  
document.write("After Sort " + "<br/>");  
for (let i = 0; i < n; i++)  
    document.write(arr[i] + " ");  
  
// This code is contributed by chinmoy1997pal.  
</script>
```



Output:

Start Your Coding Journey Now!

[Login](#)[Register](#)

Time complexity: $O(n \log n)$

Efficient solution is based on the fact that the given array is already sorted. We do the following two steps.

1. Divide the array into two-part "Negative and positive".
2. Use [merge function](#) to merge two sorted arrays into a single sorted array.

Below is the implementation of the above idea.

C++

```
// C++ program to Sort square of the numbers of the array
#include <bits/stdc++.h>
using namespace std;

// function to sort array after doing squares of elements
void sortSquares(int arr[], int n)
{
    // first divide array into negative and positive part
    int K = 0;
    for (K = 0; K < n; K++)
        if (arr[K] >= 0)
            break;
```


Start Your Coding Journey Now!

[Login](#)[Register](#)

```
int j = K; // Initial index of second half
int ind = 0; // Initial index of temp array

// store sorted array
int temp[n];
while (i >= 0 && j < n) {
    if (arr[i] * arr[i] < arr[j] * arr[j]) {
        temp[ind] = arr[i] * arr[i];
        i--;
    }
    else {
        temp[ind] = arr[j] * arr[j];
        j++;
    }
    ind++;
}

/* Copy the remaining elements of first half */
while (i >= 0) {
    temp[ind] = arr[i] * arr[i];
    i--;
    ind++;
}

/* Copy the remaining elements of second half */
while (j < n) {
    temp[ind] = arr[j] * arr[j];
    j++;
    ind++;
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Driver program to test above function
int main()
{
    int arr[] = { -6, -3, -1, 2, 4, 5 };
    int n = sizeof(arr) / sizeof(arr[0]);

    cout << "Before sort " << endl;
    for (int i = 0; i < n; i++)
        cout << arr[i] << " ";
    sortSquares(arr, n);

    cout << "\nAfter Sort " << endl;
    for (int i = 0; i < n; i++)
        cout << arr[i] << " ";

    return 0;
}
```

Java

```
// Java program to Sort square of the numbers
// of the array
import java.util.*;
import java.io.*;

class GFG {
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
for (k = 0; k < n; k++) {
    if (arr[k] >= 0)
        break;
}

// Now do the same process that we learnt
// in merge sort to merge two sorted arrays
// here both two halves are sorted and we traverse
// first half in reverse manner because
// first half contains negative elements
int i = k - 1; // Initial index of first half
int j = k; // Initial index of second half
int ind = 0; // Initial index of temp array

int[] temp = new int[n];
while (i >= 0 && j < n) {
    if (arr[i] * arr[i] < arr[j] * arr[j]) {
        temp[ind] = arr[i] * arr[i];
        i--;
    }
    else {
        temp[ind] = arr[j] * arr[j];
        j++;
    }
    ind++;
}

while (i >= 0) {
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
    }

    // copy 'temp' array into original array
    for (int x = 0; x < n; x++)
        arr[x] = temp[x];
}

// Driver program to test above function
public static void main(String[] args)
{
    int arr[] = { -6, -3, -1, 2, 4, 5 };
    int n = arr.length;

    System.out.println("Before sort ");
    for (int i = 0; i < n; i++)
        System.out.print(arr[i] + " ");

    sortSquares(arr);
    System.out.println("");
    System.out.println("After Sort ");
    for (int i = 0; i < n; i++)
        System.out.print(arr[i] + " ");
}
}
```



Python3

Start Your Coding Journey Now!

[Login](#)[Register](#)

```

K = 0
for K in range(n):
    if (arr[K] >= 0 ):
        break

# Now do the same process that we learnt
# in merge sort to merge to two sorted array
# here both two halves are sorted and we traverse
# first half in reverse manner because
# first half contains negative elements
i = K - 1 # Initial index of first half
j = K # Initial index of second half
ind = 0 # Initial index of temp array

# store sorted array
temp = [0]*n
while (i >= 0 and j < n):

    if (arr[i] * arr[i] < arr[j] * arr[j]):
        temp[ind] = arr[i] * arr[i]
        i -= 1

    else:

        temp[ind] = arr[j] * arr[j]
        j += 1

    ind += 1
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
''' Copy the remaining elements of second half '''
while (j < n):
    temp[ind] = arr[j] * arr[j]
    j += 1
    ind += 1

# copy 'temp' array into original array
for i in range(n):
    arr[i] = temp[i]

# Driver code
arr = [-6, -3, -1, 2, 4, 5 ]
n = len(arr)

print("Before sort ")
for i in range(n):
    print(arr[i], end = " " )

sortSquares(arr, n)
print("\nAfter Sort ")
for i in range(n):
    print(arr[i], end = " " )

# This code is contributed by shubhamsingh10
```

**C#**

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Function to sort an square array
public static void sortSquares(int[] arr)
{
    int n = arr.Length;

    // first divide array into negative and positive part
    int k;
    for (k = 0; k < n; k++) {
        if (arr[k] >= 0)
            break;
    }

    // Now do the same process that we learnt
    // in merge sort to merge to two sorted array
    // here both two halves are sorted and we traverse
    // first half in reverse manner because
    // first half contains negative elements
    int i = k - 1; // Initial index of first half
    int j = k; // Initial index of second half
    int ind = 0; // Initial index of temp array

    int[] temp = new int[n];
    while (i >= 0 && j < n) {
        if (arr[i] * arr[i] < arr[j] * arr[j]) {
            temp[ind] = arr[i] * arr[i];
            i--;
        }
        else {

```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
while (i >= 0) {
    temp[ind++] = arr[i] * arr[i];
    i--;
}
while (j < n) {
    temp[ind++] = arr[j] * arr[j];
    j++;
}

// copy 'temp' array into original array
for (int x = 0; x < n; x++)
    arr[x] = temp[x];
}

// Driver code
public static void Main(String[] args)
{
    int[] arr = { -6, -3, -1, 2, 4, 5 };
    int n = arr.Length;

    Console.WriteLine("Before sort ");
    for (int i = 0; i < n; i++)
        Console.Write(arr[i] + " ");

    sortSquares(arr);
    Console.WriteLine("");
    Console.WriteLine("After Sort ");
    for (int i = 0; i < n; i++)
        Console.Write(arr[i] + " ");
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

Javascript

<script>

```
// Javascript program to Sort  
// square of the numbers  
// of the array
```

```
// Function to sort an square array
```

```
function sortSquares(arr)
```

```
{
```

```
    let n = arr.length;
```

```
    // first divided array into part
```

```
    // negative and positive
```

```
    let k;
```

```
    for (k = 0; k < n; k++) {
```

```
        if (arr[k] >= 0)
```

```
            break;
```

```
    }
```

```
    // Now do the same process that we learn
```

```
    // in merge sort to merge to two sorted array
```

```
    // here both two half are sorted and we traverse
```

```
    // first half in reverse manner because
```

```
    // first half contain negative element
```

```
    let i = k - 1; // Initial index of first half
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// ... \arr[ind] = arr[i] * arr[i];
temp[ind] = arr[i] * arr[i];
i--;
}
else {

    temp[ind] = arr[j] * arr[j];
    j++;
}
ind++;
}

while (i >= 0) {
    temp[ind++] = arr[i] * arr[i];
    i--;
}
while (j < n) {
    temp[ind++] = arr[j] * arr[j];
    j++;
}

// copy 'temp' array into original array
for (let x = 0; x < n; x++)
    arr[x] = temp[x];
}

// Driver program to test above function
let arr=[ -6, -3, -1, 2, 4, 5 ];
let n = arr.length;
document.write("Before sort <br>");
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
document.write(arr[i] + " ");  
for (let i = 0; i < n; i++)  
    document.write(arr[i] + " ");  
  
// This code is contributed by rag2127
```

</script>

Output

Before sort
-6 -3 -1 2 4 5
After Sort
1 4 9 16 25 36

Time complexity: $O(n)$

space complexity: $O(n)$

Method 3 –

Another efficient solution is based on the two-pointer method as the array is already sorted we can compare the first and last element to check which is bigger and proceed with the result.



Algorithm –

- Initialize left=0 and right=n-1

Start Your Coding Journey Now!

[Login](#)[Register](#)

C++

```
// CPP code for the above approach
#include <bits/stdc++.h>
using namespace std;

// Function to sort an square array
void sortSquares(vector<int>& arr, int n)
{
    int left = 0, right = n - 1;
    int result[n];

    // Iterate from n - 1 to 0
    for (int index = n - 1; index >= 0; index--) {

        // Check if abs(arr[left]) is greater
        // than arr[right]
        if (abs(arr[left]) > arr[right]) {
            result[index] = arr[left] * arr[left];
            left++;
        }
        else {
            result[index] = arr[right] * arr[right];
            right--;
        }
    }
}
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// C++ program to sort an array after  
// converting its elements to their squares  
{  
    vector<int> arr;  
    arr.push_back(-6);  
    arr.push_back(-3);  
    arr.push_back(-1);  
    arr.push_back(2);  
    arr.push_back(4);  
    arr.push_back(5);  
  
    int n = 6;  
  
    cout << "Before sort " << endl;  
    for (int i = 0; i < n; i++)  
        cout << arr[i] << " ";  
  
    sortSquares(arr, n);  
    cout << endl;  
    cout << "After Sort " << endl;  
    for (int i = 0; i < n; i++)  
        cout << arr[i] << " ";  
    return 0;  
}  
  
// this code is contributed by Manu Pathria
```



Java



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Function to sort an square array
public static void sortSquares(int arr[])
{
    int n = arr.length, left = 0,
        right = n - 1;

    int result[] = new int[n];

    for(int index = n - 1; index >= 0; index--)
    {
        if (Math.abs(arr[left]) > arr[right])
        {
            result[index] = arr[left] * arr[left];
            left++;
        }
        else
        {
            result[index] = arr[right] * arr[right];
            right--;
        }
    }
    for(int i = 0; i < n; i++)
        arr[i] = result[i];
}

// Driver code
public static void main(String[] args)
{
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
sortSquares(arr);
System.out.println("");
System.out.println("After Sort ");
for(int i = 0; i < n; i++)
    System.out.print(arr[i] + " ");
}
}

// This code is contributed by jinalparmar2382
```

Python3

Python3 program to Sort square of the numbers of the array

function to sort array after doing squares of elements

```
def sortSquares(arr, n):
    left, right = 0, n - 1
    index = n - 1
    result = [0 for x in arr]

    while index >= 0:

        if abs(arr[left]) >= abs(arr[right]):
            result[index] = arr[left] * arr[left]
            left += 1
        else:
```

Start Your Coding Journey Now!

[Login](#)[Register](#)

```
# Driver code
arr = [-6, -3, -1, 2, 4, 5 ]
n = len(arr)

print("Before sort ")
for i in range(n):
    print(arr[i], end = " ")

sortSquares(arr, n)
print("\nAfter Sort ")
for i in range(n):
    print(arr[i], end = " ")
```

C#

```
// C# program to Sort square of
// the numbers of the array
using System;
class GFG{

// Function to sort an square array
public static void sortSquares(int [] arr)
{
    int n = arr.Length, left = 0,
    right = n - 1;
    int []result = new int[n];
```


Start Your Coding Journey Now!

[Login](#)[Register](#)

```
        result[index] = arr[left] *
                        arr[left];
        left++;
    }
    else
    {
        result[index] = arr[right] *
                        arr[right];
        right--;
    }
}
for(int i = 0; i < n; i++)
    arr[i] = result[i];
}

// Driver code
public static void Main(string[] args)
{
    int []arr = {-6, -3, -1, 2, 4, 5};
    int n = arr.Length;
    Console.WriteLine("Before sort ");

    for(int i = 0; i < n; i++)
        Console.Write(arr[i] + " ");

    sortSquares(arr);
    Console.WriteLine("");
    Console.WriteLine("After Sort ");
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

// This code is contributed by Chitranayal

Javascript

```
<script>
// Javascript program to Sort square of
// the numbers of the array

// Function to sort an square array
function sortSquares(arr)
{
    let n = arr.length, left = 0,
        right = n - 1;
    let result = new Array(n);
    result.fill(0);

    for(let index = n - 1; index >= 0; index--)
    {
        if (Math.abs(arr[left]) >
            arr[right])
        {
            result[index] = arr[left] *
                            arr[left];
            left++;
        }
        else
        {
            result[index] = arr[right] *
                            arr[right];
            right--;
        }
    }
}
```



Start Your Coding Journey Now!

[Login](#)[Register](#)

```
    arr[i] = result[i];  
  }  
  
  let arr = [-6, -3, -1, 2, 4, 5];  
  let n = arr.length;  
  document.write("Before sort " + "</br>");  
  
  for(let i = 0; i < n; i++)  
    document.write(arr[i] + " ");  
  
  sortSquares(arr);  
  document.write("</br>");  
  document.write("After Sort " + "</br>");  
  
  for(let i = 0; i < n; i++)  
    document.write(arr[i] + " ");  
  
  // This code is contributed by rameshtravel07.  
</script>
```

Output

Before sort

-6 -3 -1 2 4 5



Start Your Coding Journey Now!

[Login](#)[Register](#)

Auxiliary Space: $O(n)$

This article is contributed by [Nishant singh](#). If you like GeeksforGeeks and would like to contribute, you can also write an article using write.geeksforgeeks.org or mail your article to review-team@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

**Curated by experts.
Trusted by 1 Lac+ students.**

Data Structures & Algorithms Self-Paced Course

[Enrol Now](#)



Like 25

Start Your Coding Journey Now!

[Login](#)[Register](#)

before or after it

RECOMMENDED ARTICLES

Page : [1](#) [2](#) [3](#)

01 Sort a linked list after converting elements to their squares

11, Nov 21

02 Replace the odd positioned elements with their cubes and even positioned elements with their squares

26, Mar 19

03 Sort perfect squares in an array at their relative positions

26, Nov 18

04 Modify array by sorting nearest perfect squares of array elements having their digits sorted in

05 Maximize sum of squares of array elements possible by replacing pairs with their Bitwise AND and Bitwise OR

12, Oct 20

06 Sort Array according to modulus of their values with their frequencies

13, Dec 21

07 Count of primes after converting given binary number in base between L to R

10, May 20

08 Sort an array of strings by replacements with

Start Your Coding Journey Now!

[Login](#)[Register](#)

Article Contributed By :



GeeksforGeeks

Vote for difficulty

Current difficulty : [Medium](#)

[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)

Improved By : [shrikanth13](#), [vt_m](#), [29AjayKumar](#), [SHUBHAMSINGH10](#), [skrish87](#), [parmarjinal](#), [ukasp](#), [manupathria](#), [chinmoy1997pal](#), [rag2127](#), [rameshtravel07](#), [uppooraprajwal](#)

Article Tags : [Arrays](#), [Sorting](#)

Practice Tags : [Arrays](#), [Sorting](#)

[Improve Article](#)[Report Issue](#)

Start Your Coding Journey Now!

[Login](#)[Register](#)

Writing code in comment? Please use <https://www.geeksforgeeks.org/>, generate link and share the link here.

[Load Comments](#)

GeeksforGeeks

5th Floor, A-118,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Company

[About Us](#)[Careers](#)[Privacy Policy](#)[Contact Us](#)[Copyright Policy](#)

News

[Technology](#)

Learn

[Algorithms](#)[Data Structures](#)[Machine learning](#)[CS Subjects](#)[Video Tutorials](#)

Languages

[Python](#)

Start Your Coding Journey Now!

[Login](#)[Register](#)

Web Development

Web Tutorials

HTML

CSS

JavaScript

Bootstrap

Contribute

Write an Article

Pick Topics to Write

Write Interview Experience

Internships

Video Internship

@geeksforgeeks , Some rights reserved

