



[Array](#) [Matrix](#) [Strings](#) [Hashing](#) [Linked List](#) [Stack](#) [Queue](#) [Binary Tree](#) [Binary Search Tree](#) [Heap](#) [Graph](#) [Searching](#) [Sc](#)

## K'th Largest element in BST using constant extra space


Difficulty Level : Hard • Last Updated : 21 May, 2021

Given a binary search tree, task is to find Kth largest element in the binary search tree.

**Example:**

Input : k = 3

Root of following BST



Output : 15



Recommended: Please try your approach on **{IDE}** first, before moving on to the solution.

## Start Your Coding Journey Now!

[Login](#)[Register](#)

The special thing about [Morris traversal](#) is that we can do Inorder traversal without using stack or recursion which saves us memory consumed by stack or recursion call stack.

*Reverse Morris traversal is just the reverse of Morris traversal which is majorly used to do Reverse Inorder traversal with constant  $O(1)$  extra memory consumed as it does not use any Stack or Recursion.*

To find [Kth largest element](#) in a Binary search tree, the simplest logic is to do reverse inorder traversal and while doing reverse inorder traversal simply keep a count of number of Nodes visited. When the count becomes equal to k, we stop the traversal and print the data. It uses the fact that reverse inorder traversal will give us a list sorted in descending order.

### Algorithm

- 1) Initialize Current as root.
- 2) Initialize a count variable to 0.
- 3) While current is not NULL :
  - 3.1) If current has no right child
    - a) Increment count and check if count is equal to K.
      - 1) If count is equal to K, simply return current Node as it is the Kth largest Node.



## Start Your Coding Journey Now!

[Login](#)[Register](#)

Inorder successor is the left most node

in the right subtree or right child itself.

- b) If the left child of the inorder successor is NULL:
    - 1) Set current as the left child of its inorder successor.
    - 2) Move current Node to its right.
  - c) Else, if the threaded link between the current Node and its inorder successor already exists :
    - 1) Set left pointer of the inorder successor as NULL.
    - 2) Increment count and check if count is equal to K.
      - a) If count is equal to K, simply return current Node as it is the Kth largest Node.
- 3) Otherwise, Move current to its left child.

## C++

```
// CPP code for finding K-th largest Node using O(1)
// extra memory and reverse Morris traversal.
#include <bits/stdc++.h>
using namespace std;

struct Node {
```

# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
Node* insert(Node* root, int data)
{
    Node* temp = new Node;
    temp->data = data;
    temp->right = temp->left = NULL;
    return temp;
}

Node* KthLargestUsingMorrisTraversal(Node* root, int k)
{
    Node* curr = root;
    Node* Klargest = NULL;

    // count variable to keep count of visited Nodes
    int count = 0;

    while (curr != NULL) {
        // if right child is NULL
        if (curr->right == NULL) {

            // first increment count and check if count = k
            if (++count == k)
                Klargest = curr;

            // otherwise move to the left child
            curr = curr->left;
        }

        else {
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
if (succ->left == NULL) {

    // set left child of successor to the
    // current Node
    succ->left = curr;

    // move current to its right
    curr = curr->right;
}

// restoring the tree back to original binary
// search tree removing threaded links
else {

    succ->left = NULL;

    if (++count == k)
        Klargest = curr;

    // move current to its left child
    curr = curr->left;
}
}

return Klargest;
}

int main()
```



# Start Your Coding Journey Now!

[Login](#)
[Register](#)

```

      /  \  /  \
     1   3 6   10 */

```

```

Node* root = newNode(4);
root->left = newNode(2);
root->right = newNode(7);
root->left->left = newNode(1);
root->left->right = newNode(3);
root->right->left = newNode(6);
root->right->right = newNode(10);

cout << "Finding K-th largest Node in BST : "
      << KthLargestUsingMorrisTraversal(root, 2)->data;

return 0;
}

```

## Java

```

// Java Program for finding K-th largest Node using O(1)
// extra memory and reverse Morris traversal.
class GfG
{
    static class Node
    {
        int data;
    }
}

```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
Node temp = new Node();
temp.data = data;
temp.right = null;
temp.left = null;
return temp;
}

static Node KthLargestUsingMorrisTraversal(Node root, int k)
{
    Node curr = root;
    Node Klargest = null;

    // count variable to keep count of visited Nodes
    int count = 0;

    while (curr != null)
    {
        // if right child is NULL
        if (curr.right == null)
        {
            // first increment count and check if count = k
            if (++count == k)
                Klargest = curr;

            // otherwise move to the left child
            curr = curr.left;
        }
    }
}
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
while (succ.left != null && succ.left != curr)
    succ = succ.left;

if (succ.left == null)
{
    // set left child of successor to the
    // current Node
    succ.left = curr;

    // move current to its right
    curr = curr.right;
}

// restoring the tree back to original binary
// search tree removing threaded links
else
{
    succ.left = null;

    if (++count == k)
        Klargest = curr;

    // move current to its left child
    curr = curr.left;
}
}
```





## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// Your Java Code
```

```
/* Constructed binary tree is
```

```
    4
```

```
   / \
```

```
  2  7
```

```
 / \ / \
```

```
1 3 6 10 */
```

```
Node root = newNode(4);
```

```
root.left = newNode(2);
```

```
root.right = newNode(7);
```

```
root.left.left = newNode(1);
```

```
root.left.right = newNode(3);
```

```
root.right.left = newNode(6);
```

```
root.right.right = newNode(10);
```

```
System.out.println("Finding K-th largest Node in BST : " +  
                    KthLargestUsingMorrisTraversal(root, 2).data);
```

```
}
```

```
}
```

## Python3



```
# Python3 code for finding K-th largest  
# Node using O(1) extra memory and  
# reverse Morris traversal.
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
def KthLargestUsingMorrisTraversal(root, k):  
    curr = root  
    Klargest = None  
  
    # count variable to keep count  
    # of visited Nodes  
    count = 0  
  
    while (curr != None):  
  
        # if right child is None  
        if (curr.right == None):  
  
            # first increment count and  
            # check if count = k  
            count += 1  
            if (count == k):  
                Klargest = curr  
  
            # otherwise move to the left child  
            curr = curr.left  
  
        else:  
  
            # find inorder successor of  
            # current Node  
            succ = curr.right  
  
            while (succ.left != None and
```



# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
.....
# to the current Node
succ.left = curr

# move current to its right
curr = curr.right

# restoring the tree back to
# original binary search tree
# removing threaded links
else:

    succ.left = None
    count += 1
    if (count == k):
        Klargest = curr

# move current to its left child
curr = curr.left
```

```
return Klargest
```

```
# Driver Code
```

```
if __name__ == '__main__':
```

```
    # Constructed binary tree is
```

```
    #      4
```

```
    #    / \
```

```
    # 2   7
```

```
    # / \ / \
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
.....\gfg\newnode\-,  
root.right.left = newNode(6)  
root.right.right = newNode(10)  
  
print("Finding K-th largest Node in BST : ",  
      KthLargestUsingMorrisTraversal(root, 2).data)
```

# This code is contributed by Pranchalk

## C#

```
// C# Program for finding K-th largest Node using O(1)  
// extra memory and reverse Morris traversal.  
using System;  
using System.Collections.Generic;  
  
class GfG  
{  
  
    public class Node  
    {  
        public int data;  
        public Node left, right;  
    }  
  
    // helper function to create a new Node  
    static Node newNode(int data)  
    {
```

# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
static Node KthLargestUsingMorrisTraversal(Node root, int k)
{
    Node curr = root;
    Node Klargest = null;

    // count variable to keep count of visited Nodes
    int count = 0;

    while (curr != null)
    {
        // if right child is NULL
        if (curr.right == null)
        {

            // first increment count and check if count = k
            if (++count == k)
                Klargest = curr;

            // otherwise move to the left child
            curr = curr.left;
        }

        else
        {

            // find inorder successor of current Node
            Node succ = curr.right;
```



## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
// set left child of successor to the
// current Node
succ.left = curr;

// move current to its right
curr = curr.right;
}

// restoring the tree back to original binary
// search tree removing threaded links
else
{
    succ.left = null;

    if (++count == k)
        Klargest = curr;

    // move current to its left child
    curr = curr.left;
}
}
}
return Klargest;
}

// Driver code
public static void Main(String[] args)
{
```



# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
1 3 6 10 */
```

```
Node root = newNode(4);
root.left = newNode(2);
root.right = newNode(7);
root.left.left = newNode(1);
root.left.right = newNode(3);
root.right.left = newNode(6);
root.right.right = newNode(10);
```

```
Console.WriteLine("Finding K-th largest Node in BST : " +
                  KthLargestUsingMorrisTraversal(root, 2).data);
}
```

```
// This code has been contributed by 29AjayKumar
```

## Javascript

```
<script>
```

```
// JavaScript Program for finding
// K-th largest Node using O(1)
// extra memory and reverse
// Morris traversal.
```

```
class Node
```

## Start Your Coding Journey Now!

[Login](#)[Register](#)

```
}
```

```
// helper function to create a new Node
```

```
function newNode(data)
```

```
{
```

```
    var temp = new Node();
```

```
    temp.data = data;
```

```
    temp.right = null;
```

```
    temp.left = null;
```

```
    return temp;
```

```
}
```

```
function KthLargestUsingMorrisTraversal(root , k)
```

```
{
```

```
    var curr = root;
```

```
    var Klargest = null;
```

```
// count variable to keep count of visited Nodes
```

```
var count = 0;
```

```
while (curr != null)
```

```
{
```

```
    // if right child is NULL
```

```
    if (curr.right == null)
```

```
    {
```

```
        // first increment count and
```

```
        // check if count = k
```

```
        if (++count == k)
```





# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
else
{

    // find inorder successor of
    // current Node
    var succ = curr.right;

    while (succ.left != null && succ.left != curr)
        succ = succ.left;

    if (succ.left == null)
    {

        // set left child of successor to the
        // current Node
        succ.left = curr;

        // move current to its right
        curr = curr.right;
    }

    // restoring the tree back to original binary
    // search tree removing threaded links
    else
    {

        succ.left = null;

        if (++count == k)
```



# Start Your Coding Journey Now!

[Login](#)[Register](#)

```
}  
    }  
    return Klargest;  
}  
  
// Driver code  
  
// Your JavaScript Code  
/* Constructed binary tree is  
    4  
   / \  
  2  7  
 / \  
1 3 6 10 */  
  
    root = newNode(4);  
    root.left = newNode(2);  
    root.right = newNode(7);  
    root.left.left = newNode(1);  
    root.left.right = newNode(3);  
    root.right.left = newNode(6);  
    root.right.right = newNode(10);  
  
    document.write("Finding K-th largest Node in BST : " +  
        KthLargestUsingMorrisTraversal(root, 2).data);  
  
// This code contributed by aashish1995  
</script>
```

**Start Your Coding Journey Now!**

Login

Register

**Time Complexity :**  $O(n)$

**Auxiliary Space :**  $O(1)$

Like

Previous



**K'th Largest Element in BST when  
modification to BST is not allowed**

Next

**Second largest element in BST**

# Start Your Coding Journey Now!

[Login](#)[Register](#)

## RECOMMENDED ARTICLES

Page :

### Article Contributed By :

**AnishSinghWalia**

@AnishSinghWalia

### Vote for difficulty

Current difficulty : [Hard](#)[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)Improved By : [prerna saini](#), [PranchalKatiyar](#), [29AjayKumar](#), [aashish1995](#)Article Tags : [Order-Statistics](#), [Binary Search Tree](#)Practice Tags : [Binary Search Tree](#)

## Start Your Coding Journey Now!

[Login](#)[Register](#)

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

[Load Comments](#)

5th Floor, A-118,  
Sector-136, Noida, Uttar Pradesh - 201305

[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

### Company

[About Us](#)[Careers](#)[In Media](#)[Contact Us](#)[Privacy Policy](#)

### Learn

[Algorithms](#)[Data Structures](#)[SDE Cheat Sheet](#)[Machine learning](#)[CS Subjects](#)

# Start Your Coding Journey Now!

[Login](#)[Register](#)

Top news

Technology

Work & Career

Business

Finance

Lifestyle

Java

CPP

Golang

C#

SQL

## Web Development

Web Tutorials

Django Tutorial

HTML

CSS

JavaScript

Bootstrap

## Contribute

Write an Article

Improve an Article

Pick Topics to Write

Write Interview Experience

Internships

Video Internship

@geeksforgeeks , Some rights reserved

