

Deletion in doubly linked list at the end

Deletion of the last node in a doubly linked list needs traversing the list in order to reach the last node of the list and then make pointer adjustments at that position.

In order to delete the last node of the list, we need to follow the following steps.

- If the list is already empty then the condition `head == NULL` will become true and therefore the operation can not be carried on.
- If there is only one node in the list then the condition `head → next == NULL` become true. In this case, we just need to assign the head of the list to `NULL` and free head in order to completely delete the list.
- Otherwise, just traverse the list to reach the last node of the list. This will be done by using the following statements.

```
ptr = head;  
    if(ptr->next != NULL)  
    {  
        ptr = ptr -> next;  
    }
```

- The `ptr` would point to the last node of the list at the end of the for loop. Just make the next pointer of the previous node of **ptr** to **NULL**.



```
ptr → prev → next = NULL
```

free the pointer as this the node which is to be deleted.

```
free(ptr)
```

- **Step 1:** IF HEAD = NULL


Write UNDERFLOW
Go to Step 7
[END OF IF]

- **Step 2:** SET TEMP = HEAD
- **Step 3:** REPEAT STEP 4 WHILE TEMP->NEXT != NULL
- **Step 4:** SET TEMP = TEMP->NEXT

[END OF LOOP]

- **Step 5:** SET TEMP ->PREV-> NEXT = NULL
- **Step 6:** FREE TEMP
- **Step 7:** EXIT





Deletion in doubly linked list at the end

C Function

```
#include<stdio.h>
#include<stdlib.h>
void create(int);
void last_delete();
struct node
{
    int data;
    struct node *next;
    struct node *prev;
};
struct node *head;
void main ()
{
```



```
int choice,item;
do
{
    printf("1.Append List\n2.Delete node from end\n3.Exit\n4.Enter your choice?");
    scanf("%d",&choice);
    switch(choice)
    {
        case 1:
            printf("\nEnter the item\n");
            scanf("%d",&item);
            create(item);
            break;
        case 2:
            last_delete();
            break;
        case 3:
            exit(0);
            break;
        default:
            printf("\nPlease enter valid choice\n");
    }

}while(choice != 3);
}

void create(int item)
{

    struct node *ptr = (struct node *)malloc(sizeof(struct node));
    if(ptr == NULL)
```



```
{
    printf("\nOVERFLOW\n");
}
else
{

    if(head==NULL)
    {
        ptr->next = NULL;
        ptr->prev=NULL;
        ptr->data=item;
        head=ptr;
    }
    else
    {
        ptr->data=item;
        ptr->prev=NULL;
        ptr->next = head;
        head->prev=ptr;
        head=ptr;
    }
    printf("\nNode Inserted\n");
}

}

void last_delete()
{
    struct node *ptr;
```



```
if(head == NULL)
{
    printf("\n UNDERFLOW\n");
}
else if(head->next == NULL)
{
    head = NULL;
    free(head);
    printf("\nNode Deleted\n");
}
else
{
    ptr = head;
    if(ptr->next != NULL)
    {
        ptr = ptr -> next;
    }
    ptr -> prev -> next = NULL;
    free(ptr);
    printf("\nNode Deleted\n");
}
}
```

Output

```
1.Append List
2.Delete node from end
3.Exit
4.Enter your choice?1
```



Enter the item

12

Node Inserted

1.Append List

2.Delete node from end

3.Exit

4.Enter your choice?1

Enter the item

90

Node Inserted

1.Append List

2.Delete node from end

3.Exit

4.Enter your choice?2

Node Deleted

← prev

next →



Please Share



Learn Latest Tutorials



Swift



Pig



Flask



C. Graphics



Automata



Testing

Preparation





Aptitude



Reasoning



Verbal A.



Interview

B.Tech / MCA



DBMS



DS



DAA



OS



C. Network



Compiler D.



COA



D. Math.



E. Hacking



Web Tech.



Cyber Sec.



C



C++



Java



.Net



Python





Programs



Control S.

1. [Bachelor Degrees](#)

2. [Distance Learning](#)

3. [2019 College Rankings](#)

4. [Higher Education Ideas](#)

