




Deletion

Delete function is used to delete the specified node from a binary search tree. However, we must delete a node from a binary search tree in such a way, that the property of binary search tree doesn't violate. There are three situations of deleting a node from binary search tree.

The node to be deleted is a leaf node

It is the simplest case, in this case, replace the leaf node with the NULL and simply free the allocated space.


In the following image, we are deleting the node 85, since the node is a leaf node, therefore the node will be replaced with NULL and allocated space will be freed.



The node to be deleted has only one child.

In this case, replace the node with its child and delete the child node, which now contains the value which is to be deleted. Simply replace it with the NULL and free the allocated space.

In the following image, the node 12 is to be deleted. It has only one child. The node will be replaced with its child node and the replaced node 12 (which is now leaf node) will simply be deleted.




The node to be deleted has two children.

It is a bit complex case compare to other two cases. However, the node which is to be deleted, is replaced with its in-order successor or predecessor recursively until the node value (to be deleted) is placed on the leaf of the tree. After the procedure, replace the node with NULL and free the allocated space.

In the following image, the node 50 is to be deleted which is the root node of the tree. The in-order traversal of the tree given below.

6, 25, 30, 50, 52, 60, 70, 75.

replace 50 with its in-order successor 52. Now, 50 will be moved to the leaf of the tree, which will simply be deleted.



Algorithm

Open an **HSBC Advance**
and get **1,000** EGP cash
Offer valid until 30 April 2019.



*Terms and Conditions apply.

Delete (TREE, ITEM)

- **Step 1:** IF TREE = NULL
Write "item not found in the tree" ELSE IF ITEM < TREE -> DATA
Delete(TREE->LEFT, ITEM)
ELSE IF ITEM > TREE -> DATA
Delete(TREE -> RIGHT, ITEM)
ELSE IF TREE -> LEFT AND TREE -> RIGHT
SET TEMP = findLargestNode(TREE -> LEFT)
SET TREE -> DATA = TEMP -> DATA
Delete(TREE -> LEFT, TEMP -> DATA)
ELSE
SET TEMP = TREE
IF TREE -> LEFT = NULL AND TREE -> RIGHT = NULL
SET TREE = NULL
ELSE IF TREE -> LEFT != NULL
SET TREE = TREE -> LEFT
ELSE

```
    SET TREE = TREE -> RIGHT  
[END OF IF]  
    FREE TEMP  
[END OF IF]
```

- **Step 2:** END

Function:

```
void deletion(Node*& root, int item)  
{  
    Node* parent = NULL;  
    Node* cur = root;  
  
    search(cur, item, parent);  
    if (cur == NULL)  
        return;  
  
    if (cur->left == NULL && cur->right == NULL)  
    {  
        if (cur != root)  
        {  
            if (parent->left == cur)  
                parent->left = NULL;  
            else  
                parent->right = NULL;  
        }  
        else  
            root = NULL;  
  
        free(cur);  
    }  
    else if (cur->left && cur->right)  
    {  
        Node* succ = findMinimum(cur->right);  
  
        int val = succ->data;  
  
        deletion(root, succ->data);  
  
        cur->data = val;  
    }  
  
    else  
    {  
        Node* child = (cur->left)? cur->left: cur->right;  
  
        if (cur != root)  
        {  
            if (cur == parent->left)  
                parent->left = child;  
            else
```



```
        parent->right = child;
    }

    else
        root = child;
    free(cur);
}

Node* findMinimum(Node* cur)
{
    while(cur->left != NULL) {
        cur = cur->left;
    }
    return cur;
}
```

[< prev](#)[next >](#)

WebLogic Monitoring Tool

Ad No additional server, database, memc
operational cost is required


WLSDM

Download

Please Share



Learn Latest Tutorials



Preparation



Aptitude



Reasoning



Verbal A.



Interview

B.Tech / MCA



DBMS



DS



DAA



OS



C. Network



Compiler D.



COA



D. Math.



Web Tech.



Cyber Sec.



C



C++



Java



.Net



Python



Programs



Control S.

