

A computer science portal for geeks

Self-Balancing-Binary-Searchers (Comparisons)

when insertion and deletion operations are policies on the control of the control

Self-Balancing Binary Search Trees are hei

Custom Search


tomatically keeps height as small as possible maintained in order of Log n so that all

operations take O(Log n) time on average.


Hire with us!

Examples:

Red Black Tree



AVL Tree:





How do Self-Balancing-Tree maintain height?

A typical operation done by trees is rotation. Following are two basic operations that can be performed to re-balance a BST without violating the BST property (keys(left) < key(root) < keys(right)). 1) Left Rotation 2) Right Rotation

```
T1, T2 and T3 are subtrees of the tree rooted with y (on the left side) or x (on the right side)
```

Keys in both of the above trees follow the following order

keys(T1) < key(x) < keys(T2) < key(y) < keys(T3)So BST property is not violated anywhere.

We have already discussed AVL tree, Red Black Tree and Splay Tree. In this acrticle, we will compare the efficiency of these trees:

METRIC	RB TREE	AVL TREE	SPLAY TREE
Insertion in	O(1)	O(logn)	Amortized O(logn)
worst case			
Maximum height	2*log(n)	1.44*log(n)	O(n)
of tree			
Search in	O(logn),	O(logn),	Amortized O(logn),
worst case	Moderate	Faster	Slower
Efficient	Three pointers with color	Two pointers with	Only two pointers with
Implementation	bit per node	balance factor per	no extra information
requires		node	

METRIC	RB TREE	AVL TREE	SPLAY TREE
Deletion in	O(logn)	O(logn)	Amortized O(logn)
worst case			
Mostly used	As universal data	When frequent lookups	When same element is
	structure	are required	retrieved again and again
Real world Application	Multiset, Multimap, Map,	Database Transactions	Cache implementation, Garbage
	Set, etc.		collection Algorithms



Recommended Posts:

Comparisons involved in Modified Quicksort Using Merge Sort Tree Second minimum element using minimum comparisons Counting Inversions using Ordered Set and GNU C++ PBDS

Shortest Path Faster Algorithm

Total number of BSTs using array elements

Ackermann Function

Count the number of words with given prefix using Trie

Vertical and Horizontal retrieval (MRT) on Tapes

Duplicates Removal in Array using BST

Build a segment tree for N-ary rooted tree

Minimum Cost Graph

Count of different groups using Graph

Count number of increasing sub-sequences: O(NlogN)

Median of sliding window in an array



<u>Abhishek rajput</u> Check out this Author's <u>contributed articles</u>.

If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please Improve this article if you find anything incorrect by clicking on the "Improve Article" button below.

Article Tags: Advanced Data Structure Binary Search Tree AVL-Tree

Practice Tags: Binary Search Tree AVL-Tree



3.6 Based on 3 vote(s) Feedback/ Suggest Improvement Add Notes Improve Article Please write to us at contribute@geeksforgeeks.org to report any issue with the above content. Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here. **Load Comments**

https://www.geeksforgeeks.org/self-balancing-binary-search-trees-comparisons/

A computer science portal for geeks

5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305 feedback@geeksforgeeks.org

COMPANY

About Us Careers Privacy Policy Contact Us

PRACTICE

Courses Company-wise Topic-wise How to begin?

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

CONTRIBUTE

Write an Article
Write Interview Experience
Internships
Videos

@geeksforgeeks, Some rights reserved